LINEAR SYSTEMS

LS358
MONOLITHIC DUAL
PNP TRANSISTOR

micross

Linear Systems Log Conformance Monolithic Dual PNP

The LS358 is a monolithic pair of PNP transistors mounted in a single TO-71 package. The monolithic dual chip design reduces parasitics and is ideal for use in logging applications. See LS318 for NPN.

The hermetically sealed TO-71 is well suited for hi-rel and harsh environment applications.

(See Packaging Information).

LS358 Features:

- Tight matching
- Low Output Capacitance

FEATURES	
LOG CONFORMANCE	Δre = 1.5Ω
ABSOLUTE MAXIMUM RATINGS [1] @ 25°C (unless otherwise noted)	
Maximum Temperatures	
Storage Temperature	-65°C to +200°C
Operating Junction Temperature	-55°C to +150°C
Maximum Power Dissipation	
Continuous Power Dissipation (One side)	250mW
Continuous Power Dissipation (Both sides)	500mW
Linear Derating factor (One side)	2.3mW/°C
Linear Derating factor (Both sides)	4.3mW/°C
Maximum Currents	
Collector Current	10mA

MATCHING CHARACTERISTICS @ 25°C (unless otherwise stated)

SYMBOL	CHARACTERISTIC	MIN	TYP	MAX	UNITS	CONDITIONS
$\|V_{BE1} - V_{BE2}\|$	Base Emitter Voltage Differential	--	0.4	1	mV	I_C = 10μA, V_{CE} = 5V
$\Delta\|(V_{BE1} - V_{BE2})\| / \Delta T$	Base Emitter Voltage Differential Change with Temperature	--	1	10	μV/°C	I_C = 10μA, V_{CE} = 5V T_A = -55°C to +125°C
$\|I_{B1} - I_{B2}\|$	Base Current Differential	--	--	10	nA	I_C = 10μA, V_{CE} = 5V
$\|\Delta (I_{B1} - I_{B2})\|$/°C	Base Current Differential Change with Temperature	--	--	0.5	nA/°C	I_C = 10μA, V_{CE} = 5V T_A = -55°C to +125°C
h_{FE1}/h_{FE2}	DC Current Gain Differential	--	5	--	%	I_C = 10μA, V_{CE} = 5V

Click To Buy

ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTICS	MIN.	TYP.	MAX.	UNITS	CONDITIONS
Δre	Log Conformance	--	--	1.5	Ω	I_C = 10-100-1000μA, V_{CE} = 5V
BV_{CBO}	Collector to Base Voltage	20	--	--	V	I_C = 10μA, I_E = 0
BV_{CEO}	Collector to Emitter Voltage	20	--	--	V	I_C = 10μA, I_B = 0
BV_{EBO}	Emitter-Base Breakdown Voltage	6.2	--	--	V	I_E = 10μA, I_C = 0 [2]
BV_{CCO}	Collector to Collector Voltage	45	--	--	V	I_C = 10μA, I_E = 0
h_{FE}	DC Current Gain	100	--	600		I_C = 10μA, V_{CE} = 5V
		100	--	600		I_C = 100μA, V_{CE} = 5V
		100	--	--		I_C = 1mA, V_{CE} = 5V
$V_{CE}(SAT)$	Collector Saturation Voltage	--	--	0.5	V	I_C = 1mA, I_B = 0.1mA
I_{EBO}	Emitter Cutoff Current	--	--	0.2	nA	I_C = 0, V_{EB} = 3V
I_{CBO}	Collector Cutoff Current	--	--	0.2	nA	I_E = 0, V_{CB} = 15V
C_{OBO}	Output Capacitance	--	--	2	pF	I_E = 0, V_{CB} = 5V
C_{C1C2}	Collector to Collector Capacitance	--	--	2	pF	V_{CC} = 0V
I_{C1C2}	Collector to Collector Leakage Current	--	--	0.5	nA	V_{CC} = ±45V
f_T	Current Gain Bandwidth Product	200	--	--	MHz	I_C = 1mA, V_{CE} = 5V
NF	Narrow Band Noise Figure	--	--	3	dB	I_C = 100μA, V_{CE} = 5V, BW=200Hz, R_G= 10KΩ, f = 1KHz

Notes:
1. Absolute Maximum ratings are limiting values above which serviceability may be impaired
2. The reverse base-to-emitter voltage must never exceed 6.2 volts; the reverse base-to-emitter current must never exceed 10μA.

micross

Available Packages:

LS358 in TO-71
LS358 available as bare die

Please contact Micross for full package and die dimensions:

Email: chipcomponents@micross.com
Web: www.micross.com/distribution.aspx

TO-71 (Bottom View)



Information furnished by Linear Integrated Systems and Micross Components is believed to be accurate and reliable. However, no responsibility is assumed for its use; nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Linear Integrated Systems.