



# **Application Note**

## **AN\_329**

# **User Guide for LibFT4222**

**Version 1.5**

**Issue Date: 2020-04-15**

The application note is a guide for LibFT4222 based on D2XX. It provides high-level and convenient APIs for FT4222H application development.

Use of FTDI devices in life support and/or safety applications is entirely at the user's risk, and the user agrees to defend, indemnify and hold FTDI harmless from any and all damages, claims, suits or expense resulting from such use.

**Future Technology Devices International Limited (FTDI)**

Unit 1, 2 Seaward Place, Glasgow G41 1HH, United Kingdom

Tel.: +44 (0) 141 429 2777 Fax: + 44 (0) 141 429 2758

Web Site: <http://ftdichip.com>

Copyright © Future Technology Devices International Limited

## **Table of Contents**


|          |                                                      |           |
|----------|------------------------------------------------------|-----------|
| <b>1</b> | <b>Introduction .....</b>                            | <b>4</b>  |
| 1.1      | Overview .....                                       | 5         |
| 1.2      | Scope .....                                          | 7         |
| <b>2</b> | <b>Getting Started .....</b>                         | <b>8</b>  |
| <b>3</b> | <b>Application Programming Interface (API) .....</b> | <b>10</b> |
| 3.1      | Typedefs.....                                        | 10        |
| 3.2      | FT4222 General Functions .....                       | 10        |
| 3.2.1    | Open and Close .....                                 | 10        |
| 3.2.2    | Un-initialize.....                                   | 10        |
| 3.2.3    | Set Clock .....                                      | 11        |
| 3.2.4    | Get Clock .....                                      | 12        |
| 3.2.5    | Set Suspend Out.....                                 | 13        |
| 3.2.6    | Set Wake Up/Interrupt .....                          | 14        |
| 3.2.7    | Set Interrupt Trigger Condition .....                | 15        |
| 3.2.8    | Get Max Transfer Size .....                          | 18        |
| 3.2.9    | Set Event Notification .....                         | 19        |
| 3.2.10   | Get Version .....                                    | 20        |
| 3.2.11   | Chip Reset .....                                     | 22        |
| 3.3      | SPI Master Functions .....                           | 22        |
| 3.3.1    | SPI Master Init .....                                | 23        |
| 3.3.2    | SPI Master Set Lines .....                           | 25        |
| 3.3.3    | SPI Master Single Read.....                          | 26        |
| 3.3.4    | SPI Master Single Write .....                        | 27        |
| 3.3.5    | SPI Master Single Read and Write .....               | 28        |
| 3.3.6    | SPI Master Multi Read and Write .....                | 31        |
| 3.4      | SPI Slave Functions.....                             | 33        |
| 3.4.1    | SPI Slave Init .....                                 | 36        |
| 3.4.2    | SPI Slave Init extend function .....                 | 37        |
| 3.4.3    | SPI Slave Set mode function .....                    | 38        |
| 3.4.4    | SPI Slave Get Rx Status .....                        | 39        |

|            |                                                |           |
|------------|------------------------------------------------|-----------|
| 3.4.5      | SPI Slave Read .....                           | 39        |
| 3.4.6      | SPI Slave Write .....                          | 41        |
| 3.4.7      | SPI Slave RX Response Time .....               | 42        |
| <b>3.5</b> | <b>SPI General Functions .....</b>             | <b>43</b> |
| 3.5.1      | SPI Reset Transaction.....                     | 43        |
| 3.5.2      | SPI Reset.....                                 | 44        |
| 3.5.3      | SPI Set Driving Strength.....                  | 45        |
| <b>3.6</b> | <b>I<sup>2</sup>C Master Functions .....</b>   | <b>46</b> |
| 3.6.1      | I2C Master Init .....                          | 46        |
| 3.6.2      | I <sup>2</sup> C Master Read.....              | 47        |
| 3.6.3      | I <sup>2</sup> C Master Write .....            | 48        |
| 3.6.4      | I <sup>2</sup> C Master Write Extension.....   | 50        |
| 3.6.5      | I <sup>2</sup> C Master Read Extension .....   | 51        |
| 3.6.6      | I <sup>2</sup> C Master GetStatus.....         | 53        |
| 3.6.7      | I <sup>2</sup> C Master Reset.....             | 54        |
| <b>3.7</b> | <b>I<sup>2</sup>C Slave Functions .....</b>    | <b>54</b> |
| 3.7.1      | I <sup>2</sup> C Slave Init.....               | 54        |
| 3.7.2      | I <sup>2</sup> C Slave Get Address .....       | 55        |
| 3.7.3      | I <sup>2</sup> C Slave Set Address.....        | 56        |
| 3.7.4      | I <sup>2</sup> C Slave Get Rx Status .....     | 57        |
| 3.7.5      | I <sup>2</sup> C Slave Read .....              | 59        |
| 3.7.6      | I <sup>2</sup> C Slave Write .....             | 59        |
| 3.7.7      | I <sup>2</sup> C Slave Reset.....              | 60        |
| 3.7.8      | I <sup>2</sup> C Slave Clock Stretch .....     | 62        |
| 3.7.9      | I <sup>2</sup> C Slave Set Response Word ..... | 62        |
| <b>3.8</b> | <b>GPIO Functions .....</b>                    | <b>63</b> |
| 3.8.1      | GPIO Init .....                                | 63        |
| 3.8.2      | GPIO Read .....                                | 64        |
| 3.8.3      | GPIO Write.....                                | 65        |
| 3.8.4      | GPIO Set Input Trigger .....                   | 66        |
| 3.8.5      | GPIO Get Trigger Status .....                  | 67        |
| 3.8.6      | GPIO Read Trigger Queue .....                  | 68        |
| 3.8.7      | GPIO Set WaveForm Mode .....                   | 70        |

|                                                              |           |
|--------------------------------------------------------------|-----------|
| <b>4 Contact Information .....</b>                           | <b>71</b> |
| <b>Appendix A – Enumeration and Structure Definitions ..</b> | <b>72</b> |
| <b>Appendix B – References .....</b>                         | <b>74</b> |
| Document References .....                                    | 74        |
| Acronyms and Abbreviations.....                              | 74        |
| <b>Appendix C – List of Tables &amp; Figures .....</b>       | <b>75</b> |
| List of Tables.....                                          | 75        |
| List of Figures .....                                        | 75        |
| <b>Appendix D – D2XX API support .....</b>                   | <b>76</b> |
| D2XX supported API .....                                     | 76        |
| 1. FT_CreateDeviceInfoList .....                             | 76        |
| <b>Appendix E – Revision History .....</b>                   | <b>77</b> |

## 1 Introduction

The FT4222H is a USB interface device which supports SPI and I<sup>2</sup>C communication protocol. It is accompanied with the support library "LibFT4222" based on D2XX, which provides high-level APIs to facilitate user application development. At the time of writing support for Windows and Linux OS has been published. Android support uses a different package also available from the FTDI website. The FT4222H contains SPI/I<sup>2</sup>C configurable interfaces. The SPI interface can be configured as master mode with single, dual, quad bits wide data transfer or slave mode with single bit wide data transfer. The I<sup>2</sup>C interface can be configured as master or slave mode.



**Figure 1.1 The Software Stack**

Note that the Window, Linux and MAC OS version of LibFT4222 have D2XX and mini-boost built-in. The LibFT4222 sample code, release notes, and all necessary files can be downloaded from the FTDI website at: <https://www.ftdichip.com/Products/ICs/FT4222H.html>

The sample source code contained in this application note is provided as an example and is neither guaranteed nor supported by FTDI.

## 1.1 Overview

The FT4222H supports 4 operation modes to allow various I<sup>2</sup>C/SPI devices to be connected to USB bus. The attachable device configuration for each mode is listed below:

- Mode 0 (2 USB interfaces):
  - 1 SPI master, SPI slave, I<sup>2</sup>C master, or I<sup>2</sup>C slave device
  - 1 GPIO device
- Mode 1 (4 USB interfaces):
  - SPI master connects up to 3 SPI slave devices
  - 1 GPIO device
- Mode 2 (4 USB interfaces):
  - SPI master connects up to 4 SPI slave devices
- Mode 3 (1 USB interface):
  - 1 SPI master, SPI slave, I<sup>2</sup>C master, or I<sup>2</sup>C slave device

In mode 0 and 3, the connected device can be a SPI/I<sup>2</sup>C master or slave, depending on how an application developer initializes the FT4222H chip. Mode 1 and mode 2 are designed to connect to multiple SPI slave devices.


The FT4222H can be configured with up to 4 GPIO pins for user applications in mode 0 and mode 1, but each pin is multiplexed with interrupt/suspend out/SPI slave select/I<sup>2</sup>C functions as listed below:

- gpio0 / ss1o / scl
- gpio1 / ss2o / sda
- gpio2 / ss3o / suspend out
- gpio3 / wakeup/intr


If the FT4222H is initialized as an I<sup>2</sup>C device, with pins as shown above, the pins of gpio0 and gpio1 will be switched to scl and sda, and cannot be used as GPIO.

By default the pin for gpio2 is configured as suspend out, and the pin for gpio3 is configured as wakeup/intr. Only those configured GPIO pins can support GPIO read/set operation through the corresponding endpoint.


The following diagrams show the examples of FT4222H SPI/I<sup>2</sup>C master connections.



**Figure 1.2 Mode 0: FT4222H works as SPI master (Quad Mode)**



**Figure 1.3 Mode 0: FT4222H works as I²C Master**



**Figure 1.4 Mode 2: FT4222H works as SPI Master**

## 1.2 Scope

The guide is intended for developers who are creating applications, extending FTDI provided applications or implementing FTDI's applications for the FT4222H.



## 2 Getting Started

A LibFT4222 application usually starts with FT\_CreateDeviceInfoList and FT\_GetDeviceInfoList as a traditional D2XX application does. Under different chip modes, FT\_CreateDeviceInfoList reports a different number of interfaces as shown in the table below.

| Mode | Number of Interfaces | Device Function                                                                                                                                                     |
|------|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0    | 2                    | a. The first interface: it can be one of SPI master, SPI slave, I <sup>2</sup> C master, or I <sup>2</sup> C slave device.<br>b. The second interface: GPIO device. |
| 1    | 4                    | a. The first 3 interfaces: SPI master connects up to 3 SPI slaves.<br>b. The 4 <sup>th</sup> interface: GPIO device.                                                |
| 2    | 4                    | a. SPI master connects up to 4 SPI slaves. Please refer figure 1.4. FT4222H works as SPI master.                                                                    |
| 3    | 1                    | a. it can be one of SPI master, SPI slave, I <sup>2</sup> C master, or I <sup>2</sup> C slave device.                                                               |

**Table 2.1 Chip Mode and Device Functions**

After opening the device with FT\_Open, developers need to initialize the FT4222H device as either SPI master, SPI slave, I<sup>2</sup>C master, or I<sup>2</sup>C slave. Different types of device require different configurations. For more details, please refer the next chapter.

Following example code shows FT4222H works in SPI master mode.

### Example#

```
include <windows.h>
#include <stdio.h>
#include <stdlib.h>
#include <vector>
#include <string>
#include "ftd2xx.h"
#include "LibFT4222.h"
std::vector< FT_DEVICE_LIST_INFO_NODE > g_FT4222DevList;
inline std::string DeviceFlagToString(DWORD flags)
{
    std::string msg;
    msg += (flags & 0x1)? "DEVICE_OPEN" : "DEVICE_CLOSED";
    msg += ", ";
    msg += (flags & 0x2)? "High-speed USB" : "Full-speed USB";
    return msg;
}
void ListFtUsbDevices()
{
    DWORD numofDevices = 0;
    FT_STATUS status = FT_CreateDeviceInfoList(&numofDevices);

    for(DWORD iDev=0; iDev<numofDevices; ++iDev)
    {
        FT_DEVICE_LIST_INFO_NODE devInfo;
        memset(&devInfo, 0, sizeof(devInfo));

        status = FT_GetDeviceInfoDetail(iDev,
            &devInfo.Flags, &devInfo.Type, &devInfo.ID, &devInfo.LocId,
            devInfo.SerialNumber, devInfo.Description, &devInfo.ftHandle);

        if (FT_OK == status)
```

```
{
    printf("Dev %d:\n", iDev);
    printf("  Flags= 0x%x, (%s)\n", devInfo.Flags,
        DeviceFlagToString(devInfo.Flags).c_str());
    printf("  Type= 0x%x\n",      devInfo.Type);
    printf("  ID= 0x%x\n",      devInfo.ID);
    printf("  LocId= 0x%x\n",    devInfo.LocId);
    printf("  SerialNumber= %s\n", devInfo.SerialNumber);
    printf("  Description= %s\n", devInfo.Description);
    printf("  ftHandle= 0x%x\n", devInfo.ftHandle);

    const std::string desc = devInfo.Description;
    if(desc == "FT4222" || desc == "FT4222 A") {
        g_FT4222DevList.push_back(devInfo);
    }
}
}
```

```
int main(int argc, char const *argv[])
{
    ListFtUsbDevices();

    if(g_FT4222DevList.empty()) {
        printf("No FT4222 device is found!\n");
        return 0;
    }

    FT_HANDLE ftHandle = NULL;
    FT_STATUS ftStatus;
    FT4222_STATUS ft4222Status;
    ftStatus = FT_OpenEx((PVOID)g_FT4222DevList[0].LocId,
        FT_OPEN_BY_LOCATION, &ftHandle);
    if (FT_OK != ftStatus) {
        printf("Open a FT4222 device failed!\n");
        return 0;
    }
    ft4222Status = FT4222_SPIMaster_Init(ftHandle,
        SPI_IO_SINGLE, CLK_DIV_4, CLK_ACTIVE_LOW, CLK_LEADING, 0x01);
    if (FT4222_OK != ft4222Status) {
        printf("Init FT4222 as SPI master device failed!\n");
        return 0;
    }
    // TODO:
    //   Start to work as SPI master, and read/write data to an SPI slave
    //   FT4222_SPIMaster_SingleWrite
    //   FT4222_SPIMaster_SingleRead
    //   FT4222_SPIMaster_SingleReadWrite

    FT4222_Uninitialize(ftHandle);
    FT_Close(ftHandle);
    return 0;
}
```

## 3 Application Programming Interface (API)

LibFT4222 supports SPI, I<sup>2</sup>C and GPIO communication using high-level APIs. In addition, it provides chip configuration APIs, such as FT4222\_SetClock.

After calling FT\_Open, the FT4222H is required to be initialized by one of the following initial functions:

- FT4222\_SPIMaster\_Init
- FT4222\_SPISlave\_Init
- FT4222\_I2CMaster\_Init
- FT4222\_I2CSlave\_Init
- FT4222\_GPIO\_Init

The initialization functions help developers to switch the FT4222H into a specific mode.

At the end of the application, FT4222\_Uninitialize should be called to release allocated resources, before calling FT\_Close.

All the APIs return an FT4222\_STATUS, which extends FT\_STATUS that is defined in the [D2XX](#) driver. FT4222\_STATUS defines additional values to report FT4222H specific status.

All definitions with prefix "FT\_" is defined in the [D2XX driver](#).

### 3.1 Typedefs

The following typedefs have been defined for keeping cross platform portability:

- typedef unsigned long **DWORD**
- typedef unsigned char **uint8**
- typedef unsigned short **uint16**
- typedef unsigned long **uint32**
- typedef signed char **int8**
- typedef signed short **int16**
- typedef signed long **int32**
- typedef unsigned char **bool**

Please refer to [Appendix A](#) for more enumeration and structure definitions.

### 3.2 FT4222 General Functions

The functions listed in this section are system-wise configuration functions.

#### 3.2.1 Open and Close

An application of LibFT4222 should open the device and get a handle for subsequent accesses by calling FT\_Open or FT\_OpenEx. Both are D2XX API. Please refer to the [D2XX Programmers Guide](#) for more details. In addition, please note that the FT4222H assigns different functions to different interfaces. For example, under mode 0, interface A is assigned as SPI or I<sup>2</sup>C interface, and interface B is assigned as GPIO interface.

After finishing using the device, FT\_Close should be called to release the device.

#### 3.2.2 Un-initialize

FT4222\_STATUS **FT4222\_UnInitialize** (FT\_HANDLE ftHandle)

**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

### Summary:

Release allocated resources. FT4222\_Uninitialize should be called before calling FT\_Close. FT4222\_Uninitialize must be called after one of the following API.

- FT4222\_SPIMaster\_Init
- FT4222\_SPISlave\_Init
- FT4222\_I2CMaster\_Init
- FT4222\_I2CSlave\_Init
- FT4222\_GPIO\_Init

### Parameters:

|          |                       |
|----------|-----------------------|
| ftHandle | Handle of the device. |
|----------|-----------------------|

### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

### Example:

```

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;

ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
ft4222Status = FT4222_SPIMaster_Init(ftHandle, SPI_IO_SINGLE, CLK_DIV_4, CLK_IDLE_LOW,
CLK_LEADING, 0x01);
if (FT4222_OK != ft4222Status)
{
    // spi master init failed
    return;
}

FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);

```

## 3.2.3 Set Clock

FT4222\_STATUS **FT4222\_SetClock**(FT\_HANDLE ftHandle, FT4222\_ClockRate clk)

### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |

|              |     |
|--------------|-----|
| FT4222 Rev B | YES |
| FT4222 Rev C | YES |
| FT4222 Rev D | YES |

### Summary:

Set the system clock rate. The FT4222H supports 4 clock rates: 80MHz, 60MHz, 48MHz, or 24MHz. By default, the FT4222H runs at 60MHz clock rate.

### Parameters:

|          |                                                                                                                                                            |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                                                                      |
| clk      | FT4222 system clock rate: <ul style="list-style-type: none"> <li>• SYS_CLK_60</li> <li>• SYS_CLK_24</li> <li>• SYS_CLK_48</li> <li>• SYS_CLK_80</li> </ul> |

### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

### Error code:

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

### Example:

```

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;

ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
// set system clock to 80MHz
ft4222Status = FT4222_SetClock(ftHandle, SYS_CLK_80);
if (FT4222_OK != ft4222Status)
{
    // set clock failed
    return;
}
FT_Close(ftHandle);
  
```

## 3.2.4 Get Clock

FT4222\_STATUS **FT4222\_GetClock**(FT\_HANDLE ftHandle, FT4222\_ClockRate\* pClk)

### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

### Summary:

Get the current system clock rate.

### Parameters:

|          |                                                                                |
|----------|--------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                          |
| pClk     | Pointer to a variable of type FT4222_ClockRate where the value will be stored. |

### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

### Error code:

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

FT4222\_INVALID\_POINTER: Parameter pClk is NULL.

### Example:

```

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
FT4222_ClockRate clk;

ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}

ft4222Status = FT4222_GetClock(ftHandle, &clk);
if (FT4222_OK != ft4222Status)
{
    // get clock failed
    return;
}

FT_Close(ftHandle);

```

## 3.2.5 Set Suspend Out

FT4222\_STATUS **FT4222\_SetSuspendOut**(FT\_HANDLE ftHandle, BOOL enable)

### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

### Summary:

Enable or disable, suspend out, which will emit a signal when FT4222H enters suspend mode. Please note that the suspend-out pin is not available under mode 2. By default, suspend-out function is on.

When suspend-out function is on, suspend-out pin emits signal according to suspend-out polarity.

The default value of suspend-out polarity is active high. It means suspend-out pin output low in normal mode and output high in suspend mode. Suspend-out polarity only can be adjusted by [FT\\_PROG](#).

#### Parameters:

|          |                                                                                                                                         |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                                                   |
| Enable   | TRUE to enable suspend out and configure GPIO2 as an output pin for emitting a signal when suspended.<br>FALSE to switch back to GPIO2. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

#### Example:

```

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;

ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}

ft4222Status = FT4222_SetSuspendOut(ftHandle, TRUE);
if (FT4222_OK != ft4222Status)
{
    // set suspend failed
    return;
}

FT_Close(ftHandle);

```

### 3.2.6 Set Wake Up/Interrupt

FT4222\_STATUS **FT4222\_SetWakeUpInterrupt**(FT\_HANDLE ftHandle, BOOL enable)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Enable or disable wakeup/interrupt. By default, wake-up/interrupt function is on.

When Wake up/Interrupt function is on, GPIO3 pin acts as an input pin for wakeup/interrupt.

While system is in normal mode, GPIO3 acts as an interrupt pin. While system is in suspend mode,

GPIO3 acts as a wakeup pin. An example is provided with the support-lib. The file is located in the following path:

example\samples\interrupt\interrupt.cpp

#### Parameters:

|          |                                                                                                 |
|----------|-------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                           |
| enable   | TRUE to configure GPIO3 as an input pin for wakeup/interrupt.<br>FALSE to switch back to GPIO3. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

#### Example:

Please refer to the example in [FT4222\\_SetInterruptTrigger](#).

### 3.2.7 Set Interrupt Trigger Condition

FT4222\_STATUS **FT4222\_SetInterruptTrigger**(FT\_HANDLE ftHandle, GPIO\_Trigger trigger)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Set trigger condition for the pin wakeup/interrupt. By default, the trigger condition is GPIO\_TRIGGER\_RISING.

This function configures trigger condition for wakeup/interrupt.

When GPIO3 acts as wakeup pin. It means that ft4222H device has the capability to wake up the host. Only GPIO\_TRIGGER\_RISING and GPIO\_TRIGGER\_FALLING are valid when GPIO3 act as a wakeup pin. . It is not necessary to call FT4222\_GPIO\_Init to set up wake-up function.

When GPIO3 acts as interrupt pin. All trigger condition can be set. The result of trigger status can be inquired by FT4222\_GPIO\_ReadTriggerQueue or FT4222\_GPIO\_Read. This is because the trigger status is provided by the GPIO pipe. Therefore it is necessary to call FT4222\_GPIO\_Init to set up interrupt function.

For GPIO triggering conditions, GPIO\_TRIGGER\_LEVEL\_HIGH and GPIO\_TRIGGER\_LEVEL\_LOW, that can be configured when GPIO3 behaves as an interrupt pin, when the system enters suspend mode, these two configurations will act as GPIO\_TRIGGER\_RISING and GPIO\_FALLING respectively.



**Parameters:**

|          |                                                                                                                                                                                                               |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                                                                                                                         |
| trigger  | Trigger condition. One of the following: <ul style="list-style-type: none"> <li>GPIO_TRIGGER_RISING</li> <li>GPIO_TRIGGER_FALLING</li> <li>GPIO_TRIGGER_LEVEL_HIGH</li> <li>GPIO_TRIGGER_LEVEL_LOW</li> </ul> |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_INTERRUPT\_NOT\_SUPPORTED: interrupt/wakeup is disabled.

FT4222\_INVALID\_PARAMETER: parameter trigger is invalid

**Example:**

// example 1: This test code is running in Mode 0.

// sending notification while there is an interrupt happen.

```

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_OpenEx("FT4222 B", FT_OPEN_BY_DESCRIPTION, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
HANDLE hRxEvent;
hRxEvent = CreateEvent(
    NULL,
    false, // auto-reset event
    false, // non-signalled state
    NULL );
ftStatus = FT_SetEventNotification(ftHandle, FT_EVENT_RXCHAR,
hRxEvent);
if (FT_OK != ftStatus)
{
    // FT_SetEventNotification failed
    return ;
}
GPIO_Dir gpioDir[4];
gpioDir[0] = GPIO_OUTPUT;
gpioDir[1] = GPIO_OUTPUT;
gpioDir[2] = GPIO_OUTPUT;
gpioDir[3] = GPIO_INPUT;

// we must initialize gpio before FT4222_SetInterruptTrigger, because interrupt data is transmitted
// by gpio interface.

FT4222_GPIO_Init(ftHandle, gpioDir);
// enable interrupt
FT4222_SetWakeUpInterrupt(ftHandle, true);
// setup interrupt trigger level
FT4222_SetInterruptTrigger(ftHandle, GPIO_TRIGGER_RISING);
while(1)

```

```
{
    BOOL value;
    WaitForSingleObject(hRxEvent,INFINITE);
    // FT4222_GPIO_Read is a read clear function for interrupt
    if(FT4222_GPIO_Read(ftHandle, (GPIO_Port)GPIO_PORT3, &value) == FT4222_OK)
    {
        if(value == TRUE)
        {
            // got interrupt
        }
        else
        {
            // no interrupt
        }
    }
}

FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);

// example 2: This test code is running in Mode 0.
// Monitor how many interrupts happen in a period of time.
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;

ftStatus = FT_OpenEx("FT4222 B",FT_OPEN_BY_DESCRIPTION, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}

GPIO_Dir gpioDir[4];
gpioDir[0] = GPIO_OUTPUT;
gpioDir[1] = GPIO_OUTPUT;
gpioDir[2] = GPIO_OUTPUT;
gpioDir[3] = GPIO_INPUT;

// we must initial gpio before FT4222_SetInterruptTrigger, because interrupt data is transmitted
// by gpio interface.

FT4222_GPIO_Init(ftHandle, gpioDir);
// enable interrupt
FT4222_SetWakeUpInterrupt(ftHandle, true);
// setup interrupt trigger level
FT4222_SetInterruptTrigger(ftHandle, GPIO_TRIGGER_RISING);

while(1)
{
    uint16 queueSize;
    // sleep 1s
    Sleep(1000);
    if(FT4222_GPIO_GetTriggerStatus(ftHandle, GPIO_PORT3, &queueSize) == FT4222_OK)
    {
        // got interrupt times in 1s
        if(queueSize > 0)
        {
            BOOL value;
            // clear the interrupt result
            FT4222_GPIO_Read(ftHandle, (GPIO_Port)GPIO_PORT3, &value);
        }
    }
}
```

```
}
}
}
```

```
FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

### 3.2.8 Get Max Transfer Size

FT4222\_STATUS **FT4222\_GetMaxTransferSize**(FT\_HANDLE ftHandle, uint16\* pMaxSize)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

This function returns the maximum packet size in a transaction. It will be affected by different bus speeds, chip modes, and functions. The maximum transfer size is maximum size in writing path.

#### Parameters:

|          |                                                                                |
|----------|--------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                          |
| pMaxSize | Pointer to a variable of type unit16 where the returning value will be stored. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_INVALID\_POINTER: Parameter pMaxSize is NULL

#### Example:

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
uint16 maxSize;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
ft4222Status = FT4222_I2CMaster_Init(ftHandle, 1000);
if (FT4222_OK != ft4222Status)
{
    // init i2c master failed
    return;
}
ft4222Status = FT4222_GetMaxTransferSize(ftHandle, &maxSize);
if (FT4222_OK != ft4222Status)
{
    // get max transfer size failed
```

```
    return;
}

FT_Close(ftHandle);
```

### 3.2.9 Set Event Notification

FT4222\_STATUS **FT4222\_SetEventNotification**(FT\_HANDLE ftHandle, DWORD dwEventMask, PVOID pvArg)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Sets conditions for event notification.

An application can use this function to set up conditions which allow a thread to block until one of the conditions is met. Typically, an application will create an event, call this function, and then block on the event. When the conditions are met, the event is set, and the application thread unblocked. Usually, the event is set to notify the application to check the condition. The application needs to check the condition again before it goes to handle the condition. The API is only valid when the device acts as SPI slave and SPI slave protocol is not SPI\_SLAVE\_NO\_PROTOCOL.

#### Parameters:

|             |                                                                                                                                                                                                                                                                                                                                             |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle    | Handle of the device.                                                                                                                                                                                                                                                                                                                       |
| dwEventMask | Conditions that cause the event to be set. It is a bit-map that describes the events the application is interested in. Currently, this function only supports the event below: <ul style="list-style-type: none"> <li>● <b>FT4222_EVENT_RXCHAR</b><br/>The event will be set when a data packet has been received by the device.</li> </ul> |
| pvArg       | Interpreted as the handle of an event which has been created by the application. If one of the event conditions is met, the event is set.                                                                                                                                                                                                   |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_EVENT\_NOT\_SUPPORTED: The device must act as SPI slave and protocol is not SPI\_SLAVE\_NO\_PROTOCOL.

#### Prerequisite:

FT4222\_SPISlave\_InitEx or FT4222\_SPISlave\_Init

#### Example:

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
```

```

HANDLE hRxEvent;

ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}

ft4222Status = FT4222_SPISlave_InitEx(ftHandle, SPI_SLAVE_NO_ACK);
if (FT4222_OK != ft4222Status)
{
    // init spi slave failed
    return;
}

hRxEvent = CreateEvent(
    NULL,
    false, // auto-reset event
    false, // non-signalled state
    NULL );
ft4222Status = FT4222_SetEventNotification(ftHandle, FT4222_EVENT_RXCHAR, hRxEvent);
if (FT4222_OK != ft4222Status)
{
    //set event notification failed
    return;
}

uint16 rxSize;
uint16 sizeTransferred;

while(1)
{
    WaitForSingleObject(hRxEvent, 1000);
    ft4222Status = FT4222_SPISlave_GetRxStatus(ftHandle, &rxSize);
    if(ft4222Status == FT4222_OK)
    {
        if(rxSize>0)
        {
            std::vector<unsigned char> tmpBuf;
            tmpBuf.resize(rxSize);
            ft4222Status = FT4222_SPISlave_Read(ftHandle, &tmpBuf[0], rxSize,
            &sizeTransferred);
            // handle receive data
        }
    }
}

FT_Close(ftHandle);
  
```

### 3.2.10 Get Version

FT4222\_STATUS **FT4222\_GetVersion**(FT\_HANDLE ftHandle, FT4222\_Version\* pVersion)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |

|              |     |
|--------------|-----|
| FT4222 Rev D | YES |
|--------------|-----|

### Summary:

Get the versions of FT4222H and LibFT4222.

### Parameters:

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| pVersion | <p>Pointer to a variable of type FT4222_Version where the value will be stored. Type FT4222_Version is defined as follows:</p> <pre> struct FT4222_Version {     DWORD chipVersion; // The version of FT4222H chip     DWORD dllVersion;  // The version of LibFT4222 }; </pre> <p>Revision A chips report chipVersion as 0x42220100.<br/> Revision B chips report chipVersion as 0x42220200.<br/> Revision C chips report chipVersion as 0x42220300.<br/> Revision D chips report chipVersion as 0x42220400.<br/> Revision B chips require version 1.2 or later of LibFT4222, indicated by dllVersion being greater than 0x01020000;<br/> Revision C chips require version 1.3 or later of LibFT4222, indicated by dllVersion being greater than 0x01030000;<br/> Revision D chips require version 1.4 or later of LibFT4222, indicated by dllVersion being greater than 0x01040000.</p> |

### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

### Error code:

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

FT4222\_INVALID\_POINTER: Parameter pVersion is NULL.

### Example:

```

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
FT4222_Version ver;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
ft4222Status = FT4222_GetVersion(ftHandle, &ver);
if (FT4222_OK != ft4222Status)
{
    // get version failed
    return;
}
printf("%x %x\n", ver.chipVersion, ver.dllVersion);
FT_Close(ftHandle);

```

### 3.2.11 Chip Reset

FT4222\_STATUS **FT4222\_ChipReset**(FT\_HANDLE ftHandle)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Software reset for device.

This function is used to attempt to recover system after a failure. It is a software reset for device.

#### Parameters:

|          |                       |
|----------|-----------------------|
| ftHandle | Handle of the device. |
|----------|-----------------------|

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

#### Example:

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
ft4222Status = FT4222_ChipReset(ftHandle);
if (FT4222_OK == ft4222Status)
{
    // chip has been reset
}
else
{
    // chip reset failed
}
FT_Close(ftHandle);
```

## 3.3 SPI Master Functions

The FT4222H can be initialized as an SPI master under all modes.

As SPI master, it allows data transfers in three types of bit width:

- Single SPI transfer – Standard data transfer format – data is read and written simultaneously

- DUAL SPI Transfer/Receive - Data is transferred out or received in on 2 SPI lines simultaneously
- QUAD SPI Transfer/Receive - Data is transferred out or received in on 4 SPI lines simultaneously

Please refer to [DS\\_FT4222H](#) for more details.

For SPI Master Single mode, all data packets are terminated with a zero-length packet. Therefore after one data packet there will be one SOF then follow by the terminating zero-length packet then ends with another SOF. As a result, under normal conditions, these two SOF's will take approximately 250us.

### 3.3.1 SPI Master Init

```
FT4222_STATUS FT4222_SPIMaster_Init(FT_HANDLE ftHandle,
                                     FT4222_SPIMode ioLine, FT4222_SPIClock clock_div,
                                     FT4222_SPICPOL cpol, FT4222_SPICPHA cpha, uint8 ssoMap)
```

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Initialize the FT4222H as an SPI master.

In order to support various types of SPI slave devices, the FT4222H SPI master is configurable using the following parameters:

- IO lines: SPI transmission lines. The FT4222H SPI supports single, dual, or quad transmission mode. An application may override this initial selection dynamically using FT4222\_SPIMaster\_SetLines. For example, commands might be sent in single mode but data transferred in dual or quad mode.
- Clock divider: SPI clock rate is subject to system clock. The FT4222H SPI clock could be 1/2, 1/4, 1/8, 1/16, 1/32, 1/64, 1/128, 1/256, or 1/512 system clock rate.
- Clock polarity: Active high or active low.
- Clock phase: Data is sampled on the leading (first) or trailing (second) clock edge.
- Slave selection output pins: Select slave devices by ss0o, ss1o, ss2o, ss3o. The FT4222H supports active low only.
- There is only one setting stored in the MCU. If there are multi SPI masters to be initialized, keep all settings the same, including ssoMap.

Please note that the FT4222H has only one SPI controller. Even though the FT4222H provides up to 4 interfaces for connecting up to 4 SPI slave devices as per [Figure 1.4](#), the 4 slave devices share the same SPI data bus: MOSI, MISO, and SCK. A user can decide how to map the 4 interfaces to the 4 SS signals (ss0o, ss1o, ss2o and ss3o) by the ssoMap parameter.

The 4 interfaces cannot work simultaneously because there is only one data bus.

#### Parameters:

|          |                                                                                                                  |
|----------|------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                            |
| ioLine   | SPI transmission lines: <ul style="list-style-type: none"> <li>• SPI_IO_SINGLE</li> <li>• SPI_IO_DUAL</li> </ul> |



|           |                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | <ul style="list-style-type: none"> <li>• SPI_IO_QUAD</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                   |
| clock_div | Clock divider: <ul style="list-style-type: none"> <li>• CLK_DIV_2 (1/2 System Clock)</li> <li>• CLK_DIV_4 (1/4 System Clock)</li> <li>• CLK_DIV_8 (1/8 System Clock)</li> <li>• CLK_DIV_16 (1/16 System Clock)</li> <li>• CLK_DIV_32 (1/32 System Clock)</li> <li>• CLK_DIV_64 (1/64 System Clock)</li> <li>• CLK_DIV_128 (1/128 System Clock)</li> <li>• CLK_DIV_256 (1/256 System Clock)</li> <li>• CLK_DIV_512 (1/512 System Clock)</li> </ul> |
| cpol      | Clock polarity: <ul style="list-style-type: none"> <li>• CLK_IDLE_LOW</li> <li>• CLK_IDLE_HIGH</li> </ul>                                                                                                                                                                                                                                                                                                                                         |
| cpha      | Clock phase: <ul style="list-style-type: none"> <li>• CLK_LEADING</li> <li>• CLK_TRAILING</li> </ul>                                                                                                                                                                                                                                                                                                                                              |
| ssoMap    | Slave selection output pins. It's a bitmap: <ul style="list-style-type: none"> <li>• Bit 0: select device connected with ss0o</li> <li>• Bit 1: select device connected with ss1o</li> <li>• Bit 2: select device connected with ss2o</li> <li>• Bit 3: select device connected with ss3o</li> </ul>                                                                                                                                              |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

FT4222\_INVALID\_PARAMETER: Parameter is not suitable.

#### Example: single SPI master initialization

```

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;

ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}

ft4222Status = FT4222_SPIMaster_Init(ftHandle, SPI_IO_SINGLE, CLK_DIV_4, CLK_IDLE_LOW,
CLK_LEADING, 0x01);
if (FT4222_OK != ft4222Status)
{
    // spi master init failed
    return;
}

FT4222_UnInitialize(ftHandle);

FT_Close(ftHandle);

```

#### Example: multiple SPI master initialization, this sample runs in Mode 1 or Mode 2

```

FT_HANDLE ftHandle1 = NULL;

```

```

FT_HANDLE ftHandle2 = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;

ftStatus = FT_Open(0, &ftHandle1);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
ftStatus = FT_Open(1, &ftHandle2);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}

ft4222Status = FT4222_SPIMaster_Init(ftHandle1, SPI_IO_SINGLE, CLK_DIV_4,
CLK_IDLE_LOW, CLK_LEADING, 0x03);
if (FT4222_OK != ft4222Status)
{
    // spi master init failed
    return;
}
ft4222Status = FT4222_SPIMaster_Init(ftHandle2, SPI_IO_SINGLE, CLK_DIV_4,
CLK_IDLE_LOW, CLK_LEADING, 0x03);
if (FT4222_OK != ft4222Status)
{
    // spi master init failed
    return;
}

FT4222_UnInitialize(ftHandle1);
FT4222_UnInitialize(ftHandle2);

FT_Close(ftHandle1);
FT_Close(ftHandle2);
  
```

### 3.3.2 SPI Master Set Lines

FT4222\_STATUS **FT4222\_SPIMaster\_SetLines**(FT\_HANDLE ftHandle, FT4222\_SPIMode spiMode)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Switch the FT4222H SPI master to single, dual, or quad mode. This overrides the mode passed to FT4222\_SPIMaster\_init. This might be needed if a device accepts commands in single mode but data transfer is to use dual or quad mode.

**Parameters:**

|          |                                                                                                                                    |
|----------|------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                                              |
| spiMode  | SPI mode could be: <ul style="list-style-type: none"> <li>• SPI_IO_SINGLE</li> <li>• SPI_IO_DUAL</li> <li>• SPI_IO_QUAD</li> </ul> |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_IS\_NOT\_SPI\_MODE: Device does not be configured to SPI Master mode.

FT4222\_NOT\_SUPPORTED: SPI Master only support single/dual/quad mode, others are not allowed.

**Prerequisite:**

FT4222\_SPIMaster\_init

### 3.3.3 SPI Master Single Read

FT4222\_STATUS **FT4222\_SPIMaster\_SingleRead**(FT\_HANDLE ftHandle, uint8\* buffer, uint16 bytesToRead, uint16\* sizeofRead, BOOL isEndTransaction)

**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

**Summary:**

Under SPI single mode, read data from an SPI slave.

**Parameters:**

|                  |                                                                                               |
|------------------|-----------------------------------------------------------------------------------------------|
| ftHandle         | Handle of the device.                                                                         |
| Buffer           | Pointer to the buffer that receives the data from the device.                                 |
| bytesToRead      | Number of bytes to read from the device.                                                      |
| sizeofRead       | Pointer to a variable of type uint16 which receives the number of bytes read from the device. |
| isEndTransaction | If TRUE the Slave Select pin will be raised at the end of the read.                           |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_INVALID\_POINTER: Pointer is a NULL pointer.

FT4222\_IS\_NOT\_SPI\_SINGLE\_MODE: Device is not in SPI Master Single mode

FT4222\_FAILED\_TO\_WRITE\_DEVICE: Write data timeout or failed. FT\_SetTimeouts can be called to extend timeout.

FT4222\_FAILED\_TO\_READ\_DEVICE: Failed to read data.

### Prerequisite:

FT4222\_SPIMaster\_init

### Example:

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
ft4222Status = FT4222_SPIMaster_Init(ftHandle, SPI_IO_SINGLE, CLK_DIV_4, CLK_IDLE_LOW,
    CLK_LEADING, 0x01);
if (FT4222_OK != ft4222Status)
{
    // spi master init failed
    return;
}

uint8 recvData[10];
uint16 sizeTransferred;
ft4222Status = FT4222_SPIMaster_SingleRead(ftHandle, &recvData[0], 10, &sizeTransferred,
    true);
if (FT4222_OK != ft4222Status)
{
    // spi master read failed
    return;
}

FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

### 3.3.4 SPI Master Single Write

FT4222\_STATUS **FT4222\_SPIMaster\_SingleWrite**(FT\_HANDLE ftHandle, uint8\* buffer, uint16 bytesToWrite, uint16\* sizeTransferred, BOOL isEndTransaction)

### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

### Summary:

Under SPI single mode, write data to an SPI slave.

### Parameters:

|                 |                                                                                                |
|-----------------|------------------------------------------------------------------------------------------------|
| ftHandle        | Handle of the device.                                                                          |
| Buffer          | Pointer to the buffer that contains the data to be written to the device.                      |
| bytesToWrite    | Number of bytes to write to the device.                                                        |
| sizeTransferred | Pointer to a variable of type uint16 which receives the number of bytes written to the device. |

|                  |                                                                      |
|------------------|----------------------------------------------------------------------|
| isEndTransaction | If TRUE the Slave Select pin will be raised at the end of the write. |
|------------------|----------------------------------------------------------------------|

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_INVALID\_POINTER: Pointer is a NULL pointer.

FT4222\_IS\_NOT\_SPI\_SINGLE\_MODE: Device is not in SPI Master Single mode

FT4222\_FAILED\_TO\_WRITE\_DEVICE: Write data timeout or failed. FT\_SetTimeouts can be called to extend timeout.

FT4222\_FAILED\_TO\_READ\_DEVICE: Failed to read data.

#### Prerequisite:

FT4222\_SPIMaster\_init

#### Example:

```

    FT_HANDLE ftHandle = NULL;
    FT_STATUS ftStatus;
    FT4222_STATUS ft4222Status;
    ftStatus = FT_Open(0, &ftHandle);
    if (FT_OK != ftStatus)
    {
        // open failed
        return;
    }

    ft4222Status = FT4222_SPIMaster_Init(ftHandle, SPI_IO_SINGLE, CLK_DIV_4, CLK_IDLE_LOW,
    CLK_LEADING, 0x01);
    if (FT4222_OK != ft4222Status)
    {
        // spi master init failed
        return;
    }

    uint8 sendData[10];
    uint16 sizeTransferred;

    for(int idx=0;idx<10;idx++)
        sendData[idx] = idx;

    ft4222Status = FT4222_SPIMaster_SingleWrite(ftHandle, &sendData[0], 10, &sizeTransferred,
    true);
    if (FT4222_OK != ft4222Status)
    {
        // spi master write failed
        return;
    }

    FT4222_UnInitialize(ftHandle);
    FT_Close(ftHandle);
  
```

### 3.3.5 SPI Master Single Read and Write

FT4222\_STATUS **FT4222\_SPIMaster\_SingleReadWrite**(FT\_HANDLE ftHandle, uint8\* readBuffer, uint8\* writeBuffer, uint16 sizeToTransfer, uint16\* sizeTransferred, BOOL isEndTransaction)


## Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

## Summary:

Under SPI single mode, full-duplex write data to and read data from an SPI slave.

The standard SPI protocol simultaneously sends data onto the MOSI data line and receives data from the MISO line as shown below -



**Figure 3.1 SPI full duplex communication**

## Parameters:

|                  |                                                                                                         |
|------------------|---------------------------------------------------------------------------------------------------------|
| ftHandle         | Handle of the device.                                                                                   |
| readBuffer       | Pointer to the buffer that receives data from the device.                                               |
| writeBuffer      | Pointer to the buffer that contains data to be written to the device.                                   |
| sizeToTransfer   | The size of read and write buffer. They must be the same.                                               |
| sizeTransferred  | Pointer to a variable of type uint16 which receives the number of bytes read and written to the device. |
| isEndTransaction | TRUE to raise the pin of SS at the end of the transaction.                                              |

## Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

## Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_INVALID\_POINTER: Pointer is a NULL pointer.

FT4222\_IS\_NOT\_SPI\_SINGLE\_MODE: Device is not in SPI Master Single mode

FT4222\_FAILED\_TO\_WRITE\_DEVICE: Write data timeout or failed. FT\_SetTimeouts can be called to extend timeout.

FT4222\_FAILED\_TO\_READ\_DEVICE: Failed to read data.

## Prerequisite:

FT4222\_SPIMaster\_init

**Example:**

```
// This example is for mxic flash to read out RDSR(read status register)

// bit0 (WIP: write in progress bit). When WIP bit sets to 1, which means the device is
//busy in program/erase/write status register progress

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;

ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}

ft4222Status = FT4222_SPIMaster_Init(ftHandle, SPI_IO_SINGLE, CLK_DIV_4, CLK_IDLE_LOW,
CLK_LEADING, 0x01);
if (FT4222_OK != ft4222Status)
{
    // spi master init failed
    return;
}

uint8 sendData[2];
uint8 readData[2];
uint16 sizeTransferred;

// for mxic flash,
//byte 0: read status command
//byte 1: status
sendData[0] = 0x05; // read status command
sendData[1] = 0xFF; // a dummy byte,

ft4222Status = FT4222_SPIMaster_SingleReadWrite(ftHandle, &readData[0], &sendData[0], 2,
&sizeTransferred, true);
if((ft4222Status!=FT4222_OK) || (sizeTransferred!=2))
{
    // single read write failed
    return ;
}

if ((readData[1] & 0x01) == 0x00)
{
    // not in writing operation
}
else
{
    // still in writing process
}

FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

### 3.3.6 SPI Master Multi Read and Write

FT4222\_STATUS **FT4222\_SPIMaster\_MultiReadWrite**(FT\_HANDLE ftHandle, uint8\* readBuffer, uint8\* writeBuffer, uint8 singleWriteBytes, uint16 multiWriteBytes, uint16 multiReadBytes, uint32\* sizeOfRead)


#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Under SPI dual or quad mode, write data to and read data from an SPI slave.


The figure below illustrates the dual-SPI protocol supported by the FT4222H SPI master. It is a mixed protocol initiated with a single write transmission, which may be an SPI command and dummy cycles, and followed by dual-write and dual-read transmission that use 2 signals in parallel for the data. All three parts of the protocol are optional. For example, developers can ignore the multi-read part by setting multiReadBytes=0.



**Figure 3.2 Dual SPI communications**

The figure below illustrates the quad-SPI protocol supported by the FT4222H SPI master. It is the same as the dual-protocol illustrated above - it is a mixed protocol initiated with a single write transmission and followed by quad-write and quad-read transmission that use 4 signals in parallel for the data.





**Figure 3.3 Quad SPI communication**

#### Parameters:

|                  |                                                                                                                                                                                                                                                                                                              |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle         | Handle of the device.                                                                                                                                                                                                                                                                                        |
| readBuffer       | Pointer to the buffer that receives the data from the device.                                                                                                                                                                                                                                                |
| writeBuffer      | Pointer to the buffer that contains the data to be written to the device. The data is comprised of both single-write and multi-write parts. It starts with single-write data, whose length is specified by singleWriteBytes, and followed by multi-write data, whose length is specified by multiWriteBytes. |
| singleWriteBytes | Number of bytes in writeBuffer will be written on single-line. Maximum size is 15.                                                                                                                                                                                                                           |
| multiWriteBytes  | Number of bytes in writeBuffer will be written on multi-line. Maximum size is 65535.                                                                                                                                                                                                                         |
| multiReadBytes   | Number of bytes to read on multi-line. Maximum size is 65535.                                                                                                                                                                                                                                                |
| sizeofRead       | Pointer to a variable of type uint16 which receives the number of bytes read from the device.                                                                                                                                                                                                                |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called

FT4222\_INVALID\_POINTER: Parameter readBuffer or sizeofRead is NULL while multiReadBytes is not equal to zero. Parameter writeBuffer is NULL while (singleWriteBytes+ multiWriteBytes) is not equal to zero.

FT4222\_FAILED\_TO\_WRITE\_DEVICE: Write data timeout or failed. FT\_SetTimeouts can be called to extend timeout.

FT4222\_FAILED\_TO\_READ\_DEVICE: Failed to read data.

#### Prerequisite:

FT4222\_SPIMaster\_init

#### Example:

```
// This example it to read 4 IO line mxix flash
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
uint32 _addr = 0x0;
ftStatus = FT_Open(0, &ftHandle);
```

```

if (FT_OK != ftStatus)
{
    // open failed
    return;
}
ft4222Status = FT4222_SPIMaster_Init(ftHandle, SPI_IO_QUAD, CLK_DIV_4, CLK_IDLE_LOW,
                                     CLK_LEADING, 0x01);
if (FT4222_OK != ft4222Status)
{
    // spi master init failed
    return;
}

uint8 writeData[7];
uint8 readData[16];
uint32 sizeOfRead;

// for mxic flash,
writeData[0] = 0xEB; // 4 x I/O Read Mode (4READ)
writeData[1] = (unsigned char)((_addr & 0xFF0000) >> 16); // for addr
writeData[2] = (unsigned char)((_addr & 0x00FF00) >> 8); // for addr
writeData[3] = (unsigned char)((_addr & 0x0000FF)); // for addr
writeData[4] = 0xFF; // dummy byte
writeData[5] = 0xFF; // dummy byte
writeData[6] = 0xFF; // dummy byte

ft4222Status = FT4222_SPIMaster_MultiReadWrite(ftHandle, readData, &writeData[0], 1, 6, 16,
                                               &sizeOfRead);
if((ft4222Status!=FT4222_OK) || (sizeOfRead != 16))
{
    // can not get correct data
    return;
}

FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
  
```

### 3.4 SPI Slave Functions

The FT4222H can be initialized as an SPI slave under mode 0 to mode 3. As an SPI slave, the FT4222H only supports the standard single SPI transfer. Please refer to [DS\\_FT4222H](#) for more details. SPI Slave function is not suitable on Android system. Garbage collection is a form of automatic memory management. When garbage collection happens, it does not emit bulk-in packet and RX data may be lost during this period of time

A USB-SPI bridge usually faces the challenge that USB cannot guarantee the throughput for each endpoint, but SPI requires data transmission at a steady rate. It is highly possible when an SPI master starts to request data from a USB-SPI slave bridge device, the data has not arrived from the USB host side yet. In addition, SPI does not have a standard protocol to allow the master side to check the status of the slave side. The protocol is usually provided by an SPI slave device on its own, which makes the SPI master device communicate with the slave device by its specified commands.

There are there methods to access FT4222 SPI Slave function.

- SPI\_SLAVE\_WITH\_PROTOCOL
- SPI\_SLAVE\_NO\_ACK
- SPI\_SLAVE\_NO\_PROTOCOL


With all the SPI Slave operational modes listed, the support library will always add a dummy byte

of "0x00" as the first byte for every transmission. This is an internal sync byte that is needs to be removed by the SPI Master.

## ■ SPI\_SLAVE\_WITH\_PROTOCOL

The FT4222H and LibFT4222 design have implemented an SPI slave protocol which must be used to handle the integrity of data transmission. The API "**FT4222\_SPISlave\_Init**" is used to initialize the slave with this mode.

In this protocol, a master starts an SPI transaction by sending a packet in the format illustrated below. The Sync Word "0x5A" is fixed with this slave mode and user applications do not need to do any operations to add or remove the Sync Word. It is done by the support library.



**Figure 3.4 SPI Slave Protocol Format**


The packet starts with **Sync word**: 0x5A, and followed by a **Command** field:

| Command                                  | Value |
|------------------------------------------|-------|
| Master Transfer                          | 0x80  |
| Slave Transfer                           | 0x81  |
| Short master transfer (without checksum) | 0x82  |
| Short slave transfer (without checksum)  | 0x83  |
| ACK                                      | 0x84  |

**SN** stands for serial number. It is monotonically increased, and helps to identify packets. **Size** is a two-byte field, which is the size of the data field in big-endian order. The **Checksum** is the summation of all data fields' lower two bytes starting from the first byte, the sync word, to the latest data byte.


The checksum is in big-endian order as well. When the slave, FT4222H, receives the transfer request from the master, it will respond with an ACK. The master can confirm the transaction succeeded when it receives the ACK from the slave.

When SPI Slave receives the Master transfer request, it will check if the format and checksum are correct. If the answer is yes, the support-lib will send the response ACK automatically, grab the data from the packet and send it to application.




**Figure 3.5 SPI Master Transfer Request**

Here is an example of an ACK packet. The SN field of the ACK packet identifies which request it corresponds to. An ACK packet has no data therefore the Size field should be 0.



**Figure 3.6 An example of the SPI slave responding with ACK**

If the SPI master does not receive the ACK response from the slave, it should send its request again.




**Figure 3.7 An example of when the SPI master doesn't receive ACK**

When the FT4222H SPI slave wants to send data to the master, which may be requested by the master, it just sends a transfer request in the same protocol format as shown in [figure 3.4](#).

In this case, it is not necessary to append any header while API FT4222\_SPISlave\_Write is called.

The encapsulation of header is done by support-lib.




**Figure 3.8 Slave sends transfer request**


### ■ SPI\_SLAVE\_NO\_ACK

This option is to reduce the complication of SPI\_SLAVE\_WITH\_PROTOCOL.

It removes the ACK response from the Slave.



**Figure 3.9 SPI Master Transfer Request (NO ACK)**



**Figure 3.10 Slave sends transfer request (NO ACK)**

### ■ SPI\_SLAVE\_NO\_PROTOCOL

This option provides no protocol for SPI Slave function, and it is configured and initialized with the API **FT4222\_SPISlave\_InitEx**.

In this SPI Slave operational mode, the Sync Word "0x5A" is not inserted. And there is no additional process in support-lib.

Users can design own protocol(s) to communicate with a SPI master.

#### 3.4.1 SPI Slave Init

FT4222\_STATUS **FT4222\_SPISlave\_Init**(FT\_HANDLE ftHandle)

### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

### Summary:

Initialize the FT4222H as an SPI slave. Default SPI\_SlaveProtocol is

SPI\_SLAVE\_WITH\_PROTOCOL. The default setting may be replaced with another SPI SLAVE initialization API **FT4222\_SPISlave\_Init\_EX**.

### Parameters:

|          |                       |
|----------|-----------------------|
| ftHandle | Handle of the device. |
|----------|-----------------------|

### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

### Error code:

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

## 3.4.2 SPI Slave Init extend function

FT4222\_STATUS **FT4222\_SPISlave\_InitEx**(FT\_HANDLE ftHandle , SPI\_SlaveProtocol protocolOpt)

### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

### Summary:

Initialize the FT4222H as an SPI slave. It is similar to **FT4222\_SPISlave\_Init** with parameters to define the SPI Slave Protocol.

### Parameters:

|             |                                                                                                                                                                                                                                                                                                                                                                 |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle    | Handle of the device.                                                                                                                                                                                                                                                                                                                                           |
| protocolOpt | SPI SLAVE protocol could be: <ul style="list-style-type: none"> <li>SPI_SLAVE_WITH_PROTOCOL<br/>With the full SPI SLAVE PROTOCOL supported. Refer to chapter 3.4</li> <li>SPI_SLAVE_NO_PROTOCOL<br/>Remove SPI SLAVE protocol, users can design their own protocol.</li> <li>SPI_SLAVE_NO_ACK<br/>Retain SPI SLAVE protocol but remove command 'ACK'</li> </ul> |

### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code

#### Error code:

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

### 3.4.3 SPI Slave Set mode function

FT4222\_STATUS **FT4222\_SPISlave\_SetMode**(FT\_HANDLE ftHandle ,FT4222\_SPICPOL cpol, FT4222\_SPICPHA cpha)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Set SPI slave CPOL and CPHA. The Default value of CPOL is CLK\_IDLE\_LOW , default value of CPHA is CLK\_LEADING.

#### Parameters:

|          |                                                                                                           |
|----------|-----------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                     |
| cpol     | Clock polarity: <ul style="list-style-type: none"> <li>• CLK_IDLE_LOW</li> <li>• CLK_IDLE_HIGH</li> </ul> |
| cpha     | Clock phase: <ul style="list-style-type: none"> <li>• CLK_LEADING</li> <li>• CLK_TRAILING</li> </ul>      |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called  
 FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.  
 FT4222\_IS\_NOT\_SPI\_MODE: The device is not in spi slave mode.

#### Prerequisite:

FT4222\_SPISlave\_InitEx or FT4222\_SPISlave\_Init

#### Example:

```

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_OpenEx("FT4222 A",FT_OPEN_BY_DESCRIPTION, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}

if (FT4222_OK != FT4222_SPISlave_InitEx(ftHandle, SPI_SLAVE_NO_PROTOCOL))
{

```

```
// init spi slave failed
return;
}

// set spi cpol and cpha to mode 3
if (FT4222_OK != FT4222_SPISlave_SetMode(ftHandle, CLK_IDLE_HIGH, CLK_TRAILING))
{
    // set spi mode failed
    return;
}
FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

### 3.4.4 SPI Slave Get Rx Status

FT4222\_STATUS **FT4222\_SPISlave\_GetRxStatus**(FT\_HANDLE ftHandle, uint16\* pRxSize)

#### Summary:

Get number of bytes in the receive queue.

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Parameters:

|          |                                                                                               |
|----------|-----------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                         |
| pRxSize  | Pointer to a variable of type uint16 which receives the number of bytes in the receive queue. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called  
 FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.  
 FT4222\_IS\_NOT\_SPI\_MODE: The device is not in spi slave mode.  
 FT4222\_INVALID\_POINTER: The parameter pRxSize is NULL.

#### Prerequisite:

FT4222\_SPISlave\_InitEx or FT4222\_SPISlave\_Init

#### Example:

Please refer to the example in [FT4222\\_SPISlave\\_Read](#).

### 3.4.5 SPI Slave Read

FT4222\_STATUS **FT4222\_SPISlave\_Read**(FT\_HANDLE ftHandle, uint8\* buffer, uint16 bytesToRead, uint16\* sizeofRead).



**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

**Summary:**

Read data from the receive queue of the SPI slave device.

**Parameters:**

|             |                                                                                               |
|-------------|-----------------------------------------------------------------------------------------------|
| ftHandle    | Handle of the device.                                                                         |
| buffer      | Pointer to the buffer that receives the data from the device.                                 |
| bytesToRead | Number of bytes to read from the device.                                                      |
| sizeofRead  | Pointer to a variable of type uint16 which receives the number of bytes read from the device. |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

FT4222\_IS\_NOT\_SPI\_MODE: The device is not in spi slave mode.

FT4222\_INVALID\_POINTER: The parameter buffer or sizeofRead is NULL.

FT4222\_INVALID\_PARAMETER: Parameter bytesToRead is equal to zero.

**Prerequisite:**

FT4222\_SPISlave\_InitEx or FT4222\_SPISlave\_Init

**Example:**

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_OpenEx("FT4222 A", FT_OPEN_BY_DESCRIPTION, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}

if (FT4222_OK != FT4222_SPISlave_InitEx(ftHandle, SPI_SLAVE_NO_PROTOCOL))
{
    // init spi slave failed
    return;
}
uint16 sizeTransferred = 0;
uint16 rxSize;
std::vector<unsigned char> recvBuf;
while(1)
{
    if(FT4222_SPISlave_GetRxStatus(ftHandle, &rxSize) == FT4222_OK)
    {

```

```

    if(rxSize>0)
    {
        recvBuf.resize(rxSize);
        if(FT4222_SPISlave_Read(ftHandle,&recvBuf[0], rxSize, &sizeTransferred)==
FT4222_OK)
        {
            // get data
        }
        else
        {
            // get data failed
        }
    }
}

FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);

```

### 3.4.6 SPI Slave Write

FT4222\_STATUS **FT4222\_SPISlave\_Write**(FT\_HANDLE ftHandle, uint8\* buffer, uint16 bytesToWrite, uint16\* sizeTransferred)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Write data to the transmit queue of the SPI slave device.

For some reasons, support lib will append a dummy byte (0x00) at the first byte automatically. This additional byte exists at all of the three transfer methods.

#### Parameters:

|                 |                                                                                                |
|-----------------|------------------------------------------------------------------------------------------------|
| ftHandle        | Handle of the device.                                                                          |
| buffer          | Pointer to the buffer that contains the data to be written to the device.                      |
| bytesToWrite    | Number of bytes to write to the device.                                                        |
| sizeTransferred | Pointer to a variable of type uint16 which receives the number of bytes written to the device. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called  
 FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.  
 FT4222\_IS\_NOT\_SPI\_MODE: The device is not in spi slave mode.  
 FT4222\_INVALID\_POINTER: The parameter buffer or sizeTransferred is NULL.  
 FT4222\_INVALID\_PARAMETER: Parameter bytesToWrite is equal to zero.

### Prerequisite:

FT4222\_SPISlave\_InitEx or FT4222\_SPISlave\_Init

### Example:

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_OpenEx("FT4222 A",FT_OPEN_BY_DESCRIPTION, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}

if (FT4222_OK != FT4222_SPISlave_InitEx(ftHandle, SPI_SLAVE_NO_PROTOCOL))
{
    // init spi slave failed
    return;
}
uint16 sizeTransferred = 0;
uint16 rxSize;
std::vector<unsigned char> sendData;
sendData.resize(3);
sendData[0] = 'a';
sendData[1] = 'b';
sendData[2] = 'c';

FT4222_SPISlave_Write(ftHandle, &sendData[0], sendData.size(), &sizeTransferred);
FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

### 3.4.7 SPI Slave RX Response Time

FT4222\_STATUS **FT4222\_SPISlave\_RxQuickResponse**(FT\_HANDLE ftHandle, BOOL enable)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | NO        |
| FT4222 Rev B        | NO        |
| FT4222 Rev C        | NO        |
| FT4222 Rev D        | YES       |

#### Summary:

Adjust SPI Slave RX response method. By default, RX quick-response function is off.

There are three rules that SPI Slave device returns the RX data to USB Host through USB PIPE.

**Rule 1:** SPI slave device does not receives USB maximum bulk size in specific time. The device returns all rx data in device's FIFO.

- The specific time is defined by FT\_SetLatencyTimer.
- The full packet size , HS is 512 bytes, FS is 64 bytes. The device must response two status bytes at every bulk-in packet. So the actual size, HS is 510 bytes, FS is 62 bytes. These two bytes are filled by device automatically and does not affect any function. The user does not need to care about it.

**Rule 2:** SPI slave device receives USB maximum bulk size in specific time. The device returns full packet data.

**Rule 3:** The option only takes effect when FT4222\_SPISlave\_RxQuickResponse is on.

- When this option turns on, the device return the rx data when the transfer gap of two bytes is larger than 1000 MCU clock. Take an example ,the default MCU frequency is 80 MHZ. 1000MCU clock is equal to  $12.5\text{ns} \times 1000 = 12.5\mu\text{s}$
- There is a constraint. The size of rx data is not the multiple of 16 bytes or data can not be returned so fast.

Rule1 and Rule 2 are mandatory. Rule 3 is optional. If Rule 3 option turns on, the priority of rule 3 is highest.

Two things needs to notice, do not enable **FT4222\_SPISlave\_RxQuickResponse** while the transaction rate below 2 Mbps or it may cause some RX data lost. The gap between two transactions should larger than 2 ms or it may cause some RX data lost.

#### Parameters:

|          |                                                                                           |
|----------|-------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                     |
| Enable   | TRUE to enable Rule3 to speed up the response time of RX data.<br>FALSE to disable Rule3. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called  
 FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.  
 FT4222\_IS\_NOT\_SPI\_MODE: The device is not in spi slave mode.

#### Prerequisite:

FT4222\_SPISlave\_InitEx or FT4222\_SPISlave\_Init

## 3.5 SPI General Functions

### 3.5.1 SPI Reset Transaction

FT4222\_STATUS **FT4222\_SPI\_ResetTransaction**(FT\_HANDLE ftHandle, uint8 spiIdx)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Reset the SPI transaction.It would purge receive and transmit buffers in the device and reset the transaction state. D2XX has similar function(FT\_PURGE) but strongly recommend to use FT4222\_SPI\_ResetTransaction.

#### Parameters:

|          |                                                                                                                                                                                                                                                                         |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                                                                                                                                                                                   |
| spiIdx   | The index of the SPI transaction, which ranges from 0~3 depending on the mode of the chip. For example, under mode 0 and mode 3 as we mentioned in <a href="#">chapter 1.1</a> , it should be 0 because there is only one SPI master or slave connection, and so forth. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_INVALID\_PARAMETER: Parameter spiIdx is incorrect. It must depend on mode of chip.

#### Prerequisite:

FT4222\_SPISlave\_InitEx or FT4222\_SPISlave\_Init or FT4222\_SPIMaster\_Init

#### Example:

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_OpenEx("FT4222 A",FT_OPEN_BY_DESCRIPTION, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
if (FT4222_OK != FT4222_SPISlave_InitEx(ftHandle, SPI_SLAVE_NO_PROTOCOL))
{
    // init spi slave failed
    return;
}
//clear TX / RX cache
if (FT4222_OK != FT4222_SPI_ResetTransaction(ftHandle, 0))
{
    // purge usb tx/rx and SPI FIFO cache
    return;
}
// read/write data to a SPI slave
FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

### 3.5.2 SPI Reset

FT4222\_STATUS **FT4222\_SPI\_Reset** (FT\_HANDLE ftHandle)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

### Summary:

Reset the SPI master or slave device. If the SPI bus encounters errors or works abnormally, this function will reset the SPI device. It is not necessary to call SPI init function again after calling this reset function. It remains all original setting of SPI.

### Parameters:

|          |                       |
|----------|-----------------------|
| ftHandle | Handle of the device. |
|----------|-----------------------|

### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

### Prerequisite:

FT4222\_SPISlave\_InitEx or FT4222\_SPISlave\_Init or FT4222\_SPIMaster\_Init

## 3.5.3 SPI Set Driving Strength

FT4222\_STATUS **FT4222\_SPI\_SetDrivingStrength**(FT\_HANDLE ftHandle,

SPI\_DrivingStrength clkStrength,  
 SPI\_DrivingStrength ioStrength,  
 SPI\_DrivingStrength ssoStrength)

### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

### Summary:

For the FT4222H SPI, set the driving strength of clk, io, and sso pins. Default driving strength of all spi pins are 4MA. DS\_4MA is adopted mostly. Unless there is some hardware wiring requirement for device, set driving strength to 4MA is enough.

### Parameters:

|             |                                                                                                                                                                           |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle    | Handle of the device.                                                                                                                                                     |
| clkStrength | The driving strength of the clk pin (SPI master only): <ul style="list-style-type: none"> <li>• DS_4MA</li> <li>• DS_8MA</li> <li>• DS_12MA</li> <li>• DS_16MA</li> </ul> |
| ioStrength  | The driving strength of the io pin: <ul style="list-style-type: none"> <li>• DS_4MA</li> <li>• DS_8MA</li> <li>• DS_12MA</li> <li>• DS_16MA</li> </ul>                    |
| ssoStrength | The driving strength of the sso pin (SPI master only): <ul style="list-style-type: none"> <li>• DS_4MA</li> <li>• DS_8MA</li> </ul>                                       |

|  |                                                                                |
|--|--------------------------------------------------------------------------------|
|  | <ul style="list-style-type: none"> <li>• DS_12MA</li> <li>• DS_16MA</li> </ul> |
|--|--------------------------------------------------------------------------------|

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_IS\_NOT\_SPI\_MODE: The device is not in spi slave mode.

#### Prerequisite:

FT4222\_SPISlave\_InitEx or FT4222\_SPISlave\_Init or FT4222\_SPIMaster\_Init

## 3.6 I<sup>2</sup>C Master Functions

I<sup>2</sup>C (Inter Integrated Circuit) is a multi-master serial bus invented by Philips. I<sup>2</sup>C uses two bi-directional open-drain wires called serial data (SDA) and serial clock (SCL). Common I<sup>2</sup>C bus speeds are the 100 kbit/s standard mode (SM), 400 kbit/s fast mode (FM), 1 Mbit/s Fast mode plus (FM+), and 3.4 Mbit/s High Speed mode (HS)

The FT4222H device can be initialized as either an I<sup>2</sup>C master or I<sup>2</sup>C slave under mode 0 and mode 3. Here is a brief overview of FT4222H I<sup>2</sup>C features:

- Fully compatible to I<sup>2</sup>C v2.1 and v3 specification
- 7-bit address support
- Support 4 speed configurations: 100KHz(SM), 400KHz(FM), 1MHz(FM+), and 3.4MHz(HS).
- Clock stretching support in both master and slave mode.

Refer to [DS\\_FT4222H](#) for more details.

### 3.6.1 I<sup>2</sup>C Master Init

FT4222\_STATUS **FT4222\_I2CMaster\_Init**(FT\_HANDLE ftHandle, uint32 kbps)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Initialize the FT4222H as an I<sup>2</sup>C master with the requested I<sup>2</sup>C speed.

#### Parameters:

|          |                                                                                                                                                                                                                                                                                 |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                                                                                                                                                                                           |
| kbps     | The speed of I <sup>2</sup> C transmission. It ranges from 60K bps to 3400K bps. By specified speed, the initialization function helps to setup the bus speed with the corresponding mode. This parameter is used to configure the FT4222H to be either SM, FB, FM+ or HS mode. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

FT4222\_I2C\_NOT\_SUPPORTED\_IN\_THIS\_MODE: I2C is not supported in mode 1 and mode 2.

#### Example:

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
// initial i2c master with 1000K bps
ft4222Status = FT4222_I2CMaster_Init(ftHandle, 1000);
if (FT4222_OK != ft4222Status)
{
    // i2c master init failed
    return;
}
FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

### 3.6.2 I<sup>2</sup>C Master Read

FT4222\_STATUS **FT4222\_I2CMaster\_Read**(FT\_HANDLE ftHandle, uint16 slaveAddress, uint8\* buffer, uint16 bytesToRead, uint16\* sizeTransferred)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Read data from the specified I2C slave device with START and STOP conditions.

#### Parameters:

|                 |                                                                                               |
|-----------------|-----------------------------------------------------------------------------------------------|
| ftHandle        | Handle of the device.                                                                         |
| slaveAddress    | Address of the target I <sup>2</sup> C slave.                                                 |
| buffer          | Pointer to the buffer that receives data from the device.                                     |
| bytesToRead     | Number of bytes to read from the device.                                                      |
| sizeTransferred | Pointer to a variable of type uint16 which receives the number of bytes read from the device. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.



**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.  
FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode  
FT4222\_INVALID\_POINTER: Parameter buffer is NULL  
FT4222\_INVALID\_PARAMETER: bytesToRead is equal to zero  
FT4222\_FAILED\_TO\_READ\_DEVICE: Failed to read data.

**Prerequisite:**

FT4222\_I2CMaster\_Init

**Example:**

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;

ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
// initial i2c master with 1000K bps
ft4222Status = FT4222_I2CMaster_Init(ftHandle, 1000);
if (FT4222_OK != ft4222Status)
{
    // i2c master init failed
    return;
}
const uint16 slaveAddr = 0x22;
uint8 slave_data[4];
uint16 sizeTransferred = 0;

// read 4 bytes data from master
ft4222Status = FT4222_I2CMaster_Read(ftHandle, slaveAddr, slave_data, sizeof(slave_data),
&sizeTransferred);
if (FT4222_OK == ft4222Status)
{
    // read data success
}
else
{
    // read data failed
}

FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

**3.6.3 I<sup>2</sup>C Master Write**

FT4222\_STATUS **FT4222\_I2CMaster\_Write**(FT\_HANDLE ftHandle, uint16 slaveAddress, uint8\* buffer, uint16 bytesToWrite, uint16\* sizeTransferred)

**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |

|              |     |
|--------------|-----|
| FT4222 Rev C | YES |
| FT4222 Rev D | YES |

### Summary:

Write data to the specified I<sup>2</sup>C slave device with START and STOP conditions.

### Parameters:

|                 |                                                                                                |
|-----------------|------------------------------------------------------------------------------------------------|
| ftHandle        | Handle of the device.                                                                          |
| slaveAddress    | Address of the target I <sup>2</sup> C slave.                                                  |
| buffer          | Pointer to the buffer that contains the data to be written to the device.                      |
| bytesToWrite    | Number of bytes to write to the device.                                                        |
| sizeTransferred | Pointer to a variable of type uint16 which receives the number of bytes written to the device. |

### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode

FT4222\_INVALID\_POINTER: Parameter buffer is NULL

FT4222\_INVALID\_PARAMETER: bytesToWrite is equal to zero

FT4222\_FAILED\_TO\_WRITE\_DEVICE: Failed to write data.

### Prerequisite:

FT4222\_I2CMaster\_Init

### Example:

```

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
// initial i2c master with 1000K bps
ft4222Status = FT4222_I2CMaster_Init(ftHandle, 1000);
if (FT4222_OK != ft4222Status)
{
    // i2c master init failed
    return;
}
const uint16 slaveAddr = 0x22;
uint8 master_data[] = {0x1A, 0x2B, 0x3C, 0x4D};
uint16 sizeTransferred = 0;

// write 4 bytes data to master
ft4222Status = FT4222_I2CMaster_Write(ftHandle, slaveAddr, master_data,
sizeof(master_data), &sizeTransferred);
if (FT4222_OK == ft4222Status)
{
    // write data success

```

```

}
else
{
    // write data failed
}

FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);

```

### 3.6.4 I<sup>2</sup>C Master Write Extension

FT4222\_STATUS **FT4222\_I2CMaster\_WriteEx**(FT\_HANDLE ftHandle, uint16 deviceAddress, uint8 flag, uint8\* buffer, uint16 bytesToWrite, uint16\* sizeTransferred)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | NO        |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

I<sup>2</sup>C defines basic types of transactions, each of which begins with a START and ends with a STOP:

- Single message where a master writes data to a slave.
- Single message where a master reads data from a slave.
- Combined format, where a master issues at least two reads or writes to one or more slaves.

In a combined transaction, each read or write begins with a START and the slave address. The START conditions after the first are also called *repeated START* bits. Repeated STARTs are not preceded by STOP conditions, which is how slaves know that the next message is part of the same transaction.

This function is supported by the rev B FT4222H or later.

#### Parameters:

|                 |                                                                                                                                                                                                                                                                                                      |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle        | Handle of the device.                                                                                                                                                                                                                                                                                |
| slaveAddress    | Address of the target I <sup>2</sup> C slave.                                                                                                                                                                                                                                                        |
| flag            | The I <sup>2</sup> C condition will be sent with this I <sup>2</sup> C transaction <ul style="list-style-type: none"> <li>• START = 0x02</li> <li>• Repeated_START = 0x03<br/>Repeated_START will not send master code in HS mode</li> <li>• STOP = 0x04</li> <li>• START_AND_STOP = 0x06</li> </ul> |
| buffer          | Pointer to the buffer that contains the data to be written to the device.                                                                                                                                                                                                                            |
| bytesToWrite    | Number of bytes to write to the device.                                                                                                                                                                                                                                                              |
| sizeTransferred | Pointer to a variable of type uint16 which receives the number of bytes written to the device.                                                                                                                                                                                                       |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.  
 FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode

FT4222\_INVALID\_POINTER: Parameter buffer is NULL  
FT4222\_INVALID\_PARAMETER: bytesToWrite is equal to zero  
FT4222\_FAILED\_TO\_WRITE\_DEVICE: Failed to write data.

**Prerequisite:**

FT4222\_I2CMaster\_Init

**Example:**

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
// initial i2c master with 1000K bps
ft4222Status = FT4222_I2CMaster_Init(ftHandle, 1000);
if (FT4222_OK != ft4222Status)
{
    // i2c master init failed
    return;
}
const uint16 slaveAddr = 0x22;
uint8 write_req[1];
uint8 recvBuf[16];
uint16 sizeTransferred = 0;
write_req[0] = 0x00; // addr
ft4222Status = FT4222_I2CMaster_WriteEx(ftHandle, slaveAddr, START, &write_req[0], 1,
&sizeTransferred);
if (FT4222_OK == ft4222Status)
{
    // write data success
}
else
{
    // write data failed
}
ft4222Status = FT4222_I2CMaster_ReadEx(ftHandle, slaveAddr, Repeated_START | STOP,
&recvBuf[0], 16, &sizeTransferred);
if (FT4222_OK == ft4222Status)
{
    // read data success
}
else
{
    // read data failed
}

FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

**3.6.5 I<sup>2</sup>C Master Read Extension**

FT4222\_STATUS **FT4222\_I2CMaster\_ReadEx**(FT\_HANDLE ftHandle, uint16 deviceAddress, uint8 flag, uint8\* buffer, uint16 bytesToRead, uint16\* sizeTransferred).

## Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | NO        |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

## Summary:

Read data from the specified I<sup>2</sup>C slave device with the specified I<sup>2</sup>C condition.  
 This function is supported by the rev B FT4222H or later.

## Parameters:

|                 |                                                                                                                                                                                                                                                                                              |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle        | Handle of the device.                                                                                                                                                                                                                                                                        |
| slaveAddress    | Address of the target I <sup>2</sup> C slave.                                                                                                                                                                                                                                                |
| flag            | The I <sup>2</sup> C condition will be sent with this I <sup>2</sup> C transaction <ul style="list-style-type: none"> <li>START = 0x02</li> <li>Repeated_START = 0x03<br/>Repeated_START will not send master code in HS mode</li> <li>STOP = 0x04</li> <li>START_AND_STOP = 0x06</li> </ul> |
| buffer          | Pointer to the buffer that receives the data from the device.                                                                                                                                                                                                                                |
| bytesToRead     | Number of bytes to read from the device.                                                                                                                                                                                                                                                     |
| sizeTransferred | Pointer to a variable of type uint16 which receives the number of bytes read from the device.                                                                                                                                                                                                |

## Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

## Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode

FT4222\_INVALID\_POINTER: Parameter buffer is NULL

FT4222\_INVALID\_PARAMETER: bytesToRead is equal to zero

FT4222\_FAILED\_TO\_READ\_DEVICE: Failed to read data.

## Prerequisite:

FT4222\_I2CMaster\_Init

## Example:

Please refer to the example in [FT4222\\_I2CMaster\\_WriteEx](#)

## I<sup>2</sup>C combined message support

In a combined message, each read or write begins with a START and the slave address. After the first START, the subsequent starts are referred to as repeated START bits; repeated START bits are not preceded by STOP bits, which indicate to the slave the next transfer is part of the same message.

|       |                     |       |     |            |     |    |                     |      |     |            |     |            |     |      |
|-------|---------------------|-------|-----|------------|-----|----|---------------------|------|-----|------------|-----|------------|-----|------|
| Start | 7 bit slave address | write | ACK | 8 bit data | ACK | SR | 7 bit slave address | Read | ACK | 8 bit data | ACK | 8 bit data | ACK | STOP |
|-------|---------------------|-------|-----|------------|-----|----|---------------------|------|-----|------------|-----|------------|-----|------|

SR = repeated START condition

Here is an example for typical usage of I<sup>2</sup>C combined message:

```
// Write to I2C slave with START bit
```

```
FT4222_I2CMaster_WriteEx(ftHandle, deviceAddress, START, buffer, bufferSize,
sizeTransferred);
```

```
// Read from I2C slave with Repeated START and STOP bit
// Use Repeated_START flag instead of START to avoid the FT4222H sending master
code
// again in HS mode
```

```
FT4222_I2CMaster_ReadEx(ftHandle, deviceAddress, Repeated_START | STOP, buffer,
bufferSize, sizeTransferred);
```

### 3.6.6 I<sup>2</sup>C Master GetStatus

```
FT4222_STATUS FT4222_I2CMaster_GetStatus(FT_HANDLE ftHandle, uint8 *controllerStatus)
```

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Read the status of the I<sup>2</sup>C master controller. This can be used to poll a slave after i2c transmission is complete.

#### Parameters:

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle         | Handle of the device.                                                                                                                                                                                                                                                                                                                                                                                                                         |
| controllerStatus | Address of byte to receive status flags:<br>bit 0: controller busy: all other status bits invalid<br>bit 1: error condition<br>bit 2: slave address was not acknowledged during last operation<br>bit 3: data not acknowledged during last operation<br>bit 4: arbitration lost during last operation<br>bit 5: controller idle<br>bit 6: bus busy<br>The header file provides convenience macros (such as I2CM_BUS_BUSY) to test these bits. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Prerequisite:

FT4222\_I2CMaster\_Init

### 3.6.7 I<sup>2</sup>C Master Reset

FT4222\_STATUS **FT4222\_I2CMaster\_Reset**(FT\_HANDLE ftHandle)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Reset the I<sup>2</sup>C master device.

If the I<sup>2</sup>C bus encounters errors or works abnormally, this function will reset the I<sup>2</sup>C device. It is not necessary to call I2CMaster\_Init again after calling this reset function. This function will maintain the original i2c master setting and clear all cache in the device. D2XX has similar function(FT\_PURGE) but strongly recommend to use FT4222\_I2CMaster\_Reset.

#### Parameters:

|          |                       |
|----------|-----------------------|
| ftHandle | Handle of the device. |
|----------|-----------------------|

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode

#### Prerequisite:

FT4222\_I2CMaster\_Init

## 3.7 I<sup>2</sup>C Slave Functions

The FT4222H device can be initialized as an I<sup>2</sup>C slave under mode 0 and mode 3. It conforms to v2.1 and v3.0 of the I<sup>2</sup>C specification and supports all the transmission modes: Standard, Fast, Fast-plus and High Speed.

When the I<sup>2</sup>C slave receives data from the I<sup>2</sup>C bus, it will keep the data in its internal receive buffer (256 bytes), and then send the data to the USB host through IN packets.

When data is requested by an I<sup>2</sup>C master, data will be moved from an OUT packet to the transmit register directly.

### 3.7.1 I<sup>2</sup>C Slave Init

FT4222\_STATUS **FT4222\_I2CSlave\_Init**(FT\_HANDLE ftHandle)

#### Summary:

Initialize FT4222H as an I<sup>2</sup>C slave. After FT4222\_I2CSlave\_Init , I2C slave address is reset to 0x40.

**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

**Parameters:**

|          |                       |
|----------|-----------------------|
| ftHandle | Handle of the device. |
|----------|-----------------------|

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_I2C\_NOT\_SUPPORTED\_IN\_THIS\_MODE: I2C is not supported in mode 1 and mode 2.

**Example:**

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
// initial i2c slave
ft4222Status = FT4222_I2CSlave_Init(ftHandle);
if (FT4222_OK != ft4222Status)
{
    // i2c slave init failed
    return;
}
FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

**3.7.2 I<sup>2</sup>C Slave Get Address**

FT4222\_STATUS **FT4222\_I2CSlave\_GetAddress**(FT\_HANDLE ftHandle, uint8\* pAddr)

**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

**Summary:**

Get the address of the I2C slave device. The default address is 0x40.



**Parameters:**

|          |                                                                                                       |
|----------|-------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                 |
| pAddr    | Pointer to a variable of type uint16 which receives the address of the I <sup>2</sup> C slave device. |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode

**Prerequisite:**

FT4222\_I2CSlave\_Init

**Example:**

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
// initial i2c slave
ft4222Status = FT4222_I2CSlave_Init(ftHandle);
if (FT4222_OK != ft4222Status)
{
    // i2c slave init failed
    return;
}
uint8 i2cAddr;
// set new i2c slave addr
i2cAddr = 0x25;
ft4222Status = FT4222_I2CSlave_SetAddress(ftHandle, i2cAddr);
if (FT4222_OK != ft4222Status)
{
    // i2c slave get addr failed
    return;
}
ft4222Status = FT4222_I2CSlave_GetAddress(ftHandle, &i2cAddr);
if (FT4222_OK != ft4222Status)
{
    // i2c slave get addr failed
    return;
}
FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

**3.7.3 I<sup>2</sup>C Slave Set Address**

FT4222\_STATUS **FT4222\_I2CSlave\_SetAddress**(FT\_HANDLE ftHandle, uint8 addr)

**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

**Summary:**

Set the address of the I<sup>2</sup>C slave device.

**Parameters:**

|          |                                                         |
|----------|---------------------------------------------------------|
| ftHandle | Handle of the device.                                   |
| addr     | The 7-bit address of the I <sup>2</sup> C slave device. |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode

**Prerequisite:**

FT4222\_I2CSlave\_Init

**Example:**

Please refer to the example in [FT4222\\_I2CSlave\\_GetAddress](#)

### 3.7.4 I<sup>2</sup>C Slave Get Rx Status

FT4222\_STATUS **FT4222\_I2CSlave\_GetRxStatus**(FT\_HANDLE ftHandle, uint16\* pRxSize)

**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

**Summary:**

Get number of bytes in the receive queue.

**Parameters:**

|          |                                                                                               |
|----------|-----------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                         |
| pRxSize  | Pointer to a variable of type uint16 which receives the number of bytes in the receive queue. |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.  
FT4222\_INVALID\_POINTER: Parameter pRxSize is NULL

**Prerequisite:**

FT4222\_I2CSlave\_Init

**Example:**

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
// initial i2c slave
ft4222Status = FT4222_I2CSlave_Init(ftHandle);
if (FT4222_OK != ft4222Status)
{
    // i2c slave init failed
    return;
}
ft4222Status = FT4222_I2CSlave_SetClockStretch(ftHandle, TRUE);
if (FT4222_OK != ft4222Status)
{
    // set clock stretch failed
    return;
}
while(1)
{
    uint16 rxSize;

    if(FT4222_I2CSlave_GetRxStatus(ftHandle, &rxSize) == FT4222_OK)
    {
        if(rxSize>0)
        {
            uint8 *pRead_data = (uint8 *)malloc(rxSize) ;
            uint16 sizeTransferred;

            if(FT4222_I2CSlave_Read(ftHandle,pRead_data, rxSize, &sizeTransferred)==
FT4222_OK)
            {
                // got slave data
            }
            free(pRead_data);
        }
    }
    else
    {
        printf("I2C slave get status error\n");
    }
}

FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

### 3.7.5 I<sup>2</sup>C Slave Read

FT4222\_STATUS **FT4222\_I2CSlave\_Read**(FT\_HANDLE ftHandle, uint8\* buffer, uint16 bytesToRead, uint16\* sizeTransferred)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Read data from the buffer of the I<sup>2</sup>C slave device.

#### Parameters:

|                 |                                                                                               |
|-----------------|-----------------------------------------------------------------------------------------------|
| ftHandle        | Handle of the device.                                                                         |
| buffer          | Pointer to the buffer that receives the data from the device.                                 |
| bytesToRead     | Number of bytes to read from the device.                                                      |
| sizeTransferred | Pointer to a variable of type uint16 which receives the number of bytes read from the device. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.  
 FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode  
 FT4222\_INVALID\_POINTER: Parameter buffer or sizeTransferred is NULL  
 FT4222\_INVALID\_PARAMETER: Parameter bytesToRead is equal to zero

#### Prerequisite:

FT4222\_I2CSlave\_Init

#### Example:

Please refer to the example in [FT4222\\_I2CSlave\\_GetRxStatus](#)

### 3.7.6 I<sup>2</sup>C Slave Write

FT4222\_STATUS **FT4222\_I2CSlave\_Write**(FT\_HANDLE ftHandle, uint8\* buffer, uint16 bytesToWrite, uint16\* sizeTransferred)

#### Summary:

Write data to the buffer of I<sup>2</sup>C slave device.

#### Parameters:

|                 |                                                                                                |
|-----------------|------------------------------------------------------------------------------------------------|
| ftHandle        | Handle of the device.                                                                          |
| buffer          | Pointer to the buffer that contains the data to be written to the device.                      |
| bytesToWrite    | Number of bytes to write to the device.                                                        |
| sizeTransferred | Pointer to a variable of type uint16 which receives the number of bytes written to the device. |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode

FT4222\_INVALID\_POINTER: Parameter buffer or sizeTransferred is NULL

FT4222\_INVALID\_PARAMETER: Parameter bytesToWrite is equal to zero

FT4222\_FAILED\_TO\_WRITE\_DEVICE: Write data timeout or failed. FT\_SetTimeouts can be called to extend timeout.

**Prerequisite:**

FT4222\_I2CSlave\_Init

**Example:**

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
// initial i2c slave
ft4222Status = FT4222_I2CSlave_Init(ftHandle);
if (FT4222_OK != ft4222Status)
{
    // i2c slave init failed
    return;
}
ft4222Status = FT4222_I2CSlave_SetClockStretch(ftHandle, TRUE);
if (FT4222_OK != ft4222Status)
{
    // set clock stretch failed
    return;
}
uint8 sent_data[] = {0x1A, 0x2B, 0x3C, 0x4D};
uint16 sizeTransferred = 0;

ft4222Status = FT4222_I2CSlave_Write(ftHandle, sent_data, sizeof(sent_data),
&sizeTransferred);
if (FT4222_OK != ft4222Status)
{
    // write data error
}
FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

**3.7.7 I<sup>2</sup>C Slave Reset**

FT4222\_STATUS **FT4222\_I2CSlave\_Reset**(FT\_HANDLE ftHandle)

**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

**Summary:**

Reset the I<sup>2</sup>C slave device. This function will maintain the original i2c slave setting and clear all cache in the device. D2XX has similar function (FT\_PURGE) but strongly recommend to use FT4222\_I2CSlave\_Reset

**Parameters:**

|          |                       |
|----------|-----------------------|
| ftHandle | Handle of the device. |
|----------|-----------------------|

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode

**Prerequisite:**

FT4222\_I2CSlave\_Init

**Example:**

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_Open(0, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
// initial i2c slave
ft4222Status = FT4222_I2CSlave_Init(ftHandle);
if (FT4222_OK != ft4222Status)
{
    // i2c slave init failed
    return;
}
ft4222Status = FT4222_I2CSlave_Reset(ftHandle);
if (FT4222_OK != ft4222Status)
{
    // reset i2c slave failed
    return;
}
FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

### 3.7.8 I<sup>2</sup>C Slave Clock Stretch

FT4222\_STATUS **FT4222\_I2CSlave\_SetClockStretch**(FT\_HANDLE ftHandle, BOOL enable)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | NO        |
| FT4222 Rev B        | NO        |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Enable or disable Clock Stretch. The default setting of clock stretching is disabled.

Clock stretch is as a flow-control mechanism for slaves. An addressed slave device may hold the clock line (SCL) low after receiving (or sending) a byte, indicating that it is not yet ready to process more data. The master that is communicating with the slave may not finish the transmission of the current bit, but must wait until the clock line actually goes high.

#### Parameters:

|          |                                                                                    |
|----------|------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                              |
| Enable   | TRUE to enable I2C slave clock stretch<br>FALSE to disable I2C slave clock stretch |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is a FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode

#### Prerequisite:

FT4222\_I2CSlave\_Init

#### Example:

Please refer to the example in [FT4222\\_I2CSlave\\_Write](#).

### 3.7.9 I<sup>2</sup>C Slave Set Response Word

FT4222\_STATUS **FT4222\_I2CSlave\_SetRespWord** (FT\_HANDLE ftHandle, uint8 responseWord)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | NO        |
| FT4222 Rev B        | NO        |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

**Summary:**

This function only takes effect when Clock Stretch is disabled. When data is requested by an I<sup>2</sup>C master and the device is not ready to respond, the device will respond a default value. Default value is 0xFF. This function can be used to set the response word

**Parameters:**

|              |                                                                        |
|--------------|------------------------------------------------------------------------|
| ftHandle     | Handle of the device.                                                  |
| responseWord | The response word when the device is not ready to send data to master. |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is a FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_IS\_NOT\_I2C\_MODE: The device is not in i2c slave mode

**Prerequisite:**

FT4222\_I2CSlave\_Init

## 3.8 GPIO Functions

The FT4222H contains 4 GPIO. When the USB GPIO interface is supported, chip mode 0 and mode 1, LibFT4222 helps application developers to control GPIO directly. However, each GPIO pin is multiplexed with interrupt/suspend out/SPI slave select/I2C functions as listed below:

- gpio0 / ss1o / scl
- gpio1 / ss2o / sda
- gpio2 / ss3o / suspend out
- gpio3 / wakeup/intr

The number of GPIO pins available depends on the mode of the chip. For example, if the FT4222H is initialized as an I<sup>2</sup>C device, as shown above, the pins of gpio0 and gpio1 will be switched to scl and sda, and cannot be used as GPIO. If suspend out and remote wakeup are enabled gpio2 and gpio3 cannot be used as GPIO.

The FT4222H supports GPIO on the second USB interface in mode 0 or on the fourth interface in mode 2 (Please refer [table 2.1](#) for chip mode and interface).

### 3.8.1 GPIO Init

FT4222\_STATUS **FT4222\_GPIO\_Init**(FT\_HANDLE ftHandle, GPIO\_Dir gpioDir[4])

**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

**Summary:**

Initialize the GPIO interface of the FT4222H.

Please note the GPIO interface is available on the 2<sup>nd</sup> USB interface in mode 0 or on the 4<sup>th</sup> USB interface in mode 1.



**Parameters:**

|          |                                                                                                                                                               |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                                                                         |
| gpioDir  | An array defines the directions of 4 GPIO pins. The GPIO direction will be: <ul style="list-style-type: none"> <li>GPIO_OUTPUT</li> <li>GPIO_INPUT</li> </ul> |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

FT4222\_GPIO\_NOT\_SUPPORTED\_IN\_THIS\_MODE: GPIO function is not supported in mode 2 and mode 3

**Example:**

Please refer to the example in [FT4222 GPIO Read](#).

### 3.8.2 GPIO Read

FT4222\_STATUS **FT4222\_GPIO\_Read**(FT\_HANDLE ftHandle, GPIO\_Port portNum, BOOL\* pValue)

**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

**Summary:**

Read the status of a specified GPIO pin or interrupt register.

**Parameters:**

|          |                                                                                                                                                                                                                                                                                                                                                        |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                                                                                                                                                                                                                                                                  |
| portNum  | One of the following GPIO ports: <ul style="list-style-type: none"> <li>GPIO_PORT0</li> <li>GPIO_PORT1</li> <li>GPIO_PORT2</li> <li>GPIO_PORT3</li> </ul>                                                                                                                                                                                              |
| pValue   | Pointer to a variable of type BOOL which receives the value of the GPIO pin.<br>For GPIO :<br>TRUE means voltage level is high now<br>FALSE mean voltage level is low now<br><br>For Interrupt:<br>TRUE means trigger condition is invoked<br>FALSE means trigger condition is not invoked<br>Interrupt status is cleared after calling this function. |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.  
 FT4222\_GPIO\_NOT\_SUPPORTED\_IN\_THIS\_MODE: GPIO function is not supported in mode 2 and mode 3

#### Example:

// this is an example for gpio read

```
FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_OpenEx("FT4222 B", FT_OPEN_BY_DESCRIPTION, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
GPIO_Dir gpioDir[4];
gpioDir[0] = GPIO_INPUT;
gpioDir[1] = GPIO_INPUT;
gpioDir[2] = GPIO_INPUT;
gpioDir[3] = GPIO_INPUT;
FT4222_GPIO_Init(ftHandle, gpioDir);
//disable suspend out , enable gpio 2
FT4222_SetSuspendOut(ftHandle, false);
//disable interrupt , enable gpio 3
FT4222_SetWakeUpInterrupt(ftHandle, false);
BOOL value;
if(FT4222_GPIO_Read(ftHandle, (GPIO_Port)GPIO_PORT3, &value) == FT4222_OK)
{
    // got gpio status
}

FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);
```

// for interrupt read, please refer to the example2 in [FT4222\\_SetInterruptTrigger](#)

### 3.8.3 GPIO Write

FT4222\_STATUS **FT4222\_GPIO\_Write**(FT\_HANDLE ftHandle, GPIO\_Port portNum, BOOL bValue)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

#### Summary:

Write value to the specified GPIO pin.

#### Parameters:

|          |                                 |
|----------|---------------------------------|
| ftHandle | Handle of the device.           |
| portNum  | One of the following GPIO port: |

|        |                                                                                                                                  |
|--------|----------------------------------------------------------------------------------------------------------------------------------|
|        | <ul style="list-style-type: none"> <li>• GPIO_PORT0</li> <li>• GPIO_PORT1</li> <li>• GPIO_PORT2</li> <li>• GPIO_PORT3</li> </ul> |
| bValue | The output value.                                                                                                                |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_GPIO\_NOT\_SUPPORTED\_IN\_THIS\_MODE: GPIO function is not supported in mode 2 and mode 3

FT4222\_GPIO\_WRITE\_NOT\_SUPPORTED: Direction on this port is not writing direction.

#### Prerequisite:

FT4222\_GPIO\_Init

#### Example:

```

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_OpenEx("FT4222 B",FT_OPEN_BY_DESCRIPTION, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
GPIO_Dir gpioDir[4];
gpioDir[0] = GPIO_OUTPUT;
gpioDir[1] = GPIO_OUTPUT;
gpioDir[2] = GPIO_OUTPUT;
gpioDir[3] = GPIO_OUTPUT;
FT4222_GPIO_Init(ftHandle, gpioDir);

//disable suspend out , enable gpio 2
FT4222_SetSuspendOut(ftHandle, false);

//disable interrupt , enable gpio 3
FT4222_SetWakeUpInterrupt(ftHandle, false);

// set gpio0/gpio1/gpio2/gpio3 output level high
FT4222_GPIO_Write(ftHandle, GPIO_PORT0, 1);
FT4222_GPIO_Write(ftHandle, GPIO_PORT1, 1);
FT4222_GPIO_Write(ftHandle, GPIO_PORT2, 1);
FT4222_GPIO_Write(ftHandle, GPIO_PORT3, 1);
FT4222_UnInitialize(ftHandle);
FT_Close(ftHandle);

```

### 3.8.4 GPIO Set Input Trigger

FT4222\_STATUS **FT4222\_GPIO\_SetInputTrigger**(FT\_HANDLE ftHandle, GPIO\_Port portNum, GPIO\_Trigger trigger)

**Supported Chip:**

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

**Summary:**

Set software trigger conditions on the specified GPIO pin.

This function allows developers to monitor value changes of the GPIO pins. Values that satisfy the trigger condition will be stored in a queue. For example, if GPIO\_TRIGGER\_RISING is set on GPIO0, and GPIO0 then changes value from 0 to 1, the event GPIO\_TRIGGER\_RISING will be recorded into the queue. Developers can query the queue status by FT4222\_GPIO\_GetTriggerStatus, and FT4222\_GPIO\_ReadTriggerQueue.

This function can only set gpio trigger conditions. For interrupt trigger conditions, please refer to [FT4222\\_SetInterruptTrigger](#).

**Parameters:**

|          |                                                                                                                                                                                                                  |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                                                                                                                            |
| portNum  | One of the following GPIO port: <ul style="list-style-type: none"><li>GPIO_PORT0</li><li>GPIO_PORT1</li><li>GPIO_PORT2</li><li>GPIO_PORT3</li></ul>                                                              |
| trigger  | Combination of the following trigger conditions: <ul style="list-style-type: none"><li>GPIO_TRIGGER_RISING</li><li>GPIO_TRIGGER_FALLING</li><li>GPIO_TRIGGER_LEVEL_HIGH</li><li>GPIO_TRIGGER_LEVEL_LOW</li></ul> |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is an FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_GPIO\_NOT\_SUPPORTED\_IN\_THIS\_MODE: GPIO function is not supported in mode 2 and mode 3

FT4222\_GPIO\_INPUT\_NOT\_SUPPORTED: Direction on this port is not reading direction.

**Prerequisite:**

FT4222\_GPIO\_Init

**Example:**

Please refer the example in [FT4222\\_GPIO\\_ReadTriggerQueue](#)

**3.8.5 GPIO Get Trigger Status**

FT4222\_STATUS **FT4222\_GPIO\_GetTriggerStatus**(FT\_HANDLE ftHandle, GPIO\_Port portNum, uint16\* pQueueSize)

### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

### Summary:

Get the size of trigger event queue.

### Parameters:

|            |                                                                                                                                                          |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle   | Handle of the device.                                                                                                                                    |
| portNum    | One of the following GPIO port: <ul style="list-style-type: none"> <li>GPIO_PORT0</li> <li>GPIO_PORT1</li> <li>GPIO_PORT2</li> <li>GPIO_PORT3</li> </ul> |
| pQueueSize | Pointer to a variable of type uint16 where the returning value will be stored.                                                                           |

### Return Value:

FT4222\_OK if successful, otherwise the return value is an FT error code.

### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_GPIO\_NOT\_SUPPORTED\_IN\_THIS\_MODE: GPIO function is not supported in mode 2 and mode 3

FT4222\_INVALID\_POINTER: Parameter pQueueSize is NULL.

### Prerequisite:

FT4222\_GPIO\_Init

### Example:

Please refer the example in [FT4222\\_GPIO\\_ReadTriggerQueue](#).

## 3.8.6 GPIO Read Trigger Queue

FT4222\_STATUS **FT4222\_GPIO\_ReadTriggerQueue**(FT\_HANDLE ftHandle, GPIO\_Port portNum, GPIO\_Trigger\* events, uint16 readSize, uint16\* sizeofRead)

### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | YES       |
| FT4222 Rev B        | YES       |
| FT4222 Rev C        | YES       |
| FT4222 Rev D        | YES       |

### Summary:

Get events recorded in the trigger event queue. Trigger conditions are set by a call to FT4222\_GPIO\_SetInputTrigger for a GPIO or FT4222\_SetInterruptTrigger for an interrupt. After calling this function, all events will be removed from the event queue.

**Parameters:**

|            |                                                                                                                                                                                                                                                                                                                                                             |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle   | Handle of the device.                                                                                                                                                                                                                                                                                                                                       |
| portNum    | One of the following GPIO port: <ul style="list-style-type: none"> <li>GPIO_PORT0</li> <li>GPIO_PORT1</li> <li>GPIO_PORT2</li> <li>GPIO_PORT3</li> </ul>                                                                                                                                                                                                    |
| events     | Pointer to the buffer that receives the values of the trigger event queue. The value of events will be: <ul style="list-style-type: none"> <li>GPIO_TRIGGER_RISING</li> <li>GPIO_TRIGGER_FALLING</li> <li>GPIO_TRIGGER_LEVEL_HIGH</li> <li>GPIO_TRIGGER_LEVEL_LOW</li> </ul>                                                                                |
| readSize   | Number of bytes to read from trigger event queue.                                                                                                                                                                                                                                                                                                           |
| sizeofRead | Pointer to a variable of type uint16 which receives the number of bytes read from the queue.<br>Queue data is cleared after calling this function<br>For GPIO :<br>The trigger condition needs to be set by the function FT4222_GPIO_SetInputTrigger<br>For Interrupt :<br>The trigger condition needs to be set by the function FT4222_SetInterruptTrigger |

**Return Value:**

FT4222\_OK if successful, otherwise the return value is a FT error code.

**Error code:**

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.

FT4222\_GPIO\_NOT\_SUPPORTED\_IN\_THIS\_MODE: GPIO function is not supported in mode 2 and mode 3

**Prerequisite:**

FT4222\_GPIO\_Init

**Example:**

```

FT_HANDLE ftHandle = NULL;
FT_STATUS ftStatus;
FT4222_STATUS ft4222Status;
ftStatus = FT_OpenEx("FT4222 B",FT_OPEN_BY_DESCRIPTION, &ftHandle);
if (FT_OK != ftStatus)
{
    // open failed
    return;
}
GPIO_Dir gpioDir[4];
gpioDir[0] = GPIO_INPUT;
gpioDir[1] = GPIO_OUTPUT;
gpioDir[2] = GPIO_OUTPUT;
gpioDir[3] = GPIO_OUTPUT;
FT4222_GPIO_Init(ftHandle, gpioDir);
uint16 queueSize;
FT4222_GPIO_SetInputTrigger(ftHandle,
    GPIO_PORT0,
    (GPIO_Trigger)(GPIO_TRIGGER_LEVEL_HIGH |

```

```

        GPIO_TRIGGER_LEVEL_LOW |
        GPIO_TRIGGER_RISING |
        GPIO_TRIGGER_FALLING));
while(1)
{
    if(FT4222_GPIO_GetTriggerStatus(ftHandle, GPIO_PORT0, &queueSize) == FT4222_OK)
    {
        if(queueSize>0)
        {
            uint16 sizeofRead;
            std::vector<GPIO_Trigger> tmpBuf;
            tmpBuf.resize(queueSize);
            if(FT4222_GPIO_ReadTriggerQueue(ftHandle, GPIO_PORT0, &tmpBuf[0], queueSize,
            &sizeofRead) == FT4222_OK)
            {
                // tmpBuf store all trigger status of gpio0
            }
        }
    }
    // monitor gpio trigger status
    FT4222_UnInitialize(ftHandle);
    FT_Close(ftHandle);
}

```

### 3.8.7 GPIO Set WaveForm Mode

FT4222\_STATUS **FT4222\_GPIO\_SetWaveFormMode**(FT\_HANDLE ftHandle, BOOL enable)

#### Supported Chip:

| FT4222 chip version | Supported |
|---------------------|-----------|
| FT4222 Rev A        | NO        |
| FT4222 Rev B        | NO        |
| FT4222 Rev C        | NO        |
| FT4222 Rev D        | YES       |

#### Summary:

Enable or disable WaveForm Mode. When WaveForm mode is enabled, the device will record all GPIO status periodically. The peeking time depends on the system clock. The default setting of WaveForm mode is disabled.

#### Parameters:

|          |                                                                                                                                                     |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| ftHandle | Handle of the device.                                                                                                                               |
| enable   | TRUE to configure GPIO WaveForm mode<br>FALSE to switch back to GPIO normal mode. In normal mode, it only records the changing status on GPIO pins. |

#### Return Value:

FT4222\_OK if successful, otherwise the return value is a FT error

#### Error code:

FT4222\_DEVICE\_NOT\_OPENED: The initialization API is not called.  
 FT4222\_DEVICE\_NOT\_SUPPORTED: This device is not a FT4222 chip.

#### Prerequisite:

FT4222\_GPIO\_Init

## 4 Contact Information

### Head Office – Glasgow, UK

Future Technology Devices International Limited  
Unit 1, 2 Seaward Place, Centurion Business Park  
Glasgow G41 1HH  
United Kingdom  
Tel: +44 (0) 141 429 2777  
Fax: +44 (0) 141 429 2758

E-mail (Sales) [sales1@ftdichip.com](mailto:sales1@ftdichip.com)  
E-mail (Support) [support1@ftdichip.com](mailto:support1@ftdichip.com)  
E-mail (General Enquiries) [admin1@ftdichip.com](mailto:admin1@ftdichip.com)

### Branch Office – Tigard, Oregon, USA

Future Technology Devices International Limited  
(USA)  
7130 SW Fir Loop  
Tigard, OR 97223-8160  
USA  
Tel: +1 (503) 547 0988  
Fax: +1 (503) 547 0987

E-Mail (Sales) [us.sales@ftdichip.com](mailto:us.sales@ftdichip.com)  
E-Mail (Support) [us.support@ftdichip.com](mailto:us.support@ftdichip.com)  
E-Mail (General Enquiries) [us.admin@ftdichip.com](mailto:us.admin@ftdichip.com)

### Branch Office – Taipei, Taiwan

Future Technology Devices International Limited  
(Taiwan)  
2F, No. 516, Sec. 1, NeiHu Road  
Taipei 114  
Taiwan, R.O.C.  
Tel: +886 (0) 2 8797 1330  
Fax: +886 (0) 2 8751 9737

E-mail (Sales) [tw.sales1@ftdichip.com](mailto:tw.sales1@ftdichip.com)  
E-mail (Support) [tw.support1@ftdichip.com](mailto:tw.support1@ftdichip.com)  
E-mail (General Enquiries) [tw.admin1@ftdichip.com](mailto:tw.admin1@ftdichip.com)

### Branch Office – Shanghai, China

Future Technology Devices International Limited  
(China)  
Room 1103, 666 West Huaihai Road,  
Shanghai, 200052  
China  
Tel: +86 21 62351596  
Fax: +86 21 62351595

E-mail (Sales) [cn.sales@ftdichip.com](mailto:cn.sales@ftdichip.com)  
E-mail (Support) [cn.support@ftdichip.com](mailto:cn.support@ftdichip.com)  
E-mail (General Enquiries) [cn.admin@ftdichip.com](mailto:cn.admin@ftdichip.com)

### Web Site

<http://ftdichip.com>

### Distributor and Sales Representatives

Please visit the Sales Network page of the [FTDI Web site](#) for the contact details of our distributor(s) and sales representative(s) in your country.

System and equipment manufacturers and designers are responsible to ensure that their systems, and any Future Technology Devices International Ltd (FTDI) devices incorporated in their systems, meet all applicable safety, regulatory and system-level performance requirements. All application-related information in this document (including application descriptions, suggested FTDI devices and other materials) is provided for reference only. While FTDI has taken care to assure it is accurate, this information is subject to customer confirmation, and FTDI disclaims all liability for system designs and for any applications assistance provided by FTDI. Use of FTDI devices in life support and/or safety applications is entirely at the user's risk, and the user agrees to defend, indemnify and hold harmless FTDI from any and all damages, claims, suits or expense resulting from such use. This document is subject to change without notice. No freedom to use patents or other intellectual property rights is implied by the publication of this document. Neither the whole nor any part of the information contained in, or the product described in this document, may be adapted or reproduced in any material or electronic form without the prior written consent of the copyright holder. Future Technology Devices International Ltd, Unit 1, 2 Seaward Place, Centurion Business Park, Glasgow G41 1HH, United Kingdom. Scotland Registered Company Number: SC136640



## Appendix A – Enumeration and Structure Definitions

### Enumeration

#### FT4222\_STATUS

```
FT4222_DEVICE_NOT_SUPPORTED    = 1000
FT4222_CLK_NOT_SUPPORTED // spi master do not support 80MHz/CLK_2
FT4222_VENDER_CMD_NOT_SUPPORTED
FT4222_IS_NOT_SPI_MODE
FT4222_IS_NOT_I2C_MODE
FT4222_IS_NOT_SPI_SINGLE_MODE
FT4222_IS_NOT_SPI_MULTI_MODE
FT4222_WRONG_I2C_ADDR
FT4222_INVAILD_FUNCTION
FT4222_INVALID_POINTER
FT4222_EXCEEDED_MAX_TRANSFER_SIZE
FT4222_FAILED_TO_READ_DEVICE
FT4222_I2C_NOT_SUPPORTED_IN_THIS_MODE
FT4222_GPIO_NOT_SUPPORTED_IN_THIS_MODE
FT4222_GPIO_EXCEEDED_MAX_PORTNUM
FT4222_GPIO_WRITE_NOT_SUPPORTED
FT4222_GPIO_PULLUP_INVALID_IN_INPUTMODE
FT4222_GPIO_PULLDOWN_INVALID_IN_INPUTMODE
FT4222_GPIO_OPENDRAIN_INVALID_IN_OUTPUTMODE
FT4222_INTERRUPT_NOT_SUPPORTED
FT4222_GPIO_INPUT_NOT_SUPPORTED
FT4222_EVENT_NOT_SUPPORTED
FT4222_FUN_NOT_SUPPORT
```

#### FT4222\_ClockRate

```
SYS_CLK_60 = 0
SYS_CLK_24
SYS_CLK_48
SYS_CLK_80
```

#### FT4222\_SPIMode

```
SPI_IO_NONE    = 0
SPI_IO_SINGLE  = 1
SPI_IO_DUAL    = 2
SPI_IO_QUAD    = 4
```

#### FT4222\_SPIClock

```
CLK_NONE = 0
CLK_DIV_2    // 1/2   System Clock
CLK_DIV_4    // 1/4   System Clock
CLK_DIV_8    // 1/8   System Clock
CLK_DIV_16   // 1/16  System Clock
CLK_DIV_32   // 1/32  System Clock
CLK_DIV_64   // 1/64  System Clock
CLK_DIV_128  // 1/128 System Clock
CLK_DIV_256  // 1/256 System Clock
CLK_DIV_512  // 1/512 System Clock
```

#### FT4222\_SPICPOL

```
CLK_IDLE_LOW  =0
CLK_IDLE_HIGH =1
```

**FT4222\_SPICPHA**

```
CLK_LEADING  =0  
CLK_TRAILING =1
```

**SPI\_DrivingStrength**

```
DS_4MA  
DS_8MA  
DS_12MA  
DS_16MA
```

**enum GPIO\_Port**

```
GPIO_PORT0  
GPIO_PORT1  
GPIO_PORT2  
GPIO_PORT3
```

**enum GPIO\_Dir**

```
GPIO_OUTPUT  
GPIO_INPUT
```

**enum GPIO\_Trigger**

```
GPIO_TRIGGER_RISING  
GPIO_TRIGGER_FALLING  
GPIO_TRIGGER_LEVEL_HIGH  
GPIO_TRIGGER_LEVEL_LOW
```

**enum GPIO\_Output**

```
GPIO_OUTPUT_LOW  
GPIO_OUTPUT_HIGH
```

**enum I2C\_MasterFlag**

```
START          = 0x02  
Repeated_START = 0x03 // Repeated_START will not send master code in HS mode  
STOP           = 0x04  
START_AND_STOP = 0x06 // START condition followed by SEND and STOP condition
```

**Structure Definitions**

```
struct FT4222_Version  
{  
    DWORD chipVersion; // The version of FT4222H chip  
    DWORD dllVersion;  // The version of LibFT4222  
};
```

```
struct SPI_Slave_Header  
{  
    uint8      syncWord;  
    uint8      cmd;  
    uint8      sn;  
    uint16     size;  
};
```

## Appendix B – References

### Document References

[DS\\_FT4222H](#)

[D2XX Programmers Guide](#)

[D2XX Drivers](#)

[FT\\_PROG](#)

### Acronyms and Abbreviations

| Terms  | Description                                                 |
|--------|-------------------------------------------------------------|
| D2XX   | FTDI's proprietary "direct" driver interface via FTD2XX.DLL |
| GPIO   | General-purpose input/output                                |
| I2C    | Inter-Integrated Circuit                                    |
| SPI    | Serial Peripheral Interconnect                              |
| USB    | Universal Serial Bus                                        |
| USB-IF | USB Implementers Forum                                      |

## Appendix C – List of Tables & Figures

### List of Tables

|                                                |   |
|------------------------------------------------|---|
| Table 2.1 Chip Mode and Device Functions ..... | 8 |
|------------------------------------------------|---|

### List of Figures

|                                                                       |    |
|-----------------------------------------------------------------------|----|
| Figure 1.1 The Software Stack .....                                   | 4  |
| Figure 1.2 Mode 0: FT4222H works as SPI master (Quad Mode) .....      | 6  |
| Figure 1.3 Mode 0: FT4222H works as I <sup>2</sup> C Master .....     | 6  |
| Figure 1.4 Mode 2: FT4222H works as SPI Master .....                  | 7  |
| Figure 3.1 SPI full duplex communication.....                         | 29 |
| Figure 3.2 Dual SPI communications .....                              | 31 |
| Figure 3.3 Quad SPI communication .....                               | 32 |
| Figure 3.4 SPI Slave Protocol Format.....                             | 34 |
| Figure 3.5 SPI Master Transfer Request .....                          | 35 |
| Figure 3.6 An example of the SPI slave responding with ACK.....       | 35 |
| Figure 3.7 An example of when the SPI master doesn't receive ACK..... | 35 |
| Figure 3.8 Slave sends transfer request .....                         | 36 |
| Figure 3.9 SPI Master Transfer Request (NO ACK).....                  | 36 |
| Figure 3.10 Slave sends transfer request (NO ACK).....                | 36 |

## Appendix D – D2XX API support

### D2XX supported API

1. FT\_CreateDeviceInfoList
2. FT\_GetDeviceInfoList
3. FT\_GetDeviceInfoDetail
4. FT\_ListDevices
5. FT\_Open
6. FT\_OpenEx
7. FT\_Close
8. FT\_SetTimeouts
9. FT\_SetLatencyTimer
10. FT\_GetLatencyTimer
11. FT\_GetDeviceInfo
12. FT\_SetBitMode
13. FT\_SetUSBParameters
14. FT\_VendorCmdSet
15. FT\_VendorCmdGet
16. FT\_VendorCmdGetEx
17. FT\_Purge
  - Chip rev must >= D
18. FT\_ResetDevice
  - Chip rev must >= D
19. FT\_SetEventNotification
  - This function can be use on SPI Slave(NO protocol), I2C slave , interrupt
20. FT\_GetStatus
  - This function can be use on SPI Slave(NO protocol), I2C slave
21. FT\_ResetPort
22. FT\_Rescan
23. FT\_Reload
24. FT\_StopInTask
25. FT\_RestartInTask
26. FT\_CyclePort

Other APIs may conflict with FT4222 support-lib. Please inquiry FAE if you would like to use it.

## Appendix E – Revision History

Document Title: AN\_329 User Guide for LibFT4222  
Document Reference No.: FT\_001060  
Clearance No.: FTDI#406  
Product Page: <http://www.ftdichip.com/FTPProducts.htm>  
Document Feedback: [Send Feedback](#)

| Revision | Changes                                                                                                                                                                  | Date       |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| 1.0      | Initial Release                                                                                                                                                          | 2014-09-16 |
| 1.1      | Two new I <sup>2</sup> C functions are added to support combined message format<br>Update to FT4222_I2CMaster_WriteEx and FT4222_I2CMaster_ReadEx                        | 2015-09-10 |
| 1.2      | Updated description for SPI master ssoMap                                                                                                                                | 2016-10-05 |
| 1.3      | Updated FT4222_I2CSlave_SetClockStretch, FT4222_I2CSlave_SetRespWord                                                                                                     | 2017-08-03 |
| 1.4      | Updated FT4222_SPISlave_SetMode, FT4222_GPIO_SetWaveFormMode, FT4222_SPISlave_RxQuickResponse; error message; sample code; D2xx supported API & prerequisite information | 2018-04-19 |
| 1.5      | Added SPI multi-master example; Removed I2CMaster_GetStatus                                                                                                              | 2020-04-15 |