












M Series

Standard Size Slide Switches












SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

SPECIFICATIONS	FEATURES
Contact rating: 300 mA at 125 VAC or 30 VDC Initial contact resistance: 20 milliohms max. Insulation resistance: 100 megohms min. at 500 VDC Dielectric strength: 500 volts RMS at sea level Electrical life: 10,000 cycles min. Operating temperature range: -10°C to +60°C Solder heat resistance: 260°C max. for 3 seconds Solvent washing permissible	• Bifurcated wiping contact design. • Epoxy sealed terminals. • Wash-through open frame construction. • Reinforcing mounting legs. • Many actuator styles and lengths available on request.
	MATERIALS
	Contacts & terminals: Silver plated Housing: Tin plated steel Actuator: Thermoplastic Base: Phenolic laminated sheet Terminal seal: Epoxy

MODEL NO.				
M12R				
 RIGHT ANGLE ACTUATOR	1P2T  SCHEMATIC	 MECHANICAL OUTLINE	 P.C. BOARD LAYOUT	
MODEL NO.				
M13R				
 RIGHT ANGLE ACTUATOR	1P3T  SCHEMATIC	 MECHANICAL OUTLINE	 P.C. BOARD LAYOUT	
MODEL NO.				
M13AR				
 RIGHT ANGLE ACTUATOR	1P3T  SCHEMATIC	 MECHANICAL OUTLINE	 P.C. BOARD LAYOUT	

M Series

Standard Size Slide Switches














MODEL NO. M22  VERTICAL ACTUATOR	2P2T  ● = COMMON  MECHANICAL OUTLINE  P.C. BOARD LAYOUT
MODEL NO. M23  VERTICAL ACTUATOR	2P3T  ● = COMMON  MECHANICAL OUTLINE  P.C. BOARD LAYOUT
MODEL NO. M23R  RIGHT ANGLE ACTUATOR	2P3T  ● = COMMON  MECHANICAL OUTLINE  P.C. BOARD LAYOUT

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

M Series











Standard Size Slide Switches

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

MODEL NO. M42  VERTICAL ACTUATOR	4P2T  ● = COMMON MECHANICAL OUTLINE  P.C. BOARD LAYOUT 
MODEL NO. M42R  RIGHT ANGLE ACTUATOR	4P2T  ● = COMMON MECHANICAL OUTLINE  P.C. BOARD LAYOUT 
MODEL NO. M42A  VERTICAL ACTUATOR	4P2T  ● = COMMON MECHANICAL OUTLINE  P.C. BOARD LAYOUT 
MODEL NO. M43  VERTICAL ACTUATOR	4P3T  ● = COMMON MECHANICAL OUTLINE  P.C. BOARD LAYOUT 

M Series

Standard Size Slide Switches

MODEL NO. M43R  RIGHT ANGLE ACTUATOR	4P3T  ● = COMMON  MECHANICAL OUTLINE  P.C. BOARD LAYOUT
MODEL NO. M62R  RIGHT ANGLE ACTUATOR	6P2T  ● = COMMON  MECHANICAL OUTLINE  P.C. BOARD LAYOUT
MODEL NO. M62A  VERTICAL ACTUATOR	6P2T  ● = COMMON  MECHANICAL OUTLINE  P.C. BOARD LAYOUT

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE