

MABA-009005-CF1A40



1:1 Flux Coupled Balun Transformer
5 - 120 MHz


M/A-COM Products
Part Status: Released Rev V1

Features


- Surface Mount
- 1:1 Impedance
- 75 Ohm
- RoHS Compliant and lead free

Description

M/A-COM's MABA-009005-CF1A40 is a 1:1 RF flux coupled Transformer in a low cost surface mount package. Ideally suited for high volume CATV application.



Schematic







Pin Configuration

Function	Pin Number
Secondary (Output 1)	1
Secondary Centre Tap	2
Secondary Dot (Output 2)	3
Primary (Ground)	4
Primary Dot (Input)	5

Ordering Information

Part Number	Package
MABA-009005-CF1A40	2000 pieces per reel
MABA-009005-CF1ATB	Customer test board

Case Style SM-164A



Dimensions are inches (millimeters) ± 0.015 (0.38) unless otherwise specified.

1:1 Flux Coupled Balun Transformer
5 - 120 MHz

M/A-COM Products
Part Status: Released Rev V1


Electrical Specifications: $T_A = 25^\circ\text{C}$, 0dBm, $Z_0 = 75\Omega$

Parameter	Test Conditions	Units	Min.	Typ.	Max.
Frequency Range	5 – 120 MHz				
Insertion Loss 1 (Pin 5 to Pin 1)	5 – 80 MHz	dB	–	0.1	0.4
	80 – 120 MHz	dB	–	0.3	0.5
Insertion Loss 2 (Pin 5 to Pin 3)	5 – 80 MHz	dB	–	0.2	0.4
	80 – 120 MHz	dB	–	0.4	0.6
Amplitude Un-Balance	5 – 80 MHz	dB	–	± 0.06	± 0.2
	80 – 120 MHz	dB	–	± 0.18	± 0.3
Phase Un-Balance	5 – 65 MHz	$^\circ$	–	± 0.05	± 1.5
	65 – 120 MHz	$^\circ$	–	± 0.10	± 3.0
Input Return Loss (Pin 5)	5 – 70 MHz	dB	19	25	–
	70 – 120 MHz	dB	14	19	–

Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Power	250mW
DC Current	30mA
Operating Temperature	-40°C to $+85^\circ\text{C}$
Storage Temperature	-40°C to $+85^\circ\text{C}$

Recommended PCB Configuration




1:1 Flux Coupled Balun Transformer
5 - 120 MHz


M/A-COM Products
Part Status: Released Rev V1

Typical Performance: $T_A = 25^\circ\text{C}$, 0dBm, $Z_0 = 75\Omega$


Insertion Loss 1 (Pin 5 - Pin 1)




Insertion Loss 2 (Pin 5 - Pin 3)



Amplitude Balance



Phase Balance



Return Loss: Input (Pin 5)

