MASW-008206-000DIE

GaAs WLAN Dual SPDT Switch
2.4 - 5.8 GHz

Rev. V3

Features

- 802.11a & b/g, UNII, and Hiperlan Applications
- Optimized for 2.4 - 5.8 GHz WLAN
- Low Insertion Loss:
- 0.85 dB @ 2.4 GHz
- 1.1 dB @ 5.8 GHz
- High Isolation: 28 dB Typical
- Low Harmonics: <-63 dBc @ 20 dBm
- RoHS* Compliant

Description

The MASW-008206-000DIE is a WLAN GaAs pHEMT MMIC Dual SPDT switch. One SPDT (RF2) is optimized for 2.4 GHz WLAN and the other (RF5) is optimized for 5.8 GHz WLAN applications. Typical applications are for 802.11a and 802.11b/g PC card and access point applications.


The MASW-008206-000DIE delivers high isolation, low insertion loss, and high linearity up to 5.8 GHz. This device is fabricated using a 0.5 micron gate length GaAs pHEMT process. The process features full passivation for performance and reliability.

Ordering Information [1]

Part Number	Package
MASW-008206-000DIE	Separated Die on Grip Ring

1. Die quantity varies.

Die Bond Pad Layout



Die Bond Pad Configuration

Pad No.	Name	Description
1	V_C1	Voltage Control 1
2	GND	Ground
3	R_X5	5 GHz R_X Port
4	GND	Ground
5	R_X2	2.4 GHz R_X Port
6	T_X2	2.4 GHz T_X Port
7	GND	Ground
8	T_X5	5 GHz T_X Port
9	GND	Ground
10	V_C2	Voltage Control 2
11	RF2	2.4 GHz Antenna Port
12	RF5	5 GHz Antenna Port

* Restrictions on Hazardous Substances, European Union Directive 2002/95/EC.

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

- **North America** Tel: 800.366.2266 / Fax: 978.366.2266
- **Europe** Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- **Asia/Pacific** Tel: 81.44.844.8296 / Fax: 81.44.844.8298
Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

Electrical Specifications[2,3]: T_A = 25°C, Z_0 = 50 Ω, V_C = 0V / 3V, P_{IN} = 0 dBm

Parameter	Test Conditions	Units	Min.	Typ.	Max.
Insertion Loss	RF2 to Tx2/R_X2, 2.4 GHz RF5 to Tx5/Rx5, 5.0 GHz	dB	— —	0.85 1.1	1.0 1.2
Isolation	RF2 to Tx2/R_X2, 2.4 GHz RF5 to Tx5/Rx5, 5.0 GHz	dB	25.5 21.0	30.0 25.0	— —
Return Loss	DC - 6.0 GHz	dB	—	15	—
IP3	20 dBm Total Power, 1 MHz Spacing RF2 to Tx2/Rx2, 2.4 GHz RF5 to Tx5/Rx5, 4.9 GHz	dBm	— —	54 55	— —
Input P1dB	RF2 to Tx2, 2.4-2.5 GHz RF5 to Tx5, 4.9-5.9 GHz	dBm	— —	28 28	— —
Harmonics	RF2 to Tx2, 2.4-2.5 GHz, 20 dBc RF5 to Tx5, 4.9-5.9 GHz, 20 dBc	dBc	— —	-63 -67	— —
Control Current	$\|V_C\|$ = 3 V	µA	—	<1	10.0
T_{RISE} / T_{FALL}	10% - 90% RF, 90% - 10% RF	ns	—	22	—
T_{ON} / T_{OFF}	50% Control - 90% RF, 50% Control - 10% RF	ns	—	30	—

2. External blocking capacitors on all RF ports.
3. Electrical min/max are guaranteed in die form only.

Absolute Maximum Ratings[4,5]

Parameter	Absolute Maximum
Input Power @ 3 V Control @ 5 V Control	 +32 dBm +33 dBm
Operating Voltage	+8 volts
Operating Temperature	-40°C to +85°C
Storage Temperature	-65°C to +150°C

4. Exceeding any one or combination of these limits may cause permanent damage to this device.
5. M/A-COM Technology Solutions does not recommend sustained operation near these survivability limits.

Truth Table[6,7,8]

Control V_C1	Control V_C2	RF2 - T_X2 RF5 - R_X5	RF2 - R_X2 RF5 - T_X5
1	0	On	Off
0	1	Off	On

6. For positive voltage control, external DC blocking capacitors are required on all RF ports.
7. Differential voltage, V (state 1) - V (state 0), must be +2.7 V minimum and must not exceed +5 V.
8. 0 = 0 ± 0.3 V, 1 = +2.7 V to +5 V.

Qualification

Qualified to M/A-COM specification REL-201, Process Flow –2.

Handling Procedures

Please observe the following precautions to avoid damage:

Static Sensitivity

Gallium Arsenide Integrated Circuits are sensitive to electrostatic discharge (ESD) and can be damaged by static electricity. Proper ESD control techniques should be used when handling these Class Zero (100 V) devices.


ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

- **North America** Tel: 800.366.2266 / Fax: 978.366.2266
- **Europe** Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- **Asia/Pacific** Tel: 81.44.844.8296 / Fax: 81.44.844.8298
Visit www.macomtech.com for additional data sheets and product information.


M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

Typical Performance Curves: 2.4-2.5 GHz (plots = chip on board assembly)


T_X Insertion Loss




R_X Insertion Loss



T_X Isolation



R_X Isolation




ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

- **North America** Tel: 800.366.2266 / Fax: 978.366.2266
- **Europe** Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- **Asia/Pacific** Tel: 81.44.844.8296 / Fax: 81.44.844.8298
  Visit www.macomtech.com for additional data sheets and product information.


M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

Typical Performance Curves: 4.8-6.0 GHz (plots = chip on board assembly)


T_X Insertion Loss




R_X Insertion Loss



T_X Isolation



R_X Isolation




ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.


- **North America** Tel: 800.366.2266 / Fax: 978.366.2266
- **Europe** Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- **Asia/Pacific** Tel: 81.44.844.8296 / Fax: 81.44.844.8298
  Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

Outline Drawing



Chip mounted to PWB for testing purposes



Pad Configuration [9]


Die Size: 890 x 650 µm (nominal)

Die Thickness: 6 mils (nominal)

Pad No.	X (µm) nominal	Y (µm) nominal	Pad Size (µm)
0	0	0	Lower left edge of die
1	80.5	569.5	71 x 71
2	134.5	397	71 x 71
3	129	104	71 x 71
4	224	104	71 x 71
5	403.75	108	71 x 71
6	783.5	109	71 x 71
7	783.5	208	71 x 71
8	783.5	292	71 x 71
9	795.25	421.75	71 x 71
10	664	569.5	71 x 71
11	443	527	76 x 76
12	334.75	569.5	71 x 71
13	890	650	Upper right edge of die

9. All X,Y dimensions are at bond pad center.

Application Schematic



RF2 to T_X2 and RF2 to R_X2 paths are optimized for 2.4 -2.5 GHz WLAN applications.

RF5 to T_X5 and RF5 to R_X5 paths are optimized for 4.8 - 6.0 GHz WLAN applications.

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

- **North America** Tel: 800.366.2266 / Fax: 978.366.2266
- **Europe** Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- **Asia/Pacific** Tel: 81.44.844.8296 / Fax: 81.44.844.8298
Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.