



MAX15303 PMBus Command Set User's Guide

Rev 0; 1/14

Maxim Integrated cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim Integrated product. No circuit patent licenses are implied. Maxim Integrated reserves the right to change the circuitry and specifications without notice at any time.

Maxim Integrated 160 Rio Robles, San Jose, CA 95134 USA 1-408-601-1000

© 2014 Maxim Integrated Products, Inc. Maxim Integrated and the Maxim Integrated logo are trademarks of Maxim Integrated Products, Inc.

Introduction

Maxim Integrated InTune™ digital power products utilize the PMBus™ command standard for configuration, control, and telemetry.

This document lists and describes the PMBus commands implemented in the MAX15303 digital DC-DC converter. Standard commands from the PMBus specification are not described in detail unless there are deviations from the PMBus specification functionality. Maxim manufacturer-specific commands are fully described in this document.

References for this document are found on the PMBus and SMBus organization websites.

<http://pmbus.org/specs.html>

<http://smbus.org/specs/>

The commands in this document are presented in the following format:

<COMMAND_NAME>			
Reference:	<"Standard" or "Maxim Specific">	Lockable:	<yes/no>
Command Code:	<hex value>	Format:	<data format>
Data Bytes:	<byte count>	Units:	<unit of measure>
Transfer:	<SMBus transaction>	Factory Value:	<Maxim setting>
Description/Notes:	<Command definition if Maxim-specific, or notes on command functionality where it differs from the PMBus specification.>		

Table of Contents

Introduction	2
On, Off, and Margin Testing-Related Commands	6
OPERATION	6
ON_OFF_CONFIG	6
VIN_ON	7
VIN_OFF	7
Output Voltage-Related Commands	9
VOUT_MODE	9
VOUT_COMMAND	9
VOUT_TRIM	9
VOUT_CAL_OFFSET	10
VOUT_MAX	10
VOUT_MARGIN_HIGH	11
VOUT_MARGIN_LOW	11
VOUT_TRANSITION_RATE	12

VOUT_DROOP.....	12
Switching Frequency and PWM Commands.....	14
FREQUENCY_SWITCH.....	14
INTERLEAVE	14
Output Voltage Sequencing Commands.....	16
POWER_GOOD_ON	16
POWER_GOOD_OFF	16
TON_DELAY.....	17
TON_RISE	17
TOFF_DELAY.....	17
TOFF_FALL	18
Fault-Related Commands	19
CLEAR_FAULTS.....	19
VOUT_OV_FAULT_LIMIT.....	19
VOUT_OV_FAULT_RESPONSE.....	19
VOUT_UV_FAULT_LIMIT.....	20
VOUT_UV_FAULT_RESPONSE.....	20
IOUT_OC_FAULT_LIMIT	21
IOUT_OC_FAULT_RESPONSE	21
OT_FAULT_LIMIT	22
OT_FAULT_RESPONSE	23
OT_WARN_LIMIT	23
VIN_OV_FAULT_LIMIT	24
VIN_OV_FAULT_RESPONSE	24
VIN_UV_FAULT_LIMIT	25
VIN_UV_FAULT_RESPONSE	25
Unit Status Commands	27
STATUS_BYTE.....	27
STATUS_WORD	27
STATUS_VOUT	27
STATUS_IOUT.....	27
STATUS_INPUT.....	28
STATUS_TEMPERATURE.....	28
STATUS_CML.....	28

Telemetry Commands.....	29
READ_VIN	29
READ_VOUT	29
READ_IOUT	29
READ_TEMPERATURE_1	30
READ_TEMPERATURE_2	30
READ_DUTY_CYCLE.....	30
READ_FREQUENCY.....	30
PMB_VALUES	31
Calibration Commands	33
IOUT_CAL_GAIN.....	33
IOUT_CAL_OFFSET	33
EXT_TEMP_CAL.....	33
Device Identification Commands.....	35
CAPABILITY.....	35
PMBUS_REVISION	35
MFR_ID	35
MFR_MODEL.....	36
MFR_REVISION	36
MFR_LOCATION	36
MFR_DATE	36
MFR_SERIAL.....	37
IC_DEVICE_ID.....	37
IC_DEVICE_REV	37
Security Commands	38
WRITE_PROTECT.....	38
MANUF_CONF	38
MANUF_LOCK.....	39
MANUF_PASSWD.....	39
USER_CONF.....	39
USER_LOCK	40
USER_PASSWD.....	40
SECURITY_LEVEL	41
Memory and Storage Commands	42

STORE_DEFAULT_ALL	42
RESTORE_DEFAULT_ALL	43
STORE_USER_ALL.....	43
RESTORE_USER_ALL	44
RESTORE_MAXIM_ALL.....	45
STRAP_DISABLE.....	45
Control Loop Commands	47
ADAPTIVE_MODE.....	47
FEEDBACK_EFFORT	48
LOOP_CONFIG.....	48
COMP_MODEL.....	49
DEADTIME_GCTRL	49
ZETA_P	50
Trademarks	51
Revision History	52

On, Off, and Margin Testing-Related Commands

OPERATION

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x01	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read/Write Byte	Factory Value:	0x40 (see Description table)

Description/Notes:	See Section 12.1 of the PMBus Specification Part II. If the values of VOUT_OV_FAULT_LIMIT or VOUT_UV_FAULT_LIMIT are set between the values of VOUT_MARGIN_HIGH and VOUT_MARGIN_LOW, it is possible that a fault will be detected when exiting the “Margin High/Low (Ignore Fault)” command states. This occurs when fault detection is re-enabled before the output has had time to return to the VOUT_COMMAND value. This condition can be avoided in most cases by increasing the value of VOUT_TRANSITION_RATE, thereby decreasing the amount of time required for the output to return to normal VOUT_COMMAND setpoint. The value of the OPERATION command is maintained in volatile memory, and <i>cannot</i> be stored in the Default Store or User Store nonvolatile memory. This prevents inadvertent preservation of a margin-high or margin-low state. If it is desired to keep the output always enabled or always disabled upon power-up, this can be achieved by storing the appropriate value of the ON_OFF_CONFIG command. Useful values for the OPERATION command: <table> <tr> <td>0x00</td><td>Immediate-off, no sequencing: both DH and DL outputs low^a (note: same as 0x01-0x3F)</td></tr> <tr> <td>0x40</td><td>Soft-off, with sequencing (factory setting)^b (note: same as 0x41-0x7F)</td></tr> <tr> <td>0x80</td><td>Output enabled, if allowed by ON_OFF_CONFIG setting (note: same as 0x81-0x8F)</td></tr> <tr> <td>0x94</td><td>Margin low, ignore faults (note: same as 0x95-0x97)</td></tr> <tr> <td>0x98</td><td>Margin low, act on faults (note: same as 0x99-0x9B)</td></tr> <tr> <td>0xA4</td><td>Margin high, ignore faults (note: same as 0xA5-0xA7)</td></tr> <tr> <td>0xA8</td><td>Margin high, act on faults (note: same as 0xA9-0xAB)</td></tr> </table> Invalid values for the OPERATION command: 0x90-0x93 0x9C-0x9F 0xA0-0xA3 0xAC-0xFF These invalid data bytes will trigger an “Invalid Or Unsupported Data” response per section 10.9.3 of the PMBus specification. After writing the OPERATION command to enable the output, the PMBus master must either wait for a time equal to (TON_DELAY + TON_RISE + 50ms), or wait for PG to assert, before sending additional PMBus commands.	0x00	Immediate-off, no sequencing: both DH and DL outputs low ^a (note: same as 0x01-0x3F)	0x40	Soft-off, with sequencing (factory setting) ^b (note: same as 0x41-0x7F)	0x80	Output enabled, if allowed by ON_OFF_CONFIG setting (note: same as 0x81-0x8F)	0x94	Margin low, ignore faults (note: same as 0x95-0x97)	0x98	Margin low, act on faults (note: same as 0x99-0x9B)	0xA4	Margin high, ignore faults (note: same as 0xA5-0xA7)	0xA8	Margin high, act on faults (note: same as 0xA9-0xAB)
0x00	Immediate-off, no sequencing: both DH and DL outputs low ^a (note: same as 0x01-0x3F)														
0x40	Soft-off, with sequencing (factory setting) ^b (note: same as 0x41-0x7F)														
0x80	Output enabled, if allowed by ON_OFF_CONFIG setting (note: same as 0x81-0x8F)														
0x94	Margin low, ignore faults (note: same as 0x95-0x97)														
0x98	Margin low, act on faults (note: same as 0x99-0x9B)														
0xA4	Margin high, ignore faults (note: same as 0xA5-0xA7)														
0xA8	Margin high, act on faults (note: same as 0xA9-0xAB)														

ON_OFF_CONFIG

^a An “immediate-off,” “hard-stop,” or “three-state” shutdown means the MAX15303 will stop switching and keep both DH and DL outputs low, allowing the output voltage to decay naturally according to load and output capacitance.

^b In this application note (and other InTune documents) a “soft-off,” “soft-stop,” or “ramp-down” shutdown means the MAX15303 actively controls the output voltage along a linear ramp to zero Volts, per the TOFF_DELAY and TOFF_FALL values.

ON_OFF_CONFIG

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x02	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read/Write Byte	Factory Value:	0x16 (see Description table)

Description/Notes: See Section 12.2 of the PMBus Specification Part II.

Useful Values for the ON_OFF_CONFIG command:

0x00	Output always enabled (note: same as 0x01-0x0F)
0x10	Output always disabled (note: same as 0x11-0x13)
0x14	Ignore bit 7 of OPERATION , require EN low to run, soft-off on loss of EN
0x15	Ignore bit 7 of OPERATION, require EN low to run, immediate-off on loss of EN
0x16	Ignore bit 7 of OPERATION, require EN high to run, soft-off on loss of EN (factory setting)
0x17	Ignore bit 7 of OPERATION, require EN high to run, immediate-off on loss of EN
0x18	Require bit 7 of OPERATION to run, ignore EN (note: same as 0x19-0x1B)
0x1C	Require bit 7 of OPERATION <i>and</i> EN low to run, soft-off on loss of EN
0x1D	Require bit 7 of OPERATION <i>and</i> EN low to run, immediate-off on loss of EN
0x1E	Require bit 7 of OPERATION <i>and</i> EN high to run, soft-off on loss of EN
0x1F	Require bit 7 of OPERATION <i>and</i> EN high to run, immediate-off on loss of EN

In general, odd values of ON_OFF_CONFIG that require a valid EN signal will have an immediate-off shutdown when EN is not valid. Even values that require EN will have a soft-off shutdown when EN is not valid.

After writing the ON_OFF_CONFIG command to enable the output, the PMBus master must either wait for a time equal to (TON_DELAY + TON_RISE + 50ms), or wait for PG to assert, before sending additional PMBus commands.

VIN_ON

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x35	Format:	Linear
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0xCB00 (6.0V)

Description/Notes: See Section 14.5 of the PMBus Specification Part II.

The MAX15303 hardware has 8-bit resolution for the minimum input voltage required for regulation, to a maximum value of $\approx 14.75V$.

The desired value of VIN_ON is retained in memory, regardless limitations imposed by the 8-bit fault limit resolution, but the read-back value is based on actual hardware register settings.

VIN_OFF

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x36	Format:	Linear
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0xCAC0 (5.5V)

VIN_OFF

Description/Notes:	See Section 14.6 of the PMBus Specification Part II. The MAX15303 hardware has 8-bit resolution for the minimum input voltage required for regulation, to a maximum value of $\approx 14.75\text{V}$. The desired value of VIN_OFF is retained in memory, regardless limitations imposed by the 8-bit fault limit resolution, but the read-back value is based on actual hardware register settings.
---------------------------	--

Output Voltage-Related Commands

VOUT_MODE

Reference:	Standard Command	Lockable:	No
Command Code:	0x20	Format:	Mixed: bit-field and two's complement
Data Bytes:	1	Units:	N/A
Transfer:	Read Byte	Factory Value:	0x14 (Linear Mode, exponent -12)
Description/Notes:	See Section 8.2 of the PMBus Specification Part II. The MAX15303 only supports Linear Mode values for output voltage related commands. The VOUT_MODE command is read-only and the value cannot be changed. The 5-bit exponent for output voltage data is -12, or two's-complement 10100. This means that voltage command data sent to and from the MAX15303 using either the 2-byte unsigned integer mantissa or Direct mantissa formats must be divided by 4096 to determine the actual voltage value.		

VOUT_COMMAND

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x21	Format:	Unsigned integer mantissa
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0x1334 (1.200V)
Description/Notes:	See Section 8.2 of the PMBus Specification Part II. VOUT_COMMAND mantissa data sent to and from the MAX15303 must be divided by 4096 to determine the actual voltage value, according to the fixed value of VOUT_MODE. The factory value of 0x1334 (1.200V) will be overridden during initialization by the hardware (pin-strap) value determined by the resistance to ground detected at the SET pin, unless a specific value has been written to the User Store. The value of the SET pin resistance is measured only once during initialization (power-up). In the MAX15303, there are seven possible output voltage ranges based on seven corresponding internal feedback divider taps. The value of VOUT_COMMAND is retained and read back from volatile memory, regardless of limitations imposed by the feedback divider range. New values of VOUT_COMMAND can be written at any time, but large changes (specifically, those that require a different feedback divider selection; see Table 7 of the MAX15303 IC data sheet) will require the output to be disabled for the feedback divider to change.		

VOUT_TRIM

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x22	Format:	Linear
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0x0000 (0V)
Description/Notes:	See Section 13.3 of the PMBus Specification Part II. In the MAX15303, the value of VOUT_TRIM is summed with the value of VOUT_COMMAND and		

VOUT_TRIM

[VOUT_CAL_OFFSET](#), and the result is sent to the control loop as the output voltage setpoint.

Note that in the MAX15303, VOUT_TRIM is sent as a PMBus Linear value, rather than as a two's complement binary integer mantissa as specified in the PMBus standard, to avoid introducing another numeric format.

The value of VOUT_TRIM is not subtracted from READ_VOUT, so non-zero VOUT_TRIM values will result in a difference between VOUT_COMMAND and READ_VOUT.

This command is intended to allow an end user of a PMBus device to tailor a specific supply to the performance requirements of a specific load device, while retaining use of a "nominal" voltage setpoint for all similar load devices.

VOUT_CAL_OFFSET

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x23	Format:	Linear
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0x0000 (0V)
Description/Notes:	See Section 13.4 of the PMBus Specification Part II. In the MAX15303, the value of VOUT_CAL_OFFSET is summed with the value of VOUT_COMMAND and VOUT_TRIM, and the result is sent to the control loop as the output voltage setpoint. Note that in the MAX15303, VOUT_CAL_OFFSET is sent as a PMBus Linear value, rather than as a two's complement binary integer mantissa as specified in the PMBus standard, to avoid introducing another numeric format. The value of VOUT_CAL_OFFSET is subtracted from READ_VOUT, so VOUT_CAL_OFFSET values never result in a difference between VOUT_COMMAND and READ_VOUT. This command is intended to allow a PMBus device manufacturer or an end user to calibrate the output voltage of a module (or other power-supply assembly) to match an external reference instrument during their final-test process.		

VOUT_MAX

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x24	Format:	Unsigned integer mantissa
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0x5001 (5.000V)
Description/Notes:	See Section 13.5 of the PMBus Specification Part II. VOUT_MAX mantissa data sent to and from the MAX15303 must be divided by 4096 to determine the actual voltage value, according to the fixed value of VOUT_MODE. The factory value of 0x5001 (5.000V) will be overridden during initialization to VOUT_COMMAND x 1.15, unless a specific value has been written to the User Store.		

VOUT_MARGIN_HIGH

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x25	Format:	Unsigned integer mantissa
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0x14CD (1.300V)
Description/Notes:	See Section 13.6 of the PMBus Specification Part II. VOUT_MARGIN_HIGH mantissa data sent to and from the MAX15303 must be divided by 4096 to determine the actual voltage value, according to the fixed value of VOUT_MODE. The factory value of 0x14CD (1.300V) will be overridden during initialization to VOUT_COMMAND x 1.05, unless a specific value has been written to the User Store. In the MAX15303, there are seven possible output voltage ranges based on seven corresponding internal feedback divider taps. The desired value of VOUT_MARGIN_HIGH is retained and read back from Operating Memory, regardless of hardware limitations imposed by the feedback divider range. If the MAX15303 is set for margin-high operation prior to the output being enabled, the output will rise directly to VOUT_MARGIN_HIGH at the rate determined by VOUT_COMMAND/TON_RISE. Likewise, if the output is disabled from margin-high operation, the output will fall at a rate determined by -VOUT_COMMAND/TOFF_FALL.		

VOUT_MARGIN_LOW

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x26	Format:	Unsigned integer mantissa
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0x1001 (1.000V)
Description/Notes:	See Section 13.7 of the PMBus Specification Part II. VOUT_MARGIN_LOW mantissa data sent to and from the MAX15303 must be divided by 4096 to determine the actual voltage value, according to the fixed value of VOUT_MODE. The factory value of 0x1001 (1.000V) will be overridden during initialization to VOUT_COMMAND x 0.95, unless a specific value has been written to the User Store. In the MAX15303, there are seven possible output voltage ranges based on seven corresponding internal feedback divider taps. The desired value of VOUT_MARGIN_LOW is retained and read back from Operating Memory, regardless of hardware limitations imposed by the feedback divider range. If the MAX15303 is set for margin-low operation prior to the output being enabled, the output will rise directly to VOUT_MARGIN_LOW at the rate determined by VOUT_COMMAND/TON_RISE. Likewise, if the output is disabled from margin-low operation, the output will fall at a rate determined by -VOUT_COMMAND/TOFF_FALL.		

VOUT_TRANSITION_RATE

Reference:	Standard Command	Lockable:	Yes																														
Command Code:	0x27	Format:	Linear																														
Data Bytes:	2	Units:	mV/μs (or V/ms, kV/s)																														
Transfer:	Read/Write Word	Factory Value:	0x9B33 (0.1V/ms, see Description)																														
Description/Notes:	See Section 13.8 of the PMBus Specification Part II.																																
	To achieve output voltage slew-rate control, the MAX15303 has an 8-bit timer with approximately 243ns resolution. When the timer expires, the 12-bit voltage setpoint is incremented or decremented until the setpoint reaches its final value. This limits the minimum and maximum possible slew-rates for each feedback divider range as follows:																																
	<table><tr><th>Feedback Divider</th><th colspan="2">VOUT_TRANSITION_RATE, kV/s</th></tr><tr><th></th><th>Min</th><th>Max</th></tr><tr><td>0</td><td>≈ 0.005</td><td>≈ 1.171</td></tr><tr><td>1</td><td>≈ 0.005</td><td>≈ 1.323</td></tr><tr><td>2</td><td>≈ 0.006</td><td>≈ 1.519</td></tr><tr><td>3</td><td>≈ 0.007</td><td>≈ 1.782</td></tr><tr><td>4</td><td>≈ 0.008</td><td>≈ 2.16</td></tr><tr><td>5</td><td>≈ 0.011</td><td>≈ 2.736</td></tr><tr><td>6</td><td>≈ 0.015</td><td>≈ 3.725</td></tr><tr><td>7</td><td>≈ 0.023</td><td>≈ 5.862</td></tr></table>			Feedback Divider	VOUT_TRANSITION_RATE, kV/s			Min	Max	0	≈ 0.005	≈ 1.171	1	≈ 0.005	≈ 1.323	2	≈ 0.006	≈ 1.519	3	≈ 0.007	≈ 1.782	4	≈ 0.008	≈ 2.16	5	≈ 0.011	≈ 2.736	6	≈ 0.015	≈ 3.725	7	≈ 0.023	≈ 5.862
	Feedback Divider	VOUT_TRANSITION_RATE, kV/s																															
		Min	Max																														
0	≈ 0.005	≈ 1.171																															
1	≈ 0.005	≈ 1.323																															
2	≈ 0.006	≈ 1.519																															
3	≈ 0.007	≈ 1.782																															
4	≈ 0.008	≈ 2.16																															
5	≈ 0.011	≈ 2.736																															
6	≈ 0.015	≈ 3.725																															
7	≈ 0.023	≈ 5.862																															
	For each divider range, the minimum transition rate is also the resolution (minimum step size).																																
	The desired value of VOUT_TRANSITION_RATE is retained in memory, regardless of hardware limitations imposed by the feedback divider range, but the read-back value is based on actual hardware register settings.																																
	If a commanded value of VOUT_TRANSITION_RATE exceeds the maximum possible slew-rate for the feedback divider range, the MAX15303 sets the slew-rate control timer to zero, and the output voltage setpoint is updated to the new setpoint value immediately and without delay. In this case, VOUT_TRANSITION_RATE will read back as 0mV/μs to avoid a divide-by-zero operation.																																

VOUT_DROOP

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x28	Format:	Linear
Data Bytes:	2	Units:	mΩ (or mV/A)
Transfer:	Read/Write Word	Factory Value:	0x0000 (0mΩ)
Description/Notes:	See Section 13.9 of the PMBus Specification Part II. The MAX15303 uses low-pass filtered inductor DCR current-sense information (i.e., the READ_IOUT signal) to establish the load-line characteristic according to the VOUT_DROOP value. Because of this low-pass filtering of the load current information, there will be some settling time in the output voltage positioning when VOUT_DROOP is non-zero. It is also important to calibrate READ_IOUT using IOUT_CAL_GAIN and IOUT_CAL_OFFSET to achieve		

VOUT_DROOP

accurate adaptive voltage positioning results with the VOUT_DROOP command.

Note that VOUT_DROOP can accept negative resistance values, allowing a user to compensation for resistive losses between the output voltage remote sense point and the load, if desired. (Setting VOUT_DROOP to a negative value will case output voltage to rise with increasing load.)

Wait at least 500 μ s for execution after sending the VOUT_DROOP command before sending additional PMBus commands.

Switching Frequency and PWM Commands

FREQUENCY_SWITCH

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x33	Format:	Linear
Data Bytes:	2	Units:	kHz
Transfer:	Read/Write Word	Factory Value:	0x0258 (600kHz)
Description/Notes:	See Section 14.4 of the PMBus Specification Part II. The factory value of 0x0258 (600kHz) will be overridden during initialization by the hardware (pin-strap) value determined by the resistance to ground detected at the SYNC pin, unless a specific value has been written to the User Store. The value of the SYNC pin resistance is measured only once during initialization (power-up). The MAX15303 can also synchronize to an external clock at the SYNC input. If the external clock is present at or before power-up, the SYNC resistance reading will fail and FREQUENCY_SWITCH will be set to 300kHz. The MAX15303 has two different PWM “speed modes” to support FREQUENCY_SWITCH values at or below 475kHz, and above 475kHz. <u>It is important to ensure that FREQUENCY_SWITCH is set, either by PMBus command or by <i>successful</i> resistor pin-strap, to a value that is within $\pm 10\%$ of the expected external clock frequency.</u> If the external clock is present at the time of output enable, the operating memory value of FREQUENCY_SWITCH will be updated to reflect the external clock frequency. If the external clock is applied after enabling the output, the PWM will synchronize to the external clock, but FREQUENCY_SWITCH will not be updated. <u>If the external clock crosses the 475kHz boundary while regulating, unexpected results or output voltage transients may result.</u> The <i>actual</i> switching frequency can be obtained using the READ_FREQUENCY command. Wait at least 10ms for execution after sending the FREQUENCY_SWITCH command before sending additional PMBus commands.		

INTERLEAVE

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x37	Format:	4 x 4-bit unsigned integer “nibbles”
Data Bytes:	2	Units:	N/A
Transfer:	Read/Write Word	Factory Value:	0x0000 (see Description)
Description/Notes:	See Section 14.7 of the PMBus Specification Part II. The INTERLEAVE command determines the phase delay of the MAX15303, measured from the rising edge of an external clock applied at SYNC to the center of the PWM positive pulse.^c The factory value of 0x0000 (zero degrees phase shift) will be overridden during initialization by the hardware (pin-strap) value determined by the resistances to ground detected at the ADDR0 and		

^c Because the MAX15303 has dual-edge modulation, the rising and falling edges of the PWM waveform both “move” relative to the center of the high-side switch on-time.

INTERLEAVE

ADDR1 pins, unless a new value of INTERLEAVE has been written to the User Store. The value of the ADDR0 and ADDR1 pin resistance is measured only once during initialization (power-up).

Because the MAX15303 uses one of two different PWM “speed modes” depending on the switching frequency selected (see [FREQUENCY SWITCH](#)), the INTERLEAVE command will show unexpected results if switching frequency crosses the 475kHz speed-mode boundary after initialization.

The MAX15303 includes enhancements beyond the PMBus specification INTERLEAVE command functionality:

- Setting the “Number In Group” to zero will be interpreted by the MAX15303 as 16 possible phases. This allows phase-spreading in 22.5° increments.
- The low nibble of the high byte of INTERLEAVE contains the “Group ID Number” per the PMBus specification, but this is a value that has no function and no dependent parameters in either the MAX15303 device or in the PMBus specification. As a result, it is not necessary to set a “Group ID Number.” Both nibbles of the high byte of INTERLEAVE can be used separately or together as “scratchpad” data, if desired.

Output Voltage Sequencing Commands

POWER_GOOD_ON

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x5E	Format:	Unsigned integer mantissa
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0x1135 (1.080V)
Description/Notes:	See Section 15.32.1 of the PMBus Specification Part II. POWER_GOOD_ON mantissa data sent to and from the MAX15303 must be divided by 4096 to determine the actual voltage value, according to the fixed value of VOUT_MODE. In the MAX15303, there are seven possible output voltage ranges based on seven corresponding internal feedback divider taps. The MAX15303 hardware has 8-bit resolution for the power-good threshold within each of these seven ranges. The desired value of POWER_GOOD_ON is retained in memory, regardless of limitations imposed by the feedback divider range and the 8-bit fault limit resolution, but the read-back value is based on actual hardware register settings. The factory value of 0x1135 (1.080V) will be overridden during initialization to VOUT_COMMAND x 0.95, unless a specific value has been written to the User Store.		

POWER_GOOD_OFF

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x5F	Format:	Unsigned integer mantissa
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0x0F99 (0.980V)
Description/Notes:	See Section 15.32.2 of the PMBus Specification Part II. POWER_GOOD_OFF mantissa data sent to and from the MAX15303 must be divided by 4096 to determine the actual voltage value, according to the fixed value of VOUT_MODE. In the MAX15303, there are seven possible output voltage ranges based on seven corresponding internal feedback divider taps. The MAX15303 hardware has 8-bit resolution for the power-good threshold within each of these seven ranges. The desired value of POWER_GOOD_OFF is retained in memory, regardless of limitations imposed by the feedback divider range and the 8-bit fault limit resolution, but the read-back value is based on actual hardware register settings. The factory value of 0x0F99 (0.980V) will be overridden during initialization to VOUT_COMMAND x 0.93, unless a specific value has been written to the User Store.		

TON_DELAY

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x60	Format:	Linear
Data Bytes:	2	Units:	ms
Transfer:	Read/Write Word	Factory Value:	0xCA80 (5ms)
Description/Notes:	See Section 16.1 of the PMBus Specification Part II. The TON_DELAY command sets the delay time between a valid enable condition and the beginning of the output ramp to regulation at VOUT_COMMAND. The nominal factory value is 5ms. An 8-bit timer with approximately 570μs resolution allows for delay times from ≈1ms to ≈145ms.		

TON_RISE

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x61	Format:	Linear
Data Bytes:	2	Units:	ms
Transfer:	Read/Write Word	Factory Value:	0xCA80 (5ms)
Description/Notes:	See Section 16.2 of the PMBus Specification Part II. The TON_RISE command sets the ramp-up time from 0V to regulation at VOUT_COMMAND. The nominal factory value is 5ms. The MAX15303 achieves startup dV_{OUT}/dt control by incrementing the loop setpoint by one 12-bit step every time a certain number of ramp-controller clock cycles have elapsed in an 8-bit counter. This results in a setpoint that increases at a controlled rate, in turn creating a constant dV_{OUT}/dt during startup. Because the MAX15303 must calculate the ramp control timer setting based upon the value of VOUT_COMMAND, the possible range and resolution of TON_RISE will vary significantly. The desired value of TON_RISE is retained in memory, regardless of ramp-timer limitations, but the read-back value is based on actual hardware register settings.		

TOFF_DELAY

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x64	Format:	Linear
Data Bytes:	2	Units:	ms
Transfer:	Read/Write Word	Factory Value:	0xBA00 (1ms)
Description/Notes:	See Section 16.5 of the PMBus Specification Part II. The TOFF_DELAY command sets the delay time between loss of enable condition and the beginning of the output ramp-down. The nominal factory value is 1ms. An 8-bit timer with approximately 570μs resolution allows for delay times from 0ms to ≈145ms.		

TOFF_FALL

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x65	Format:	Linear
Data Bytes:	2	Units:	ms
Transfer:	Read/Write Word	Factory Value:	0xCA80 (5ms)
Description/Notes:	See Section 16.6 of the PMBus Specification Part II. The TOFF_FALL command sets the ramp-down time from regulation at VOUT_COMMAND to 0V. The nominal factory value is 5ms. The MAX15303 achieves shutdown dV_{OUT}/dt control by decrementing the loop setpoint by one 12-bit step every time a certain number of ramp-controller clock cycles have elapsed in an 8-bit counter. This results in a setpoint that decreases at a controlled rate, in turn creating a constant dV_{OUT}/dt during shutdown. Because the MAX15303 must calculate the ramp control timer setting based upon the value of VOUT_COMMAND, the possible range and resolution of TOFF_FALL will vary significantly. The desired value of TOFF_FALL is retained in memory, regardless of ramp-timer limitations, but the read-back value is based on actual hardware register settings.		

Fault-Related Commands

CLEAR_FAULTS

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x03	Format:	N/A
Data Bytes:	0	Units:	N/A
Transfer:	Send Byte	Factory Value:	N/A
Description/Notes:	See Section 15.1 of the PMBus Specification Part II. If the MAX15303 has latched off for a fault condition, sending the CLEAR_FAULTS command will cause a restart.		

VOUT_OV_FAULT_LIMIT

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x40	Format:	Unsigned integer mantissa
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0x170A (1.440V)
Description/Notes:	See Section 15.2 of the PMBus Specification Part II. VOUT_OV_FAULT_LIMIT mantissa data sent to and from the MAX15303 must be divided by 4096 to determine the actual voltage value, according to the fixed value of VOUT_MODE. In the MAX15303, there are seven possible output voltage ranges based on seven corresponding internal feedback divider taps. The MAX15303 hardware has 8-bit resolution for the overvoltage fault limit within each of these seven ranges. The desired value of VOUT_OV_FAULT_LIMIT is retained in memory, regardless of limitations imposed by the feedback divider range and the 8-bit fault limit resolution, but the read-back value is based on actual hardware register settings. The factory value of 0x170A (1.440V) will be overridden during initialization to VOUT_COMMAND x 1.15, unless a specific value has been written to the User Store.		

VOUT_OV_FAULT_RESPONSE

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x41	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read/Write Byte	Factory Value:	0x80 (Stop regulating and remain off)
Description/Notes:	See Sections 10.5.1 and 15.3 of the PMBus Specification Part II. <u>Note that the MAX15303 does not support finite, non-zero restart-attempt counts. (Continuous restart attempts are supported.)</u> The VOUT_OV_FAULT_RESPONSE command data comprises three bit-fields: Bits [7:6] determine the basic fault-response mode. The MAX15303 supports the following modes: 00 Ignore the fault condition. 01 Continue operating and wait for the fault to abate for time specified in bits [2:0]. If the		

VOUT_OV_FAULT_RESPONSE

- fault does not abate, shutdown and attempt to restart according to bits [5:3].
- 10 Stop regulating immediately, delay for the time specified in bits [2:0], then attempt to restart according to bits [5:3]. (*Default setting*)
 - 11 Stop regulating immediately, and then restart as soon as possible after the fault condition abates.

Bits [5:3] determine the number of retry attempts. The MAX15303 supports only a subset of the full PMBus functionality for this portion of the command:

- 000-110 No attempt is made to restart after a fault shutdown. (*Default setting*)
- 111 Attempt to restart continuously until commanded off, or until another fault condition causes the unit to shut down.

Bits [2:0] determine the fault-tolerance or retry-delay timing. Each binary value in bits [2:0] corresponds to a multiple of 100ms, up to a possible maximum of $111_{\text{bin}} = 700\text{ms}$. A value of 000_{bin} will cause the MAX15303 to use the minimum possible timing value, typically about 30-40ms. (*The default timing for overvoltage faults is 000_{bin} .*)

VOUT_UV_FAULT_LIMIT

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x44	Format:	Unsigned integer mantissa
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0x019A (0.100V)
Description/Notes:	See Section 15.6 of the PMBus Specification Part II. VOUT_UV_FAULT_LIMIT mantissa data sent to and from the MAX15303 must be divided by 4096 to determine the actual voltage value, according to the fixed value of VOUT_MODE. In the MAX15303, there are seven possible output voltage ranges based on seven corresponding internal feedback divider taps. The MAX15303 hardware has 8-bit resolution for the undervoltage fault limit within each of these seven ranges. The desired value of VOUT_UV_FAULT_LIMIT is retained in memory, regardless of limitations imposed by the feedback divider range and the 8-bit fault limit resolution, but the read-back value is based on actual hardware register settings. The factory value of 0x019A (0.100V) will be overridden during initialization to VOUT_COMMAND x 0.85, unless a specific value has been written to the User Store.		

VOUT_UV_FAULT_RESPONSE

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x45	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read/Write Byte	Factory Value:	0x00 (Ignore undervoltage faults)
Description/Notes:	See Sections 10.5.1 and 15.7 of the PMBus Specification Part II. <u>Note that the MAX15303 does not support finite, non-zero restart-attempt counts. (Continuous restart attempts are supported.)</u>		

VOUT_UV_FAULT_RESPONSE

The VOUT_UV_FAULT_RESPONSE command data comprises three bit-fields:

Bits [7:6] determine the basic fault-response mode. The MAX15303 supports the following modes:

- 00 Ignore the fault condition. (*Default setting*)
- 01 Continue operating and wait for the fault to abate for time specified in bits [2:0]. If the fault does not abate, shutdown and attempt to restart according to bits [5:3].
- 10 Stop regulating immediately, delay for the time specified in bits [2:0], then attempt to restart according to bits [5:3].
- 11 Stop regulating immediately, and then restart as soon as possible after the fault condition abates.

Bits [5:3] determine the number of retry attempts. The MAX15303 supports only a subset of the full PMBus functionality for this portion of the command:

- 000-110 No attempt is made to restart after a fault shutdown. (*Default setting*)
- 111 Attempt to restart continuously until commanded off, or until another fault condition causes the unit to shut down.

Bits [2:0] determine the fault-tolerance or retry-delay timing. Each binary value in bits [2:0] corresponds to a multiple of 100ms, up to a possible maximum of $111_{\text{bin}} = 700\text{ms}$. A value of 000_{bin} will cause the MAX15303 to use the minimum possible timing value, typically about 30-40ms. (*The default timing for undervoltage faults is 000_{bin} .*)

IOUT_OC_FAULT_LIMIT

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x46	Format:	Linear
Data Bytes:	2	Units:	A
Transfer:	Read/Write Word	Factory Value:	0xD200 (8A)
Description/Notes:	See Section 15.8 of the PMBus Specification Part II. The MAX15303 hardware has 8-bit resolution for the overcurrent fault limit within a 9A full-scale load current range. The desired value of IOUT_OC_FAULT_LIMIT is retained in memory, regardless limitations imposed by the 8-bit fault limit resolution, but the read-back value is based on actual hardware register settings.		

IOUT_OC_FAULT_RESPONSE

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x47	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read/Write Byte	Factory Value:	0xBF (Shut down, retry every 700ms)
Description/Notes:	See Sections 10.5.1 and 15.9 of the PMBus Specification Part II. For overcurrent faults, the MAX15303 implements the fault responses of PMBus Specification section 10.5.1, <u>rather than the responses of section 10.5.2.</u> <u>Note that...</u>		

IOUT_OC_FAULT_RESPONSE

- MAX15303 does not support finite, non-zero restart-attempt counts. (Continuous restart attempts are supported.)
- MAX15303 also does not support the “delay before shutdown” (sometimes referred to as “wait for abate”) option for overcurrent faults.

The IOUT_OC_FAULT_RESPONSE command data comprises three bit-fields:

Bits [7:6] determine the basic fault-response mode. The MAX15303 supports the following modes:

- | | |
|----|--|
| 00 | Ignore the fault condition. |
| 01 | Same as setting 10. |
| 10 | Stop regulating immediately, delay for the time specified in bits [2:0], then attempt to restart according to bits [5:3]. <i>(Default setting)</i> |
| 11 | Same as setting 10. |

Bits [5:3] determine the number of retry attempts. The MAX15303 supports only a subset of the full PMBus functionality for this portion of the command:

- | | |
|---------|--|
| 000-110 | No attempt is made to restart after a fault shutdown. |
| 111 | Attempt to restart continuously until commanded off, or until another fault condition causes the unit to shut down. <i>(Default setting)</i> |

Bits [2:0] determine the retry-delay timing. Each binary value in bits [2:0] corresponds to a multiple of 100ms, up to a possible maximum of $111_{\text{bin}} = 700\text{ms}$. A value of 000_{bin} will cause the MAX15303 to use the minimum possible timing value, typically about 30-40ms. *(The default timing for overcurrent faults is 700ms.)*

OT_FAULT_LIMIT

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x4F	Format:	Linear
Data Bytes:	2	Units:	°C
Transfer:	Read/Write Word	Factory Value:	0xEB98 (115°C)

Description/Notes:	See Section 15.17 of the PMBus Specification Part II. The MAX15303 has an internal temperature signal and can also measure temperature at an external location, using a diode junction. The OT_FAULT_LIMIT applies to the external temperature signal, if a valid sensor is detected during initialization. If no external sensor is detected, the OT_FAULT_LIMIT applies to the internal temperature signal instead. In addition to the PMBus-programmable OT_FAULT_LIMIT value, there is also a hard-coded limit of 130°C that applies solely to the internal temperature signal to protect the flash memory of the MAX15303. Overtemperature fault hysteresis is achieved in the MAX15303 by using the OT_WARN_LIMIT as the “fault cleared” threshold for OT_FAULT_LIMIT. For this reason, it is important to always set OT_WARN_LIMIT below OT_FAULT_LIMIT.
---------------------------	--

OT_FAULT_RESPONSE

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x50	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read/Write Byte	Factory Value:	0xC0 (Shut down, restart when fault abates)

Description/Notes:	See Sections 10.5.1 and 15.18 of the PMBus Specification Part II. <u>Note that the MAX15303 does not support finite, non-zero restart-attempt counts. (Continuous restart attempts are supported.)</u> The OT_FAULT_RESPONSE command data comprises three bit-fields: Bits [7:6] determine the basic fault-response mode. The MAX15303 supports the following modes: 00 Ignore the fault condition. 01 Continue operating and wait for the fault to abate for time specified in bits [2:0]. If the fault does not abate, shutdown and attempt to restart according to bits [5:3]. 10 Stop regulating immediately, delay for the time specified in bits [2:0], then attempt to restart according to bits [5:3]. 11 Stop regulating immediately, and then restart as soon as possible after the fault condition abates.^d (Default setting) Bits [5:3] determine the number of retry attempts. <u>The MAX15303 supports only a subset of the full PMBus functionality for this portion of the command:</u> 000-110 No attempt is made to restart after a fault shutdown. (Default setting) 111 Attempt to restart continuously until commanded off, or until another fault condition causes the unit to shut down. Bits [2:0] determine the fault-tolerance or retry-delay timing. Each binary value in bits [2:0] corresponds to a multiple of 100ms, up to a possible maximum of 111_{bin} = 700ms. A value of 000_{bin} will cause the MAX15303 to use the minimum possible timing value, typically about 30-40ms. (The default timing for overcurrent faults is 000_{bin}.)		
---------------------------	---	--	--

OT_WARN_LIMIT

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x51	Format:	Linear
Data Bytes:	2	Units:	°C
Transfer:	Read/Write Word	Factory Value:	0xEAF8 (95°C)

Description/Notes:	See Section 15.19 of the PMBus Specification Part II. The MAX15303 has an internal temperature signal and can also measure temperature at an external location, using a diode junction. The OT_WARN_LIMIT applies to the external temperature signal, if a valid sensor is detected during initialization. If no external sensor is detected, the OT_WARN_LIMIT applies to the internal		
---------------------------	--	--	--

^d An overtemperature fault (i.e., relevant temperature signal above OT_FAULT_LIMIT) is not considered to have abated until the temperature has fallen below the OT_WARN_LIMIT value.

OT_WARN_LIMIT

temperature signal instead.

Overtemperature fault hysteresis is achieved in the MAX15303 by using the OT_WARN_LIMIT as the “fault cleared” threshold for [OT_FAULT_LIMIT](#). For this reason, it is important to always set OT_WARN_LIMIT below OT_FAULT_LIMIT.

VIN_OV_FAULT_LIMIT

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x55	Format:	Linear
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0xD380 (14V)
Description/Notes:	See Section 15.23 of the PMBus Specification Part II. The MAX15303 hardware has 8-bit resolution for the input overvoltage fault limit, to a maximum value of $\approx 14.75V$. The desired value of VIN_OV_FAULT_LIMIT is retained in memory, regardless limitations imposed by the 8-bit fault limit resolution, but the read-back value is based on actual hardware register settings.		

VIN_OV_FAULT_RESPONSE

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x56	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read/Write Byte	Factory Value:	0xC0 (Shut down, restart when fault abates)
Description/Notes:	See Sections 10.5.1 and 15.24 of the PMBus Specification Part II. <u>Note that the MAX15303 does not support finite, non-zero restart-attempt counts. (Continuous restart attempts are supported.)</u> The VIN_OV_FAULT_RESPONSE command data comprises three bit-fields: Bits [7:6] determine the basic fault-response mode. The MAX15303 supports the following modes: 00 Ignore the fault condition. 01 Continue operating and wait for the fault to abate for time specified in bits [2:0]. If the fault does not abate, shutdown and attempt to restart according to bits [5:3]. 10 Stop regulating immediately, delay for the time specified in bits [2:0], then attempt to restart according to bits [5:3]. 11 Stop regulating immediately, and then restart as soon as possible after the fault condition abates. <i>(Default setting)</i> Bits [5:3] determine the number of retry attempts. <u>The MAX15303 supports only a subset of the full PMBus functionality for this portion of the command:</u> 000-110 No attempt is made to restart after a fault shutdown. <i>(Default setting)</i> 111 Attempt to restart continuously until commanded off, or until another fault condition causes the unit to shut down.		

VIN_OV_FAULT_RESPONSE

Bits [2:0] determine the fault-tolerance or retry-delay timing. Each binary value in bits [2:0] corresponds to a multiple of 100ms, up to a possible maximum of $111_{\text{bin}} = 700\text{ms}$. A value of 000_{bin} will cause the MAX15303 to use the minimum possible timing value, typically about 30-40ms. *(The default timing for input overvoltage faults is 000_{bin} .)*

VIN_UV_FAULT_LIMIT

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x59	Format:	Linear
Data Bytes:	2	Units:	V
Transfer:	Read/Write Word	Factory Value:	0xCA1A (4.2V)
Description/Notes:	See Section 15.27 of the PMBus Specification Part II. The MAX15303 hardware has 8-bit resolution for the input undervoltage fault limit, to a maximum value of $\approx 14.75\text{V}$. The desired value of VIN_UV_FAULT_LIMIT is retained in memory, regardless limitations imposed by the 8-bit fault limit resolution, but the read-back value is based on actual hardware register settings.		

VIN_UV_FAULT_RESPONSE

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x5A	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read/Write Byte	Factory Value:	0xC0 (Shut down, restart when fault abates)
Description/Notes:	See Sections 10.5.1 and 15.28 of the PMBus Specification Part II. <u>Note that the MAX15303 does not support finite, non-zero restart-attempt counts. (Continuous restart attempts are supported.)</u> The VIN_UV_FAULT_RESPONSE command data comprises three bit-fields: Bits [7:6] determine the basic fault-response mode. The MAX15303 supports the following modes: 00 Ignore the fault condition. 01 Continue operating and wait for the fault to abate for time specified in bits [2:0]. If the fault does not abate, shutdown and attempt to restart according to bits [5:3]. 10 Stop regulating immediately, delay for the time specified in bits [2:0], then attempt to restart according to bits [5:3]. 11 Stop regulating immediately, and then restart as soon as possible after the fault condition abates. <i>(Default setting)</i> Bits [5:3] determine the number of retry attempts. <u>The MAX15303 supports only a subset of the full PMBus functionality for this portion of the command:</u> 000-110 No attempt is made to restart after a fault shutdown. <i>(Default setting)</i> 111 Attempt to restart continuously until commanded off, or until another fault condition causes the unit to shut down. Bits [2:0] determine the fault-tolerance or retry-delay timing. Each binary value in bits [2:0]		

VIN_UV_FAULT_RESPONSE

corresponds to a multiple of 100ms, up to a possible maximum of $111_{\text{bin}} = 700\text{ms}$. A value of 000_{bin} will cause the MAX15303 to use the minimum possible timing value, typically about 30-40ms. (*The default timing for input undervoltage faults is 000_{bin} .*)

Unit Status Commands

STATUS_BYTE

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x78	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read Byte	Factory Value:	N/A
Description/Notes:	See Section 17.1 of the PMBus Specification Part II.		

STATUS_WORD

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x79	Format:	Bit field
Data Bytes:	2	Units:	N/A
Transfer:	Read Word	Factory Value:	N/A
Description/Notes:	See Section 17.2 of the PMBus Specification Part II. Bit #2 of the STATUS_WORD low byte is not implemented in the MAX15303 because there are no relevant fan-related commands.		

STATUS_VOUT

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x7A	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read Byte	Factory Value:	N/A
Description/Notes:	See Section 17.3 of the PMBus Specification Part II. Bits #5 and #6 of STATUS_VOUT are not implemented in the MAX15303 because the VOUT_UV_WARNING and VOUT_OV_WARNING commands are not supported. Bit #1 is not implemented in the MAX15303 because the TOFF_MAX_WARNING is not supported.		

STATUS_IOUT

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x7B	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read Byte	Factory Value:	N/A
Description/Notes:	See Section 17.4 of the PMBus Specification Part II. Bits #6, #4, #2, #1, and #0 are not implemented in the MAX15303 because the corresponding fault commands are not supported.		

STATUS_INPUT

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x7C	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read Byte	Factory Value:	N/A
Description/Notes:	See Section 17.5 of the PMBus Specification Part II. Bits #6, #5, #2, #1, and #0 are not implemented in the MAX15303 because the corresponding fault commands are not supported.		

STATUS_TEMPERATURE

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x7D	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read Byte	Factory Value:	N/A
Description/Notes:	See Section 17.6 of the PMBus Specification Part II. Bits #5 and #4 are not implemented in the MAX15303 because the corresponding fault commands are not supported.		

STATUS_CML

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x7E	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read Byte	Factory Value:	N/A
Description/Notes:	See Section 17.7 of the PMBus Specification Part II.		

Telemetry Commands

READ_VIN

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x88	Format:	Linear
Data Bytes:	2	Units:	V
Transfer:	Read Word	Factory Value:	N/A
Description/Notes:	See Section 18.1 of the PMBus Specification Part II. The MAX15303 has 12-bit measurement resolution for input voltage to a maximum value of about 14.75V.		

READ_VOUT

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x8B	Format:	Unsigned integer mantissa
Data Bytes:	2	Units:	V
Transfer:	Read Word	Factory Value:	N/A
Description/Notes:	See Section 18.4 of the PMBus Specification Part II. The value of VOUT_TRIM is <i>not</i> subtracted from READ_VOUT, so non-zero VOUT_TRIM values <i>will</i> result in a difference between VOUT_COMMAND and READ_VOUT. The value of VOUT_CAL_OFFSET is subtracted from READ_VOUT, so VOUT_CAL_OFFSET values <i>never</i> result in a difference between VOUT_COMMAND and READ_VOUT.		

READ_IOUT

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x8C	Format:	Linear
Data Bytes:	2	Units:	A
Transfer:	Read Word	Factory Value:	N/A
Description/Notes:	See Section 18.5 of the PMBus Specification Part II. The MAX15303 has 8-bit measurement resolution for load current over a variable, symmetric bipolar range of inductor DCR voltage. READ_IOUT data is filtered and decimated, so reported load current may display greater than 8-bit resolution. READ_IOUT must be calibrated by means of IOUT_CAL_GAIN and IOUT_CAL_OFFSET to achieve accurate results. The value of READ_IOUT is temperature compensated for sense-element resistance change according to READ_TEMPERATURE_2 and the resistive temperature coefficient value in the third data byte of EXT_TEMP_CAL.		

READ_TEMPERATURE_1

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x8D	Format:	Linear
Data Bytes:	2	Units:	°C
Transfer:	Read Word	Factory Value:	N/A
Description/Notes:	See Section 18.6 of the PMBus Specification Part II. The MAX15303 uses READ_TEMPERATURE_1 to report its internal (i.e., die) temperature.		

READ_TEMPERATURE_2

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x8E	Format:	Linear
Data Bytes:	2	Units:	°C
Transfer:	Read Word	Factory Value:	N/A
Description/Notes:	See Section 18.6 of the PMBus Specification Part II. The MAX15303 uses READ_TEMPERATURE_2 to report external temperature as measured by an external diode junction, typically placed near the power inductor to facilitate READ_IOUT temperature compensation. If no external diode junction is detected, READ_TEMPERATURE_2 returns a value of -273°C and is not used for temperature faults or READ_IOUT temperature compensation. The Maxim-specific command EXT_TEMP_CAL can be used to adjust the diode ideality factor to match that of the actual diode junction used for external temperature sensing and to add or remove a fixed temperature offset for calibration purposes.		

READ_DUTY_CYCLE

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x94	Format:	Linear
Data Bytes:	2	Units:	%
Transfer:	Read Word	Factory Value:	N/A
Description/Notes:	See Section 18.9 of the PMBus Specification Part II. The READ_DUTY_CYCLE command returns an averaged measure of the pulse-width modulator output value in percent. The duty-cycle value is averaged over 256 PWM cycles.		

READ_FREQUENCY

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x95	Format:	Linear
Data Bytes:	2	Units:	kHz
Transfer:	Read Word	Factory Value:	N/A
Description/Notes:	See Section 18.10 of the PMBus Specification Part II.		

READ_FREQUENCY

The READ_FREQUENCY command returns the *actual* switching frequency in kilohertz.

The desired switching frequency is set using the [FREQUENCY_SWITCH](#) command.

PMB_VALUES

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xF5	Format:	See Description
Data Bytes:	220	Units:	See Description
Transfer:	Read/Write Block	Factory Value:	See Description
Description/Notes:	This command returns most PMBus command values from the device for ease of recording the device configuration. The command data returned is as follows: <pre> <ON_OFF_CONFIG position="0" Type="U8" NumElem="1"/> <WRITE_PROTECT position="1" Type="U8" NumElem="1"/> <VOUT_COMMAND position="2" Type="Float" NumElem="1"/> <VOUT_TRIM position="3" Type="Float" NumElem="1"/> <VOUT_CAL_OFFSET position="4" Type="Float" NumElem="1"/> <VOUT_MAX position="5" Type="Float" NumElem="1"/> <VOUT_MARGIN_HIGH position="6" Type="Float" NumElem="1"/> <VOUT_MARGIN_LOW position="7" Type="Float" NumElem="1"/> <VOUT_TRANSITION_RATE position="8" Type="Float" NumElem="1"/> <VOUT_DROOP position="9" Type="Float" NumElem="1"/> <FREQUENCY_SWITCH position="10" Type="Float" NumElem="1"/> <VIN_ON position="11" Type="Float" NumElem="1"/> <VIN_OFF position="12" Type="Float" NumElem="1"/> <INTERLEAVE position="13" Type="U8" NumElem="2"/> <IOUT_CAL_GAIN position="14" Type="Float" NumElem="1"/> <IOUT_CAL_OFFSET position="15" Type="Float" NumElem="1"/> <VOUT_OV_FAULT_LIMIT position="16" Type="Float" NumElem="1"/> <VOUT_OV_FAULT_RESPONSE position="17" Type="U8" NumElem="1"/> <VOUT_UV_FAULT_LIMIT position="18" Type="Float" NumElem="1"/> <VOUT_UV_FAULT_RESPONSE position="19" Type="U8" NumElem="1"/> <IOUT_OC_FAULT_LIMIT position="20" Type="Float" NumElem="1"/> <IOUT_OC_FAULT_RESPONSE position="21" Type="U8" NumElem="1"/> <OT_FAULT_LIMIT position="22" Type="Float" NumElem="1"/> <OT_FAULT_RESPONSE position="23" Type="U8" NumElem="1"/> <OT_WARN_LIMIT position="24" Type="Float" NumElem="1"/> <VIN_OV_FAULT_LIMIT position="25" Type="Float" NumElem="1"/> <VIN_OV_FAULT_RESPONSE position="26" Type="U8" NumElem="1"/> <VIN_UV_FAULT_LIMIT position="27" Type="Float" NumElem="1"/> <VIN_UV_FAULT_RESPONSE position="28" Type="U8" NumElem="1"/> <POWER_GOOD_ON position="29" Type="Float" NumElem="1"/> <POWER_GOOD_OFF position="30" Type="Float" NumElem="1"/> <TON_DELAY position="31" Type="Float" NumElem="1"/> <TON_RISE position="32" Type="Float" NumElem="1"/> <TON_MAX_FAULT_LIMIT position="33" Type="U8" NumElem="2"/> <TON_MAX_FAULT_RESPONSE position="34" Type="U8" NumElem="1"/> <TOFF_DELAY position="35" Type="Float" NumElem="1"/> <TOFF_FALL position="36" Type="Float" NumElem="1"/> </pre>		

PMB_VALUES

```
<MFR_ID position="37" Type="U8" NumElem="8"/>
<MFR_MODEL position="38" Type="U8" NumElem="13"/>
<MFR_REVISION position="39" Type="U8" NumElem="7"/>
<MFR_LOCATION position="40" Type="U8" NumElem="8"/>
<MFR_DATE position="41" Type="U8" NumElem="6"/>
<MFR_SERIAL position="42" Type="U8" NumElem="13"/>
<ADAPTIVE_MODE position="43" Type="U8" NumElem="2"/>
<ADAPTIVE_MODE_FAULT_RESPONSE position="44" Type="U8" NumElem="1"/>
<FEEDBACK_EFFORT position="45" Type="Float" NumElem="1"/>
<LOOP_CONFIG position="46" Type="U8" NumElem="2"/>
<ILOAD_CAL_GAIN position="47" Type="Float" NumElem="1"/>
<COMP_MODEL position="48" Type="Float" NumElem="3"/>
<STRAP_DISABLE position="49" Type="U8" NumElem="3"/>
<MANUF_LOCK position="50" Type="U8" NumElem="2"/>
<USER_LOCK position="51" Type="U8" NumElem="2"/>
<ZETAP position="52" Type="Float" NumElem="1"/>
<EXT_TEMP_CAL position="53" Type="Float" NumElem="3"/>
```

Calibration Commands

IOOUT_CAL_GAIN

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x38	Format:	Linear
Data Bytes:	2	Units:	mΩ
Transfer:	Read/Write Word	Factory Value:	0xB200 (0.5mΩ)
Description/Notes:	See Section 14.8 of the PMBus Specification Part II. The differential voltage measured between the DCRP and DCRN pins is divided by the value of IOOUT_CAL_GAIN and the value of IOOUT_CAL_OFFSET is subtracted to provide a load current signal, accessible through the READ_IOUT command. The factory value of 0xB200 (0.5mΩ) will be overridden during initialization by the hardware (pin-strap) value determined by the resistances to ground detected at the ADDR1 pin, unless a specific value of IOOUT_CAL_GAIN has been written to the User Store. The value of the ADDR1 pin resistance is measured only once during initialization (power-up). The value of IOOUT_CAL_GAIN is internally temperature compensated according to READ TEMPERATURE 2 and EXT TEMP CAL. Wait at least 500μs for execution after sending the IOOUT_CAL_GAIN command before sending additional PMBus commands.		

IOOUT_CAL_OFFSET

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x39	Format:	Linear
Data Bytes:	2	Units:	A
Transfer:	Read/Write Word	Factory Value:	0x0000 (0A)
Description/Notes:	See Section 14.9 of the PMBus Specification Part II. The differential voltage measured between the DCRP and DCRN pins is divided by the value of IOOUT_CAL_GAIN and the value of IOOUT_CAL_OFFSET is subtracted to provide a load current signal, accessible through the READ_IOUT command. <u>Note that the MAX15303 implementation of IOOUT_CAL_OFFSET differs from the PMBus specification because the sign of IOOUT_CAL_OFFSET is inverted (i.e., IOOUT_CAL_OFFSET is subtracted rather than added.)</u>		

EXT_TEMP_CAL

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xF8	Format:	Linear
Data Bytes:	6 (see Description)	Units:	Scalar, °K, 1/°C
Transfer:	Read/Write Block	Factory Value:	0.004, -8°K, 0.0038/°C
Description/Notes:	The EXT_TEMP_CAL command allows calibration of the external temperature sense signal and adjustment of the current-sense element temperature coefficient. The three arguments of the		

EXT_TEMP_CAL

EXT_TEMP_CAL signal are as follows:

Data Byte Number	Data Byte Name	Units	Description
0	m	None	Combined temperature gain correction and diode ideality factor
1	b	°K	Temperature offset correction
2	IoutTC	Δ/°C	Current-sense element temperature coefficient of resistivity

Temperature Calibration

When reading or writing the EXT_TEMP_CAL command data, note that *only the decimal portion* of the gain correction term (data byte 0) is sent to allow greater numerical precision within the constraints of the PMBus Linear data format. In other words, the gain correction term is summed with 1 internally when received by the MAX15303. Be sure to take this into account when working with the gain correction term.

The default gain term is nominally set for use with a Fairchild MMBT3904 transistor diode junction. To correct the gain term for a different temperature sense transistor, do the following:

1. Read the existing value of EXT_TEMP_CAL from the device
2. Sum the gain correction term value with 1.0
3. Multiply the resulting value of the gain correction term by the new transistor ideality factor
4. Divide the result by 1.004
5. Subtract 1.0 from the result
6. Send the final result back to the device

Note that the Maxim PowerTool GUI performs the addition and subtraction of 1.0 automatically.

Current-Sense Temperature Compensation

The value of IoutTC is used to provide current-sense temperature compensation. The [IOUT_CAL_GAIN](#) resistance value is multiplied by ([READ_TEMPERATURE_2](#) – 25°C) and by (IoutTC + 1) to determine the temperature-compensated resistance, which is used in turn to calculate [READ_IOUT](#).

Device Identification Commands

CAPABILITY

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x19	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read Byte	Factory Value:	0xA0
Description/Notes:	See Section 11.12 of the PMBus Specification Part II.		

PMBUS_REVISION

Reference:	Standard Command	Lockable:	N/A
Command Code:	0x98	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read Byte	Factory Value:	0x22 (see Description)
Description/Notes:	See Section 22.1 of the PMBus Specification Part II.		
	Note that due to a typographical error in the PMBus Specification version 1.2, wherein bit #4 is omitted from the PMBUS_REVISION data byte, the Maxim interpretation is to correct this error and include bit #4, placing the Part I Revision level in bits [7:4] and the Part II Revision level in bits [3:0]. ^e		
	Bits [7:4] describe the PMBus specification Part I revision level as follows:		
	0000 Revision 1.0		
	0001 Revision 1.1		
	0010 Revision 1.2		
	Bits [3:0] describe the PMBus specification Part II revision level as follows:		
	0000 Revision 1.0		
	0001 Revision 1.1		
	0010 Revision 1.2		

MFR_ID

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x99	Format:	ASCII string
Data Bytes:	8	Units:	N/A
Transfer:	Read/Write Block	Factory Value:	String of 6 spaces (ASCII 0x20)
Description/Notes:	See Section 22.2.1 of the PMBus Specification Part II. Note that the MAX15303 implements MFR_ID as a fixed-width string, not as part of a shared memory space.		

^e See the PMBus Specification, Part II, draft version 1.3, where this error is corrected to agree with the interpretation described here.

MFR_MODEL

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x9A	Format:	ASCII string
Data Bytes:	13	Units:	N/A
Transfer:	Read/Write Block	Factory Value:	String of 13 spaces (ASCII 0x20)
Description/Notes:	See Section 22.2.2 of the PMBus Specification Part II. Note that the MAX15303 implements MFR_MODEL as a fixed-width string, not as part of a shared memory space.		

MFR_REVISION

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x9B	Format:	ASCII string
Data Bytes:	7	Units:	N/A
Transfer:	Read/Write Block	Factory Value:	String of 7 spaces (ASCII 0x20)
Description/Notes:	See Section 22.2.3 of the PMBus Specification Part II. Note that the MAX15303 implements MFR_REVISION as a fixed-width string, not as part of a shared memory space.		

MFR_LOCATION

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x9C	Format:	ASCII string
Data Bytes:	8	Units:	N/A
Transfer:	Read/Write Block	Factory Value:	String of 8 spaces (ASCII 0x20)
Description/Notes:	See Section 22.2.4 of the PMBus Specification Part II. Note that the MAX15303 implements MFR_LOCATION as a fixed-width string, not as part of a shared memory space.		

MFR_DATE

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x9D	Format:	ASCII string
Data Bytes:	6	Units:	N/A
Transfer:	Read/Write Block	Factory Value:	String of 6 spaces (ASCII 0x20)
Description/Notes:	See Section 22.2.5 of the PMBus Specification Part II. Note that the MAX15303 implements MFR_DATE as a fixed-width string, not as part of a shared memory space. The recommended format is YYMMDD where Y, M, and D are integer values from 0 to 9, inclusive.		

MFR_SERIAL

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x9E	Format:	ASCII string
Data Bytes:	13	Units:	N/A
Transfer:	Read/Write Block	Factory Value:	String of 13 spaces (ASCII 0x20)
Description/Notes:	See Section 22.2.6 of the PMBus Specification Part II. Note that the MAX15303 implements MFR_SERIAL as a fixed-width string, not as part of a shared memory space.		

IC_DEVICE_ID

Reference:	Standard Command	Lockable:	N/A
Command Code:	0xAD	Format:	ASCII string
Data Bytes:	12	Units:	N/A
Transfer:	Read Block	Factory Value:	MAX15303AA00
Description/Notes:	See Section 22.2.7 of the PMBus Specification Part II. Note that the MAX15303 implements IC_DEVICE_ID as a fixed-width string, not as part of a shared memory space.		

IC_DEVICE_REV

Reference:	Standard Command	Lockable:	N/A
Command Code:	0xAE	Format:	ASCII string
Data Bytes:	8	Units:	N/A
Transfer:	Read Block	Factory Value:	Firmware revision (see Description)
Description/Notes:	See Section 22.2.8 of the PMBus Specification Part II. Note that the MAX15303 implements IC_DEVICE_REV as a fixed-width string, not as part of a shared memory space. The default value is the firmware revision number stored as an ASCII string, typically a 4-digit number. The Maxim PowerTool™ GUI uses this information to identify the supported command set for a particular slave device.		

Security Commands

WRITE_PROTECT

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x10	Format:	Bit field
Data Bytes:	1	Units:	N/A
Transfer:	Read/Write Byte	Factory Value:	0x00
Description/Notes:	See Section 11.1 of the PMBus Specification Part II.		

MANUF_CONF

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xE0	Format:	Bit field
Data Bytes:	32	Units:	N/A
Transfer:	Read/Write Block	Factory Value:	0
Description/Notes:	To allow password-based write-protection on a per-command basis, the MANUF_CONF command has 32 data bytes, with one bit per possible PMBus command; the byte order is low to high. Each bit position within the 32 bytes correlates to a PMBus command number from 0x00 to 0xFF. For example: Byte 0, bit 0: PAGE command Byte 0, bit 1: OPERATION command Byte 0, bit 2: ON_OFF_CONFIG command ... Byte 6, bit 3: FREQUENCY_SWITCH command etc... If the bit for a particular command is set in MANUF_CONF, and the read-only SECURITY_LEVEL command is <i>not</i> set to level 2 by successfully sending a value of MANUF_PASSWD that matches the working memory value of MANUF_LOCK, then the MAX15303 will ignore attempts to write data to that command. Note that setting a bit for a read-only PMBus command or send-byte PMBus command has no effect, regardless of SECURITY_LEVEL. Likewise, read operations for any PMBus command are never blocked on the basis of MANUF_CONF and SECURITY_LEVEL. The 32 data bytes for MANUF_CONF are saved in flash memory as a unique, single instance (i.e., not as part of the USER, DEFAULT, or MAXIM PMBus command stores.) The data is written to flash every time the MANUF_CONF command data is written to the MAX15303. Wait at least 350ms for execution after sending the MANUF_CONF command before sending additional PMBus commands.		

MANUF_LOCK

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xE1	Format:	Direct
Data Bytes:	2	Units:	N/A
Transfer:	Write Word	Factory Value:	0x0000
Description/Notes:	The MANUF_LOCK command contains the password value for the “manufacturer” PMBus command security level. If the working-memory value of MANUF_PASSWD matches the working-memory value of MANUF_LOCK, the SECURITY_LEVEL value is set to 2, and any PMBus commands flagged in MANUF_CONF or USER_CONF are unlocked for write operations. Note that SECURITY_LEVEL must be set to 2 before a new value can be written to MANUF_LOCK. The value of MANUF_LOCK can be stored in both the USER and DEFAULT nonvolatile PMBus memory with separate and distinct values – this should be taken into account when setting up command security.		

MANUF_PASSWD

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xE2	Format:	Direct
Data Bytes:	2	Units:	N/A
Transfer:	Read/Write Word	Factory Value:	N/A
Description/Notes:	The MANUF_PASSWD command is the “key” or password-attempt command used to unlock the “manufacturer” security level. If the working-memory value of MANUF_PASSWD matches the working-memory value of MANUF_LOCK, the SECURITY_LEVEL value is set to 2, and any PMBus commands flagged in MANUF_CONF or USER_CONF are unlocked for write operations. The value of MANUF_PASSWD is only retained in working memory and cannot be stored.		

USER_CONF

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xE3	Format:	Bit field
Data Bytes:	32	Units:	N/A
Transfer:	Read/Write Block	Factory Value:	0
Description/Notes:	To allow password-based write-protection on a per-command basis, the USER_CONF command has 32 data bytes, with one bit per possible PMBus command; the byte order is low to high. Each bit position within the 32 bytes correlates to a PMBus command number from 0x00 to 0xFF. For example: Byte 0, bit 0: PAGE command Byte 0, bit 1: OPERATION command Byte 0, bit 2: ON_OFF_CONFIG command ... Byte 6, bit 3: FREQUENCY_SWITCH command etc... If the bit for a particular command is set in USER_CONF, and the read-only SECURITY_LEVEL command is <i>not</i> set to level 1 by successfully sending a value of USER_PASSWD that matches the working		

USER_CONF

memory value of [USER_LOCK](#), then the MAX15303 will ignore attempts to write data to that command.

Note that setting a bit for a read-only PMBus command or send-byte PMBus command has no effect, regardless of SECURITY_LEVEL. Likewise, read operations for any PMBus command are never blocked on the basis of USER_CONF and SECURITY_LEVEL.

The 32 data bytes for USER_CONF are saved in flash memory as a unique, single instance (i.e., not as part of the USER, DEFAULT, or MAXIM PMBus command stores.) The data is written to flash every time the USER_CONF command data is written to the MAX15303.

Wait at least 350ms for execution after sending the USER_CONF command before sending additional PMBus commands.

USER_LOCK

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xE4	Format:	Direct
Data Bytes:	2	Units:	N/A
Transfer:	Read Word	Factory Value:	0x0000
Description/Notes:	The USER_LOCK command contains the password value for the “user” PMBus command security level. If the working-memory value of USER_PASSWD matches the working-memory value of USER_LOCK, the SECURITY_LEVEL value is set to 1, and any PMBus commands flagged in USER_CONF are unlocked for write operations. Note that SECURITY_LEVEL must be set to 1 before a new value can be written to USER_LOCK. The value of USER_LOCK can be stored in both the USER and DEFAULT nonvolatile PMBus memory with separate and distinct values – this should be taken into account when setting up command security.		

USER_PASSWD

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xE5	Format:	Direct
Data Bytes:	2	Units:	N/A
Transfer:	Read/Write Word	Factory Value:	N/A
Description/Notes:	The USER_PASSWD command is the “key” or password-attempt command used to unlock the “user” security level. If the working-memory value of USER_PASSWD matches the working-memory value of USER_LOCK, the SECURITY_LEVEL value is set to 1, and any PMBus commands flagged in USER_CONF are unlocked for write operations. The value of USER_PASSWD is only retained in working memory and cannot be stored.		

SECURITY_LEVEL

Reference:	Maxim Specific	Lockable:	N/A
Command Code:	0xE6	Format:	Direct
Data Bytes:	1	Units:	N/A
Transfer:	Read Byte	Factory Value:	0
Description/Notes:	The MAX15303 provides two levels of password protection for all writable PMBus commands, on a per-command basis. The SECURITY_LEVEL command value shows the present security level as follows:		
	<u>SECURITY_LEVEL</u>	<u>Description</u>	
	0	No write access to commands locked by USER_CONF or MANUF_CONF	
	1	Write access granted to commands locked by USER_CONF	
	2	Write access granted to commands locked by MANUF_CONF and USER_CONF	
	Note that SECURITY_LEVEL is 0 until a value is written to USER_PASSWD or MANUF_PASSWD that matches the working-memory value of USER_LOCK or MANUF_LOCK respectively.		
	When the working-memory value of USER_LOCK is written to USER_PASSWD, SECURITY_LEVEL is set to 1.		
	When the working-memory value of MANUF_LOCK is written to MANUF_PASSWD, SECURITY_LEVEL is set to 2.		
	Writing a “mismatched” (or wrong) value of USER_PASSWD or MANUF_PASSWD causes SECURITY_LEVEL to reset to 0.		
	The values of USER_LOCK and USER_CONF can only be changed when SECURITY_LEVEL is 1 or 2.		
The values of MANUF_LOCK and MANUF_CONF can only be changed when SECURITY_LEVEL is 2.			

Memory and Storage Commands

STORE_DEFAULT_ALL

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x11	Format:	N/A
Data Bytes:	0	Units:	N/A
Transfer:	Send Byte	Factory Value:	N/A

Description/Notes:	See Section 11.2 of the PMBus Specification Part II.	
	The MAX15303 includes three banks of nonvolatile (flash memory) storage for most “writable” PMBus command values, referred to as the USER, DEFAULT, and MAXIM stores. These stores are fully independent, but identical in structure.	
	The DEFAULT store is intended to function as a backup of an original equipment manufacturer (OEM) preferred device configuration. OEMs should save identical configurations to the USER store and the DEFAULT store, such that the USER store can be refreshed from the DEFAULT store if needed.	
	The contents of the DEFAULT store are never loaded into working memory unless the RESTORE_DEFAULT_ALL command is sent.	
	In general, when the STORE_DEFAULT_ALL command is sent, the existing contents of the DEFAULT store are erased, and the contents of the working PMBus memory (volatile RAM) are written into the DEFAULT store. There are exceptions to this behavior, as follows:	
	OPERATION	The OPERATION command is not stored to prevent unintentional enabling/disabling of the output.
	COMP_MODEL	The working memory COMP_MODEL data is only stored if the command has been edited (as recorded by STRAP_DISABLE).
	MANUF_CONF	The manufacturer flags for password command locking are stored independently in nonvolatile memory for security.
	MANUF_PASSWD	The manufacturer security password is always volatile for obvious reasons.
	USER_CONF	The user flags for password command locking are stored independently in nonvolatile memory for security.
USER_PASSWD	The user security password is always volatile for obvious reasons.	
DEADTIME_GCTRL	This command is used to initiate a partial internal edit of the nonvolatile “Config Page” special-purpose memory bank.	
Wait at least 450ms for execution after sending the STORE_DEFAULT_ALL command before sending additional PMBus commands.		

RESTORE_DEFAULT_ALL

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x12	Format:	N/A
Data Bytes:	0	Units:	N/A
Transfer:	Send Byte	Factory Value:	N/A
Description/Notes:	See Section 11.3 of the PMBus Specification Part II. The MAX15303 includes three banks of nonvolatile (flash memory) storage for most “writable” PMBus command values, referred to as the USER, DEFAULT, and MAXIM stores. These stores are fully independent, but identical in structure. The DEFAULT store is intended to function as a backup of an original equipment manufacturer (OEM) preferred device configuration. The contents of the DEFAULT store are only loaded into working memory when the RESTORE_DEFAULT_ALL command is sent; there are no other conditions or actions that result in loading of the DEFAULT store to working memory. Wait at least 10ms for execution after sending the RESTORE_DEFAULT_ALL command before sending additional PMBus commands. See STORE_DEFAULT_ALL for exceptions to PMBus nonvolatile command storage.		

STORE_USER_ALL

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x15	Format:	N/A
Data Bytes:	0	Units:	N/A
Transfer:	Send Byte	Factory Value:	N/A
Description/Notes:	See Section 11.6 of the PMBus Specification Part II. The MAX15303 includes three banks of nonvolatile (flash memory) storage for most “writable” PMBus command values, referred to as the USER, DEFAULT, and MAXIM stores. These stores are fully independent, but identical in structure. The USER store functions as the primary nonvolatile storage of all PMBus command values. Original equipment manufacturers (OEMs) should save identical configurations to the USER store and the DEFAULT store, such that the USER store can be refreshed from the DEFAULT store if needed. The contents of the USER store are loaded into working memory every time input power is applied to the MAX15303 device. The USER store can also be loaded to working memory at any time by sending the RESTORE_USER_ALL command. In general, when the STORE_USER_ALL command is sent, the existing contents of the USER store are erased, and the contents of the working PMBus memory (volatile RAM) are written into the USER store. There are exceptions to this behavior, as follows: OPERATION The OPERATION command is not stored to prevent unintentional enabling/disabling of the output. COMP_MODEL The working memory COMP_MODEL data is only stored if the command has been edited (as recorded by STRAP_DISABLE). MANUF_CONF The manufacturer flags for password command locking are stored		

STORE_USER_ALL

		independently in nonvolatile memory for security.
	MANUF_PASSWD	The manufacturer security password is always volatile for obvious reasons.
	USER_CONF	The user flags for password command locking are stored independently in nonvolatile memory for security.
	USER_PASSWD	The user security password is always volatile for obvious reasons.
	DEADTIME_GCTRL	This command is used to initiate a partial internal edit of the nonvolatile "Config Page" special-purpose memory bank.
	Wait at least 450ms for execution after sending the STORE_USER_ALL command before sending additional PMBus commands.	

RESTORE_USER_ALL

Reference:	Standard Command	Lockable:	Yes
Command Code:	0x16	Format:	N/A
Data Bytes:	0	Units:	N/A
Transfer:	Send Byte	Factory Value:	N/A
Description/Notes:	See Section 11.7 of the PMBus Specification Part II. The MAX15303 includes three banks of nonvolatile (flash memory) storage for most "writable" PMBus command values, referred to as the USER, DEFAULT, and MAXIM stores. These stores are fully independent, but identical in structure. The USER store functions as the primary nonvolatile storage of all PMBus command values. Original equipment manufacturers (OEMs) should save identical configurations to the USER store and the DEFAULT store, such that the USER store can be refreshed from the DEFAULT store if needed. The contents of the USER store are loaded into working memory every time input power is applied to the MAX15303 device. The USER store can also be loaded to working memory at any time by sending the RESTORE_USER_ALL command. Wait at least 10ms for execution after sending the RESTORE_USER_ALL command before sending additional PMBus commands. See STORE_USER_ALL for exceptions to PMBus nonvolatile command storage.		

RESTORE_MAXIM_ALL

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xEA	Format:	N/A
Data Bytes:	0	Units:	N/A
Transfer:	Send Byte	Factory Value:	N/A
Description/Notes:	The MAX15303 includes three banks of nonvolatile (flash memory) storage for most “writable” PMBus command values, referred to as the USER, DEFAULT, and MAXIM stores. These stores are fully independent, but identical in structure. The MAXIM store functions as a backup of the firmware default configuration, and it cannot be edited. The contents of the MAXIM store are only loaded into working memory when the RESTORE_MAXIM_ALL command is sent; there are no other conditions or actions that result in loading of the MAXIM store to working memory. Wait at least 10ms for execution after sending the RESTORE_MAXIM_ALL command before sending additional PMBus commands.		

STRAP_DISABLE

Reference:	Maxim Specific	Lockable:	Yes																								
Command Code:	0xDC	Format:	Bit field																								
Data Bytes:	3	Units:	N/A																								
Transfer:	Read/Write Word	Factory Value:	0x000000																								
Description/Notes:	Several commands in the MAX15303 can be set directly by resistor value connected to a device pin, or are set indirectly according the value of other pin-configurable commands. Of these “pin-configurable” commands, the STRAP_DISABLE command keeps track of those that have been directly altered by a user through the SMBus serial interface. When one of the commands in the table below is edited, the corresponding bit-flag in STRAP_DISABLE is set, and this flag prevents the device from automatically setting the value of that command in the future, preserving the user-set value instead. Note that the STRAP_DISABLE command can be saved in the USER and DEFAULT nonvolatile stores. In order to disable pin-configuration of a command, the flag for that command must be 1, and a STORE_USER_ALL operation must have been performed, to ensure that the device powers up with the flag set in the working-memory version of STRAP_DISABLE. (This process is handled automatically without need for special user interaction in most situations.) To restore pin-configuration capability for a command, clear the corresponding bit in STRAP_DISABLE and send the STORE_USER_ALL command. <table><tr><th>Bit</th><th>Command</th><th>Comments</th></tr><tr><td>23</td><td><RESERVED></td><td></td></tr><tr><td>22</td><td><RESERVED></td><td></td></tr><tr><td>21</td><td><RESERVED></td><td></td></tr><tr><td>20</td><td><RESERVED></td><td></td></tr><tr><td>19</td><td><RESERVED></td><td></td></tr><tr><td>18</td><td><RESERVED></td><td></td></tr><tr><td>17</td><td><RESERVED></td><td></td></tr></table>			Bit	Command	Comments	23	<RESERVED>		22	<RESERVED>		21	<RESERVED>		20	<RESERVED>		19	<RESERVED>		18	<RESERVED>		17	<RESERVED>	
Bit	Command	Comments																									
23	<RESERVED>																										
22	<RESERVED>																										
21	<RESERVED>																										
20	<RESERVED>																										
19	<RESERVED>																										
18	<RESERVED>																										
17	<RESERVED>																										

STRAP_DISABLE

16	<u>VOUT_TRIM</u>	No function; intended to support a possible pin-strap voltage trimming scheme that was never implemented.
15	<u>INTERLEAVE</u>	Command set indirectly by the SMBus slave address, from R _{ADDR0} and R _{ADDR1} resistor values.
14	<u>COMP_MODEL</u>	The F _{LC} data is set automatically by the parametric extraction process
13	<u>VOUT_MAX</u>	Command set indirectly according to VOUT_COMMAND x 110%
12	<u>IOUT_CAL_GAIN</u>	Command set by R _{ADDR1} resistor value
11	<u>FREQUENCY_SWITCH</u>	Command set by R _{SYNC} resistor value
10	<RESERVED>	
9	<u>IOUT_OC_FAULT_LIMIT</u>	Command not set automatically; flag is for future sue
8	<u>VOUT_MARGIN_LOW</u>	Command set indirectly according to VOUT_COMMAND x 95%
7	<u>VOUT_MARGIN_HIGH</u>	Command set indirectly according to VOUT_COMMAND x 105%
6	<u>POWER_GOOD_OFF</u>	Command set indirectly according to VOUT_COMMAND x 85%
5	<u>POWER_GOOD_ON</u>	Command set indirectly according to VOUT_COMMAND x 90%
4	VOUT_UV_WARN_LIMIT	Undervoltage warning is not implemented
3	<u>VOUT_UV_FAULT_LIMIT</u>	Command set indirectly according to VOUT_COMMAND x 85%
2	VOUT_OV_WARN_LIMIT	Overvoltage warning is not implemented
1	<u>VOUT_OV_FAULT_LIMIT</u>	Command set indirectly according to VOUT_COMMAND x 115%
0	<u>VOUT_COMMAND</u>	Command set by R _{SET} resistor value

Control Loop Commands

ADAPTIVE_MODE

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xD0	Format:	Bit field
Data Bytes:	2	Units:	N/A
Transfer:	Read/Write Word	Factory Value:	0x024B

Description/Notes: The ADAPTIVE_MODE command configures the automatic tuning features of the MAX15303. Each bit in the two data bytes enables a particular function as follows:

Bit	Name	Effect When True
15	<RESERVED>	
14	<RESERVED>	
13	<RESERVED>	
12	FIRST_ENABLE_ONLY	Perform parametric extraction on first enable only
11	<RESERVED>	
10	<RESERVED>	
9	ADAPT_POST_RAMP	Perform parametric extraction after the startup ramp (set by default)
8	ADAPT_CONTINUOUS	Perform parametric extraction periodically while regulating
7	<RESERVED>	
6	UPDATE_FLC	Update working memory LC double-pole frequency (F_{LC}) after parametric extraction (set by default)
5	UPDATE_FZ	Update working memory output capacitor ESR zero frequency (F_Z) after parametric extraction
4	UPDATE_ZLC	Update working memory LC damping factor (Z_{LC}) after parametric extraction
3	RESET_GAINS	Reset gain registers based on USER store values when output is disabled (set by default)
2	WRITEFLASH	Execute STORE_USER_ALL after adaptive measurement (note that this bit is cleared from the working memory copy of ADAPTIVE_MODE after execution)
1	GAIN_CALC	Calculate new NLSS “fast gain” register values based on COMP_MODEL parameters (set by default)
0	FAST_GAINS	The control loop will switch to using the NLSS “fast gains” registers after ramp-up is complete (set by default)

Wait at least 500 μ s for execution after sending the ADAPTIVE_MODE command before sending additional PMBus commands.

FEEDBACK_EFFORT

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xD3	Format:	Linear
Data Bytes:	2	Units:	Scalar
Transfer:	Read Byte	Factory Value:	0xB200 (0.5)

Description/Notes:	This command allows some user adjustment of the tradeoff between transient response, load regulation, and output noise. The default value is 0.5, which provides a good balance of transient response performance and output noise characteristics. Lower values of FEEDBACK_EFFORT (as low as 0.0) will tend to provide lower output noise, at the expense of transient performance and slightly reduced load regulation accuracy. Higher values of FEEDBACK_EFFORT (up to 1.0) will provide improved transient response and load regulation, at the expense of increased output noise and PWM waveform rising/falling edge “jitter.” As a generalization, increasing FEEDBACK_EFFORT tends to increase effective control loop bandwidth, while decreasing FEEDBACK_EFFORT reduces bandwidth. Wait at least 500μs for execution after sending the FEEDBACK_EFFORT command before sending additional PMBus commands.
---------------------------	---

LOOP_CONFIG

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xD5	Format:	Bit field
Data Bytes:	2	Units:	N/A
Transfer:	Read/Write Word	Factory Value:	0x0100

Description/Notes:	The LOOP_CONFIG command configures miscellaneous control-loop features of the MAX15303. Each bit in the two data bytes enables a particular function as follows:
---------------------------	---

Bit	Name	Effect When True
15	<RESERVED>	
14	<RESERVED>	
13	<RESERVED>	
12	<RESERVED>	
11	<RESERVED>	
10	<RESERVED>	
9	NOGAINCALC	The control loop will only use hard-coded NLSS gain values
8	PIDMODE	Enable integral term in the control loop (set by default)
7	<RESERVED>	
6	<RESERVED>	
5	<RESERVED>	
4	AGDEN	Enable adaptive gate-drive timing system (not supported)
3	NEGDUTYEN	Enable low-side body diode “braking” on load-release transient
2	<RESERVED>	
1	<RESERVED>	
0	<RESERVED>	

Wait at least 500μs for execution after sending the LOOP_CONFIG command before sending additional PMBus commands.

COMP_MODEL

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xDB	Format:	Linear
Data Bytes:	6 (see Description)	Units:	Scalar
Transfer:	Read/Write Block	Factory Value:	0.025, 0.41666, 1.0

Description/Notes: The COMP_MODEL command provides access to key control loop tuning parameters. The three arguments are as follows:

Data Byte Number	Data Byte Name	Units	Description
0	F_{LC}/F_{SW}	None	Power stage LC double-pole frequency, as a fraction of the PWM fundamental frequency. In typical operation, this parameter is determined by parametric extraction.
1	F_z/F_{SW}	None	Output capacitor ESR zero frequency, as a fraction of the PWM fundamental frequency.
2	Z_{LC}	None	Power stage damping factor. Higher values indicate a more damped LC filter; lower values represent a less damped filter.

The values of COMP_MODEL can be altered by the parametric extraction function of the MAX15303. They will reset to the USER store values whenever the output is disabled, unless bit 3 of [ADAPTIVE_MODE](#) is cleared.

Note that the values in COMP_MODEL are not saved during a [STORE_USER_ALL](#) or [STORE_DEFAULT_ALL](#) operation, unless the values have previously been set by a PMBus write to COMP_MODEL, as indicated by bit 14 of [STRAP_DISABLE](#). This safety feature prevents inadvertent storage of parametric extraction results that could adversely affect the initial ramp control loop tuning.

Wait at least 500μs for execution after sending the COMP_MODEL command before sending additional PMBus commands.

DEADTIME_GCTRL

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xE7	Format:	See Description
Data Bytes:	19	Units:	N/A
Transfer:	Read/Write Block	Factory Value:	See Description

Description/Notes: The DEADTIME_GCTRL command allows configuration and adjustment of static gate-drive timing. The arguments for this command are as follows:

Byte #	Data Name	Data Type	Description	Default Value
0	fixedDTR (LSB)	Signed Integer	Static rising-edge deadtime adjustment, given in nanoseconds	20
1	fixedDTR (MSB)			
2	fixedDTF (LSB)	Signed Integer	Static falling-edge deadtime adjustment, given in nanoseconds	20
3	fixedDTF (MSB)			
4	TDR (LSB)	Signed Integer	AGD system rising edge deadtime target value (AGD system disabled, do not alter this value)	3
5	TDR (MSB)			
6	TDF (LSB)	Signed	AGD system falling edge deadtime target value	8

DEADTIME_GCTRL

7	TDF (MSB)	Integer	(AGD system disabled, do not alter this value)	
8	LXDAC	Unsigned Byte	(AGD system disabled, do not alter this value)	15
9	GCTRL[0]	Unsigned Byte	Function disabled; not applicable	0
10	GCTRL[1]	Unsigned Byte	Function disabled; not applicable	0
11	GCTRL[2]	Unsigned Byte	Function disabled; not applicable	0
12	GCTRL[3]	Unsigned Byte	Function disabled; not applicable	0
13	GCTRL[4]	Unsigned Byte	Function disabled; not applicable	0
14	GCTRL[5]	Unsigned Byte	Function disabled; not applicable	0
15	GCTRL[6]	Unsigned Byte	Function disabled; not applicable	0
16	GCTRL[7]	Unsigned Byte	Function disabled; not applicable	0
17	GCTRLDAC (LSB)	Unsigned Integer	Function disabled; not applicable	0
18	GCTRLDAC (MSB)			

Non-overlap/Deadtime Adjustment

The fixedDTR and fixedDTF terms adjust the gate-drive non-overlap timing. For the MAX15303, these deadtime adjustment values are in nanoseconds, and constant timing is maintained regardless of switching frequency.

Caution must be exercised when trimming the gate-drive non-overlap timing; it is possible to set negative values and cause the high-side driver to enable before the low-side driver has disabled, and vice-versa.

Body-Diode Conduction Comparator

The LXDAC term is used to adjust the low-side MOSFET body-diode conduction detection comparator reference threshold. Note: the default setting is LXDAC = 15 and this value should not be changed.

Gate-Drive Voltage

Unlike some other Maxim digital power controllers, the MAX15303 does not allow adjustment of the gate drive voltage because of the use of internal MOSFETs which are optimized for operation at a fixed drive voltage.

Wait at least 500ms for execution after sending the DEADTIME_GCTRL command before sending additional PMBus commands.

ZETA_P

Reference:	Maxim Specific	Lockable:	Yes
Command Code:	0xE8	Format:	Linear

ZETA_P			
Data Bytes:	2	Units:	Scalar
Transfer:	Read/Write Byte	Factory Value:	0xBB00 (1.5)
Description/Notes:	The ZETA_P command sets the damping ratio for the closed-loop response. The value can be changed to improve performance when using non-ceramic output capacitors with higher equivalent series resistance. Wait at least 500μs for execution after sending the ZETA_P command before sending additional PMBus commands.		

Trademarks

InTune is a trademark of Maxim Integrated Products, Inc.

PMBus is a trademark of SMIF, Inc.

Revision History

REVISION NUMBER	REVISION DATE	DESCRIPTION	PAGES CHANGED
0	1/14	Initial release	—