



MBR735 THRU MBR760



Plastic package has Underwriters Laboratory
Flammability Classifications 94V-0

- ♦ Metal to silicon rectifier, majority carrier conduction
- ♦ Low power loss, high efficiency
- ♦ High current capability, low forward voltage drop
- ♦ High surge capability
- ♦ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- ♦ Guardring for overvoltage protection
- ♦ High temperature soldering guaranteed:
250°C/10 seconds, 0.25" (6.35mm) from case



MECHANICAL DATA

Case: JEDEC TO-220AC molded plastic body
Terminals: Lead solderable per MIL-STD-750, Method 2026

Polarity: As marked

Mounting Position: Any

Mounting Torque: 5 in. - lbs. max.

Weight: 0.08 ounces, 2.24 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

	SYMBOLS	MBR735	MBR745	MBR750	MBR760	UNITS
Maximum repetitive peak reverse voltage	V _{RRM}	35	45	50	60	Volts
Maximum working peak reverse voltage	V _{RWM}	35	45	50	60	Volts
Maximum DC blocking voltage	V _{DC}	35	45	50	60	Volts
Maximum average forward rectified current (SEE FIG 1)	I(AV)	7.5				Amps
Peak repetitive forward current (square wave, 20 KHz) at T _C =105°C	I _{FRM}	15.0				Amps
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	150.0				Amps
Peak repetitive reverse surge current (NOTE 1)	I _{RRM}	1.0		0.5		Amps
Maximum instantaneous forward voltage at I _F =7.5A, T _C =25°C I _F =7.5A, T _C =125°C (NOTE 2) I _F =15A, T _C =25°C I _F =15A, T _C =125°C	V _F	- 0.57 0.84 0.72		0.75 0.65 - -		Volts
Maximum instantaneous reverse current at rated DC blocking voltage T _C =25°C (NOTE 1) T _C =125°C	I _R	0.1 15.0		0.5 50		mA
Voltage rate of change (rated V _R)	dv/dt	10,000				V/μs
Maximum thermal resistance, (NOTE 3)	R _{θJC} R _{θJA}	3.0 60.0				°C/W
Operating junction temperature range	T _J	-65 to +150				°C
Storage temperature range	T _{STG}	-65 to +175				°C

NOTES:

(1) 2.0 μs , pulse width, f=1.0 KHz

(2) Pulse test: 300 μs pulse width, 1% duty cycle

(3) Thermal resistance from junction to case and/or thermal resistance from junction to ambient

RATINGS AND CHARACTERISTIC CURVES MBR735 THRU MBR760

FIG. 1 - FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE




FIG. 6 - TYPICAL TRANSIENT THERMAL IMPEDANCE

