Thyristor Module

V_{RRM} = 1600 V
I_{TAV} = 600 A
V_T = 1.06 V

Single Thyristor

Part number

MCO600-16io1



Backside: isolated

E72873



Features / Advantages:

- Thyristor for line frequency
- Planar passivated chip
- Long-term stability
- Direct Copper Bonded Al2O3-ceramic

Applications:

- Line rectifying 50/60 Hz
- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control

Package: Y1

- Isolation Voltage: 3600 V~
- Industry standard outline
- RoHS compliant
- Soldering pins for PCB mounting
- Base plate: Copper internally DCB isolated
- Advanced power cycling

Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

© 2019 IXYS all rights reserved

Thyristor

Symbol	Definition	Conditions		Ratings min.	typ.	max.	Unit
$V_{RSM/DSM}$	*max. non-repetitive reverse/forward blocking voltage*		T_{VJ} = 25°C			1700	V
$V_{RRM/DRM}$	*max. repetitive reverse/forward blocking voltage*		T_{VJ} = 25°C			1600	V
$I_{R/D}$	*reverse current, drain current*	$V_{R/D}$ = 1600 V	T_{VJ} = 25°C			2	mA
		$V_{R/D}$ = 1600 V	T_{VJ} = 125°C			40	mA
V_T	*forward voltage drop*	I_T = 600 A	T_{VJ} = 25°C			1.12	V
		I_T = 1200 A				1.34	V
		I_T = 600 A	T_{VJ} = 125°C			1.06	V
		I_T = 1200 A				1.33	V
I_{TAV}	*average forward current*	T_C = 85°C	T_{VJ} = 140°C			600	A
$I_{T(RMS)}$	*RMS forward current*	180° sine				940	A
V_{T0}	*threshold voltage* } *for power loss calculation only*		T_{VJ} = 140°C			0.81	V
r_T	*slope resistance* }					0.4	mΩ
R_{thJC}	*thermal resistance junction to case*					0.065	K/W
R_{thCH}	*thermal resistance case to heatsink*				0.02		K/W
P_{tot}	*total power dissipation*		T_C = 25°C			1770	W
I_{TSM}	*max. forward surge current*	t = 10 ms; (50 Hz), sine	T_{VJ} = 45°C			15.0	kA
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			16.2	kA
		t = 10 ms; (50 Hz), sine	T_{VJ} = 140°C			12.8	kA
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			13.8	kA
I^2t	*value for fusing*	t = 10 ms; (50 Hz), sine	T_{VJ} = 45°C			1.13	MA^2s
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			1.09	MA^2s
		t = 10 ms; (50 Hz), sine	T_{VJ} = 140°C			812.8	kA^2s
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			788.8	kA^2s
C_J	*junction capacitance*	V_R = 400 V f = 1 MHz	T_{VJ} = 25°C		620		pF
P_{GM}	*max. gate power dissipation*	t_P = 30 µs	T_C = 140°C			120	W
		t_P = 300 µs				60	W
P_{GAV}	*average gate power dissipation*					20	W
$(di/dt)_{cr}$	*critical rate of rise of current*	T_{VJ} = 140°C; f = 50 Hz	repetitive, I_T = 1800 A			100	A/µs
		t_P = 200 µs; di_G/dt = 1 A/µs;					
		I_G = 1 A; V = ⅔ V_{DRM}	non-repet., I_T = 600 A			500	A/µs
$(dv/dt)_{cr}$	*critical rate of rise of voltage*	V = ⅔ V_{DRM}	T_{VJ} = 140°C			1000	V/µs
		R_{GK} = ∞; method 1 (linear voltage rise)					
V_{GT}	*gate trigger voltage*	V_D = 6 V	T_{VJ} = 25°C			2	V
			T_{VJ} = -40°C			3	V
I_{GT}	*gate trigger current*	V_D = 6 V	T_{VJ} = 25°C			300	mA
			T_{VJ} = -40°C			400	mA
V_{GD}	*gate non-trigger voltage*	V_D = ⅔ V_{DRM}	T_{VJ} = 140°C			0.25	V
I_{GD}	*gate non-trigger current*					10	mA
I_L	*latching current*	t_p = 30 µs	T_{VJ} = 25°C			400	mA
		I_G = 1 A; di_G/dt = 1 A/µs					
I_H	*holding current*	V_D = 6 V R_{GK} = ∞	T_{VJ} = 25°C			300	mA
t_{gd}	*gate controlled delay time*	V_D = ½ V_{DRM}	T_{VJ} = 25°C			2	µs
		I_G = 1 A; di_G/dt = 1 A/µs					
t_q	*turn-off time*	V_R = 100 V; I_T = 600A; V = ⅔ V_{DRM}	T_{VJ} = 125 °C		350		µs
		di/dt = 10 A/µs dv/dt = 50 V/µs t_p = 200 µs					

© 2019 IXYS all rights reserved

Package Y1				Ratings			
Symbol	**Definition**	**Conditions**		**min.**	**typ.**	**max.**	**Unit**
I_{RMS}	*RMS current*	per terminal				600	A
T_{VJ}	*virtual junction temperature*			-40		140	°C
T_{op}	*operation temperature*			-40		125	°C
T_{stg}	*storage temperature*			-40		125	°C
Weight					650		g
M_D	*mounting torque*			4.5		7	Nm
M_T	*terminal torque*			11		13	Nm
$d_{Spp/App}$	*creepage distance on surface | striking distance through air*		*terminal to terminal*	16.0			mm
$d_{Spb/Apb}$			*terminal to backside*	25.0			mm
V_{ISOL}	*isolation voltage*	t = 1 second	50/60 Hz, RMS; I_{ISOL} ≤ 1 mA	3600			V
		t = 1 minute		3000			V



Data Matrix: *part no.* (1-19), DC + *PI* (20-25), *lot.no.#* (26-31), *blank* (32), *serial no.#* (33-36)

Ordering	Ordering Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	MCO600-16io1	MCO600-16io1	Box	2	474304

Equivalent Circuits for Simulation

** on die level* T_{VJ} = 140°C



Thyristor

$V_{0\,max}$	*threshold voltage*	0.81	V
$R_{0\,max}$	*slope resistance **	0.22	mΩ

© 2019 IXYS all rights reserved

Outlines Y1



Optional accessories for modules
Keyed gate/cathode twin plugs with wire length = 350 mm, gate = white, cathode = red
Type ZY 180L (L = Left for pin pair 4/5) UL 758, style 3751



© 2019 IXYS all rights reserved

Thyristor



Fig. 1 Forward characteristics



Fig. 2 Surge overload current



Fig. 3 I^2t versus time (1-10 ms)



Fig. 4 Gate trigger characteristics



Fig. 5 Gate controlled delay time



Fig. 6 Max. forward current at case temperature



Fig. 7a Power dissipation versus direct output current
Fig. 7b and ambient temperature



Fig. 8 Transient thermal impedance

© 2019 IXYS all rights reserved