



Price** : 1,372.00 USD



Main

Range	PowerLogic
Product name	CT
Product or component type	Current transformer
Secondary current	5 A
Accuracy class	Class 1 1.5 VA Class 3 2.5 VA
Line Rated Current	75 A

Complementary

Current transformer type	Tropicalised for cable
Current transformer ratio	75/5
[Ith] conventional free air thermal current	4.5 kA
Dynamic withstand current	2.5 Ith
Maximum safety factor	5
[Ue] rated operational voltage	< 720 V AC 50/60 Hz
[Ui] rated insulation voltage	3 kV
Mounting mode	Clip-on By screws
Mounting support	DIN rail Mounting plate
Width	Outside 1.73 in (44 mm)
Height	Outside 2.56 in (65 mm)
Depth	Frame 1.18 in (30 mm) Total 1.46 in (37 mm)
Diameter	0.83 in (21 mm)
Net weight	0.42 lb(US) (0.19 kg)

[Uimp] rated impulse withstand voltage	3 kV
Electrical insulation class	Class B
Cable outer diameter	0.83 in (21 mm)
Sealing	With

Environment

Standards	IEC 61869-2 VDE 0414
Product certifications	CE EAC
IP degree of protection	IP20
Relative humidity	0...95 %
Ambient air temperature for operation	-13...140 °F (-25...60 °C)

Ordering and shipping details

Category	01290 - MASTERPACT ACCESSORIES
Discount Schedule	DE2F
GTIN	03303431123421
Returnability	No
Country of origin	TN

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.