
55-65GHz Single Side Band Mixer

GaAs Monolithic Microwave IC

preliminary

Description

The MFC-P09828 is a multifunction chip (MFC) which integrates a LO buffer amplifier and a sub-harmonically balanced diode mixer for 2LO suppression and image rejection. It is usable both for up-conversion and down-conversion. It is designed for a wide range of applications, from military to commercial communication systems. The backside of the chip is both RF and DC grounds. This helps simplify the assembly process.
The circuit is manufactured with a PM-HEMT process, 0.25µm gate length, via holes through the substrate, air bridges and electron beam gate lithography.
It is available in chip form.



Main Features

- Broadband performance : 55-65 GHz RF
- 12dB conversion Loss
- 10dBc image rejection
- +10dBm LO input power
- +0dBm input power (1dB gain comp.)
- DC power consumption, 90mA @ 3.5V
- Chip size : 2.10 x 1.17 x 0.10 mm

Main Characteristics

Tamb. = 25°C

	Parameter	Min	Typ	Max	Unit
F_{RF}	RF frequency range	55		65	GHz
F_{LO}	LO frequency range	27.5		32.5	GHz
F_{IF}	IF frequency range	DC		5	GHz
L_c	Conversion Loss		12		dB

ESD Protection : Electrostatic discharge sensitive device. Observe handling precautions !

United Monolithic Semiconductors S.A.S.
Route Départementale 128 - B.P.46 - 91401 Orsay Cedex France
Tel. : +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09

Electrical Characteristics

Tamb = +25°C, Vd = 3.5V

preliminary

Symbol	Parameter	Min	Typ	Max	Unit
F_{RF}	RF frequency range	55		65	GHz
F_{LO}	LO frequency range	27.5		32.5	GHz
F_{IF}	IF frequency range	DC		5	GHz
L_c	Conversion Loss		12		dB
P_{LO}	LO Input power		+10		dBm
2xLO Leak	2xLO Leakage (for P_{LO}=+5dBm)		-35		dBm
Img Rej	Image Rejection (1)		10		dBc
P1dB	Input power at 1dB gain compression		+0		dBm
P03	Input power at 3dB gain compression		+2		dBm
IP3	Input 3rd order intercept point		+8		dBm
LO Match	LO Matching		2.0:1		
RF Match	RF Matching		2.0:1		
IF Match	IF Matching		2.0:1		
Id	Bias current		90		mA

(1) With external quadrature hybrid coupler (reference on request)

A wire bond of typically 0.1 to 0.15 nH will improve the input and output matching.

Absolute Maximum Ratings

Tamb = +25°C

Symbol	Parameter	Values	Unit
Vd	Drain bias voltage	*4.0*	V
Id	Drain bias current	*150*	mA
Ta	Operating temperature range	*-40 to +85*	°C
Tstg	Storage temperature range	*-55 to +125*	°C

(1) Operation of device above anyone of these parameters may cause permanent damage.


Route Départementale 128 , B.P.46 - 91401 ORSAY Cedex - FRANCE
Tel.: +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09


united monolithic semiconductors


preliminary


Typical On-wafer Measurements in Up-Conversion mode with external combiner

Bias conditions: Tamb = +25°C, Vd = 3.5V, Id = 90mA










Typical On-wafer Measurements in Down-Conversion mode with external combiner

Bias conditions: Tamb = +25°C, Vd = 3.5V, Id = 90mA




Route Départementale 128 , B.P.46 - 91401 ORSAY Cedex - FRANCE
Tel.: +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09


united monolithic semiconductors


preliminary

Typical On-wafer Measurements in Up-Conversion mode without external combiner

Bias conditions: Tamb = +25°C, Vd = 3.5V, Id = 90mA








Route Départementale 128 , B.P.46 - 91401 ORSAY Cedex - FRANCE
Tel.: +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09

united monolithic semiconductors


Chip Assembly and Mechanical Data

preliminary



Note : Supply feed should be capacitively bypassed. 25µm diameter gold wire is to be prefered.

It is necessary to use an external hybrid quadrature combiner on the IF ports if the image rejection functionality is required.



Bonding pad positions.

(Chip thickness : 100µm. All dimensions are in micrometers)

Route Départementale 128 , B.P.46 - 91401 ORSAY Cedex - FRANCE
Tel.: +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09

united monolithic semiconductors

preliminary

Ordering Information

Chip form : MFC - P09828-99F/00

Information furnished is believed to be accurate and reliable. However **United Monolithic Semiconductors S.A.S.** assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of **United Monolithic Semiconductors S.A.S.**. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. **United Monolithic Semiconductors S.A.S.** products are not authorised for use as critical components in life support devices or systems without express written approval from **United Monolithic Semiconductors S.A.S.**

Route Départementale 128 , B.P.46 - 91401 ORSAY Cedex - FRANCE
Tel.: +33 (0)1 69 33 03 08 - Fax : +33 (0)1 69 33 03 09