



Features

- High resistance to heat and humidity
- Resistance to mechanical shock and pressure
- Accurate dimensions for automatic surface mounting
- Wide impedance range
- RoHS compliant* and halogen free**



The models indicated in grey are currently available but not recommended for new designs.

MH Series High Current Chip Ferrite Beads

Electrical Specifications

Model Number	Impedance (Ω) at 100 MHz	RDC (m Ω) Max.	IDC (A) Max.
MH4532-700Y	70 ± 25 %	30	6.0
MH4516-600Y	60 ± 25 %	10	6.0
MH4516-750Y	75 ± 25 %	25	3.0
MH4516-800Y	80 ± 25 %	50	3.0
MH4516-102Y	1000 ± 25 %	150	1.5
MH3261-260Y	26 ± 25 %	40	3.0
MH2029-070Y	7 ± 25 %	30	3.0
MH2029-100Y	10 ± 25 %	10	6.0
MH2029-300Y	30 ± 25 %	25	3.0
MH2029-400Y	40 ± 25 %	20	5.0
MH2029-600Y	60 ± 25 %	20	5.0
MH2029-800Y	80 ± 25 %	40	3.0
MH2029-101Y	100 ± 25 %	100	2.0
MH2029-121Y	120 ± 25 %	100	2.0
MH2029-151Y	150 ± 25 %	100	2.0
MH2029-221Y	220 ± 25 %	100	2.0
MH2029-301Y	300 ± 25 %	200	1.0
MH2029-401Y	400 ± 25 %	100	2.0
MH2029-471Y	470 ± 25 %	200	1.0
MH2029-601Y	600 ± 25 %	200	1.0
MH1608-100Y	10 ± 25 %	100	6.0
MH1608-300Y	30 ± 25 %	60	3.0
MH1608-600Y	60 ± 25 %	40	3.0
MH1608-800Y	80 ± 25 %	40	3.0
MH1608-101Y	100 ± 25 %	40	3.0
MH1608-121Y	120 ± 25 %	100	2.0
MH1608-151Y	150 ± 25 %	100	2.0
MH1608-221Y	220 ± 25 %	100	2.0
MH1608-301Y	300 ± 25 %	200	1.0
MH1608-471Y	470 ± 25 %	200	1.0
MH1608-601Y	600 ± 25 %	200	1.0

General Specifications

Operating Temperature
.....-55 °C to +125 °C

Storage Temperature
.....-55 °C to +125 °C

Storage Condition
.....+40 °C max. at 70 % RH

Reflow Soldering .. 230 °C, 50 sec. max.

Resistance to Soldering Heat
..... +260 °C, 5 seconds

Rated Current.....Based on max
.....temperature rise of +40 °C

Terminal Strength
(Force "F" applied for 30 seconds)

4532 Series..... 1.5 F (Kg)

4516 Series..... 1.0 F (Kg)

3261 Series..... 1.0 F (Kg)

2029 Series..... 0.6 F (Kg)

1608 Series..... 0.5 F (Kg)

Materials

Core Material.....Ferrite

Internal Conductor.....Ag or Ag/Pd

Terminal.....Ag/Ni/Sn

* RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

** Bourns follows the prevailing definition of "halogen free" in the industry. Bourns considers a product to be "halogen free" if (a) the Bromine (Br) content is 900 ppm or less; (b) the Chlorine (Cl) content is 900 ppm or less; and (c) the total Bromine (Br) and Chlorine (Cl) content is 1500 ppm or less.

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.

Users should verify actual device performance in their specific applications.

Applications


- Power supply lines
- IC power lines
- Signal lines

MH Series High Current Chip Ferrite Beads


BOURNS®

Electrical Specifications (continued)


MH 4532- 700Y




MH 4516- 600Y




MH 4516- 750Y




MH 4516- 800Y




MH 4516- 102Y




MH 3261- 260Y




MH 2029- 070Y



MH 2029- 100Y



MH 2029- 300Y



REV. 02/13


Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

MH Series High Current Chip Ferrite Beads


BOURNS®

Electrical Specifications (continued)


MH 2029 -400Y




MH 2029 -600Y




MH 2029- 800Y




MH 2029- 101Y




MH 2029- 121Y




MH 2029- 151Y




MH 2029- 221Y



MH 2029- 301Y



MH 2029 -401Y



Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.


Users should verify actual device performance in their specific applications.

MH Series High Current Chip Ferrite Beads


BOURNS®

Electrical Specifications (continued)


MH 2029- 471Y




MH 2029- 601Y




MH 1608 -100Y




MH 1608- 300Y




MH 1608 -600Y




MH 1608- 800Y




MH 1608- 101Y



MH 1608- 121Y



MH 1608- 151Y




Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

MH Series High Current Chip Ferrite Beads


BOURNS®

Electrical Specifications (continued)


MH 1608- 221Y




MH 1608- 301Y




MH 1608- 471Y




MH 1608- 601Y



Equivalent Circuit



Recommended Soldering




Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

MH Series High Current Chip Ferrite Beads


BOURNS®

Product Dimensions





DIMENSIONS: $\frac{\text{MM}}{(\text{INCHES})}$

Recommended Land Pattern



Series	A	B	C	D	G	H	I
4532	$\frac{4.5 \pm 0.2}{(.177 \pm .008)}$	$\frac{3.2 \pm 0.2}{(.126 \pm .008)}$	$\frac{1.5 \pm 0.2}{(.059 \pm .008)}$	$\frac{0.5 \pm 0.2}{(.020 \pm .008)}$	$\frac{3.0}{(.118)}$	$\frac{3.0}{(.118)}$	$\frac{1.5}{(.059)}$
4516	$\frac{4.5 \pm 0.2}{(.177 \pm .008)}$	$\frac{1.6 \pm 0.2}{(.063 \pm .008)}$	$\frac{1.6 \pm 0.2}{(.063 \pm .008)}$	$\frac{0.5 \pm 0.2}{(.020 \pm .008)}$	$\frac{3.0}{(.118)}$	$\frac{1.4}{(.055)}$	$\frac{1.5}{(.059)}$
3261	$\frac{3.2 \pm 0.2}{(.126 \pm .008)}$	$\frac{1.6 \pm 0.2}{(.063 \pm .008)}$	$\frac{1.1 \pm 0.2}{(.043 \pm .008)}$	$\frac{0.5 \pm 0.2}{(.020 \pm .008)}$	$\frac{2.0}{(.079)}$	$\frac{1.4}{(.053)}$	$\frac{1.1}{(.043)}$
2029	$\frac{2.0 \pm 0.2}{(.079 \pm .008)}$	$\frac{1.2 \pm 0.2}{(.047 \pm .008)}$	$\frac{0.9 \pm 0.2}{(.035 \pm .008)}$	$\frac{0.5 \pm 0.2}{(.020 \pm .008)}$	$\frac{1.0}{(.040)}$	$\frac{1.0}{(.040)}$	$\frac{1.0}{(.040)}$
1608	$\frac{1.6 \pm 0.2}{(.063 \pm .008)}$	$\frac{0.8 \pm 0.2}{(.031 \pm .008)}$	$\frac{0.8 \pm 0.2}{(.031 \pm .008)}$	$\frac{0.5 \pm 0.2}{(.020 \pm .008)}$	$\frac{0.7}{(.028)}$	$\frac{0.7}{(.028)}$	$\frac{0.7}{(.028)}$

Reel Dimensions



DIMENSIONS: $\frac{\text{MM}}{(\text{INCHES})}$

Series	Pcs. per Reel	Gross Weight (g)	D	E	G	T
4532	1,000	170	$\frac{12.0}{(.472)}$	$\frac{8.0}{(.315)}$	$\frac{14.0 + 0}{(.551 + 0)}$	$\frac{16.5}{(.650)}$
4516	2,000	180	$\frac{12.0}{(.472)}$	$\frac{8.0}{(.315)}$	$\frac{14.0 + 0}{(.551 + 0)}$	$\frac{16.5}{(.650)}$
3261	3,000	150	$\frac{8.0}{(.315)}$	$\frac{4.0}{(.157)}$	$\frac{10.0 + 0}{(.394 + 0)}$	$\frac{12.5}{(.492)}$
2029	4,000	120	$\frac{8.0}{(.315)}$	$\frac{4.0}{(.157)}$	$\frac{10.0 + 0}{(.394 + 0)}$	$\frac{12.5}{(.492)}$
1608	4,000	90	$\frac{8.0}{(.315)}$	$\frac{4.0}{(.157)}$	$\frac{10.0 + 0}{(.394 + 0)}$	$\frac{12.5}{(.492)}$

REV. 01/14

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.