
MINT3110

110W Triple Output
Medical Series



Features

- 2” x 4” x 1.3” Package
- Suitable for 1U Applications
- Class I and Class II versions
- 110W w/air, 80W convection cooled
- Universal Input 90-264Vac
- Efficiency 87% typical
- Approved to CSA/EN/IEC/UL60601-1, 3rd Edition
- 2 x MOPP Isolation
- Power Fail Signal
- Remote Sense (optional)
- 3 Year Warranty
- RoHS Compliant

Description

The MINT3110 Series are medical grade, high efficiency, triple output power supplies in a small 2” x 4” size. The MINT3110 family is ideal for medical applications in surgical and laboratory instruments requiring low leakage, multiple outputs and small footprint. Surpassing the strict requirements of IEC 60601-1 3rd edition, the MINT3110 models feature outputs of 5/±12V, 5/±15V, 5/±24V, Power Fail/DC OK signal, very low earth leakage current of 200µA, Class B Conducted EMI, 2 MOPP (means of patient protection) isolation, and are available in Class I and Class II configurations.

Model Selection

Model Number	Volts*		Output Current** w/200LFM air	Output Current** Convection	Ripple & Noise***	Total Regulation	OVP Threshold
MINT3110A0508K01	V1	5V	14.0A	10.0A	1.0% pk-pk	±2%	7.5V max.
	V2	12V	6.0A	4.5A	1.0% pk-pk	±3%	115%-135%
	V3	-12V	1.0A	1.0A	2.0% pk-pk	±10%	115%-135%
MINT3110A1708K01	V1	5V	14.0A	10.0A	1.0% pk-pk	±2%	7.5V max.
	V2	15V	4.5A	3.5A	1.0% pk-pk	±3%	115%-135%
	V3	-15V	1.0A	1.0A	2.0% pk-pk	±10%	115%-135%
MINT3110A1908K01	V1	5V	12.0A	8.0A	1.0% pk-pk	±2%	7.5V max.
	V2	24V	4.0A	3.0A	1.0% pk-pk	±3%	115%-135%
	V3	-24V	1.0A	1.0A	2.0% pk-pk	±10%	115%-135%

Notes:
* 5V output is adjustable with +/-10% range
** Total convection power is 80 Watts.
*** Measured with noise probe directly across output terminals, and load terminated with 0.1µF ceramic and 10µF low ESR capacitors. Ripple & Noise of V2 at no load is 2% maximum.

General Specifications

AC Input	100-240Vac, ±10%, 47-63Hz, 1∅ 120–370Vdc	**Turn On Time**	Less than 2 sec. @115Vac (inversely proportional to input voltage and thermistor temperature)
Input Current	115Vac: 1.5A, 230Vac: 0.75A	**Hold-up Time**	16mS typical at 110W, 120Vac input

General Specifications (continued)

Inrush Current	264Vac, cold start: will not exceed 45A	**Signals**	AC Power Fail, DC OK
Input Fuses	F1, F2: 2.5A, 250Vac fuses provided on all models	**Overload Protection**	150%-300% above rating for V2 & V3, 110%-200% for V1. Hiccup Mode
Earth Leakage Current	<290µA@264Vac, 60Hz, NC	**Short Circuit Protection**	Provided - no damage will occur if the output is shorted.
Efficiency	87% typical at 230Vac	**Overvoltage Protection**	See models chart for trip range.
Output Power	110W continuous with 200 lfm airflow, 80W convection cooled – See chart for specific voltage model ratings.	**Switching Frequency**	PFC: Variable 30-400kHz. Main Converter: Variable 35-180kHz, 65-70kHz at full load.
Transient Response	500µS typ. for return to within 0.5% of nominal, 50% load step. $\Delta i/\Delta t$ <0.2A/µS. Max Volt Deviation = 3%	**Isolation**	Input-Output: 4000Vac, 2 x MOPP Input-Ground: 1800Vac, 1 x MOPP Output-Ground: 500Vac
Ripple and Noise	See models chart	**Operating Temperature**	-10℃ to +70℃
Output Voltage	See models chart	**Temperature Derating**	Derate output power linearly above 50℃ to 50% at 70℃
Voltage Adjustability	+/-10% from nominal on 5V output	**Storage Temperature**	-40℃ to +85℃
Minimum Load	Not required	**Altitude**	Operating: -500 to 10,000 ft. Non-operating: -500 to 40,000 ft.
Total Regulation	See models chart	**Relative Humidity**	5% to 95%, non-condensing
Vibration	Operating: 0.003g²/Hz, 1.5grms overall, 3 axes, 10 min/axis Non-Operating: 0.026g²/Hz, 5.0grms overall, 3 axes, 1 hr/axis	**Shock**	Operating: Half-sine, 20gpk, 10ms, 3 axes, 6 shocks total Non-Operating: Half-sine, 40 gpk, 10 ms, 3 axes, 6 shocks total
Dimensions	W: 2.0” x L: 4.0” x H: 1.3”	**Safety Standards**	EN/CSA/UL/IEC 60601-1, 3rd Edition
Weight	200g	**MTBF**	245,000 hours, 25°C Ambient, 110Vac input

Auxiliary Signals

AC Power Fail:	During normal operation, stays HIGH. Signal goes LOW with at least 6mS warning before loss of DC output from AC failure.	**DC OK:**	Open collector logic signal goes and stays HIGH 100mS to 500mS after main output reaches regulation.
Remote Sense:	(5V output, optional) Will compensate for 0.5V drop min. Will operate without remote sense connected. Reverse connection protected.		


Notes:

1. Specifications are for convection rating at factory settings at 115 Vac input, 25°C ambient unless otherwise stated.
2. For DC input an external DC safety rated fuse must be used.

EMI/EMC Compliance

Conducted Emissions	EN55011/22 Class B, FCC Part 15, Subpart B, Class B
Radiated Emissions	EN55011/22 Class A; FCC Part 15, Subpart A, Class A
Static Discharge Immunity	EN61000-4-2, Criteria A, 6kV Contact Discharge, 8kV air discharge
Radiated RF Immunity	EN61000-4-3, 3V/m. Criteria A
EFT/Burst Immunity	EN61000-4-4, 2kV/5kHz, Criteria A
Line Surge Immunity	EN61000-4-5, 1kV differential, 2kV common-mode, Criteria A
Conducted RF Immunity	EN61000-4-6, 3Vrms, Criteria A
Power Frequency Magnetic Field Immunity	EN61000-4-8, 3A/m, Criteria A
Voltage Dip Immunity	EN61000-4-11, 0% Vin, 0.5cycle; 40% Vin, 5 cycles; 70% Vin, 25 cycles; Criteria A
Line Harmonic Emissions	EN61000-3-2, Class A, B, C, & D
Flicker Test	EN61000-3-3, Complies (dmax<6%)

Mechanical Drawing



Notes:

1. All dimensions in inches (mm), tolerance is ±.02".
2. Mounting holes should be grounded for EMI purpose
3. Mounting J101 is safety ground connection
4. This power supply requires mounting on metal standoffs 0.20" (5 m) in height.

Connector Information

Input Connector J100	Ground J101	DC Output Connector J200	Signal Connector J300
PIN 1) AC NEUTRAL PIN 2) EMPTY PIN 3) AC LINE	0.187" FASTON TAB	PIN 1) +V1 PIN 4) GND PIN 7) V2 PIN 2) +V1 PIN 5) GND PIN 8) V3 PIN 3) GND PIN 6) GND	PIN 1) Power Fail/DC OK PIN 2) GND PIN 3) +Remote Sense PIN 4) –Remote Sense
Mating Connector: Molex 09-50-3031 Pins= 08-52-0072 AMP #640250-3 Pins= 3-640706-1	Mating Connector: Molex 01-90020001	Mating Connector: Amp #640250-8 Pins=Amp #3-640706-1	Mating Connector: Amp #1375820-4 Pin= Amp #1375819

Isolation Specifications

Parameter	Conditions/Description	Min	Nom	Max	Units
Insulation Safety Rating	Input/Ground Input/Output Output/Ground	Basic (1 MOPP) Reinforced (2 MOPP) Operational			
Electric Strength Test Voltage	Input/Ground Input/Output Output/Ground	1800 4000 500	-	-	Vac Vac Vac

Leakage Current

Parameter	Conditions/Description	Max
Earth Leakage Current	Normal Condition (NC) Single Fault Condition (SFC)	290µA 420µA
Touch Current	Normal Condition (NC) Single Fault Condition (SFC)	90µA 170µA

Input Specifications

All specifications apply over specified input voltage, output load, and temperature range, unless otherwise noted.

Parameter	Conditions/Description	Min	Nom	Max	Units
Input Voltage		90	115/230	264	Vac
Input Frequency		47	50/60	63	Hz
Input Current	115Vac/max load			1.5	A
Input Current	230Vac/max load			0.75	A
Inrush Current	264Vac, cold start, 25°C	-	-	45	A
Efficiency	Vi_{nom}, Io_{nom} MINT3110A0508K01 MINT3110A1708K01 MINT3110A1908K01	-	87%	-	%

Output Specifications

Parameter	Conditions/Description	Min	Nom	Max	Units
Output Current V1 Output Current V2 Output Current V3	MINT3110A0508K01	0 0 0	10.0 4.5 1	14.0 6.0 1	ADC
Output Current V1 Output Current V2 Output Current V3	MINT3110A1708K01	0 0 0	10.0 3.5 1	14.0 4.5 1	ADC
Output Current V1 Output Current V2 Output Current V3	MINT3110A1908K01	0 0 0	8.0 3.0 1	12.0 4.0 1	ADC

Output Specifications (continued)

Parameter	Conditions/Description	Min	Nom	Max	Units
Static Line Regulation V1	*Vi* min-*Vi* max, *Vi* nom, 0-100% *Io*1 max	-2	-	2	% *Vo* nom
Static Line Regulation V2	*Vi* min-*Vi* max, *Vi* nom, 0-100% *Io*2 max	-3	-	3	% *Vo* nom
Static Line Regulation V3	*Vi* min-*Vi* max, *Vi* nom, 0-100% *Io*3 max	-10	-	10	% *Vo* nom
Static Load Regulation V1 (Droop Characteristic)	*Vi* min-*Vi* max, *Vi* nom, 0-100% *Io*1 max	-2	-	2	% *Vo* nom
Static Load Regulation V2 (Droop Characteristic)	*Vi min-Vi max, Vi nom, 0-100% Io2 max*	-3	-	3	% Vo nom
Static Load Regulation V3 (Droop Characteristic)	*Vi min-Vi max, Vi nom, 0-100% Io3 max*	-10	-	10	% Vo nom
Hold-Up Time	*Vin* = 120Vac, *Po* = 110W	16	-	-	mS
Dynamic Load Regulation V1, V2, V3	Load change =50%, di/dt = 0.2A/µS	0		3	% Vo nom
Start-Up Time	*Vin* = 115Vac, *Io* nom	0	-	2	S
Ripple & Noise V1	20MHz bandwidth	0		1%	% Vo nom
Ripple & Noise V2	20MHz bandwidth	0		1%	% Vo nom
Ripple & Noise V3	20MHz bandwidth	0		2%	% Vo nom

Protection


All specifications apply over specified input voltage, output load, and temperature range, unless otherwise noted.

Parameter	Conditions/Description	Min	Nom	Max	Units
Input Fuse	T2.5A/250V internal fuse in both line & neutral	Not user accessible			
Input Transient Protection	2KV(CM) and 1KV(DM) surge			2	KV (CM)
Short Circuit Protection		Hiccup Mode			
Overload Protection		Hiccup Mode			
Overvoltage Protection	Latching Type, recycle AC input to reset	See models chart for trip ranges			

Characteristic Curves


Output vs. Temperature


80W convection cooled and 110W continuous with 200 LFM airflow. Derate output power to 50% at 70°C.



Ripple & Noise


To verify that the output ripple and noise does not exceed the level specified in the product specification. Measured using a scope probe socket with 0.1µF ceramic and a 10µF electrolytic capacitor connected in parallel across it, BW limit with 20MHz.






Output Transient Response V1


50% load step within the regulation limits of minimum and maximum load, di/dt<0.2A/µSec. Recovery time not specified as there is no laps in regulation with a 50% Load Step. Maximum voltage deviation is 3%.






Output Transient Response V2


50% load step within the regulation limits of minimum and maximum load, di/dt<0.2A/µSec. Recovery time not specified as there is no laps in regulation with a 50% Load Step. Maximum voltage deviation is 3%.






Output Transient Response V3


50% load step within the regulation limits of minimum and maximum load, di/dt<0.2A/µSec. Recovery time not specified as there is no laps in regulation with a 50% Load Step. Maximum voltage deviation is 3%.






Output Overload Characteristic V1


Supply shall protect itself against Overload conditions. The Power Supply shall recover from Overload Conditions without operator intervention.






Output Overload Characteristic V2


Supply shall protect itself against Overload conditions. The Power Supply shall recover from Overload Conditions without operator intervention.






Output Overload Characteristic V3


Supply shall protect itself against Overload conditions. The Power Supply shall recover from Overload Conditions without operator intervention.






Output Short Circuit Characteristic V1


Supply shall protect itself against Short Circuit conditions. The Power Supply shall recover from short circuit conditions without operator intervention.






Output Short Circuit Characteristic V2


Supply shall protect itself against Short Circuit conditions. The Power Supply shall recover from short circuit conditions without operator intervention.






Output Short Circuit Characteristic V3


Supply shall protect itself against Short Circuit conditions. The Power Supply shall recover from short circuit conditions without operator intervention.






Output Overvoltage Characteristic V1


Supply shall protect itself against over voltage conditions. The Power Supply shall latch and require AC input recycle to reset.






Output Overvoltage Characteristic V2


Supply shall protect itself against over voltage conditions. The Power Supply shall latch and require AC input recycle to reset.






Output Overvoltage Characteristic V3


Supply shall protect itself against over voltage conditions. The Power Supply shall latch and require AC input recycle to reset.






Startup Time

Start up time is <2seconds




Hold-up Time


Hold up time is 16mS minimum



Power Fail Signal Timing

Active Low TTL logic signal goes high 100 - 500 ms after main output; it goes low at least 6 mS before loss of regulation.





Data Sheet © 2012 SL Power Electronics Corp. The information and specifications contained herein are believed to be correct at the time of publication. However, SL Power accepts no responsibility for consequences arising from reproduction errors or inaccuracies. Specifications are subject to change without notice.