

# MJD243 (NPN), MJD253 (PNP)

## Complementary Silicon Plastic Power Transistors

### DPAK-3 for Surface Mount Applications

Designed for low voltage, low-power, high-gain audio amplifier applications.

#### Features

- High DC Current Gain
- Lead Formed for Surface Mount Applications in Plastic Sleeves (No Suffix)
- Straight Lead Version in Plastic Sleeves ("–1" Suffix)
- Low Collector-Emitter Saturation Voltage
- High Current-Gain – Bandwidth Product
- Annular Construction for Low Leakage
- Epoxy Meets UL 94 V-0 @ 0.125 in
- NJV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

#### MAXIMUM RATINGS

| Rating                                                                                             | Symbol         | Value        | Unit                     |
|----------------------------------------------------------------------------------------------------|----------------|--------------|--------------------------|
| Collector-Base Voltage                                                                             | $V_{CB}$       | 100          | Vdc                      |
| Collector-Emitter Voltage                                                                          | $V_{CEO}$      | 100          | Vdc                      |
| Emitter-Base Voltage                                                                               | $V_{EB}$       | 7.0          | Vdc                      |
| Collector Current – Continuous                                                                     | $I_C$          | 4.0          | Adc                      |
| Collector Current – Peak                                                                           | $I_{CM}$       | 8.0          | Adc                      |
| Base Current                                                                                       | $I_B$          | 1.0          | Adc                      |
| Total Device Dissipation<br>@ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$          | $P_D$          | 12.5<br>0.1  | W<br>W/ $^\circ\text{C}$ |
| Total Device Dissipation<br>@ $T_A = 25^\circ\text{C}$ (Note 2)<br>Derate above $25^\circ\text{C}$ | $P_D$          | 1.4<br>0.011 | W<br>W/ $^\circ\text{C}$ |
| Operating and Storage Junction<br>Temperature Range                                                | $T_J, T_{stg}$ | -65 to +150  | $^\circ\text{C}$         |
| ESD – Human Body Model                                                                             | HBM            | 3B           | V                        |
| ESD – Machine Model                                                                                | MM             | C            | V                        |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. When surface mounted on minimum pad sizes recommended.





**ON Semiconductor®**


[www.onsemi.com](http://www.onsemi.com)

### 4.0 A, 100 V, 12.5 W POWER TRANSISTOR

#### COMPLEMENTARY




**IPAK  
CASE 369D  
STYLE 1**




**DPAK-3  
CASE 369C  
STYLE 1**

#### MARKING DIAGRAMS



**IPAK**



**DPAK**

A = Assembly Location  
Y = Year  
WW = Work Week  
x = 4 or 5  
G = Pb-Free Package

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

# MJD243 (NPN), MJD253 (PNP)

## THERMAL CHARACTERISTICS

| Characteristic                                                         | Symbol                             | Value      | Unit                 |
|------------------------------------------------------------------------|------------------------------------|------------|----------------------|
| Thermal Resistance<br>Junction-to-Case<br>Junction-to-Ambient (Note 2) | $R_{\theta JC}$<br>$R_{\theta JA}$ | 10<br>89.3 | $^{\circ}\text{C/W}$ |

2. When surface mounted on minimum pad sizes recommended.

## ELECTRICAL CHARACTERISTICS ( $T_C = 25^{\circ}\text{C}$ unless otherwise noted)

| Characteristic | Symbol | Min | Max | Unit |
|----------------|--------|-----|-----|------|
|----------------|--------|-----|-----|------|

### OFF CHARACTERISTICS

|                                                                                                                                                                   |               |          |            |                         |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|----------|------------|-------------------------|
| Collector-Emitter Sustaining Voltage (Note 3)<br>( $I_C = 10 \text{ mAdc}$ , $I_B = 0$ )                                                                          | $V_{CE(sus)}$ | 100      | –          | Vdc                     |
| Collector Cutoff Current<br>( $V_{CB} = 100 \text{ Vdc}$ , $I_E = 0$ )<br>( $V_{CB} = 100 \text{ Vdc}$ , $I_E = 0$ , $T_J = 125^{\circ}\text{C}$ )                | $I_{CBO}$     | –<br>–   | 100<br>100 | nAdc<br>$\mu\text{Adc}$ |
| Emitter Cutoff Current<br>( $V_{BE} = 7.0 \text{ Vdc}$ , $I_C = 0$ )                                                                                              | $I_{EBO}$     | –        | 100        | nAdc                    |
| DC Current Gain (Note 3)<br>( $I_C = 200 \text{ mAdc}$ , $V_{CE} = 1.0 \text{ Vdc}$ )<br>( $I_C = 1.0 \text{ Adc}$ , $V_{CE} = 1.0 \text{ Vdc}$ )                 | $h_{FE}$      | 40<br>15 | 180<br>–   | –                       |
| Collector-Emitter Saturation Voltage (Note 3)<br>( $I_C = 500 \text{ mAdc}$ , $I_B = 50 \text{ mAdc}$ )<br>( $I_C = 1.0 \text{ Adc}$ , $I_B = 100 \text{ mAdc}$ ) | $V_{CE(sat)}$ | –<br>–   | 0.3<br>0.6 | Vdc                     |
| Base-Emitter Saturation Voltage (Note 3)<br>( $I_C = 2.0 \text{ Adc}$ , $I_B = 200 \text{ mAdc}$ )                                                                | $V_{BE(sat)}$ | –        | 1.8        | Vdc                     |
| Base-Emitter On Voltage (Note 3)<br>( $I_C = 500 \text{ mAdc}$ , $V_{CE} = 1.0 \text{ Vdc}$ )                                                                     | $V_{BE(on)}$  | –        | 1.5        | Vdc                     |

### DYNAMIC CHARACTERISTICS

|                                                                                                                                     |          |    |    |     |
|-------------------------------------------------------------------------------------------------------------------------------------|----------|----|----|-----|
| Current-Gain – Bandwidth Product (Note 4)<br>( $I_C = 100 \text{ mAdc}$ , $V_{CE} = 10 \text{ Vdc}$ , $f_{test} = 10 \text{ MHz}$ ) | $f_T$    | 40 | –  | MHz |
| Output Capacitance<br>( $V_{CB} = 10 \text{ Vdc}$ , $I_E = 0$ , $f = 0.1 \text{ MHz}$ )                                             | $C_{ob}$ | –  | 50 | pF  |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulse Test: Pulse Width = 300  $\mu\text{s}$ , Duty Cycle  $\approx 2\%$ .

4.  $f_T = |h_{FE}| \cdot f_{test}$ .

## MJD243 (NPN), MJD253 (PNP)




Figure 1. Power Derating

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate  $I_C - V_{CE}$  limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.




Figure 2. Active Region Maximum Safe Operating Area

The data of Figure 2 is based on  $T_{J(pk)} = 150^\circ\text{C}$ ;  $T_C$  is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided  $T_{J(pk)} \leq 150^\circ\text{C}$ .  $T_{J(pk)}$  may be calculated from the data in Figure 3. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.






Figure 3. Thermal Response

# MJD243 (NPN), MJD253 (PNP)



**NPN  
MJD243**





**PNP  
MJD253**



**Figure 4. DC Current Gain**



**Figure 5. "On" Voltages**



**Figure 6. Temperature Coefficients**

## MJD243 (NPN), MJD253 (PNP)




Figure 7. Switching Time Test Circuit




Figure 8. Turn-On Time




Figure 9. Turn-Off Time




Figure 10. Capacitance




Figure 11. Capacitance

## MJD243 (NPN), MJD253 (PNP)

### ORDERING INFORMATION

| Device        | Package Type        | Package | Shipping <sup>†</sup> |
|---------------|---------------------|---------|-----------------------|
| MJD243G       | DPAK-3<br>(Pb-Free) | 369C    | 75 Units / Rail       |
| MJD243T4G     | DPAK-3<br>(Pb-Free) | 369C    | 2,500 / Tape & Reel   |
| NJVMJD243T4G* | DPAK-3<br>(Pb-Free) | 369C    | 2,500 / Tape & Reel   |
| MJD253-1G     | IPAK<br>(Pb-Free)   | 369D    | 75 Units / Rail       |
| MJD253T4G     | DPAK-3<br>(Pb-Free) | 369C    | 2,500 / Tape & Reel   |
| NJVMJD253T4G* | DPAK-3<br>(Pb-Free) | 369C    | 2,500 / Tape & Reel   |



<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*NJV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable

# MJD243 (NPN), MJD253 (PNP)

## PACKAGE DIMENSIONS

### DPAK (SINGLE GAUGE) CASE 369C ISSUE F




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCHES.
3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3 and Z.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
5. DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
6. DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.
7. OPTIONAL MOLD FEATURE.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.086     | 0.094 | 2.18        | 2.38  |
| A1  | 0.000     | 0.005 | 0.00        | 0.13  |
| b   | 0.025     | 0.035 | 0.63        | 0.89  |
| b2  | 0.028     | 0.045 | 0.72        | 1.14  |
| b3  | 0.180     | 0.215 | 4.57        | 5.46  |
| c   | 0.018     | 0.024 | 0.46        | 0.61  |
| c2  | 0.018     | 0.024 | 0.46        | 0.61  |
| D   | 0.235     | 0.245 | 5.97        | 6.22  |
| E   | 0.250     | 0.265 | 6.35        | 6.73  |
| e   | 0.090 BSC |       | 2.29 BSC    |       |
| H   | 0.370     | 0.410 | 9.40        | 10.41 |
| L   | 0.055     | 0.070 | 1.40        | 1.78  |
| L1  | 0.114 REF |       | 2.90 REF    |       |
| L2  | 0.020 BSC |       | 0.51 BSC    |       |
| L3  | 0.035     | 0.050 | 0.89        | 1.27  |
| L4  | ---       | 0.040 | ---         | 1.01  |
| Z   | 0.155     | ---   | 3.93        | ---   |

#### STYLE 1:

1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR




SCALE 3:1  $\left( \frac{\text{mm}}{\text{inches}} \right)$

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERM/D.

# MJD243 (NPN), MJD253 (PNP)

## PACKAGE DIMENSIONS

### IPAK CASE 369D ISSUE C



#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

| DIM | INCHES |       | MILLIMETERS |      |
|-----|--------|-------|-------------|------|
|     | MIN    | MAX   | MIN         | MAX  |
| A   | 0.235  | 0.245 | 5.97        | 6.35 |
| B   | 0.250  | 0.265 | 6.35        | 6.73 |
| C   | 0.086  | 0.094 | 2.19        | 2.38 |
| D   | 0.027  | 0.035 | 0.69        | 0.88 |
| E   | 0.018  | 0.023 | 0.46        | 0.58 |
| F   | 0.037  | 0.045 | 0.94        | 1.14 |
| G   | 0.090  | BSC   | 2.29        | BSC  |
| H   | 0.034  | 0.040 | 0.87        | 1.01 |
| J   | 0.018  | 0.023 | 0.46        | 0.58 |
| K   | 0.350  | 0.380 | 8.89        | 9.65 |
| R   | 0.180  | 0.215 | 4.45        | 5.45 |
| S   | 0.025  | 0.040 | 0.63        | 1.01 |
| V   | 0.035  | 0.050 | 0.89        | 1.27 |
| Z   | 0.155  | ---   | 3.93        | ---  |

#### STYLE 1:

- PIN 1. BASE
- 2. COLLECTOR
- 3. EMITTER
- 4. COLLECTOR

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marketing.pdf](http://www.onsemi.com/site/pdf/Patent-Marketing.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative