
MARKING / Aufdruck




 MEDER-Label, Type
 Production code,
 EN60062 / Factory code
 Circuit diagram

MEDER-Logo, Typ
Produktionscode
EN60062/Fertigungsstätte
Schalbild


 Abmessungen / dimensions (mm)
 Tolerances acc. to DIN ISO 2768-m


CABLE / Kabel

 PVC LIYY 2x0.25 mm²
 Ø 3.4mm, grey
 colour of wires: blue, brown (white/brown)
 ends with blade terminal 2.8x0.8

PVC LIYY 2x0.25 mm²
Ø 3.4mm, grau
Aderfarben: blau, braun (weiss/braun)
Enden mit Flachsteckhülse 2.8x0.8

SWITCHING DISTANCES
Schaltwege


SENSOR


 MAGNETICALLY CONDUCTIVE MATERIAL
 Magnetisch leitendes Material

CIRCUIT DIAGRAM
Schalbild


Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull in	at 20 °C	4,5		10	mm
Drop out	at 20 °C	5,5		13,5	mm
Test equipment		SV 002			

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - form		A - NO			
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
operating voltage	DC or Peak AC			400	VDC
operating ampere	DC or Peak AC			1	A
Switching current	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive			440	mOhm
Case color		blue			
Sealing compound		Polyurethan			

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	cable not moved	-30		80	°C
Operating temperature	cable moved	-5		80	°C
Storage temperature		-30		80	°C

Customer side	Conditions	Min	Typ	Max	Unit
connector design		receptacles			

Cable specification	Conditions	Min	Typ	Max	Unit
Cable typ		round cable			
Cable material		PVC			
Cross section		0,25 gmm			

General data	Conditions	Min	Typ	Max	Unit
Mounting advice		over 5m cable, a series resistor is recommended.			
mounting advice 1		Decreased switching distances by mounting on iron			
mounting advice 2		Magnetically conductive screws must not be used			
tightening torque	Screw M3 ISO 1207 Disk ISO 7089			0,5	Nm
Customer		Miele			