
MMBT1815

NPN SILICON TRANSISTOR

HIGH FREQUENCY NPN AMPLIFIER TRANSISTOR



*Pb-free plating product number: MMBT1815L

■ FEATURES

*Collector-Emitter Voltage:
BV_{CEO}=50V
*Collector current up to 150mA
*High h_{FE} linearity
*Complement to MMBT1015


■ ORDERING INFORMATION

Order Number		Package	Pin Assignment			Packing
Normal	Lead Free Plating		1	2	3	
MMBT1815-x-AC3-R	MMBT1815L-x-AC3-R	SOT-113	E	B	C	Tape Reel
MMBT1815-x-AE3-R	MMBT1815L-x-AE3-R	SOT-23	E	B	C	Tape Reel
MMBT1815-x-AL3-R	MMBT1815L-x-AL3-R	SOT-323	E	B	C	Tape Reel
MMBT1815-x-AN3-R	MMBT1815L-x-AN3-R	SOT-523	E	B	C	Tape Reel

MMBT1815L-x-AC3-R
(1)Packing Type
(2)Package Type
(3)Rank
(4)Lead Plating

(1) R: Tape Reel
(2) AC3: SOT-113, AE3: SOT-23, AL3: SOT-323, AN3: SOT-523
(3) x: refer to Classification of h_{FE1}
(4) L: Lead Free Plating, Blank: Pb/Sn

■ MARKING



Copyright © 2005 Unisonic Technologies Co., Ltd

■ ABSOLUTE MAXIMUM RATING (Ta=25°C , unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Collector-Base Voltage		V_{CBO}	60	V
Collector-Emitter Voltage		V_{CEO}	50	V
Emitter-Base Voltage		V_{EBO}	5	V
Collector Dissipation (Ta=25°C)	SOT-23	P_C	250	mW
	SOT-523/SOT-113/SOT-323		200	mW
Collector Current		I_C	150	mA
Base Current		I_B	50	mA
Junction Temperature		T_J	150	℃
Storage Temperature		T_{STG}	-55 ~ +150	℃

Note Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS (Ta=25°C, unless otherwise specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	Ic = 100mA, I_B = 10mA		0.1	0.25	V
Base-Emitter Saturation Voltage	$V_{BE(SAT)}$	Ic = 100mA, I_B = 10mA			1.0	V
Collector Cut-off Current	I_{CBO}	V_{CB} = 60V, I_E = 0			100	nA
Emitter Cut-off Current	I_{EBO}	V_{EB} = 5V, Ic = 0			100	nA
DC Current Gain	h_{FE1} h_{FE2}	V_{CE} = 6V, Ic = 2mA V_{CE} = 6V, Ic = 150mA	120 25		700	
Transition Frequency	f_T	V_{CE} = 10V,Ic = 50mA	80			MHz
Output Capacitance	C_{OB}	V_{CB} = 10V, I_E = 0, f = 1MHz		2.0	3.0	pF
Noise Figure	NF	Ic = -0.1mA, V_{CE} = 6V R_G = 10kΩ, f = 100Hz		1.0	1.0	dB

■ CLASSIFICATION OF h_{FE1}


RANK	Y	GR	BL
RANGE	120-240	200-400	350-700

■ TYPICAL CHARACTERISTICS


Static Characteristics




DC Current Gain




Base-Emitter On Voltage




Saturation Voltage



Current Gain-Bandwidth Product



Collector Output Capacitance



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.