


## 500mW SURFACE MOUNT ZENER DIODE

### Features

- Planar Die Construction
- 500mW Power Dissipation
- 2.4 – 51V Nominal Zener Voltage
- 5% Standard Vz Tolerance
- Designed for Surface Mount Application
- Plastic Material – UL Recognition Flammability Classification 94V-O



| SOD-123              |      |      |
|----------------------|------|------|
| Dim                  | Min  | Max  |
| A                    | 3.6  | 3.9  |
| B                    | 2.5  | 2.8  |
| C                    | 1.4  | 1.8  |
| D                    | 0.5  | 0.7  |
| E                    | —    | 0.2  |
| G                    | 0.4  | —    |
| H                    | 0.95 | 1.35 |
| J                    | —    | 0.12 |
| All Dimensions in mm |      |      |

### Mechanical Data

- Case: SOD-123, Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band
- Weight: 0.01 grams (approx.)
- Marking: Device Code, See Page 2
- **Lead Free: For RoHS / Lead Free Version, Add “-LF” Suffix to Part Number, See Page 4**

### Maximum Ratings @T<sub>A</sub>=25°C unless otherwise specified

| Characteristic                                                 | Symbol                            | Value       | Unit |
|----------------------------------------------------------------|-----------------------------------|-------------|------|
| Peak Pulse Power Dissipation at T <sub>A</sub> = 25°C (Note 1) | P <sub>d</sub>                    | 500         | mW   |
| Forward Voltage @ I <sub>F</sub> = 10mA                        | V <sub>F</sub>                    | 0.9         | V    |
| Thermal Resistance Junction to Ambient (Note 1)                | R <sub>θJA</sub>                  | 340         | °C/W |
| Operating and Storage Temperature Range                        | T <sub>J</sub> , T <sub>STG</sub> | -65 to +150 | °C   |

Note: 1. Diode on ceramic substrate 10mm x 8mm x 0.7mm.

## Electrical Characteristics @T<sub>A</sub>=25°C unless otherwise specified

| Type Number<br>(Note 1) | Device Marking Code | Zener Voltage Range<br>(Note 2)  |         |         | Maximum Zener Impedance<br>(Note 3) |      |                                   |      | Max Reverse Leakage Current |                  | Typical Temp. Coefficient of Zener Voltage |
|-------------------------|---------------------|----------------------------------|---------|---------|-------------------------------------|------|-----------------------------------|------|-----------------------------|------------------|--------------------------------------------|
|                         |                     | V <sub>Z</sub> @ I <sub>ZT</sub> |         |         | Z <sub>zT</sub> @ I <sub>ZT</sub>   |      | Z <sub>zK</sub> @ I <sub>zK</sub> |      | I <sub>R</sub>              | @ V <sub>R</sub> |                                            |
|                         |                     | Nom (V)                          | Min (V) | Max (V) | (Ω)                                 | (mA) | (Ω)                               | (mA) | (μA)                        | (V)              |                                            |
| MMSZ5221B               | C1                  | 2.4                              | 2.28    | 2.52    | 30                                  | 20   | 1200                              | 0.25 | 100                         | 1.0              | -0.075                                     |
| MMSZ5222B               | C2                  | 2.5                              | 2.38    | 2.63    | 30                                  | 20   | 1250                              | 0.25 | 100                         | 1.0              | -0.075                                     |
| MMSZ5223B               | C3                  | 2.7                              | 2.57    | 2.84    | 30                                  | 20   | 1300                              | 0.25 | 75                          | 1.0              | -0.075                                     |
| MMSZ5225B               | C5                  | 3.0                              | 2.85    | 3.15    | 30                                  | 20   | 1600                              | 0.25 | 50                          | 1.0              | -0.075                                     |
| MMSZ5226B               | D1                  | 3.3                              | 3.14    | 3.47    | 28                                  | 20   | 1600                              | 0.25 | 25                          | 1.0              | -0.070                                     |
| MMSZ5227B               | D2                  | 3.6                              | 3.42    | 3.78    | 24                                  | 20   | 1700                              | 0.25 | 15                          | 1.0              | -0.065                                     |
| MMSZ5228B               | D3                  | 3.9                              | 3.71    | 4.10    | 23                                  | 20   | 1900                              | 0.25 | 10                          | 1.0              | -0.060                                     |
| MMSZ5229B               | D4                  | 4.3                              | 4.09    | 4.52    | 22                                  | 20   | 2000                              | 0.25 | 5.0                         | 1.0              | -0.055                                     |
| MMSZ5230B               | D5                  | 4.7                              | 4.47    | 4.94    | 19                                  | 20   | 1900                              | 0.25 | 5.0                         | 2.0              | ±0.030                                     |
| MMSZ5231B               | E1                  | 5.1                              | 4.85    | 5.36    | 17                                  | 20   | 1600                              | 0.25 | 5.0                         | 2.0              | ±0.030                                     |
| MMSZ5232B               | E2                  | 5.6                              | 5.32    | 5.88    | 11                                  | 20   | 1600                              | 0.25 | 5.0                         | 3.0              | +0.038                                     |
| MMSZ5234B               | E4                  | 6.2                              | 5.89    | 6.51    | 7.0                                 | 20   | 1000                              | 0.25 | 5.0                         | 4.0              | +0.045                                     |
| MMSZ5235B               | E5                  | 6.8                              | 6.46    | 7.14    | 5.0                                 | 20   | 750                               | 0.25 | 3.0                         | 5.0              | +0.050                                     |
| MMSZ5236B               | F1                  | 7.5                              | 7.13    | 7.88    | 6.0                                 | 20   | 500                               | 0.25 | 3.0                         | 6.0              | +0.058                                     |
| MMSZ5237B               | F2                  | 8.2                              | 7.79    | 8.61    | 8.0                                 | 20   | 500                               | 0.25 | 3.0                         | 6.0              | +0.062                                     |
| MMSZ5239B               | F4                  | 9.1                              | 8.65    | 9.56    | 10                                  | 20   | 600                               | 0.25 | 3.0                         | 6.5              | +0.068                                     |
| MMSZ5240B               | F5                  | 10                               | 9.50    | 10.50   | 17                                  | 20   | 600                               | 0.25 | 3.0                         | 8.0              | +0.075                                     |
| MMSZ5241B               | H1                  | 11                               | 10.45   | 11.55   | 22                                  | 20   | 600                               | 0.25 | 2.0                         | 8.4              | +0.076                                     |
| MMSZ5242B               | H2                  | 12                               | 11.40   | 12.60   | 30                                  | 20   | 600                               | 0.25 | 1.0                         | 9.1              | +0.077                                     |
| MMSZ5243B               | H3                  | 13                               | 12.35   | 13.65   | 13                                  | 9.5  | 600                               | 0.25 | 0.5                         | 9.9              | +0.079                                     |
| MMSZ5245B               | H5                  | 15                               | 14.25   | 15.75   | 16                                  | 8.5  | 600                               | 0.25 | 0.1                         | 11               | +0.082                                     |
| MMSZ5246B               | J1                  | 16                               | 15.20   | 16.80   | 17                                  | 7.8  | 600                               | 0.25 | 0.1                         | 12               | +0.083                                     |
| MMSZ5248B               | J3                  | 18                               | 17.10   | 18.90   | 21                                  | 7.0  | 600                               | 0.25 | 0.1                         | 14               | +0.085                                     |
| MMSZ5250B               | J5                  | 20                               | 19.00   | 21.00   | 25                                  | 6.2  | 600                               | 0.25 | 0.1                         | 15               | +0.086                                     |
| MMSZ5251B               | K1                  | 22                               | 20.90   | 23.10   | 29                                  | 5.6  | 600                               | 0.25 | 0.1                         | 17               | +0.087                                     |
| MMSZ5252B               | K2                  | 24                               | 22.80   | 25.20   | 33                                  | 5.2  | 600                               | 0.25 | 0.1                         | 18               | +0.087                                     |
| MMSZ5254B               | K4                  | 27                               | 25.65   | 28.35   | 41                                  | 5.0  | 600                               | 0.25 | 0.1                         | 21               | +0.090                                     |
| MMSZ5255B               | K5                  | 28                               | 26.60   | 29.40   | 44                                  | 4.5  | 600                               | 0.25 | 0.1                         | 21               | +0.091                                     |
| MMSZ5256B               | M1                  | 30                               | 28.50   | 31.50   | 49                                  | 4.2  | 600                               | 0.25 | 0.1                         | 23               | +0.091                                     |
| MMSZ5257B               | M2                  | 33                               | 31.35   | 34.65   | 58                                  | 3.8  | 700                               | 0.25 | 0.1                         | 25               | +0.092                                     |
| MMSZ5258B               | M3                  | 36                               | 34.20   | 37.80   | 70                                  | 3.4  | 700                               | 0.25 | 0.1                         | 27               | +0.093                                     |
| MMSZ5259B               | M4                  | 39                               | 37.05   | 40.95   | 80                                  | 3.2  | 800                               | 0.25 | 0.1                         | 30               | +0.094                                     |
| MMSZ5260B               | M5                  | 43                               | 40.85   | 45.15   | 93                                  | 3.0  | 900                               | 0.25 | 0.1                         | 33               | +0.095                                     |
| MMSZ5261B               | N1                  | 47                               | 44.65   | 49.35   | 105                                 | 2.7  | 1000                              | 0.25 | 0.1                         | 36               | +0.095                                     |
| MMSZ5262B               | N2                  | 51                               | 48.45   | 53.55   | 125                                 | 2.5  | 1100                              | 0.25 | 0.1                         | 39               | +0.096                                     |


Note: 1. Type numbers listed have standard tolerance on the nominal zener voltage of ±5%.  
2. Measured with pulses t<sub>p</sub> = 1ms.  
3. f = 1KHz

## MARKING INFORMATION




Cathode = Polarity Band  
xx = Device Code, See Page 2

## RECOMMENDED FOOTPRINT



## PACKAGING INFORMATION

### TAPE & REEL



| Reel Diameter (mm) | Quantity (PCS) | Inner Box Size L x W x H (mm) | Quantity (PCS) | Carton Size L x W x H (mm) | Quantity (PCS) | Approx. Gross Weight (KG) |
|--------------------|----------------|-------------------------------|----------------|----------------------------|----------------|---------------------------|
| 178                | 3,000          | 187 x 187 x 65                | 15,000         | 390 x 240 x 420            | 150,000        | 10.0                      |

**Note:** 1. Anti-static plastic reel, white, water clear or blue color. Inspection hole might be varied in different alignment.  
2. Components are packed in accordance with EIA standard 481-1 and 481-2.

## ORDERING INFORMATION

| Product No.  | Package Type | Shipping Quantity |
|--------------|--------------|-------------------|
| MMSZ52xxB-T1 | SOD-123      | 3000/Tape & Reel  |

1. Shipping quantity given is for minimum packing quantity only. For minimum order quantity, please consult the Sales Department.
2. **To order RoHS / Lead Free version (with Lead Free finish), add “-LF” suffix to part number above. For example, MMSZ5221B-T1-LF.**

Won-Top Electronics Co., Ltd (WTE) has checked all information carefully and believes it to be correct and accurate. However, WTE cannot assume any responsibility for inaccuracies. Furthermore, this information does not give the purchaser of semiconductor devices any license under patent rights to manufacturer. WTE reserves the right to change any or all information herein without further notice.

**WARNING:** DO NOT USE IN LIFE SUPPORT EQUIPMENT. WTE power semiconductor products are not authorized for use as critical components in life support devices or systems without the express written approval.

**Won-Top Electronics Co., Ltd.**

No. 44 Yu Kang North 3rd Road, Chine Chen Dist., Kaohsiung, Taiwan

**Phone:** 886-7-822-5408 or 886-7-822-5410

**Fax:** 886-7-822-5417

**Email:** sales@wontop.com

**Internet:** <http://www.wontop.com>

*We power your everyday.*