MP2040

Fast Transient Response, 3A Dual Supply Very Low Dropout Linear Regulator

DESCRIPTION

The MP2040 is a very low dropout, dual supply linear regulator. The use of two supplies allows the BIAS to control an NMOS device. The NMOS device supplies power to the load via the IN. In this way the input supply can be just above the desired output, yet still provide very good regulation performance due to the higher bias supply. The BIAS operates from a 3.3V to 5.5V input and regulates the output voltage to as low as 0.9V, and as high as 3.3V.

The MP2040 can supply up to 3A of load current with a typical dropout voltage of 150mV. The BIAS runs the internal reference and drive circuitry, while the output current comes directly from the IN for high efficiency regulation.

Other features of MP2040 include thermal overload and current limit protection, power good indicator, stability with ultra low ESR ceramic capacitors as low as 1uF, and fast transient response. The MP2040 is available in 10-pin QFN (3mm x 3mm), and in QFN (5mm x 5mm) packages.

FEATURES


- Wide 1.1V to 5V Input Voltage Range
- Stable with Very Small Ceramic Capacitors
- 150mV Dropout at 3A Output
- 2% Accurate Output Voltage
- Adjustable Output Range of 0.9V to 3.3V
- Low Noise: 80μV_{RMS} (10Hz to 100kHz)
- Very fast transient response
- PSRR
  - 40dB at 100kHz
- Better Than 0.001%/mA Load Regulation
- Stable With Low-ESR Output Capacitors
- Internal Thermal Protection
- Current Limit Protection
- 0.1µA Typical Quiescent Current at Shutdown
- Power Good Indicator

APPLICATIONS

- Industrial Process & Control Equipment
- Telecom Equipment
- PAID Storage
- DSP/ASIC/µC Post Regulation for Switching Power Supplies

All MPS parts are lead-free and adhere to the RoHS directive. For MPS green status, please visit MPS website under Quality Assurance. “MPS” and “The Future of Analog IC Technology” are Registered Trademarks of Monolithic Power Systems, Inc.

TYPICAL APPLICATION



NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP2046


MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.

ORDERING INFORMATION

Part Number	Package	Top Marking	Free Air Temperature (T_A)
MP2040DQ*	3x3 QFN10	8H	-40°C to +85°C
MP2040DU**	5x5 QFN32	MP2040DU	-40°C to +85°C

* For Tape & Reel, add suffix –Z (e.g. MP2040DQ–Z).
For RoHS compliant packaging, add suffix –LF (e.g. MP2040DQ–LF–Z)
** For Tape & Reel, add suffix –Z (e.g. MP2040DU–Z).
For RoHS compliant packaging, add suffix –LF (e.g. MP2040DU–LF–Z)

PACKAGE REFERENCE



3x3 QFN10 | 5x5 QFN32

ABSOLUTE MAXIMUM RATINGS (1)

V_{BIAS}, V_{IN} to GND ..... -0.3V to +6V
FB, EN, to GND ..... -0.3V to 6V
V_{OUT} ..... -0.3V to V_{IN} + 0.3 or 6V
PGOOD ..... -0.3V to V_{BIAS} + 0.3 or 6V
BYPASS ..... -0.3V to V_{BIAS} +0.3 or 6V
Continuous Power Dissipation (T_A = +25°C) (2)
QFN10 3X3 ..... 2.5W
QFN32 5X5 ..... 3.47W
Junction Temperature ..... 150°C
Lead Temperature ..... 260°C
Storage Temperature ..... -65°C to +150°C

Recommended Operating Conditions (3)

Input Voltage V_{IN} ..... 1.1V to 5.5V
Input Voltage V_{BIAS} ..... 3.3V to 5.5V
Output Voltage ..... 0.9V to 3.3V
Load Current ..... 3.0A Maximum
Operating Junct. Temp (T_J) ..... -40°C to +125°C

Thermal Resistance (4) θ_{JA} θ_{JC}

QFN10 3X3 ..... 50 ..... 12 °C/W
QFN32 5X5 ..... 36 ..... 8 °C/W

Notes:
1) Exceeding these ratings may damage the device.
2) The maximum allowable power dissipation is a function of the maximum junction temperature T_J (MAX), the junction-to-ambient thermal resistance θ_{JA}, and the ambient temperature T_A. The maximum allowable continuous power dissipation at any ambient temperature is calculated by P_D (MAX) = (T_J (MAX)-T_A)/θ_{JA}. Exceeding the maximum allowable power dissipation will cause excessive die temperature, and the regulator will go into thermal shutdown. Internal thermal shutdown circuitry protects the device from permanent damage.
3) The device is not guaranteed to function outside of its operating conditions.
4) Measured on JESD51-7, 4-layer PCB.

NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP20046

MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.

ELECTRICAL CHARACTERISTICS

V_{IN} = 1.5V, V_{BIAS} = 3.6V, V_{OUT} = 1.2V, C_{OUT} = 1µF, C_{IN} = 0.1µF, T_A = +25°C, unless otherwise noted.

Parameter	Symbol	Condition	Min	Typ	Max	Units
V_{IN} Operating Voltage			1.1		5.5	V
V_{BIAS} Operating Voltage		I_{OUT} = 2A	3.3		5.5	V
V_{BIAS} Operating Current				3.5		mA
FB Regulation Voltage			0.5	0.51	0.52	V
		-40°C ≤ T_A ≤ +85°C	0.495	0.51	0.525	
Dropout Voltage		I_{OUT} = 3A, V_{BIAS} = 3.6V		150		mV
V_{IN} Line Regulation		I_{OUT} = 1mA, V_{IN} = 1.5 to 5V V_{BIAS} = 5V V_{OUT} = 1.2V		1		mV
V_{BIAS} Line Regulation		I_{OUT} = 1mA, V_{BIAS} = 3.6V to 5.5V V_{OUT} = 1.2V V_{IN} = 1.5V		2		mV
Load Regulation		I_{OUT} = 1mA to 1A		0.001		%/mA
PSRR (V_{IN})		V_{IN} > V_{OUT} + 0.5V, C_{OUT} = 4.7µF, V_{IN}(AC) = 100mV, f = 100kHz V_B=5V		40		dB
Power Good Threshold				440		mV
Power Good Delay				80		µs
Current Limit (5)				3.6		A
Soft Start		BYPASS=open		280		µs
Power Good Voltage		I_{sink}=230µA		0.39		V
EN Input High Voltage			1.5			V
EN Input Low Voltage					0.8	V
EN Input Bias Current		V_{EN} = 1.2V	–1		+1	µA
Thermal Protection				135		°C
Thermal Protection Hysteresis				15		°C

Notes:

5) Guaranteed by Designer.

NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP2046

MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.

PIN FUNCTIONS

QFN3X3 10pins

Pin #	Name	Description
9, 10	VOUT	Regulator Output. OUT is the output of the linear regulator, By pass OUT to GND with a 4.7μF or greater capacitor.
3	BIAS	Bias Voltage. Bypass to ground with a 1μF or greater capacitor, VB>=VIN.
8	FB	Feedback Input. Connect a resistive voltage divider from OUT to FB to set the output voltage. OUT feedback threshold is 0.51V.
7	EN	Enable Input. Drive EN high to turn on the MP2040, drive EN low to turn it off. For automatic startup, connect EN to IN.
5	GND	Ground, exposed pad.
1, 2	VIN	Power Source Input. IN supplies power to the load at the output (through the power transistor). Bypass IN to GND with a 1μF or greater capacitor.
4	PGOOD	Open drain output. High indicated V_{OUT}> **90%** final value.
6	BYPASS	Connect a 1nF to this pin. Do not load this pin resistively.

QFN5x5 32pins

Pin #	Name	Description
20, 21,22, 23	VOUT	Regulator Output. OUT is the output of the linear regulator, By pass OUT to GND with a 4.7μF or greater capacitor.
6	BIAS	Bias Voltage. Bypass to ground with a 1μF or greater capacitor, VB>=VIN.
19	FB	Feedback Input. Connect a resistive voltage divider from OUT to FB to set the output voltage. OUT feedback threshold is 0.51V.
18	EN	Enable Input. Drive EN high to turn on the MP2040, drive EN low to turn it off. For automatic startup, connect EN to IN.
8	GND	Ground, exposed pad.
2, 3, 4, 5	VIN	Power Source Input. IN supplies power to the load at the output (through the power transistor). Bypass IN to GND with a 1μF or greater capacitor.
7	PGOOD	Open drain output. High indicated V_{OUT}> **90%** final value.
17	BYPASS	Connect a 1nF to this pin. Do not load this pin resistively.
1, 9, 10, 11, 12, 13, 14, 15, 16, 24, 25, 26, 27, 28, 29, 30, 31, 32	NC	These are no connection pins.

NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP2046


MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.

TYPICAL PERFORMANCE CHARACTERISTICS


C1=22µF, C2=0.1µF, C3=1.0µF, C4=4.7µF, C6=22nF, V_B=5V, T_A=25ºC, unless otherwise noted

Voltage Dropout


V_{OUT}=1.2V



Line Regulation




Load Regulation




PSRR vs. Frequency


V_{IN}=1.5V,V_{OUT}=1.2V



Line Regulation




Load Regulation




MP2040DU Case Temperature vs. P_D


V_B=5V,V_{OUT}=1.2V



Line Regulation



Load Regulation



NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP2046


MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.

TYPICAL PERFORMANCE CHARACTERISTICS *(continued)*

C1=22µF, C2=0.1µF, C3=1.0µF, C4=4.7µF, C6=22nF, V_B=5V, T_A=25ºC, unless otherwise noted


$V_{DROPOUT}$ vs. Temperature

V_O=1.2V, I_O=1A




V_{BF} vs. Temperature

V_{IN}=1.5V, V_B=3.6V




V_{OUT} vs. Temperature

V_{IN}=1.5V, V_O=1.5V, I_O=1mA




Load Transient

V_{IN}=1.9V, V_O=1.2V, I_O=0 to 3A




Enable Turn ON

V_{IN}=1.6V, V_O=1.2V,
V_{EN}=0V to 3V, I_O=3A




Enable Turn Off

V_{IN}=1.6V, V_O=1.2V,
V_{EN}=3V to 0V, I_O=3A




Short Circuit

V_{IN}=2.1V, V_O=1.2V




Short Circuit Recovery

V_{IN}=2.1V, V_O=1.2V



Thermal Protection

V_{IN}=3.8V, V_O=2.5V, I_O=3.6A



NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP2046


MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.

TYPICAL PERFORMANCE CHARACTERISTICS *(CONTINUED)*

C1=22µF, C2=0.1µF, C3=1.0µF, C4=4.7µF, C6=22nF, V_B=5V, T_A=25ºC, unless otherwise noted


Power Ramp Up

V_{IN}=1.5V, V_O=1.2V, I_O=3A
with Resistor load




Power Ramp Down

V_{IN}=1.5V, V_O=1.2V, I_O=3A
with Resistor load



Line Transient

V_{IN}=1.5V to 4.5V, V_O=1.2V, I_O=0.4A



NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP20046

MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.

BLOCK DIAGRAM




Figure 1—Block Diagram of Low Dropout Regulator

OPERATION

MP2040 Theory of Operation

The MP2040 linear dropout regulator provides adjustable output voltages from 0.9V to 3.3V at currents up to 3A. This LDO is protected against short circuits, and it has thermal shut down protection with 15°C hystheresis.

Utilizing Two Power Supplies

In order to maximize the efficiency MP2040 uses two power supplies. One power supply is connected to the BIAS pin and it is used to power up the internal circuitries including band gap reference and the rest of control circuitries. The other power supply is connected to the VIN pins which are the drain of pass device. This power supply can be set close to output voltage of LDO. The output pins are the source of the pass device. The smaller voltage drop across the pass device translates to the smaller power loss in pass device. Thus, the part operates with higher efficiency.

Internal Current Limit

The MP2040 has an internal current limit set at almost 3.8A. Internal current limit is very well controlled over process variations and ambient temperature.

Enable

The enable (EN) pin is active high. The enable pin has a built-in hystheresis. If this pin is held below 0.8V then part shuts down and draws less than 1uA from V_{BIAS} supply.

If not used then connect this pin to V_{BIAS}.

Under Voltage Lockout

The Bias voltage is monitored by a circuit that prevents the LDO start up when the bias voltage is below 2.35V. This circuitry has an approximate hystheresis of 90mV.

NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP2046

MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.

Soft Start

MP2040 incorporates internal soft start function. This internal function reduces the start up current surge into the output capacitor. This allows the gradual built up of output voltage to its final set value. The internal soft start cap is held to ground if there is a fault condition. The fault conditions are UVLO, Thermal shut down, and disable. The internal soft start time is almost 280µ

Power Good

The Power Good pin is an open drain output and can be connected to Bias voltage via a pull up resistor. Open drain transistor turns off and PG pin voltage value becomes V_{BIAS} when V_{FB} exceeds 450mV. Also PG pin can sink at least 230µA while being low.

Setting the Output Voltage

The MP2040 has an adjustable output voltage, set by using a resistive voltage divider from the output voltage to FB pin. The voltage divider divides the output voltage down to the feedback voltage by the ratio:

$$V_{FB} = V_{OUT} \times R_2/ (R_1+R_2)$$

Where V_{FB} is the feedback threshold voltage (V_{FB}=0.5V), and V_{OUT} is the output voltage. R_1 connects between V_{OUT} and V_{FB}, and R_2 connects between V_{FB} and ground.

Thus the output voltage is:

$$V_{OUT} = 0.5 \times (R_1+R_2)/R_2$$

R_2 can be as high as 100kΩ, but a typical value is 10kΩ. Using that value, R_1 is determined by:

$$R_1=R_2 \times (V_{OUT}-V_{FB})/V_{FB}$$

For example, for a 1.8V output voltage, R_2 is 10kΩ, and R_1 is 26kΩ. You can select 26kΩ (1%) resistor for R_1.

Power Dissipation

Most of the power dissipation is due to power dissipation in PASS device. For example, assume V_{BIAS}=5.0V, V_{IN}=2.0V, V_{OUT}=1.8V, and I_{OUT}=3A:

$$P_D\ (_{PASS}) = (V_{IN}-V_{OUT}) \times I_{OUT}$$

$$P_D\ (_{PASS}) = (2.0V-1.8V) \times 3A=0.6W$$

$P_{BIAS} = V_{BIAS} \times I_{GND}$= 5V x (220µA) = 1.25mW. This is negligible compared to $P_D\ (_{PASS})$ =0.6W

For QFN 3X3 θ_{JA} is 50°C/W.

0.6W power is dissipated when 3A output current goes through PASS device with V_{IN}=2.0V, and V_{OUT}=1.8V.

This gives a rise in die temperature for 0.6 x 50°C/W=30°CThis is a safe operating point assuming a junction temperature of 135°C at an 85°C ambient temperature.

A heat sink needs to be utilized for a better temperature performance.

NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP20046

MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.

APPLICATION INFORMATION

PG

The power good pin is an open drain output a pull up resistor (100kΩ recommended). The pull up resistor can be tied to a supply within the voltage range of the pin (0 to 5.5V). For example, the pull up resistor can be tied to the input voltage that is monitored by an IC powered from this input voltage. If the output voltage is 10% below its regulation point, the PG pin becomes low.

Bypass Capacitors

For lower noise, the reference voltage can be bypassed by an external capacitor. A low ESR capacitor, such as the ceramic type, will provide the best performance.

It also can function as an external soft start, the soft start time;

$$Tss=1000 \times C_{BP}$$

Performance Transient Response

For a 3A transient response, suggests increasing the input capacitance should be increased to 22µF or higher to get better performance. This will also avoid glitches on the PG pin due to excessive undershoot. Also increase the input voltage 0.4V above the V_{OUT}, to improve the load transient response.

Maximum Output Voltage and Load Current

If the V_{OUT} is set to 3.3V then the maximum output current will be decreased to 2.5A. The maximum bias voltage limits the V_{OUT}. V_{OUT} must be at least 2.5V less than V_B;

$$V_{OUT}=V_B -2.5V$$

Bias Input Voltage

The bias input is designed for low drop application. The bias pin must be at least 3.3V,


and at least 2.5V higher than the output voltage. If the V_{IN} supply voltage meets these requirements, the bias pin can be tied to V_{IN}.

NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP20046


MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.

PACKAGE INFORMATION


QFN10 (3mm x 3mm)




TOP VIEW




BOTTOM VIEW



SIDE VIEW



DETAIL A



RECOMMENDED LAND PATTERN


NOTE:

1) ALL DIMENSIONS ARE IN MILLIMETERS.
2) EXPOSED PADDLE SIZE DOES NOT INCLUDE MOLD FLASH.
3) LEAD COPLANARITY SHALL BE 0.10 MILLIMETER MAX.
4) DRAWING CONFORMS TO JEDEC MO-229, VARIATION VEED-5.
5) DRAWING IS NOT TO SCALE.

NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP20046

MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.

QFN32 (5mm x 5mm)



NOTE:

1) ALL DIMENSIONS ARE IN MILLIMETERS.
2) EXPOSED PADDLE SIZE DOES NOT INCLUDE MOLD FLASH.
3) LEAD COPLANARITY SHALL BE 0.10 MILLIMETER MAX.
4) DRAWING CONFIRMS TO JEDEC MO-220, VARIATION VHHC-2.
5) DRAWING IS NOT TO SCALE.

NOT RECOMMENDED FOR NEW DESIGNS REFER TO MP20046

NOTICE: The information in this document is subject to change without notice. Please contact MPS for current specifications. Users should warrant and guarantee that third party Intellectual Property rights are not infringed upon when integrating MPS products into any application. MPS will not assume any legal responsibility for any said applications.

MPS Proprietary Information. Unauthorized Photocopy and Duplication Prohibited.
© 2016 MPS. All Rights Reserved.