UPS
Mplus 120K

FEATURES

- N+1 or N+R Parallel Redundancy for power guarantee
- Modular design decreases MTTR
- High scalability
- Built-in maintenance bypass switch for easy maintenance without interruptible
- High efficiency double conversion online UPS
- Adjustable battery numbers
- Adjustable charging current
- Graphic 5.7'' LCD design for easy configuration



PHASE (ONLY FOR ONLINE UPS)

Phase:	3-phase in / 3-phase out

INPUT

Capacity:	120 KW
Voltage:	3 x 400 VAC (3Ph+N)
Voltage Range:	305-478 VAC (3-phase) @ 100% load 190-520 VAC (3-phase) @ 50% load
Frequency Range:	40Hz ~ 70 Hz

OUTPUT

AC Voltage Regulation (Batt. Mode) :	±5 %
Frequency Range (Batt. Mode):	46~54Hz or 56~64Hz
Waveform (Batt. Mode):	Pure Slin Wave

BATTERY

Battery Type:	NONE
Battery Number:	NONE
Typical Recharge Time:	NONE

SAFETY STANDARD APPAOVAL

CE

PROTECTION

Full Protection:	Full Protection

PHYSICAL

Output Receptacles:	India, French, Schuko, NEMA, and IEC selections
Dimension:	600mm(L) x 1100mm(W) x 2030mm(H)
Net Weight (kgs):	NONE

OPERATING ENVIRONMENT

Humidity:	0-90 % RH @ 0- 40°C (non-condensing)
Noise Level:	NONE

MANAGEMENT

Optional USB/RS-232 Port:	Support Windows 98/2000/2003/XP/Vista/2008, Windows 7, Linux, and MAC8

This content is subject to change, please refer to specification for more detail.
FSP reserve the right to change the content without prior notice