Multi-outlet Vehicular Power Distribution System
MRC-141



Features

- **DC input power 24-28 VDC**
- **Handles loads up to 30 amps in 24 VDC operation, 16.5 amps in 12 VDC mode**
- **Seven additional output connectors to provide 12 or 24 VDC to power other equipment such as laptops, GPS, etc.**

Overview

The MRC-141 is a self-contained multiple outlet power system that directly connects to a Scope Shield Communications System and dependent on the current draw up to seven other items of equipment.

2000 Technology Parkway, Newark, New York | 315-332-7100 | Fax: 315-331-7800
©2010 Ultralife Corporation • www.ultralifecorp.com • all specifications subject to change without notice
The information contained herein is for reference only and does not constitute a warranty of performance • 23 Apr 2010 Rev A

Multi-outlet Vehicular Power Distribution System
MRC-141

Technical Specifications:

Part No.	MRC-141
DC input	24-28 VDC
DC output	12 VDC and/or 24 VDC
Size	10.75”L x 8.75”W x 4.25”H
Weight	8.6 lbs. (without battery)
Operating temperature	-30° to +55° C
Storage temperature	-50° to +65° C
Operating altitude	27,000 ft.
Storage altitude	55,000 ft.
Immersion	3 ft.
Humidity	95% relative
Cables optional	MRC-141-07-01 (scoope shield) MRC-141-07-02 (input w/NATO plug)

2000 Technology Parkway, Newark, New York | 315-332-7100 | Fax: 315-331-7800
©2010 Ultralife Corporation • www.ultralifecorp.com • all specifications subject to change without notice
The information contained herein is for reference only and does not constitute a warranty of performance • 23 Apr 2010 Rev A