PIC GmbH • Nibelungenstr. 5A
90530 Wendelstein, Germany
Phone +49 911 99 59 06-0
Fax +49 911 99 59 06-99
info@pic-gmbh.com • www.pic-gmbh.com

MS-106-3

Miniature Reed Sensor • pitch 15.24 mm

Lead free

Electrical Characteristics

Contact form		A
Contact rating max.	W / VA	10
Switching current max.	A	0.7
Carry current max.	A	1.0
Switching voltage max.	VDC	180
	VAC	130
Breakdown voltage min.	VDC	200
Contact resistance (initial) max.	mΩ	100
Insulation resistance min.	Ω	10^9
Capacitance typ.	pF	0.5

Magnetical Characteristics

Pull in range available [1]	AT	10-25


[1] AT range stated for **unmodified** Reed Switch

Operating Characteristics

Operate time (incl. bounce) max.	ms	0.5
Release time max.	ms	0.3
Switching frequency max.	Hz	500
Resonant frequency typ.	Hz	5,000
Vibration (50-2000 Hz)	g	20
Shock (1/2 sin 11 ms)	g	50
Operating temperature	°C	-20 to +85

Dimensions

in mm



Ordering Information

Series	AT Range
MS-106-3	**1** = 10-15 / **2** = 15-20 / **3** = 20-25

Ordering example: MS-106-3-2 describes MS-106-3 with 15-20 AT

Customized types available.

© PIC GmbH, Nürnberg (GERMANY)