PIC GmbH • Nibelungenstr. 5A
90530 Wendelstein, Germany
Phone +49 911 99 59 06-0
Fax +49 911 99 59 06-99
info@pic-gmbh.com • www.pic-gmbh.com

MS-217-5

Mains switching Reed Sensor

Lead free

Electrical Characteristics

Contact form		A
Contact rating max.	W / VA	10
Switching current max.	A	0.5
Carry current max.	A	1.5
Switching voltage max.	VDC	200
	VAC	260
Breakdown voltage min.	VDC	450
Contact resistance (initial) max.	mΩ	100
Insulation resistance min.	Ω	10^{10}
Capacitance typ.	pF	0.2

Magnetical Characteristics

Pull in range available [1]	AT	20-35


[1] AT range stated for **unmodified** Reed Switch

Operating Characteristics

Operate time (incl. bounce) max.	ms	0.6
Release time max.	ms	0.2
Switching frequency max.	Hz	400
Resonant frequency typ.	Hz	3,900
Vibration (50-2000 Hz)	g	30
Shock (1/2 sin 11 ms)	g	100
Operating temperature	°C	-20 to +85

Dimensions

in mm



Wire: AWG 24, black, stripped and tinned

Ordering Information

Series	AT Range
MS-217-5	**3** = 20-25 / **4** = 25-30 / **5** = 30-35

Ordering example: MS-217-5-4 describes MS-217-5 with 25-30 AT

Customized types available.

© PIC GmbH, Nürnberg (GERMANY)