
Ultra Bright Yellow 3mm LED

MT3303B−UY



Features

High Intensity
Reliable Rugged
Low Current Requirements
IC Compatible

Maximum Ratings (Ta=25°C)

Characteristic	Symbol	Max.	Unit
Forward Current	I_F	30	mA
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	84.00	mW
Operating Temperature	T_{opr}	−25 ~ +85	°C
Storage Temperature	T_{stg}	−40 ~ +100	°C
Soldering Temperature	T_{sol}	260	°C
Soldering Time	−	for 5 sec. max	−

Notes:

1.All dimensions are in millimeters.

2.Tolerance is ±0.25mm unless otherwise noted.

Opto−Electrical Characteristics (Ta=25°C)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage	V_F	I_F=20mA	−	2.20	2.80	V
Reverse Current	I_R	V_R=5V	−	−	100	μ A
Luminous Intensity	I_V	I_F=20mA	950.00	1600.00	−	mcd
Viewing Angle	$2\theta^{1/2}$	−	−	36°	−	deg.
Peak Wavelength	λp	I_F=20mA	−	589	−	nm
Dominant Wavelength	λd	I_F=20mA	−	591	−	nm
Spectral Line Half Width	Δλ	I_F=20mA	−	15	−	nm


Company Headquarters
3 Northway Lane North
Latham, New York 12110
Toll Free: 800.984.5337
Fax: 518.785.4725

Web: www.marktechopto.com | Email: info@marktechopto.com


West Coast Sales Office
950 South Coast Drive, Suite 265
Costa Mesa, California 92626
Toll Free: 800.984.5337
Fax: 714.850.9314

MT3303B−UY Graphs


Typical Electrical / Optical Characteristics Curves :




FORWARD CURRENT VS.APPLIED VOLTAGE



FORWARD CURRENT VS. LUMINOUS INTENSITY



AMBIENT TEMPERATURE VS. FORWARD CURRENT



RADIATION DIAGRAM

Company Headquarters
3 Northway Lane North
Latham, New York 12110
Toll Free: 800.984.5337
Fax: 518.785.4725

marktech optoelectronics
Web: www.marktechopto.com | Email: info@marktechopto.com

West Coast Sales Office
950 South Coast Drive, Suite 265
Costa Mesa, California 92626
Toll Free: 800.984.5337
Fax: 714.850.9314