

GENERAL SPECIFICATION

Item	Content
Number of Character	16x2
Module Size	122.0(W)x44.0(H)x10.5/14.0(D)mm Max
Viewing Area	99.0(W)x24.0(H)mm
Character Size	4.84(W)x8.06(H)mm
Dot Size/Dot Pitch	0.92(W)x1.1(H)mm/0.98(W)x1.16(H)mm
Backlight	Without/EL/LED
Options	Gray STN/Yellow STN/Extended Temperature/Bottom/Top Viewing


ELECTRICAL CHARACTERISTICS

Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Power Supply for Logic	$V_{DD}-V_{SS}$	-	2.7	4.5	5.5	Volt	-
Input Voltage	V_{IL}	L level	V_{SS}	$0.2V_{DD}$	-	Volt	-
	V_{IH}	H level	$0.8V_{DD}$	V_{DD}	-	Volt	
LCM Recommend LCD Module Driving Voltage	$V_{DD}=5V$	$T_a=0^{\circ}C$	-	-	-	Volt	-
		$T_a=25^{\circ}C$	3.8	4.1	4.4		
		$T_a=50^{\circ}C$	-	-	-		
Power Supply Current for LCM	I_{DD} (B/L OFF)	$V_{DD}=5.0V$ $V_{DD}-V_O=4.1V$	-	1.5	2.0	mA	-
	I_{LED}	$V_{LED}=4.2V$ $T_a=25^{\circ}C$	-	120	180		


INTERFACE PIN ASSIGNMENT

Pin No.	Pin Out	Function Description
1	V_{SS}	Ground
2	V_{DD}	Logic Circuit Power Supply
3	V_O	Power Supply for LCD Panel
4	RS	Data/Instruction Register Select
5	R/W	Read/Write Select
6	E	Enable Signal
7~14	DB0~DB7	3-State I/O Data Bus
15	BKL1	Power Supply for Backlight. 100V/400Hz AC for EL, 4.2V or 120~180mA DC for LED backlight. Don't care if no backlight
16	BKL2	

BLOCK DIAGRAM



POWER SUPPLY



MECHANICAL

