

Attenuator

Manual Adjustable Attenuator

➔ Specifications

Parameter	Specification
Central Wavelength	980 nm, 1064 nm, 1310 nm, or 1550 nm
Bandwidth	± 20 nm
Attenuation Range	1-30 dB
Resolution	0.1 dB
PDL	≤ 0.1 dB (@ low attenuation)
Return Loss	≥ 50 dB
Fiber Type	SMF 28e or HI 1060 fiber
Power Handling	300 mW
Operating Temperature	0° C ~ + 70° C
Storage Temperature	- 40° C ~ + 85° C
Package Dimensions	15 mm x 13 mm x 6 mm

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

➔ Ordering Information

M	V	O	A	-		-	3	0	-		-		-								
				Wavelength						Max Attenuation						Pigtail Length					
				0980: 980 nm 1064: 1064 nm 1310: 1310 nm 1550: 1550 nm						30: 30 dB						1: 1 meter 2: 2 meter S: Special					
																Pigtail Style (=Package style) B: bare fiber L: 900 μm loose tube K: 2 mm cable R: 3 mm cable					
																Connector 0: None 7: LC/UPEC 1: FC/PC 8: LC/SPC 2: FC/APC 9: Special 3: SC/ PC A: FC/UPEC 4: SC/APC B: SC/UPEC 5: FC/SPC C: ST 6: SC/SPC					