DATA SHEET

74F240/74F240A
Octal inverter buffer (3-State)
74F241/74F241A
Octal buffer (3-State)

Product specification

1001 Jan 02

IC15 Data Handbook

Philips
Semiconductors

PHILIPS

FEATURES

- Octal bus interface
- 3-State buffer outputs sink 64mA
- 15mA source current
- Guaranteed output skew less than 2.0ns (74F240A/74F241A)
- Reduced ground bounce (74F240A/74F241A)
- Reduced I_{CC} (74F241A only)
- Reduced loading (74F240A I_{IL} = 100µA, 74F241A I_{IL} = 40µA)

DESCRIPTION

The 74F240 and 74F241 are octal buffers that are ideal for driving bus lines of buffer memory address registers. The outputs are all capable of sinking 64mA and sourcing up to 15mA. The device features two output enables, each controlling four of the 3–state outputs.

The 74F240A and 74F241A are functionally equivalent to their non–A counterparts. They have been designed to reduce effects of ground noise. Other advantages are noted in the features.

TYPE	TYPICAL PROPAGATION DELAY	TYPICAL SUPPLY CURRENT (TOTAL)
74F240	4.3ns	37mA
74F240A	3.8ns	40mA
74F241	5.0ns	53mA
74F241A	4.5ns	32mA

ORDERING INFORMATION


DESCRIPTION	ORDER CODE COMMERCIAL RANGE V_{CC} = 5V ±10%, T_{amb} = 0°C to +70°C	PKG DWG #
20–pin plastic DIP	N74F240N, N74F240AN, N74F241N, N74F241AN	SOT146-1
20–pin plastic SOL	N74F240D, N74F240AD, N74F241D, N74F241AD	SOT163-1
20-pin plastic SSOP II	N74F240DB	SOT339-1

INPUT AND OUTPUT LOADING AND FAN OUT TABLE


PINS	DESCRIPTION	74F (U.L.) HIGH/LOW	LOAD VALUE HIGH/LOW
Ian, Ibn	Data inputs (74F240)	1.0/1.67	20µA/1.0mA
	Data inputs (74F240A)	1.0/0.167	20µA/100µA
	Data inputs (74F241)	1.0/2.67	20µA/1.6mA
	Data inputs (74F241A)	1.0/0.067	20µA/40µA
$\overline{OE}$a, $\overline{OE}$b	Output enable inputs (active low) (74F240)	1.0/0.33	20µA/0.2mA
	Output enable inputs (active low) (74F240A)	1.0/0.167	20µA/100µA
$\overline{OE}$a, OEb	Output enable input (74F241)	1.0/1.67	20µA/1.0mA
	Output enable input (74F241A)	1.0/0.067	20µA/40µA
Yan, Ybn	Data outputs (74F241, 74F241A)	750/106.7	15mA/64mA
$\overline{Y}$an, $\overline{Y}$bn	Data outputs (74F240, 74F240A)	750/106.7	15mA/64mA

Note to input and output loading and fan out table
One (1.0) FAST unit load is defined as: 20µA in the high state and 0.6mA in the low state.


PIN CONFIGURATION FOR 74F240/74F240A




IEC/IEEE SYMBOL FOR 74F240/74F240A



LOGIC SYMBOL FOR 74F240/74F240A



LOGIC DIAGRAM FOR 74F240/74F240A




FUNCTION TABLE FOR 74F240/74F240A

INPUTS				OUTPUTS	
$\overline{OE}a$	Ia	$\overline{OE}b$	Ib	$\overline{Y}a$	$\overline{Y}b$
L	L	L	L	H	H
L	H	L	H	L	L
H	X	H	X	Z	Z


Notes to function table for 74F240/74F240A

H = High voltage level
L = Low voltage level
X = Don't care
Z = High impedance "off" state


PIN CONFIGURATION FOR 74F241/74F241A




IEC/IEEE SYMBOL FOR 74F241/74F241A



LOGIC SYMBOL FOR 74F241/74F241A



LOGIC DIAGRAM FOR 74F241/74F241A



FUNCTION TABLE FOR 74F241/74F241A

INPUTS				OUTPUTS	
$\overline{OE}$a	Ia	OEb	Ib	Ya	Yb
L	L	H	L	L	L
L	H	H	H	H	H
H	X	L	X	Z	Z

Notes to function table for 74F241/74F241A

H = High voltage level
L = Low voltage level
X = Don't care
Z = High impedance "off" state

ABSOLUTE MAXIMUM RATINGS

(Operation beyond the limit set forth in this table may impair the useful life of the device. Unless otherwise noted these limits are over the operating free air temperature range.)

SYMBOL	PARAMETER	RATING	UNIT
V_{CC}	Supply voltage	–0.5 to +7.0	V
V_{IN}	Input voltage	–0.5 to +7.0	V
I_{IN}	Input current	–30 to +5	mA
V_{OUT}	Voltage applied to output in high output state	–0.5 to V_{CC}	V
I_{OUT}	Current applied to output in low output state	128	mA
T_{amb}	Operating free air temperature range	0 to +70	°C
T_{stg}	Storage temperature range	–65 to +150	°C

RECOMMENDED OPERATING CONDITIONS

SYMBOL	PARAMETER	LIMITS			UNIT
		MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5.0	5.5	V
V_{IH}	High–level input voltage	2.0			V
V_{IL}	Low–level input voltage			0.8	V
I_{Ik}	Input clamp current			–18	mA
I_{OH}	High–level output current			–15	mA
I_{OL}	Low–level output current			64	mA
T_{amb}	Operating free air temperature range	0		+70	°C

DC ELECTRICAL CHARACTERISTICS

(Over recommended operating free-air temperature range unless otherwise noted.)

SYMBOL	PARAMETER			TEST CONDITIONS[1]			LIMITS			UNIT
							MIN	TYP[2]	MAX	
V_{OH}	High-level output voltage			V_{CC} = MIN, V_{IL} = MAX, V_{IH} = MIN	I_{OH} = –3mA	±10%V_{CC}	2.4			V
						±5%V_{CC}	2.7	3.4		V
					I_{OH} = –15mA	±10%V_{CC}	2.0			V
						±5%V_{CC}	2.0			V
V_{OL}	Low-level output voltage			V_{CC} = MIN, V_{IL} = MAX, V_{IH} = MIN,	I_{OL} = MAX	±10%V_{CC}			0.50	V
						±5%V_{CC}		0.42	0.50	V
V_{IK}	Input clamp voltage			V_{CC} = MIN, I_I = I_{IK}				–0.73	-1.2	V
I_I	Input current at maximum input voltage			V_{CC} = MAX, V_I = 7.0V					100	µA
I_{IH}	High–level input current			V_{CC} = MAX, V_I = 2.7V					20	µA
I_{IL}	Low–level input current	74F240 all inputs		V_{CC} = MAX, V_I = 0.5V					–1.0	mA
		74F240A all inputs							–100	µA
		74F241 $\overline{OE}$a, OEb							–1.0	mA
		74F241 Ian, Ibn							–1.6	mA
		74F241A all inputs							–40	µA
I_{OZH}	Off–state output current, high–level voltage applied			V_{CC} = MAX, V_O = 2.7V					50	µA
I_{OZL}	Off–state output current, low–level voltage applied			V_{CC} = MAX, V_O = 0.5V					–50	µA
I_{OS}	Short–circuit output current[3]			V_{CC} = MAX			-100		-225	mA
I_{CC}	Supply current (total)	74F240	I_{CCH}	V_{CC} = MAX				12	18	mA
			I_{CCL}					50	70	mA
			I_{CCZ}					35	45	mA
		74F240A	I_{CCH}					28	37	mA
			I_{CCL}					58	75	mA
			I_{CCZ}					34	50	mA
		74F241	I_{CCH}	V_{CC} = MAX				40	60	mA
			I_{CCL}					60	90	mA
			I_{CCZ}					65	90	mA
		74F241A	I_{CCH}					20	30	mA
			I_{CCL}					49	65	mA
			I_{CCZ}					26	40	mA

Notes to DC electrical characteristics

1. For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions for the applicable type.
2. All typical values are at V_{CC} = 5V, T_{amb} = 25°C.
3. Not more than one output should be shorted at a time. For testing I_{OS}, the use of high-speed test apparatus and/or sample-and-hold techniques are preferable in order to minimize internal heating and more accurately reflect operational values. Otherwise, prolonged shorting of a high output may raise the chip temperature well above normal and thereby cause invalid readings in other parameter tests. In any sequence of parameter tests, I_{OS} tests should be performed last.


AC ELECTRICAL CHARACTERISTICS

SYMBOL	PARAMETER		TEST CONDITION	LIMITS					UNIT
				T_{amb} = +25°C, V_{CC} = +5.0V, C_L = 50pF, R_L = 500Ω			T_{amb} = 0°C to +70°C, V_{CC} = +5.0V ± 10%, C_L = 50pF, R_L = 500Ω		
				MIN	TYP	MAX	MIN	MAX	
t_{PLH} t_{PHL}	Propagation delay Ian, Ibn to $\overline{Y}$n	74F240	Waveform 1	3.0 2.0	4.5 3.0	6.5 4.5	3.0 2.0	7.5 5.0	ns
t_{PZH} t_{PZL}	Output enable time to high or low level		Waveform 3 Waveform 4	3.0 4.5	5.0 6.5	7.5 8.5	3.0 4.0	9.0 10.0	ns
t_{PHZ} t_{PLZ}	Output disable time from high or low level		Waveform 3 Waveform 4	3.0 3.0	5.5 5.0	7.0 7.0	3.0 3.0	7.5 7.5	ns
t_{PLH} t_{PHL}	Propagation delay Ian, Ibn to $\overline{Y}$n	74F240A	Waveform 1	2.5 2.0	4.0 3.5	5.5 5.5	2.0 2.0	6.5 6.0	ns
t_{PZH} t_{PZL}	Output enable time to high or low level		Waveform 3 Waveform 4	2.0 3.5	4.0 5.0	6.5 7.5	2.0 3.0	7.0 8.5	ns
t_{PHZ} t_{PLZ}	Output disable time from high or low level		Waveform 3 Waveform 4	2.0 1.5	3.5 2.5	6.0 5.0	1.5 1.0	6.5 5.5	ns
$t_{sk(0)}$	Output skew[1, 2]		Waveform 5			1.5		2.0	ns
t_{PLH} t_{PHL}	Propagation delay Ian, Ibn to Yn	74F241	Waveform 2	2.5 2.5	4.0 4.0	5.2 5.2	2.5 2.5	6.2 6.5	ns
t_{PZH} t_{PZL}	Output enable time to high or low level		Waveform 3 Waveform 4	2.0 2.0	4.0 5.0	5.7 7.0	2.0 2.0	6.7 8.0	ns
t_{PHZ} t_{PLZ}	Output disable time from high or low level		Waveform 3 Waveform 4	2.0 2.0	4.0 4.0	6.0 6.0	2.0 2.0	7.0 7.0	ns
t_{PLH} t_{PHL}	Propagation delay Ian, Ibn to Yn	74F241A	Waveform 2	2.5 2.5	4.5 4.5	5.8 5.8	2.5 2.5	6.5 6.5	ns
t_{PZH} t_{PZL}	Output enable time to high or low level		Waveform 3 Waveform 4	2.5 3.5	4.5 5.0	6.0 7.0	2.0 3.0	6.7 8.0	ns
t_{PHZ} t_{PLZ}	Output disable time from high or low level		Waveform 3 Waveform 4	2.0 1.5	4.0 3.5	6.0 5.5	1.5 1.0	6.5 6.0	ns
$t_{sk(0)}$	Output skew[1, 2]		Waveform 5			1.5		2.0	ns


Notes to AC electrical characteristics

1. $|t_{PN}$ actual – t_{PM} actual| for any output compared to any other output where N and M are either LH or HL.
2. Skew times are valid only under same test conditions (temperature, V_{CC}, loading, etc.,).


AC WAVEFORMS




Waveform 1. Propagation delay for inverting outputs




Waveform 2. Propagation delay for non–invertIng outputs



Waveform 3. 3-state output enable time to high level and output disable time from high level



Waveform 5. Output skew




Waveform 4. 3-state output enable time to low level and output disable time from low level


Notes to AC waveforms

1. For all waveforms, V_M = 1.5V.
2. The shaded areas indicate when the input is permitted to change for predictable output performance.

TEST CIRCUIT AND WAVEFORMS



Test Circuit for Open Collector Outputs



Input Pulse Definition

SWITCH POSITION

TEST	SWITCH
t_{PLZ}	closed
t_{PZL}	closed
All other	open


DEFINITIONS:

R_L = Load resistor; see AC electrical characteristics for value.
C_L = Load capacitance includes jig and probe capacitance; see AC electrical characteristics for value.
R_T = Termination resistance should be equal to Z_{OUT} of pulse generators.

family	INPUT PULSE REQUIREMENTS					
	amplitude	V_M	rep. rate	t_w	t_{TLH}	t_{THL}
74F	3.0V	1.5V	1MHz	500ns	2.5ns	2.5ns

SF00128

DIP20: plastic dual in-line package; 20 leads (300 mil) SOT146-1



DIMENSIONS (inch dimensions are derived from the original mm dimensions)


UNIT	A max.	A_1 min.	A_2 max.	b	b_1	c	D (1)	E (1)	e	e_1	L	M_E	M_H	w	Z (1) max.
mm	4.2	0.51	3.2	1.73 1.30	0.53 0.38	0.36 0.23	26.92 26.54	6.40 6.22	2.54	7.62	3.60 3.05	8.25 7.80	10.0 8.3	0.254	2.0
inches	0.17	0.020	0.13	0.068 0.051	0.021 0.015	0.014 0.009	1.060 1.045	0.25 0.24	0.10	0.30	0.14 0.12	0.32 0.31	0.39 0.33	0.01	0.078

Note

1. Plastic or metal protrusions of 0.25 mm maximum per side are not included.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT146-1			SC603			~~92-11-17~~ 95-05-24

SO20: plastic small outline package; 20 leads; body width 7.5 mm **SOT163-1**



DIMENSIONS (inch dimensions are derived from the original mm dimensions)


UNIT	A max.	A_1	A_2	A_3	b_p	c	$D^{(1)}$	$E^{(1)}$	e	H_E	L	L_p	Q	v	w	y	$Z^{(1)}$	θ
mm	2.65	0.30 0.10	2.45 2.25	0.25	0.49 0.36	0.32 0.23	13.0 12.6	7.6 7.4	1.27	10.65 10.00	1.4	1.1 0.4	1.1 1.0	0.25	0.25	0.1	0.9 0.4	8^o 0^o
inches	0.10	0.012 0.004	0.096 0.089	0.01	0.019 0.014	0.013 0.009	0.51 0.49	0.30 0.29	0.050	0.419 0.394	0.055	0.043 0.016	0.043 0.039	0.01	0.01	0.004	0.035 0.016	


Note

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT163-1	075E04	MS-013AC				~~95-01-24~~ 97-05-22

SSOP20: plastic shrink small outline package; 20 leads; body width 5.3 mm **SOT339-1**





DIMENSIONS (mm are the original dimensions)

UNIT	A max.	A_1	A_2	A_3	b_p	c	$D^{(1)}$	$E^{(1)}$	e	H_E	L	L_p	Q	v	w	y	$Z^{(1)}$	θ
mm	2.0	0.21 0.05	1.80 1.65	0.25	0.38 0.25	0.20 0.09	7.4 7.0	5.4 5.2	0.65	7.9 7.6	1.25	1.03 0.63	0.9 0.7	0.2	0.13	0.1	0.9 0.5	8° 0°

Note

1. Plastic or metal protrusions of 0.20 mm maximum per side are not included.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT339-1		MO-150AE				~~93-09-08~~ 95-02-04

Data sheet status

Data sheet status	Product status	Definition [1]
Objective specification	Development	This data sheet contains the design target or goal specifications for product development. Specification may change in any manner without notice.
Preliminary specification	Qualification	This data sheet contains preliminary data, and supplementary data will be published at a later date. Philips Semiconductors reserves the right to make chages at any time without notice in order to improve design and supply the best possible product.
Product specification	Production	This data sheet contains final specifications. Philips Semiconductors reserves the right to make changes at any time without notice in order to improve design and supply the best possible product.

[1] Please consult the most recently issued datasheet before initiating or completing a design.

Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Disclaimers

Life support — These products are not designed for use in life support appliances, devices or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes, without notice, in the products, including circuits, standard cells, and/or software, described or contained herein in order to improve design and/or performance. Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

Philips Semiconductors
811 East Arques Avenue
P.O. Box 3409
Sunnyvale, California 94088–3409
Telephone 800-234-7381

© Copyright Philips Electronics North America Corporation 1998
All rights reserved. Printed in U.S.A.

print code Date of release: 10-98

Document order number: 9397-750-05101

Let's make things better.

Philips Semiconductors

PHILIPS