



## NA1394-6-W

Firewire 6 with IEEE 1394 6 pole receptacles on both ends, Nickel D-housing

Due to the rising digitisation the interface problems between audio/video networks, IT equipment (e.g. Mac) and mLAN connections increase.

Neutrik's Firewire feedthrough type 1394a, mounted in the standardized D-shape housing, solves this problem.

### Features & Benefits

- Ideal for audio networking and integration of digital equipment into audio systems
- Universally accepted standard D-shape housing
- Firewire feedthrough with 6 pole IEEE 1394 receptacle at both ends
- Removable screen to chassis grounding:

## Technical Information

| Product         |            |
|-----------------|------------|
| Title           | NA1394-6-W |
| Connection Type | Firewire   |
| Gender          | female     |

| Mechanical         |                |
|--------------------|----------------|
| Wiresize           |                |
| Mounting direction | Front mounting |
| Chassis shape      | D              |

| Material        |                         |
|-----------------|-------------------------|
| Contact plating | Au                      |
| Contacts        | Brass (CuZn39Pb3)       |
| Insert          | PBTP 15 % GR            |
| Shell           | Zinc diecast (ZnAl4Cu1) |
| Shell plating   | Nickel                  |

| Environmental       |                  |
|---------------------|------------------|
| Flammability        | UL 94 V-0        |
| Standard compliance | IEEE 1394        |
| Temperature range   | -25 °C to +85 °C |