Deutsche Version

Home
About Us
Products
Support
News
Sitemap

Search

Products only

© Neutrik® AG
All rights reserved
Legal Notices

Chassis Connectors

back

Print

NL4MP

4 pole chassis connector, black D-size flange, countersunk thru holes, 3/16" flat tabs

The state-of-the-art chassis connector for loudspeaker / amplifier applications. They feature a unique locking system, robust plastic housing and high current silver plated contacts.

Features & Benefits

- Standard current rating 30 Amp
- High current version up to 50 Amp audio current
- Glass reinforced materials make it extremely robust and dependable
- Precise keyway for secure mating
- Accurate twist lock latching system
- Metal insert in locking area
- Airtight design - optimized for speaker applications

Accessories

MFD

NLFASTON

SCDR

SCDX

SCL







Frontplattenausschnitt (Rückseite)
Panel Cutout (rear side)



Allgemeintoleranzen ISO 2768-m	Werkstoff	Massstab:		Datum	Name
			Gezeichnet	23.06.99	Martinek
Zeichnung urheberrechtlich geschuetzt (DIN 34) (C)	- -	2:1 (A3)	Freigegeben	-	-
			Geaendert	15.09.03	Mijatovic
Benennung NL4MP NL4MP			Aend.-Nr. -		Aend.-Index F
			Ersatz fuer: 3102ST0505		Blatt 1 von 1 Bl.
NEUTRIK AG FL-9494 SCHAAN			Zeichn. Nr. ST-NL4MP		

Chassis Connectors

NL4MP



There are no technical infos for this product.

Product	
Connector Type	Speakon
Gender	male
Electrical	
Contact resistance	≤ 3 mΩ (after lifetime)
Dielectric strength	4 kVdc (peak)
Insulation resistance	> 1 GΩ (after dampheat)
Rated current per contact	30 A rms continuous
Rated current per contact	40 A audiosignal, duty cycle 50 %
Rated voltage	250 V (Insulation)
Mechanical	
Lifetime	> 5000 mating cycles
Wiring	3/16'' flat tabs
Locking device	Quick Lock
Mounting direction	front & rear
Chassis shape	D
Layout	standard hole position, thru holes
Material	
Contact plating	4 µm Ag
Contacts	Bronze (CuSn6)
Shell	Polyamide (PA 6 30 % GR) black

Environmental	
Approvals	UL,CSA
Flammability	UL 94 HB
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C
Optical	
Mobile Cables	