NSS60101DMT

60 V, 1 A, Low $V_{CE(sat)}$ NPN Transistors

ON Semiconductor's e^2PowerEdge family of low $V_{CE(sat)}$ transistors are miniature surface mount devices featuring ultra low saturation voltage ($V_{CE(sat)}$) and high current gain capability. These are designed for use in low voltage, high speed switching applications where affordable efficient energy control is important.

Typical applications are DC−DC converters and LED lightning, power management…etc. In the automotive industry they can be used in air bag deployment and in the instrument cluster. The high current gain allows e^2PowerEdge devices to be driven directly from PMU's control outputs, and the Linear Gain (Beta) makes them ideal components in analog amplifiers.

Features

- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- NSV60101DMTWTBG − Wettable Flanks Device
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

MAXIMUM RATINGS (T_A = 25°C)

Rating	Symbol	Max	Unit
Collector−Emitter Voltage	V_{CEO}	60	Vdc
Collector−Base Voltage	V_{CBO}	60	Vdc
Emitter−Base Voltage	V_{EBO}	6	Vdc
Collector Current − Continuous	I_C	1	A
Collector Current − Peak	I_{CM}	2	A

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance Junction−to−Ambient (Notes 1 and 2)	$R_{\theta JA}$	55	°C/W
Total Power Dissipation per Package @ T_A = 25°C (Note 2)	P_D	2.27	W
Thermal Resistance Junction−to−Ambient (Note 3)	$R_{\theta JA}$	69	°C/W
Power Dissipation per Transistor @ T_A = 25°C (Note 3)	P_D	1.8	W
Junction and Storage Temperature Range	T_J, T_{stg}	−55 to +150	°C


1. Per JESD51−7 with 100 mm^2 pad area and 2 oz. Cu (Dual Operation).
2. P_D per Transistor when both are turned on is one half of Total P_D or 1.13 Watts.
3. Per JESD51−7 with 100 mm^2 pad area and 2 oz. Cu (Single−Operation).

ON Semiconductor®


www.onsemi.com

60 Volt, 1 Amp
NPN Low $V_{CE(sat)}$ Transistors

MARKING DIAGRAM




WDFN6
CASE 506AN




AN = Specific Device Code
M = Date Code
▪ = Pb−Free Package

(Note: Microdot may be in either location)

PIN CONNECTIONS





ORDERING INFORMATION

Device	Package	Shipping†
NSS60101DMTTBG	WDFN6 (Pb−Free)	3000/Tape & Reel
NSV60101DMTWTBG	WDFN6 (Pb−Free)	3000/Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2016

Table 1. ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector−Emitter Breakdown Voltage (I_C = 10 mA, I_B = 0)	$V_{(BR)CEO}$	60			V
Collector−Base Breakdown Voltage (Ic = 0.1 mA, I_E = 0)	$V_{(BR)CBO}$	80			V
Emitter−Base Breakdown Voltage (I_E = 0.1 mA, I_C = 0)	$V_{(BR)EBO}$	6			V
Collector Cutoff Current (V_{CB} = 60 V, I_E = 0)	I_{CBO}			100	nA
Emitter Cutoff Current (V_{BE} = 5.0 V)	I_{EBO}			100	nA
ON CHARACTERISTICS					
DC Current Gain (Note 4) (I_C = 100 mA, V_{CE} = 2.0 V) (I_C = 500 mA, V_{CE} = 2.0 V) (I_C = 1 A, V_{CE} = 2.0 V) (I_C = 2 A, V_{CE} = 2.0 V	h_{FE}	 150 120 90 35	 250 240 180 55		
Collector−Emitter Saturation Voltage (Note 4) (I_C = 500 mA, I_B = 50 mA) (I_C = 1 A, I_B = 50 mA) (I_C = 1 A, I_B = 100 mA)	$V_{CE(sat)}$		 0.063 0.130 0.115	 0.100 0.200 0.180	V
Base − Emitter Saturation Voltage (Note 4) (I_C = 500 mA, I_B = 50 mA) (I_C = 1 A, I_B = 50 mA) (I_C = 1 A, I_B = 100 mA)	$V_{BE(sat)}$			 1.0 1.0 1.1	V
Base−Emitter Turn−on Voltage (Note 4) (I_C = 500 mA, V_{CE} = 2 V)	$V_{BE(on)}$			0.9	V
DYNAMIC CHARACTERISTICS					
Output Capacitance (V_{CB} = 10 V, f = 1.0 MHz)	C_{obo}		10		pF
Cutoff Frequency (I_C = 50 mA, V_{CE} = 2.0 V, f = 100 MHz)	f_T		180		MHz
SWITCHING TIMES					
Delay Time (V_{CC} = 10 V, I_C = 0.5 A, I_{B1} = 25 mA, I_{B2} = −25 mA)	t_d		13		ns
Rise Time (V_{CC} = 10 V, I_C = 0.5 A, I_{B1} = 25 mA, I_{B2} = −25 mA)	t_r		18		ns
Storage Time (V_{CC} = 10 V, I_C = 0.5 A, I_{B1} = 25 mA, I_{B2} = −25 mA)	t_s		700		ns
Fall Time (V_{CC} = 10 V, I_C = 0.5 A, I_{B1} = 25 mA, I_{B2} = −25 mA)	t_f		80		ns

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Pulse Condition: Pulse Width = 300 μsec, Duty Cycle ≤ 2%

TYPICAL CHARACTERISTICS




Figure 1. DC Current Gain




Figure 2. DC Current Gain




Figure 3. Collector Current as a Function of Collector Emitter Voltage




Figure 4. Collector−Emitter Saturation Voltage




Figure 5. Collector−Emitter Saturation Voltage




Figure 6. Base−Emitter Saturation Voltage

TYPICAL CHARACTERISTICS




Figure 7. Base−Emitter “ON” Voltage




Figure 8. Collector Saturation Region




Figure 9. Input Capacitance




Figure 10. Output Capacitance




Figure 11. f_T, Current Gain Bandwidth Product




Figure 12. Power Derating

TYPICAL CHARACTERISTICS




Figure 13. Thermal Resistance by Transistor





Figure 14. Thermal Resistance for Both Transistors

NSS60101DMT


PACKAGE DIMENSIONS

WDFN6 2x2, 0.65P
CASE 506AN
ISSUE G




NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 mm FROM THE TERMINAL TIP.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

	MILLIMETERS	
DIM	MIN	MAX
A	0.70	0.80
A1	0.00	0.05
A3	0.20 REF	
b	0.25	0.35
D	2.00 BSC	
D2	0.57	0.77
E	2.00 BSC	
E2	0.90	1.10
e	0.65 BSC	
F	0.95 BSC	
K	0.25 REF	
L	0.20	0.30
L1	---	0.10



SOLDERMASK DEFINED MOUNTING FOOTPRINT



DIMENSIONS: MILLIMETERS

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative