NST856BF3T5G

PNP General Purpose Transistor

The NST856BF3T5G device is a spin−off of our popular SOT−23/SOT−323/SOT−563/SOT−963 three−leaded device. It is designed for general purpose amplifier applications and is housed in the SOT−1123 surface mount package. This device is ideal for low−power surface mount applications where board space is at a premium.

Features

- h_{FE}, 220−475
- Low $V_{CE(sat)}$, ≤ −0.3 V
- Reduces Board Space
- This is a Halide−Free Device
- This is a Pb−Free Device

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector − Emitter Voltage	V_{CEO}	−65	Vdc
Collector − Base Voltage	V_{CBO}	−80	Vdc
Emitter − Base Voltage	V_{EBO}	−5.0	Vdc
Collector Current − Continuous	I_C	−100	mAdc

THERMAL CHARACTERISTICS


Characteristic	Symbol	Max	Unit
Total Device Dissipation, T_A = 25°C Derate above 25°C	P_D (Note 1)	290 2.3	mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$ (Note 1)	432	°C/W
Total Device Dissipation, T_A = 25°C Derate above 25°C	P_D (Note 2)	347 2.8	mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$ (Note 2)	360	°C/W
Thermal Resistance, Junction−to−Lead 3	$R_{\Psi JL}$ (Note 2)	143	°C/W
Junction and Storage Temperature Range	T_J, T_{stg}	−55 to +150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.


1. 100 mm^2 1 oz, copper traces.
2. 500 mm^2 1 oz, copper traces.

ON Semiconductor®

http://onsemi.com




NST856BF3T5G



SOT−1123
CASE 524AA
STYLE 1

MARKING DIAGRAM



A = Device Code
M = Date Code

ORDERING INFORMATION

Device	Package	Shipping†
NST856BF3T5G	SOT−1123 (Pb−Free)	8000/Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2012

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector – Emitter Breakdown Voltage (I_C = −10 mA)	$V_{(BR)CEO}$	−65	–	–	V
Collector – Emitter Breakdown Voltage (I_C = −10 μA, V_{EB} = 0)	$V_{(BR)CES}$	−80	–	–	V
Collector – Base Breakdown Voltage (I_C = −10 μA)	$V_{(BR)CBO}$	−80	–	–	V
Emitter – Base Breakdown Voltage (I_E = −1.0 μA)	$V_{(BR)EBO}$	−5.0	–	–	V
Collector Cutoff Current (V_{CB} = −30 V) (V_{CB} = −30 V, T_A = 150°C)	I_{CBO}	– –	– –	−15 −4.0	nA μA
ON CHARACTERISTICS					
DC Current Gain (I_C = −10 μA, V_{CE} = −5.0 V) (I_C = −2.0 mA, V_{CE} = −5.0 V)	h_{FE}	 – 220	 150 290	 – 475	–
Collector – Emitter Saturation Voltage (I_C = −10 mA, I_B = −0.5 mA) (I_C = −100 mA, I_B = −5.0 mA)	$V_{CE(sat)}$	 – –	 – –	 −0.3 −0.8	V
Base – Emitter Saturation Voltage (I_C = −10 mA, I_B = −0.5 mA) (I_C = −100 mA, I_B = −5.0 mA)	$V_{BE(sat)}$	 – –	 −0.7 −0.9	 – –	V
Base – Emitter On Voltage (I_C = −2.0 mA, V_{CE} = −5.0 V) (I_C = −10 mA, V_{CE} = −5.0 V)	$V_{BE(on)}$	 −0.6 –	 – –	 −0.75 −0.82	V
SMALL−SIGNAL CHARACTERISTICS					
Current – Gain – Bandwidth Product (I_C = −10 mA, V_{CE} = −5.0 Vdc, f = 100 MHz)	f_T	100	–	–	MHz
Output Capacitance (V_{CB} = −10 V, f = 1.0 MHz)	C_{obo}	–	–	4.5	pF
Input Capacitance (V_{EB} = −0.5 V, I_C = 0 mA, f = 1.0 MHz)	C_{ibo}	–	–	10	pF
Noise Figure (I_C = −0.2 mA, V_{CE} = −5.0 Vdc, R_S = 2.0 kΩ, f = 1.0 kHz, BW = 200 Hz)	NF	–	–	10	dB




Figure 1. Collector Emitter Saturation Voltage vs. Collector Current




Figure 2. DC Current Gain vs. Collector Current




Figure 3. Base Emitter Saturation Voltage vs. Collector Current




Figure 4. Base Emitter Turn−On Voltage vs. Collector Current




Figure 5. Saturation Region




Figure 6. Input Capacitance






Figure 7. Output Capacitance

PACKAGE DIMENSIONS


SOT−1123
CASE 524AA
ISSUE C



TOP VIEW



SIDE VIEW




BOTTOM VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

	MILLIMETERS	
DIM	MIN	MAX
A	0.34	0.40
b	0.15	0.28
b1	0.10	0.20
c	0.07	0.17
D	0.75	0.85
E	0.55	0.65
e	0.35	0.40
H_E	0.95	1.05
L	0.185 REF	
L2	0.05	0.15

STYLE 1:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative