

FEATURES

Fast

- Slew Rate 50V/ μ s Min
- Settling-Time (0.01%) 1 μ s Max
- Gain-Bandwidth Product 10MHz Typ

Precise

- Common-Mode Rejection 88dB Min
- Open-Loop Gain 500V/mV Min
- Offset Voltage 750 μ V Max
- Bias Current 200pA Max

Excellent Radiation Hardness

Available in Die Form

ORDERING INFORMATION [†]

$T_A = 25^\circ\text{C}$ $V_{OS} \text{ MAX}$ (mV)	PACKAGE					OPERATING TEMPERATURE RANGE
	TO-99	CERDIP 8-PIN	PLASTIC 8-PIN	SO 8-PIN	LCC 20-CONTACT	
1.0	OP42AJ*	OP42AZ*	—	—	OP42ARC/883	MIL
0.75	OP42EJ	OP42EZ	—	—	—	IND
1.5	OP42FJ	OP42FZ	—	—	—	IND
5.0	—	—	OP42GP	OP42GS	—	XIND

* For devices processed in total compliance to MIL-STD-883, add /883 after part number. Consult factory for 883 data sheet.

[†] Burn-in is available on commercial and industrial temperature range parts in cerdip, plastic dip, and TO-can packages.

GENERAL DESCRIPTION


The OP-42 is a fast precision JFET-input operational amplifier. Similar in speed to the OP-17, the OP-42 offers a symmetric

58V/ μ s slew rate and is internally compensated for unity-gain operation. OP-42 speed is achieved with a supply current of less than 6mA. Unity-gain stability, a wide full-power bandwidth of 900kHz, and a fast settling-time of 800ns to 0.01% make the OP-42 an ideal output amplifier for fast digital-to-analog converters.


Equal attention was given to both speed and precision in the OP-42 design. Its tight 750 μ V maximum input offset voltage combined with well-controlled drift of less than 10 μ V/ $^\circ$ C eliminates the need for external nulling in many circuits. The OP-42's

Continued

PIN CONNECTIONS



SIMPLIFIED SCHEMATIC



OP-42

GENERAL DESCRIPTION *Continued*

common-mode rejection of 88dB minimum over a $\pm 11\text{V}$ input voltage range is exceptional for a high-speed amplifier. High CMR combined with a minimum 500V/mV gain into 10k Ω load ensure excellent linearity in both noninverting and inverting gain configurations. The low input bias and offset currents provided by the JFET input stage suit the OP-42 for use in high-speed sample and hold circuits, peak detectors, and log amplifiers. Excellent radiation hardness characteristics make the OP-42 ideal for military and aerospace applications.

The OP-42 conforms to the standard 741 pinout with nulling to V₋. The OP-42 upgrades the performance of circuits using the AD544, AD611, AD711, and LF400 by direct replacement. In circuits without nulling, the OP-42 offers an upgrade for designs using the OP-16, OP-17, LT1022, LT1056, and HA2510.

ABSOLUTE MAXIMUM RATINGS (Note 1)

Supply Voltage	$\pm 20\text{V}$
Input Voltage (Note 2)	$\pm 20\text{V}$
Differential Input Voltage (Note 2)	40V
Output Short-Circuit Duration	Indefinite

Storage Temperature Range -65°C to $+175^{\circ}\text{C}$

Operating Temperature Range

OP42A (J, Z) -55°C to $+125^{\circ}\text{C}$

OP42E, F (J, Z) -25°C to $+85^{\circ}\text{C}$

OP42G -40°C to $+85^{\circ}\text{C}$

Junction Temperature -65°C to $+175^{\circ}\text{C}$

Lead Temperature Range (Soldering, 60 sec.) $+300^{\circ}\text{C}$

PACKAGE TYPE	θ_{JA} (NOTE 3)	θ_{JC}	UNITS
TO-99 (J)	150	18	$^{\circ}\text{C/W}$
8-Pin Hermetic DIP (Z)	148	16	$^{\circ}\text{C/W}$
8-Pin Plastic DIP (P)	103	43	$^{\circ}\text{C/W}$
20-Contact LCC (RC, TC)	98	38	$^{\circ}\text{C/W}$
8-Pin SO (S)	158	43	$^{\circ}\text{C/W}$

NOTES:

1. Absolute maximum ratings apply to both DICE and packaged parts, unless otherwise noted.
2. For supply voltages less than $\pm 20\text{V}$, the absolute maximum input voltage is equal to the supply voltage.
3. θ_{JA} is specified for worst case mounting conditions, i.e., θ_{JA} is specified for device in socket for TO, CERDIP, P-DIP, and LCC packages; θ_{JA} is specified for device soldered to printed circuit board for SO package.

ELECTRICAL CHARACTERISTICS at $V_S = \pm 15\text{V}$, $T_A = +25^{\circ}\text{C}$, unless otherwise noted.

PARAMETER	SYMBOL	CONDITIONS	OP-42E			OP-42F			OP-42G			UNITS
			MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
Offset Voltage	V_{OS}		—	0.3	0.75	—	0.4	1.5	—	1.5	5.0	mV
Input Bias Current	I_B	$V_{CM} = 0\text{V}$ $T_J = 25^{\circ}\text{C}$	—	80	200	—	130	250	—	130	250	pA
Input Offset Current	I_{OS}	$V_{CM} = 0\text{V}$ $T_J = 25^{\circ}\text{C}$	—	4	40	—	6	50	—	6	50	pA
Input Voltage Range	IVR	(Note 1)	± 11	$+12.5$ -12.0	—	± 11	$+12.5$ -12.0	—	± 11	$+12.5$ -12.0	—	V
Common-Mode Rejection	CMR	$V_{CM} = \pm 11\text{V}$	88	98	—	80	92	—	80	92	—	dB
Power-Supply Rejection Ratio	PSRR	$V_S = \pm 10\text{V}$ to $\pm 20\text{V}$	—	9	40	—	12	50	—	12	50	$\mu\text{V/V}$
Large-Signal Voltage Gain	A_{VO}	$R_L = 10\text{k}\Omega$	500	900	—	500	900	—	500	900	—	V/mV
		$R_L = 2\text{k}\Omega$	200	260	—	200	260	—	200	260	—	
		$R_L = 1\text{k}\Omega$	100	170	—	100	170	—	100	170	—	
Output Voltage Swing	V_O	$R_L = 1\text{k}\Omega$	± 11.5	$+12.5$ -11.9	—	± 11.5	$+12.5$ -11.9	—	± 11.5	$+12.5$ -11.9	—	V
Short-Circuit Current Limit	I_{SC}	Output Shorted to Ground	± 20	$+33$ -28	± 60	± 20	$+33$ -28	± 60	± 20	$+33$ -28	± 60	mA
Supply Current	I_{SY}	No Load $V_O = 0\text{V}$	—	5.1	6.0	—	5.1	6.5	—	5.1	6.5	mA
Slew Rate	SR		50	58	—	40	50	—	40	50	—	V/ μs
Full-Power Bandwidth	BW_p	(Note 2)	750	900	—	600	800	—	600	800	—	kHz
Gain-Bandwidth Product	GBW	$f_O = 10\text{kHz}$	—	10	—	—	10	—	—	10	—	MHz
Settling Time	t_s	10V Step 0.01% (Note 3)	—	0.8	1.0	—	0.9	1.2	—	0.9	1.2	μs
Overload Recovery Time	t_{OR}		—	700	—	—	700	—	—	700	—	ns
Phase Margin	ϕ_O	0db Gain	—	47	—	—	47	—	—	47	—	degrees
Gain Margin	A_{180}	180° Open-Loop Phase Shift	—	9	—	—	9	—	—	9	—	dB
Capacitive Load Drive Capability	C_L	Unity-Gain Stable (Note 4)	100	300	—	100	300	—	100	300	—	pF

ELECTRICAL CHARACTERISTICS at $V_S = \pm 15V$, $T_A = +25^\circ C$, unless otherwise noted. *Continued*

PARAMETER	SYMBOL	CONDITIONS	OP-42E			OP-42F			OP-42G			UNITS
			MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
Differential Input Impedance	Z_{IN}		—	$10^{12} 6$	—	—	$10^{12} 6$	—	—	$10^{12} 6$	—	ΩpF
Open-Loop Output Resistance	R_O		—	50	—	—	50	—	—	50	—	Ω
Voltage Noise	$e_{n\ p-p}$	0.1Hz to 10Hz	—	2	—	—	2	—	—	2	—	μV_{p-p}
Voltage Noise Density	e_n	$f_O = 10Hz$	—	38	—	—	38	—	—	38	—	$nV/\sqrt{Hz}$
		$f_O = 100Hz$	—	16	—	—	16	—	—	16	—	
		$f_O = 1kHz$	—	13	—	—	13	—	—	13	—	
		$f_O = 10kHz$	—	12	—	—	12	—	—	12	—	
Current Noise Density	i_n	$f_O = 1kHz$	—	0.007	—	—	0.007	—	—	0.007	—	$pA/\sqrt{Hz}$
External V_{OS} Trim Range		$R_{pot} = 20k\Omega$	—	4	—	—	4	—	—	4	—	mV
Long-Term V_{OS} Drift			—	5	—	—	5	—	—	5	—	$\mu V/month$
Supply Voltage Range	V_S		± 8	± 15	± 20	± 8	± 15	± 20	± 8	± 15	± 20	V

NOTES:

1. Guaranteed by CMR test.
2. Guaranteed by slew-rate test and formula $BW_p = SR/(2\pi 10V_{PEAK})$.
3. Settling-time is sample tested for A and E grades. Test circuit is shown in Figure 4. Settling-time for F grade is guaranteed but not tested.
4. Guaranteed but not tested.

ELECTRICAL CHARACTERISTICS at $V_S = \pm 15V$, $T_A = +25^\circ C$, unless otherwise noted.

PARAMETER	SYMBOL	CONDITIONS	OP-42A			UNITS
			MIN	TYP	MAX	
Offset Voltage	V_{OS}		—	0.3	1.0	mV
Input Bias Current	I_B	$V_{CM} = 0V$ $T_J = 25^\circ C$	—	80	200	pA
Input Offset Current	I_{OS}	$V_{CM} = 0V$ $T_J = 25^\circ C$	—	4	40	pA
Input Voltage Range	IVR	(Note 1)	± 11	+12.5 -12.0	—	V
Common-Mode Rejection	CMR	$V_{CM} = \pm 11V$	86	96	—	dB
Power-Supply Rejection Ratio	PSRR	$V_S = \pm 10V$ to $\pm 20V$	—	9	40	$\mu V/V$
Large-Signal Voltage Gain	A_{VO}	$R_L = 10k\Omega$ $V_O = \pm 10V$	500	900	—	V/mV
		$R_L = 2k\Omega$ $T_J = 25^\circ C$	200	260	—	
		$R_L = 1k\Omega$	100	170	—	
Output Voltage Swing	V_O	$R_L = 1k\Omega$	± 11.5	+12.5 -11.9	—	V
Short-Circuit Current Limit	I_{SC}	Output Shorted to Ground	± 20	+33 -28	± 60	mA
Supply Current	I_{SY}	No Load $V_O = 0V$	—	5.1	6.0	mA
Slew Rate	SR		45	52	—	V/ μs
Full-Power Bandwidth	BW_p	(Note 2)	700	850	—	kHz
Gain-Bandwidth Product	GBW	$f_O = 10kHz$	—	10	—	MHz
Settling -Time	t_s	10V Step 0.01% (Note 3)	—	0.8	1.0	μs
Overload Recovery Time	t_{OR}		—	700	—	ns
Phase Margin	ϕ_o	0db Gain	—	47	—	degrees

OP-42

ELECTRICAL CHARACTERISTICS at $V_S = \pm 15V$, $T_A = 25^\circ C$, unless otherwise noted. *Continued*

PARAMETER	SYMBOL	CONDITIONS	MIN	OP-42A TYP	MAX	UNITS
Gain Margin	A_{180}	180° Open-Loop Phase Shift	—	9	—	dB
Capacitive Load Drive Capability	C_L	Unity-Gain Stable (Note 4)	100	300	—	pF
Differential Input Impedance	Z_{IN}		—	$10^{12} 6$	—	ΩpF
Open-Loop Output Resistance	R_O		—	50	—	Ω
Voltage Noise	$e_{n\ p-p}$	0.1Hz to 10Hz	—	2	—	μV_{p-p}
Voltage Noise Density	e_n	$f_o = 10Hz$	—	38	—	$nV/\sqrt{Hz}$
		$f_o = 100Hz$	—	16	—	
		$f_o = 1kHz$	—	13	—	
		$f_o = 10kHz$	—	12	—	
Current Noise Density	i_n	$f_o = 1kHz$	—	0.007	—	$pA/\sqrt{Hz}$
External V_{OS} Trim Range		$R_{pot} = 20k\Omega$	—	4	—	mV
Long-Term V_{OS} Drift			—	5	—	$\mu V/month$
Supply Voltage Range	V_S		± 8	± 15	± 20	V

NOTES:

1. Guaranteed by CMR test.
2. Guaranteed by slew-rate test and formula $BW_p = SR/(2\pi 10V_{PEAK})$.

3. Settling-time is sample tested for A and E grades. Test circuit is shown in Figure 4. Settling-time for F grade is guaranteed but not tested.
4. Guaranteed but not tested.

ELECTRICAL CHARACTERISTICS at $V_S = \pm 15V$, $-25^\circ C \leq T_A \leq 85^\circ C$ for E/F grades, and $-40^\circ C \leq T_A \leq +85^\circ C$ for G grade, unless otherwise noted.

PARAMETER	SYMBOL	CONDITIONS	OP-42E			OP-42F			OP-42G			UNITS
			MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
Offset Voltage	V_{OS}		—	0.4	1.2	—	0.6	2.5	—	2.0	6.0	mV
Offset Voltage Temperature Coefficient	TCV_{OS}		—	4	10	—	8	—	—	8	—	$\mu V/^\circ C$
Input Bias Current	I_B	(Note 1)	—	0.5	1.2	—	0.6	2.0	—	0.6	2.0	nA
Input Offset Current	I_{OS}	(Note 1)	—	0.05	0.2	—	0.06	0.4	—	0.06	0.4	nA
Input Voltage Range	IVR	(Note 2)	± 11	$+12.5$ -12.0	—	± 11	$+12.5$ -12.0	—	± 11	$+12.5$ -12.0	—	V
Common-Mode Rejection	CMR	$V_{CM} = \pm 11V$	86	96	—	80	94	—	80	94	—	dB
Power-Supply Rejection Ratio	PSRR	$V_S = \pm 10V$ to $\pm 20V$	—	2	40	—	6	50	—	6	50	$\mu V/V$
Large-Signal Voltage Gain	A_{VO}	$R_L = 10k\Omega$ (Note 1)	200	500	—	200	500	—	200	500	—	V/mV
		$R_L = 2k\Omega$ $V_O = \pm 10V$	100	160	—	100	160	—	100	160	—	
Output Voltage Swing	V_O	$R_L = 2k\Omega$	± 11.0	$+12.3$ -11.8	—	± 11.0	$+12.3$ -11.8	—	± 11.0	$+12.3$ -11.8	—	V
Short-Circuit Current Limit	I_{SC}	Output Shorted to Ground	± 8	—	± 60	± 8	—	± 60	± 8	—	± 60	mA
Supply Current	I_{SY}	No Load $V_O = 0V$	—	5.1	6.0	—	5.1	6.5	—	5.1	6.5	mA
Slew Rate	SR	$R_L = 2k\Omega$	45	57	—	40	50	—	40	50	—	V/ μs
Capacitive Load Drive Capability	C_L	Unity-Gain Stable (Note 3)	100	250	—	100	250	—	100	250	—	pF

NOTES:

1. $T_j = 85^\circ C$ for E/F/G Grades; $T_j = 125^\circ C$ for A grade.

2. Guaranteed by CMR test.
3. Guaranteed but not tested.

ELECTRICAL CHARACTERISTICS at $V_S = \pm 15V$, $-55^\circ C \leq T_A \leq 125^\circ C$ for A grade, unless otherwise noted.


PARAMETER	SYMBOL	CONDITIONS	OP-42A			UNITS
			MIN	TYP	MAX	
Offset Voltage	V_{OS}		–	0.5	2.0	mV
Offset Voltage Temperature Coefficient	TCV_{OS}		–	4	10	$\mu V/^\circ C$
Input Bias Current	I_B	(Note 1)	–	6	20	nA
Input Offset Current	I_{OS}	(Note 1)	–	0.2	1.0	nA
Input Voltage Range	IVR	(Note 2)	± 11	+12.5 –12.0	–	V
Common-Mode Rejection	CMR	$V_{CM} = \pm 11V$	80	94	–	dB
Power-Supply Rejection Ratio	PSRR	$V_S = \pm 10V$ to $\pm 20V$	–	10	50	$\mu V/V$
Large-Signal Voltage Gain	A_{VO}	$R_L = 10k\Omega$ (Note 1)	160	350	–	V/mV
		$R_L = 2k\Omega$ $V_O = \pm 10V$	80	110	–	
Output Voltage Swing	V_O	$R_L = 2k\Omega$	± 11.0	+12.3 –11.8	–	V
Short-Circuit Current Limit	I_{sc}	Output Shorted to Ground	± 8	–	± 60	mA
Supply Current	I_{SY}	No Load $V_O = 0V$	–	5.1	6.0	mA
Slew Rate	SR	$R_L = 2k\Omega$	40	52	–	V/ μs
Capacitive Load Drive Capability	C_L	Unity-Gain Stable (Note 3)	100	250	–	pF

NOTES:

1. $T_j = 85^\circ C$ for E/F Grades; $T_j = 125^\circ C$ for A grade.
2. Guaranteed by CMR test.
3. Guaranteed but not tested.

OP-42

DICE CHARACTERISTICS



DIE SIZE 0.098 × 0.070 inch, 6860 sq. mils
(2.49 × 1.78 mm, 4.43 sq. mm)

1. OFFSET VOLTAGE NULL
2. INVERTING INPUT
3. NONINVERTING INPUT
4. NEGATIVE SUPPLY
5. OFFSET VOLTAGE NULL
6. AMPLIFIER OUTPUT
7. POSITIVE SUPPLY

WAFER TEST LIMITS at $V_S = \pm 15V$, $T_J = 25^\circ C$, unless otherwise noted.


PARAMETER	SYMBOL	CONDITIONS	OP-42N LIMIT	UNITS
Offset Voltage	V_{OS}		1.5	mV MAX
Input Bias Current	I_B	$V_{CM} = 0V$	250	pA MAX
Input Offset Current	I_{OS}	$V_{CM} = 0V$	50	pA MAX
Input Voltage Range	IVR	(Note 1)	± 11	V MIN
Common-Mode Rejection	CMR	$V_{CM} = \pm 11V$	80	dB MIN
Power-Supply Rejection Ratio	PSRR	$V_S = \pm 10V$ to $\pm 20V$	50	$\mu V/V$ MAX
Large-Signal Voltage Gain	A_{VO}	$R_L = 10k\Omega$	500	V/mV MIN
		$R_L = 2k\Omega$	200	
		$R_L = 1k\Omega$	100	
Output Voltage Swing	V_O	$R_L = 1k\Omega$	± 11.5	V MIN
Short-Circuit Current Limit	I_{SC}	Output Shorted to Ground	$\pm 20/\pm 60$	mA MIN/MAX
Supply Current	I_{SY}	No Load $V_O = 0V$	6.5	mA MAX
Slew Rate	SR		40	V/ μs MIN
Capacitive Load Drive Capability	C_L	Unity-Gain Stable (Note 2)	100	pF MIN

NOTES:

1. Guaranteed by CMR test.
2. Guaranteed but not tested.


Electrical tests are performed at wafer probe to the limits shown. Due to variations in assembly methods and normal yield loss, yield after packaging is not guaranteed for standard product dice. Consult factory to negotiate specifications based on dice lot qualification through sample lot assembly and testing.

BURN-IN CIRCUIT




TYPICAL PERFORMANCE CHARACTERISTICS


OPEN-LOOP GAIN, PHASE
vs FREQUENCY




COMMON-MODE
REJECTION vs FREQUENCY




POWER-SUPPLY REJECTION
vs FREQUENCY




SLEW RATE vs
TEMPERATURE




SLEW RATE vs
DIFFERENTIAL
INPUT VOLTAGE




SLEW RATE vs
CAPACITIVE LOAD




SETTLING-TIME
vs STEP SIZE



DISTORTION
vs FREQUENCY




CLOSED-LOOP GAIN
vs FREQUENCY




OP-42

TYPICAL PERFORMANCE CHARACTERISTICS


**CLOSED-LOOP
OUTPUT IMPEDANCE
vs FREQUENCY**




**MAXIMUM OUTPUT SWING
vs FREQUENCY**




**SMALL-SIGNAL
OVERSHOOT vs
LOAD CAPACITANCE**




**OUTPUT SWING vs
LOAD RESISTANCE**




**SUPPLY CURRENT
vs TEMPERATURE**




**SUPPLY CURRENT vs
SUPPLY VOLTAGE**




**TYPICAL DISTRIBUTION OF
INPUT OFFSET VOLTAGE**



**TYPICAL DISTRIBUTION
OF TCV_{OS}**




**OFFSET VOLTAGE
WARM-UP DRIFT**




TYPICAL PERFORMANCE CHARACTERISTICS


**BIAS CURRENT vs
JUNCTION TEMPERATURE**




**BIAS CURRENT vs
COMMON-MODE VOLTAGE**




**BIAS CURRENT
WARM-UP DRIFT**




**OFFSET CURRENT vs
JUNCTION TEMPERATURE**




**OPEN-LOOP GAIN vs
JUNCTION TEMPERATURE**



**SHORT CIRCUIT
OUTPUT CURRENT vs
JUNCTION TEMPERATURE**



**VOLTAGE NOISE DENSITY
vs FREQUENCY**



OP-42

APPLICATIONS INFORMATION

The OP-42 combines speed with a high level of input precision usually found only with slower devices. Well-behaved AC performance in the form of clean transient response, symmetrical slew-rates and a high degree of forgiveness to supply decoupling are the hallmarks of this amplifier. AC gain and phase response are quite independent of temperature or supply voltage. Figure 1 shows the OP-42's small-signal response. Even with 75pF loads, there is minimal ringing in the output waveform. Large-signal response is shown in Figure 2. This figure clearly shows the OP-42's exceptionally close matching between positive and negative slew-rates. Slew-rate symmetry decreases the DC offset a system encounters when processing high-frequency signals, and thus reduces the DC current necessary for load driving.

FIGURE 1: Small-Signal Transient Response,
 $Z_L = 2k\Omega || 75pF$





FIGURE 2: Large-Signal Transient Response,
 $Z_L = 2k\Omega || 75pF$



As with most JFET-input amplifiers, the output of the OP-42 may undergo phase inversion if either input exceeds the specified input voltage range. Phase inversion will not damage the amplifier, nor will it cause an internal latch-up.

Supply decoupling should be used to overcome inductance and resistance associated with supply lines to the amplifier.


For most applications a 0.1 μ F to 0.01 μ F capacitor should be placed between each supply pin and ground.

The OP-42 displays excellent resistance to radiation. Radiation hardness data is available by contacting the factory.

OFFSET VOLTAGE ADJUSTMENT

Offset voltage is adjusted with a 10k Ω to 100k Ω potentiometer as shown in Figure 3. The potentiometer should be connected between pins 1 and 5 with its wiper connected to the V₋ supply. Nulling V_{OS} in this manner changes TCV_{OS} by no more than 5 μ V/ $^{\circ}$ C per millivolt of V_{OS} change. Alternately, V_{OS} may be nulled by attaching the potentiometer wiper through a 1M Ω resistor to the positive supply rail.

FIGURE 3: Input Offset Voltage Nulling



SETTLING-TIME

Guaranteed fast-settling is assured by sample-testing during production. The OP-42 is configured as a unity-gain follower in the test circuit of Figure 4. This test method has advantages over false-sum-node techniques in that the actual output of the amplifier is measured, instead of an error-voltage at the sum node. Common-mode settling effects are exercised in this circuit, in addition to the slew-rate and bandwidth effects measured by the false-sum-node method. A reasonably flat-top pulse is required as a stimulus.

The output waveform of the OP-42 being tested is clamped by Schottky diodes and buffered by the JFET source-follower. The signal is amplified by a factor of ten by the fast amplifier IC1, then Schottky-clamped before being output. The OP-41 provides overall offset nulling. Analysis of the waveform using a digitizing oscilloscope determines the op amp's settling-time.

The circuit diagram illustrates a precision rectifier with a differential amplifier output stage. The input stage consists of a differential amplifier (DUT) with two inputs, V+ and V-, each biased with a 16-20V source and a 0.1μF capacitor. The output of the DUT is connected to a load resistor R_L (1kΩ) and a diode D1. The output of the DUT is also connected to the base of a 2N4416 transistor, which is biased with a +15V source. The collector of the 2N4416 transistor is connected to the non-inverting input of a differential amplifier (IC1). The inverting input of IC1 is connected to a feedback network consisting of a 10kΩ resistor (R_F) and a 2kΩ resistor (R_G), which is also connected to the output of IC1. The output of IC1 is connected to the non-inverting input of a second differential amplifier (IC2). The inverting input of IC2 is connected to a feedback network consisting of a 10kΩ resistor (R_F) and a 2kΩ resistor (R_G), which is also connected to the output of IC2. The output of IC2 is connected to the base of a 2N2222A transistor, which is biased with a -15V source. The collector of the 2N2222A transistor is connected to the output of the circuit, which is also connected to a 750Ω resistor. The output of the circuit is connected to a load resistor R_L (1kΩ) and a diode D2. The output of the circuit is also connected to a diode D3 and a diode D4, which are connected to a 1kΩ resistor and a 1μF capacitor, respectively. The output of the circuit is connected to a scope.

SCHOTTKY DIODES D1-D4
ARE HEWLETT-PACKARD HP5082-2835
IC1 IS COMLINEAR CLC200A1
IC2 IS PMI OP41EJ

The figure consists of two vertically stacked plots showing the positive and negative edges of a signal. Both plots have a horizontal axis representing time in microseconds (μs), ranging from 0 to 2.5 with major ticks every 0.5 μs and minor ticks every 0.1 μs . The vertical axis represents signal amplitude, with a central horizontal dashed line indicating the zero level. Two additional horizontal dashed lines above and below the center define the 0.01% error band.

The top plot is titled "POSITIVE EDGE". It shows a signal that transitions from a low level to a high level. The signal starts at a low level, rises sharply, and then settles to a high level. A vertical dashed line marks the time $t_s = 730\text{ns}$, which is the time taken for the signal to settle within the 0.01% error band. The signal exhibits some oscillations as it settles.

The bottom plot is titled "NEGATIVE EDGE". It shows a signal that transitions from a high level to a low level. The signal starts at a high level, falls sharply, and then settles to a low level. A vertical dashed line marks the time $t_s = 740\text{ns}$, which is the time taken for the signal to settle within the 0.01% error band. The signal also exhibits some oscillations as it settles.

The OP-42 is an excellent choice for a DAC output amplifier, since its high speed and fast settling-time allow quick transitions between codes, even for full-scale changes in output level. The DAC output capacitance appears at the operational amplifier inputs, and must be compensated to ensure

The diagram shows a PM-7548 DAC connected to an OP-42 op-amp configured as a voltage follower. The DAC's output I_O is connected to the op-amp's non-inverting input (+). The op-amp's inverting input (-) is connected to ground through a capacitor C_{IN} . A feedback network consisting of a resistor R_F and a capacitor C (labeled 20pF) is connected between the op-amp's output and its inverting input. The output of the op-amp is also connected to the output of the DAC.

NOTE: R_F IS INTERNAL TO MOST CMOS DACs


CMOS digital-to-analog converters have higher output capacitances and lower output resistances than bipolar DACs.

OP-42

This results in slower settling-times, higher sensitivity to offset voltages and a reduction in the output amplifier's bandwidth. These trade-offs must be balanced against the CMOS DAC's advantages in terms of interfacing capability, power dissipation, accuracy levels and cost. Using the internal feedback resistor which is present on most CMOS converters, the gain applied to offset voltage varies between 4/3 and 2, depending upon output code. Contributions to linearity error will be as much as $2/3V_{OS}$. In a 10-volt 12-bit system, this may add up to an additional 1/5LSB DNL with the OP-42E. Amplifier bandwidth is reduced by the same gain factor applied to offset voltage, however the OP-42's 10MHz gain-bandwidth product results in no reduction of the CMOS converter's multiplying bandwidth.

Individual DAC data-sheets should be consulted for more complete descriptions of the converters and their circuit applications.

FIGURE 7: DAC Output Amplifier Response (PM-7545 DAC)



DRIVING A HIGH-SPEED ADC

The OP-42's open-loop output resistance is approximately 50Ω . When feedback is applied around the amplifier, output resistance decreases in proportion to open-loop gain divided by closed-loop gain (A_{VOL}/A_{VCL}). Output impedance increases as open-loop gain rolls-off with frequency. High-speed analog-to-digital converters require low source impedances at high frequency. Output impedance at 1MHz is typically 5Ω for an OP-42 operating at unity-gain. If lower output impedances are required, an output buffer may be placed at the output of the OP-42.

HIGH-CURRENT OUTPUT BUFFER

The circuit in Figure 8 shows a high-current output stage for the OP-42. Output current is limited by R1 and R2. For good tracking between the output transistors Q1, Q2 and their biasing diodes D1 and D2, thermal contact must be maintained between the transistor and its associated diode. If good thermal contact is not maintained, R1 and R2 must be increased to $5\text{--}6\Omega$ in order to prevent thermal runaway. Using 5Ω resistors, the circuit easily drives a 75Ω load (Figure 9). Output resistance is decreased and heavier loads may be driven by decreasing R1 and R2.

Base current and biasing for Q1 and Q2 are provided by two current sources, the MAT-02 and the JFET. The $2k\Omega$ potentiometer in the JFET current source should be trimmed for optimum transient performance. The case of the MAT-02 should be connected to V^- , and decoupled to ground with a

$0.1\mu\text{F}$ capacitor. Compensation for the OP-42's input capacitance is provided by C_C . The circuit may be operated at any gain, in the usual op amp configurations.

FIGURE 8: High-Current Output Buffer





FIGURE 9: Output Buffer Large-Signal Response



DRIVING CAPACITIVE LOADS

Best performance will always be achieved by minimizing input and load capacitances around any high-speed amplifier. However, the OP-42 is guaranteed capable of driving a 100pF capacitive load over its full operating temperature range while operating at any gain including unity. Typically, an OP-42 will drive more than 250pF at any temperature. Supply decoupling does affect capacitive load driving ability. Extra care should be given to ensure good decoupling when driving capacitive loads, and a larger decoupling capacitor between $1\mu\text{F}$ and $10\mu\text{F}$ should be placed in parallel with the usual decoupling capacitor on each supply.

Large capacitive loads may be driven utilizing the circuit shown in Figure 10. R1 and C1 introduce a small amount of feedforward compensation around the amplifier to counteract the phase lag induced by the output impedance and load capacitance. At DC and low frequencies, R1 is contained within the feedback loop. At higher frequencies, feedforward compensation becomes increasingly dominant, and R1's effect on output impedance will become more noticeable.


When driving very large capacitances, slew-rate will be limited by the short-circuit current limit. Although the unloaded slew-rate is insensitive to variations in temperature, the output current limit has a negative temperature coefficient, and is asymmetrical with regards to sourcing and sinking current. Therefore, slew-rate into excessive capacities will decrease with increasing temperature, and will lose symmetry.

COMPUTER SIMULATIONS

Many electronic design and analysis programs include models for op amps which calculate AC performance from the location of poles and zeros. As an aid to designers utilizing such a program, major poles and zeros of the OP-42 are listed below. Their location will vary slightly between production lots. Typically, they will be within $\pm 15\%$ of the frequency listed. Use of this data will enable the designer to evaluate gross circuit performance quickly, but should not supplant rigorous characterization of a breadboarded circuit.

POLES	ZEROS
20Hz	1MHz
300kHz	
3MHz	

FIGURE 10: Compensation for Large Capacitive Loads




AUTOZEROING OFFSET VOLTAGE

Figure 11 describes a circuit for automatic offset voltage and drift correction. The OP-41 is used in a servo loop to force the OP-42 output equal to the OP-41's offset voltage. Thus, the OP-42's effective input offset is held below $10\mu\text{V}$ ($1\text{mV}/A_{VCL} = 100$) despite any temperature variations. This circuit will be most advantageous in high-gain applications.

Feedback is accomplished using the OP-42's null pins, leaving both inputs free for other purposes. In the application

FIGURE 11: OP-41 Servo Amplifier Provides Offset Correction



OP-42

shown, the OP-42 has seven multiplexed inputs, while the eighth input provides a ground reference. Nulling is accomplished by addressing the grounded channel. This address should be held for at least $200\mu\text{s}$. After this time, the address may be changed to another channel. The MUX-08 ENABLE pin must be high during the entire nulling cycle. During this time, JFET switch J1 turns on, completing feedback around

the OP-41 servo amplifier. A charge is developed across C_H to compensate for the OP-42's offset voltage. When another channel is addressed, J1 turns off, and the correction charge is maintained across C_H by the OP-41. Droop is exceptionally low — only $1.3\mu\text{V/s}$ at 25°C . A correction range of more than 4mV allows nulling of minor system offsets as well as the OP-42's offset voltage.