



PASSIVATED JUNCTION TRANSIENT VOLTAGE SUPPRESSOR

P6KE6.8 THRU P6KE440CA(GPP)
P6KE6.8J THRU P6KE440CAJ(OPEN JUNCTION)


Breakdown Voltage 6.8 to 440 Volts
Peak Pulse Power 600 Watts

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O
- Glass passivated or silastic guard junction (open junction)
- 600W peak pulse power capability with a 10/1000 μ s Waveform, repetition rate (duty cycle): 0.01%
- Excellent clamping capability
- Low incremental surge resistance
- Fast response time: typically less than 1.0ps from 0 Volts to $V_{(BR)}$ for unidirectional and 5.0ns for bidirectional types
- Typical I_b less than 1.0 μ A above 10V
- High temperature soldering guaranteed: 265°C/10 seconds, 0.375" (9.5mm) lead length, 51bs.(2.3kg) tension

MECHANICAL DATA

- Cass: JEDEC DO-204AC, molded plastic body over passivated junction
- Terminals: Axial leads, solderable per MIL-STD-750, Method 2026
- Polarity: Color bands denotes positive end (cathode) except for bidirectional types
- Mounting position: any
- Weight: 0.015 ounces, 0.4 gram



DEVICES FOR BIDIRECTIONAL APPLICATIONS

- For bidirectional use C or CA Suffix for types P6KE6.8 thru P6K440 (e.g. P6KE6.8C, P6KE440CA). Electrical Characteristics apply in both directions.
- Suffix A denotes $\pm 5\%$ tolerance device, No suffix A denotes $\pm 10\%$ tolerance device

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified

Ratings	Symbols	Value	Unit
Peak Pulse power dissipation with a 10/1000 μ s waveform(NOTE1,FIG.1)	P _{PPM}	Minimum 400	Watts
Peak Pulse current with a 10/1000 μ s waveform (NOTE1,FIG.3)	I _{PPM}	See Table 1	Watt
Steady Stage Power Dissipation at T _L =75°C Lead lengths 0.375"(9.5)(Note2)	P _{M(AV)}	5.0	Amps
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method) (Note3)	I _{FSM}	100.0	Amps
Maximum instantaneous forward voltage at 50.0A for unidirectional only (NOTE 4)	V _F	3.5/5.0	Volts
Operating Junction and Storage Temperature Range	T _J , T _{STG}	50 to +150	°C

Notes:

- Non-repetitive current pulse, per Fig.3 and derated above T_A=25°C per Fig.2
- Mounted on copper pad area of 1.6 × 1.6"(40 × 40mm) per Fig 5.
- Measured at 8.3ms single half sine-wave or equivalent square wave duty cycle = 4 pulses per minutes maximum.
- V_F=3.0 Volts max. for devices of V_(BR) ≤ 200V, and V_F=5.0V for devices of V_(BR) ≥ 200v



PASSIVATED JUNCTION TRANSIENT VOLTAGE SUPPRESSOR

P6KE6.8 THRU P6KE440CA(GPP)

Breakdown Voltage 6.8 to 440 Volts

P6KE6.8J THRU P6KE440CAJ(OPEN JUNCTION)

Peak Pulse Power 600 Watts

Electrical Characteristic at (T_A = 25°C unless otherwise noted)

Device Type	Breakdown Voltage at Test Current I _r			Stand-off Voltage	Maximum Reverse Leakage at V _{WM}	Maximum Peak Pulse Current	Maximum Clamping Voltage at I _{PPM}	Maximum Temperature Coefficient of V _{BR}
	MIN	MAX						
	V _{BR} (V)		I _r (mA)					
	Note 1							
P6KE6.8/J	6.12	7.48	10	5.5	1000	55.6	10.8	0.067
P6KE6.8A/J	6.45	7.14	10	5.8	1000	57.1	10.5	0.057
P6KE7.5/J	6.75	8.25	10	6.05	500	51.3	11.7	0.061
P6KE7.5A/J	7.13	7.88	10	6.4	500	53.1	11.3	0.061
P6KE8.2/J	7.38	9.02	10	6.63	200	48.0	12.5	0.065
P6KE8.2A/J	7.79	8.61	10	7.02	200	49.6	12.1	0.065
P6KE9.1/J	8.19	10	1	7.37	50	43.6	13.8	0.068
P6KE9.1A/J	8.65	9.55	1	7.78	50	44.8	13.4	0.068
P6KE10/J	9	11	1	8.1	10	40.0	15	0.073
P6KE10A/J	9.5	10.5	1	8.55	10	41.4	14.5	0.073
P6KE11/J	9.9	12.1	1	8.92	5	37	16.2	0.075
P6KE11A/J	10.5	11.6	1	9.4	5	38.5	15.6	0.075
P6KE12/J	10.8	13.2	1	9.72	5	34.7	17.3	0.078
P6KE12A/J	11.4	12.6	1	10.2	5	35.9	16.7	0.078
P6KE13/J	11.7	14.3	1	10.5	5	31.6	19	0.061
P6KE13A/J	12.4	13.7	1	11.1	5	33.0	18.2	0.081
P6KE15/J	13.5	16.5	1	12.1	5	27.3	22	0.084
P6KE15A/J	14.3	15.8	1	12.8	5	28.3	21.2	0.084
P6KE16/J	14.4	17.6	1	12.9	5	25.5	23.5	0.086
P6KE16A/J	15.2	16.8	1	13.6	5	26.7	22.5	0.086
P6KE18/J	16.2	19.8	1	14.5	5	22.6	26.5	0.088
P6KE18A/J	17.1	18.9	1	15.3	5	23.8	25.2	0.088
P6KE20/J	18	22	1	16.2	5	20.6	29.1	0.09
P6KE20A/J	19	21	1	17.1	5	21.7	27.7	0.09
P6KE22/J	19.8	24.2	1	17.8	5	18.8	31.9	0.092
P6KE22A/J	20.9	23.1	1	18.8	5	19.6	30.6	0.092
P6KE24/J	21.6	26.4	1	19.4	5	17.6	34.7	0.094
P6KE24A/J	22.8	25.2	1	20.5	5	18.1	33.2	0.094
P6KE27/J	24.3	29.37	1	21.8	5	15.3	39.1	0.096
P6KE27A/J	25.7	28.4	1	23.1	5	16.0	37.5	0.096
P6KE30/J	27	33	1	24.3	5	13.8	43.5	0.097
P6KE30A/J	28.5	31.5	1	25.6	5	14.5	41.4	0.097
P6KE33/J	29.7	36.3	1	26.8	5	12.6	47.7	0.098
P6KE33A/J	31.4	34.7	1	28.2	5	13.1	45.7	0.098
P6KE36/J	32.4	39.6	1	29.1	5	11.5	52	0.099
P6KE36A/J	34.2	37.8	1	30.8	5	12.0	49.9	0.099
P6KE39/J	35.1	42.9	1	31.6	5	10.6	56.4	0.1
P6KE39A/J	37.1	41	1	33.3	5	11.1	53.9	0.1
P6KE43/J	38.7	47.3	1	34.8	5	9.7	61.9	0.101
P6KE43A/J	40.9	45.2	1	36.8	5	10.1	59.3	0.101
P6KE47/J	42.3	51.7	1	38.1	5	8.8	67.8	0.101
P6KE47A/J	44.7	49.4	1	40.2	5	9.3	64.8	0.101
P6KE51/J	45.9	56.1	1	41.3	5	8.2	73.5	0.102
P6KE51A/J	48.5	53.6	1	43.6	5	8.6	70.1	0.102
P6KE56/J	50.4	61.6	1	45.4	5	7.5	80.5	0.103
P6KE56A/J	53.2	58.8	1	47.8	5	7.8	77	0.103
P6KE62/J	55.8	68.2	1	50.2	5	6.7	89	0.104



PASSIVATED JUNCTION TRANSIENT VOLTAGE SUPPRESSOR

P6KE6.8 THRU P6KE440CA(GPP)

Breakdown Voltage 6.8 to 440 Volts

P46KE6.8J THRU P6KE440CAJ(OPEN JUNCTION)

Peak Pulse Power 600 Watts

Electrical Characteristic at (T_A =25°C unless otherwise noted)

Device Type	Breakdown Voltage at Test Current I _r			Stand-off Voltage	Maximum Reverse Leakage at V _{WM}	Maximum Peak Pulse Current	Maximum Clamping Voltage at I _{PPM}	Maximum Temperature Coefficient of V _{BR}					
	MIN	MAX											
	V _{BR} (V)		I _r (mA)						V _{WM}	I _D (μ A)	I _{PPM} (A)	V _C (V)	X _{Vz} (%°C)
	Note 1									Note 3	Note 2		
P6KE62A/J	58.9	65.1	1	53	5	7.1	85	0.104					
P6KE68/J	61.2	74.8	1	55.1	5	6..1	98	0.104					
P6KE68A/J	64.6	71.4	1	58.1	5	6.5	92	0.104					
P6KE75/J	67.5	82.5	1	60.7	5	5.6	108	0.105					
P6KE75A/J	71.3	78.8	1	64.1	5	5.8	103	0.105					
P6KE82/J	73.8	90.2	1	66.4	5	5.1	116	0.105					
P6KE82A/J	77.9	86.1	1	70.1	5	5.3	113	0.105					
P6KE91/J	81.9	100	1	73.7	5	4.6	131	0.106					
P6KE91A/J	86.5	85.5	1	77.8	5	4.8	125	0.106					
P6KE100/J	90	110	1	81	5	4.2	144	0.106					
P6KE100A/J	95	105	1	85.5	5	4.4	137	0.106					
P6KE110/J	99	121	1	89.2	5	3.8	158	0.107					
P6KE110A/J	105	116	1	94	5	3.9	152	0.107					
P6KE120/J	108	132	1	97.2	5	3.5	173	0.107					
P6KE120A/J	114	126	1	102	5	3.6	165	0.107					
P6KE130/J	117	143	1	105	5	3.2	187	0.107					
P6KE130A/J	124	137	1	111	5	3.4	179	0.107					
P6KE150/J	135	165	1	121	5	2.8	215	0.108					
P6KE150A/J	143	158	1	128	5	2.9	207	0.108					
P6KE160/J	144	176	1	130	5	2.6	230	0.108					
P6KE160A/J	152	168	1	136	5	2.7	219	0.108					
P6KE170/J	153	187	1	138	5	2.5	244	0.108					
P6KE170A/J	162	179	1	145	5	2.6	234	0.108					
P6KE180/J	162	198	1	146	5	2.3	258	0.108					
P6KE180A/J	171	189	1	154	5	2.4	246	0.108					
P6KE200/J	180	220	1	162	5	2.1	287	0.108					
P6KE200A/J	190	210	1	171	5	2.2	274	0.108					
P6KE220/J	198	242	1	175	5	1.7	344	0.108					
P6KE220A/J	/209	231	1	185	5	1.8	328	0.108					
P6KE250/J	225	275	1	202	5	1.7	360	0.11					
P6KE250A/J	237	263	1	214	5	1.7	344	0..11					
P6KE300/J	270	330	1	243	5	1.4	430	0.11					
P6KE300A/J	285	315	1	256	5	1.4	414	0.11					
P6KE350/J	315	385	1	284	5	1.2	504	0.11					
P6KE350A/J	332	368	1	300	5	1.2	482	0.11					
P6KE400/J	360	440	1	324	5	1.0	571	0.11					
P6KE400A/J	380	420	1	342	5	1.1	548	0.11					
P6KE440/J	396	484	1	356	5	0.95	631	0.11					
P6KE440A/J	418	462	1	376	5	1.0	602	0.11					

Notes:

- (1) V_(BR) measured after I_r applied for 300ms I_r =square wave pulse or equivalent
- (2) Surge current waveform per Figure 3 and derate per Fig.2
- (3) For bidirectional type having V_{WM} of 10 volts and less, the I_D limit is doubled



PASSIVATED JUNCTION TRANSIENT VOLTAGE SUPPRESSOR

P6KE6.8 THRU P6KE440CA(GPP)

Breakdown Voltage 6.8 to 440 Volts

P6KE6.8J THRU P6KE440CAJ(OPEN JUNCTION)

Peak Pulse Power 600 Watts

RATING AND CHARACTERISTIC CURVES P6KE6.8/J THRU P6KE440CA/J

FIG.1- PEAK PULSE POWER RATING CURVE




FIG.2- PULSE DERATING CURVE




FIG.3- PULSE WAVEFORM




FIG.4- STEADY STATE POWER DERATING CURVE




FIG.5- TYPICAL JUNCTION CAPACITANCE UNIDIRECTIONAL




FIG.6- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT UNIDIRECTIONAL

