
PBPC801 - PBPC807

8.0A BRIDGE RECTIFIER

Features

- High Current Capability
- Surge Overload Rating to 125A Peak
- High Case Dielectric Strength of 1500V
- Ideal for Printed Circuit Board Application
- UL Listed Under Recognized Component Index, File Number E94661



PBPC-8		
Dim	**Min**	**Max**
A	18.54	19.56
B	6.35	7.60
C	22.20	—
D	1.27	Typical
E	5.33	7.37
G	3.60	4.00
H	12.70 Typical	
J	2.38 X 45° Typical	
All Dimensions in mm		

Mechanical Data

- Case: PBPC-8
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: Marked on Body
- Mounting: Through Hole for #6 Screw
- Mounting Torque: 5.0 Inch-pounds Maximum
- Ordering Information: See Last Page
- Marking: Type Number
- Weight: 5.4 grams (approximate)

Maximum Ratings and Electrical Characteristics

@ T_A = 25°C unless otherwise specified

Single phase, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

Characteristic	Symbol	PBPC 801	PBPC 802	PBPC 803	PBPC 804	PBPC 805	PBPC 806	PBPC 807	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	50	100	200	400	600	800	1000	V
RMS Reverse Voltage	$V_{R(RMS)}$	35	70	140	280	420	560	700	V
Average Rectified Output Current (Note 1) @ T_C = 50°C (Note 2) @ T_C = 50°C	I_O	8.0 6.0							A
Non-Repetitive Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	125							A
Forward Voltage (per element) @ I_F = 4.0A	V_{FM}	1.1							V
Peak Reverse Current @ T_C = 25°C at Rated DC Blocking Voltage (per element) @ T_C = 100°C	I_R	10 1.0							μA mA
I^2t Rating for Fusing (t<8.3ms) (Note 3)	I^2t	64							A^2s
Typical Total Capacitance (Note 4)	C_T	100							pF
Typical Thermal Resistance Junction to Case (per element)	R_{JC}	9.4							°C/W
Operating and Storage Temperature Range	T_j, T_{STG}	-65 to +125							°C

Notes:
1. Mounted on metal chassis.
2. Mounted on PC board FR-4 material.
3. Non-repetitive, for t > 1.0ms and < 8.3ms.
4. Per element, measured at 1.0 MHz and applied reverse voltage of 4.0V DC.




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics, per element




Fig. 3 Typical Reverse Characteristics




Fig. 4 Typical Reverse Characteristics, per element

Ordering Information (Note 5)

Device	Packaging	Shipping
PBPC801	PBPC-8	150/Box
PBPC802	PBPC-8	150/Box
PBPC803	PBPC-8	150/Box
PBPC804	PBPC-8	150/Box
PBPC805	PBPC-8	150/Box
PBPC806	PBPC-8	150/Box
PBPC807	PBPC-8	150/Box

Notes: 5. For packaging details, visit our website at http://www.diodes.com/datasheets/ap02008.pdf.

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.