
DATA SHEET



PBSS5350S

50 V low V_{CEsat} PNP transistor

Product data sheet
Supersedes data of 2001 Nov 19

2004 Aug 20

NXP founded by Philips

50 V low V_{CEsat} PNP transistor PBSS5350S

FEATURES

- High power dissipation (830 mW)
- Ultra low collector-emitter saturation voltage
- 3 A continuous current
- High current switching
- Improved device reliability due to reduced heat generation.

APPLICATIONS

- Medium power switching and muting
- Linear regulators
- DC/DC convertor
- Supply line switching circuits
- Battery management applications
- Strobe flash units
- Heavy duty battery powered equipment (motor and lamp drivers).

DESCRIPTION

PNP low V_{CEsat} transistor in a SOT54 plastic package.
NPN complement: PBSS4350S.

MARKING

TYPE NUMBER	MARKING CODE
PBSS5350S	S5350S

QUICK REFERENCE DATA

SYMBOL	PARAMETER	MAX.	UNIT
V_{CEO}	collector-emitter voltage	–50	V
I_C	collector current (DC)	–3	A
I_{CM}	peak collector current	–5	A
R_{CEsat}	equivalent on-resistance	<150	mΩ

PINNING

PIN	DESCRIPTION
1	base
2	collector
3	emitter




Fig.1 Simplified outline (SOT54) and symbol.

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 60134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{CBO}	collector-base voltage	open emitter	–	–60	V
V_{CEO}	collector-emitter voltage	open base	–	–50	V
V_{EBO}	emitter-base voltage	open collector	–	–6	V
I_C	collector current (DC)		–	–3	A
I_{CM}	peak collector current		–	–5	A
I_{BM}	peak base current		–	–1	A
P_{tot}	total power dissipation	$T_{amb} \leq 25$ °C; note 1	–	830	mW
T_{stg}	storage temperature		–65	+150	°C
T_j	junction temperature		–	150	°C
T_{amb}	operating ambient temperature		–65	+150	°C

Note

1. Device mounted on a printed-circuit board, single sided copper, tinplated and standard footprint.

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th\ j\text{-}a}$	thermal resistance from junction to ambient	in free air; note 1	150	K/W

Note

1. Device mounted on a printed-circuit board, single sided copper, tinplated and standard footprint.


CHARACTERISTICS

T_{amb} = 25 °C unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
I_{CBO}	collector-base cut-off current	V_{CB} = –50 V; I_E = 0	–	–	–100	nA
		V_{CB} = –50 V; I_E = 0; T_j = 150 °C	–	–	–50	μA
I_{EBO}	emitter-base cut-off current	V_{EB} = –5 V; I_C = 0	–	–	–100	nA
h_{FE}	DC current gain	V_{CE} = –2 V; I_C = –500 mA	200	–	–	
		V_{CE} = –2 V; I_C = –1 A; note 1	200	–	–	
		V_{CE} = –2 V; I_C = –2 A; note 1	100	–	–	
V_{CEsat}	collector-emitter saturation voltage	I_C = –500 mA; I_B = –50 mA	–	–	–100	mV
		I_C = –1 A; I_B = –50 mA	–	–	–180	mV
		I_C = –2 A; I_B = –200 mA; note 1	–	–	–300	mV
R_{CEsat}	equivalent on-resistance	I_C = –2 A; I_B = –200 mA; note 1	–	120	<150	mΩ
V_{BEsat}	base-emitter saturation voltage	I_C = –2 A; I_B = –200 mA; note 1	–	–	–1.2	V
V_{BE}	base-emitter turn-on voltage	V_{CE} = –2 V; I_C = –1 A; note 1	–	–	–1.1	V
f_T	transition frequency	I_C = –100 mA; V_{CE} = –5 V; f = 100 MHz	100	–	–	MHz
C_c	collector capacitance	V_{CB} = –10 V; I_E = I_e = 0; f = 1 MHz	–	–	40	pF


Note

1. Pulse test: $t_p \leq 300$ μs; $\delta \leq 0.02$.




V_{CE} = −2 V.
(1) T_{amb} = 150 °C.
(2) T_{amb} = 25 °C.
(3) T_{amb} = −55 °C.

Fig.2 DC current gain as a function of collector current; typical values.




V_{CE} = −2 V.
(1) T_{amb} = −55 °C.
(2) T_{amb} = 25 °C.
(3) T_{amb} = 150 °C.

Fig.3 Base-emitter voltage as a function of collector current; typical values.




I_C/I_B = 20.
(1) T_{amb} = 150 °C.
(2) T_{amb} = 25 °C.
(3) T_{amb} = −55 °C.

Fig.4 Collector-emitter saturation voltage as a function of collector current; typical values.



I_C/I_B = 20.
(1) T_{amb} = −55 °C.
(2) T_{amb} = 25 °C.
(3) T_{amb} = 150 °C.


Fig.5 Base-emitter saturation voltage as a function of collector current; typical values.



T_{amb} = 25 °C.

(1) I_B = −3.96 nA.
(2) I_B = −3.63 nA.
(3) I_B = −3.30 nA.
(4) I_B = −2.97 nA.
(5) I_B = −2.64 nA.
(6) I_B = −2.31 nA.
(7) I_B = −1.98 nA.
(8) I_B = −1.65 nA.
(9) I_B = −1.32 nA.
(10) I_B = −0.99 nA.
(11) I_B = −0.66 nA.
(12) I_B = −0.33 nA.


Fig.6 Collector current as a function of collector-emitter voltage; typical values.



T_{amb} = 25 °C.

(1) I_B = −250 mA.
(2) I_B = −225 mA.
(3) I_B = −200 mA.
(4) I_B = −175 mA.
(5) I_B = −150 mA.
(6) I_B = −125 mA.
(7) I_B = −100 mA.
(8) I_B = −75 mA.
(9) I_B = −50 mA.
(10) I_B = −25 mA.

Fig.7 Collector current as a function of collector-emitter voltage; typical values.




I_C/I_B = 20.

(1) T_{amb} = 150 °C. (2) T_{amb} = 25 °C. (3) T_{amb} = −55 °C.

Fig.8 Collector-emitter equivalent on-resistance as a function of collector current; typical values.

PACKAGE OUTLINE

Plastic single-ended leaded (through hole) package; 3 leads **SOT54**



DIMENSIONS (mm are the original dimensions)

UNIT	A	b	b_1	c	D	d	E	e	e_1	L	L_1 (1) max.
mm	5.2 5.0	0.48 0.40	0.66 0.55	0.45 0.38	4.8 4.4	1.7 1.4	4.2 3.6	2.54	1.27	14.5 12.7	2.5

Note

1. Terminal dimensions within this zone are uncontrolled to allow for flow of plastic and terminal irregularities.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT54		TO-92	SC-43A			~~04-06-28~~ 04-11-16

DATA SHEET STATUS

DOCUMENT STATUS[1]	PRODUCT STATUS[2]	DEFINITION
Objective data sheet	Development	This document contains data from the objective specification for product development.
Preliminary data sheet	Qualification	This document contains data from the preliminary specification.
Product data sheet	Production	This document contains the product specification.

Notes

1. Please consult the most recently issued document before initiating or completing a design.
2. The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nxp.com.

DISCLAIMERS

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nxp.com/profile/terms, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

NXP Semiconductors

Customer notification

This data sheet was changed to reflect the new company name NXP Semiconductors, including new legal definitions and disclaimers. No changes were made to the technical content, except for package outline drawings which were updated to the latest version.

Contact information

For additional information please visit: **http://www.nxp.com**
For sales offices addresses send e-mail to: **salesaddresses@nxp.com**

© NXP B.V. 2009

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands R75/02/pp8 Date of release: 2004 Aug 20 Document order number: 9397 750 13638

founded by

PHILIPS