

PCI/ISA Backplanes


20-slot PCI/ISA Backplanes



Compatible with IPC Chassis : IPC-623, IPC-622, ACP-7000, ACP-5260

PCA-6115QP2X-0A2E

- Segments: 4
- Slots: 8 PCI, 7 PICMG
- Size: 417 x 300 mm (16.42" x 11.81")
- Ordering Information: PCA-6115QP2X-0A2E



PCA-6116QP2-0B2E

- Segments: 4
- Slots: 1 ISA, 8 PCI, 7 PICMG
- Size: 417 x 260 mm (16.42" x 10.24")
- Ordering Information: PCA-6116QP2-0B2E




PCA-6120DP4-0B2E

- Segments: 2
- Slots: 1 ISA, 6 PCI, 2 PICMG/PCI, 4 PICMG
- Size: 420 x 260 mm (16.42" x 10.24")
- Ordering Information: PCA-6120DP4-0B2E



PCA-6119P17-0B2E

- Segments: 1
- Slots: 16 PCI, 1 PICMG/PCI, 1 PICMG
- Size: 417 x 260 mm (16.42" x 10.24")
- PCI bridge: Dual Pericom PI7C8150MA
- Primary PCI: 2 slots; Secondary PCI: 8 slots + 7 slots
- Ordering Information: PCA-6119P17-0B2E



PCA-6120P18-0A2E

- Segments: 1
- Slots: 1 ISA, 17 PCI, 1 PICMG/PCI, 1 PICMG
- Size: 417 x 260 mm (16.42" x 10.24")
- PCI bridge: Three Pericom PI7C8150MA
- Secondary: 6 slot/6 slot/6 slot
- Ordering Information: PCA-6120P18-0A1



PCA-6120P12-0A2E

- Segments: 1
- Slots: 7 ISA, 11 PCI, 1 PICMG/PCI, 1 PICMG
- Size: 417 x 260 mm (16.42" x 10.24")
- PCI bridge: Pericom PI7C8150MA
- Primary PCI: 3 slots; Secondary PCI: 9 slots
- Ordering Information: PCA-6120P12-0A2E



PCA-6119P7-0B3E

- Segments: 1
- Slots: 10 ISA, 7 PCI, 2 PICMG/PCI
- Size: 417 x 260 mm (16.42" x 10.24")
- PCI bridge: Intel 21152
- Primary PCI: 3 slots; Secondary PCI: 4 slots
- Ordering Information: PCA-6119P7-0B3E



PCA-6119P16X-0A2E

- Segments: 1
- Slots: 1 ISA, 16 PCI, 2 PICMG
- Size: 417 x 300 mm (16.4" x 11.8")
- PCI bridge: Three Intel 21154
- Secondary (64-bit/66 MHz): 4 + 3 slots
- Secondary (64-bit/33 MHz): 9 slots
- Jumper selectable 1: V/I/O 3.3 V or 5V
- Jumper selectable 2: PCI bus 33 MHz or PCI bus 66 MHz
- Chassis: IPC-623, IPC-622, ACP-7000, ACP-5260
- Ordering Information: PCA-6119P16X-0A2E

