

Sales Region	USA/China/ASEAN/India
Series	PHV
Model	
Status	 Production
Option	Positive polarity
Option Lineup	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics	
Input	3-phase
Input Voltage Range[AC]	187 to 229VAC
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	3500Vdc
Output Voltage Range[DC]	0 to 3500V
Rated Output Current	3A
Output Current	0 to 3000mA
Rated Output Power	10kW
Polarity	Positive
Power Factor	0.9
Efficiency	90% Typ.
Voltage Ripple Noise	400mV

Package Type & Size	
Package / Mounting	Rack mount
Width(W)	443mm Nom. (17.44in Nom.)
Height(H)	399mm Nom. (15.71in Nom.)
Depth(D)	650mm Nom. (25.59in Nom.)
Weight	75kg Typ. (165.3lbs Typ.)

Other	
Operating Temp. Range	0 to 40°C
Storage Temp. Range	0 to 40°C
Cooling	Forced air
Safety Standard(Certified)	
Safety Standard(Conformed)	EN61010-1 CE Mark
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.