
3 Amp Low Dropout Positive Voltage Regulator

THe PJ1085 Series of high performance positive voltage Regulators are designed for use in applications requiring

low dropout performance at full rated current, Additionally, the PJ1085 Series provides excellent regulation over variations due to changes in line, load and temperature. Outstanding features include low dropout performance at rated current, fast transient response, internal current limiting and thermal shutdown protection of the output device. The PJ1085 Series are three terminal regulators with fixed and adjustable voltage options available in popular packages.



FEATURES


- Low dropout voltage 1.3V max.
- Full current rating over line and temperature
- Fast transient response
- Total output regulation ±2% over line, load and temperature
- Adjust pin current max 120 μ A over temperature
- Line regulation typical 0.015%.
- Load regulation typical 0.05%.
- Fixed/adjustable output voltage
- TO-220 & TO-263 & To-252 package

ORDERING INFORMATION

Device	Operating Temperature (Ambient)	Package
PJ1085CZ PJ1085CZ-2.5 PJ1085CZ-3.3	-20℃ to +85℃	TO-220
PJ1085CM PJ1085CM-2.5 PJ1085CM-3.3		TO-263
PJ1085CP PJ1085CP-2.5 PJ1085CP-3.3		TO-252

NOTE: Contact factory for additional voltage option.

BLOCK DIAGRAM



ABSOLUTE MAXIMUM RATING

Parameter	Symbol	Maximum	Units
Input Voltage	V_{IN}	7	V
Power Dissipation	P_D	Internally Limited	W
Thermal Resistance Junction to Case	θ_{JC}	2.5	℃/W
Thermal Resistance Junction to Ambient	θ_{JA}	50	
Operating Junction Temperature Range	T_J	0 to +125	℃
Operating Ambient Temperature Range	T_A	-20 to +85	
Storage Temperature Range	T_{STG}	-25 to 150	
Lead Temperature (Soldering) 10 Sec.	T_{LEAD}	260	

ELECTRICAL CHARACTERISTICS


Unless otherwise specified, Adjust V_{IN} = 2.75V to 12V and Adjust Io = 10mA to 3.0A
Fixed V_{IN} = 4.75V to 12V and Fixed Io = 10mA to 3.0A

Parameter	Symbol	Test Conditions			Test Limits			Units
		V_{IN} -V_{OUT}	I_O	T_J(4)	Min	Typ	Max	
Output Voltage(1)	Vo	5V	10mA	25	0.99|Vo|	Vo	1.01|Vo|	V
Fixed Voltage				Over Temp.	0.98|Vo|		1.02|Vo|	
Reference Voltage(1)	V_{REF}	5V	10mA	25	1.238	1.250	1.262	
Adj Voltage				Over Temp.	1.225		1.275	
Line Regulation(1)	$REG_{(LINE)}$		10mA	25		0.015	0.2	%
(Vin-Vout=3V)				Over Temp.		0.035		
Load Regulation(1)	$REG_{(LOAD)}$			25		0.05	0.3	
(Vin-Vout=3V)				Over Temp.		0.2	0.4	
Dropout Voltage	V_D			25		1		V
ΔV_{REF} =1%						1.1	1.3	
Current Limit	Ic_L				3.2	4.0		A
(Vin-Vout=5V)				Over Temp.				
Quiescent Current Fixed Model	I_Q	5V				12	14	mA
Temperature Coefficient	Tc					0.005		%/℃
Adjust Pin Current	I_{ADJ}			25		55		μA
				Over Temp.			120	
Adjust Pin Current Change	ΔI_{ADJ}					0.2	5	
Temperature Stability	Ts	5V	500mA	Over Temp.		0.5		%
Minimum Load Current Adjust Model	Io	5V				5	10	mA
RMS Output Noise(2)	V_N			25		0.003		%Vo
Ripple Rejection Ratio(3)	R_A	5V	3.0A	Over Temp.	60	72		dB

(1)Low duty cycle pulse testing with Kelvin connections required.
(2)Bandwidth of 10Hz to 10KHz.
(3)120Hz input ripple (C_{ADJ} for ADJ) =25 μF .
(4)Over Temp.-over specified operating junction temperature range.


Typical Application Circuit

FIXED VOLTAGE REGULATOR (1)(2)



(1) C1 NEEDED IF DEVICE IS FAR FROM FILTER CAPACITORS
(2) C2 REQUIRED FOR STABILITY


ADJUSTABLE VOLTAGE REGULATOR (1)(2)




$V_{out} = V_{ref} (1 + R_2/R_1) + I_{adj}R_2$

(1) C1 NEEDED IF DEVICE IS FAR FROM FILTER CAPACITORS
(2) C2 REQUIRED FOR STABILITY


Dropout Voltage




Load Regulation




Temperature Stability




Ripple Rejection




Ripple Rejection vs. Current




Short-Circuit Current




Load Transient Response



Line Transient Response




Maximum Power Dissipation*




*AS LIMITED BY MAXIMUM JUNCTION TEMPERATURE

Minimum Operating Current
(Adjustable only)




Adjust Pin Current
(Adjustable only)



TO-220 Mechanical drawing


TO-220 Unit:mm



TO-220 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	10.00	10.50	0.394	0.413
B	3.24	4.44	0.128	0.175
C	2.44	2.94	0.096	0.116
D	3.565	4.315	0.140	0.170
E	0.68	0.92	0.027	0.036
F	1.115	1.485	0.044	0.058
G	2.345	2.715	0.092	0.107
H	13.49	14.31	0.531	0.563
I	4.475	5.225	0.176	0.206
J	1.15	1.39	0.045	0.055
K	27.78	29.62	1.094	1.166
L	2.175	2.925	0.086	0.115
M	0.297	0.477	0.012	0.019
N	8.28	8.80	0.326	0.346
O	14.29	15.31	0.563	0.603
P	6.01	6.51	0.237	0.256


TO-263 Mechanical drawing

TO-263 Unit:mm



TO-263 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	10.00	10.50	0.394	0.413
B	14.60	15.87	0.575	0.625
C	0.68	0.92	0.027	0.036
D	2.42	2.66	0.095	0.105
E	4.31	4.83	0.170	0.190
F	1.14	1.40	0.045	0.055
G	2.28	2.79	0.090	0.110
H	0.45	0.73	0.018	0.029
I	8.28	8.80	0.326	0.346
J	1.14	1.4	0.045	0.055

TO-252 Mechanical drawing



TO-252 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	6.57	6.84	0.259	0.269
B	9.25	10.40	0.364	0.409
C	0.62	0.76	0.024	0.030
D	2.56	2.67	0.101	0.105
E	2.30	2.39	0.090	0.094
F	0.49	0.57	0.019	0.022
G	1.46	1.58	0.057	0.062
H	0.52	0.57	0.020	0.022
I	5.34	5.55	0.210	0.219
J	1.46	1.64	0.057	0.065