P-tec Corp.
2405 Commerce Circle
Alamosa Co. 81101
www.p-tec.net

Tel:(800)688-0613
Tel:(719) 589 3122
Fax:(719) 589 3592
sales@p-tec.net

PL008 Series SMD LED PLCC-2 Package Green

Features

*PLCC-2 Package 3.2 x 2.7 x 1.9 mm
*High Luminous Output
*Very Wide Viewing Angle
*For use as Optical Indicator, Backlighting
*For Optical Coupling into Light Pipes/Lenses
*12mm Tape, 2000pc Reels
*RoHS Compliant


Absolute Maximum Ratings at T_A = 25°C

Power Dissipation	78mW
Reverse Voltage (<100µA)	5.0V
Max Forward Current	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100mA
Operating Temperature Range	-25°C to + 85°C
Storage Temperature Range	-40°C to + 100°C
Reflow Soldering Temperature	260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
Water Clear Lens			nm	nm	Deg	Typ	Max	Min	Typ
PL008-WCG13	Green	GaP	567	572	120°	2.1	2.6	9.0	15.0

Package Dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.



Recommended solder pad

