Plug-In

Low Pass Filter

PLP-10.7-75+

75Ω DC to 11 MHz



CASE STYLE: A01

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input	0.5W max.

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

INPUT	1
OUTPUT	8
GROUND	2,3,4,5,6,7
CASE GROUND	2,3,4,5,6,7

Features

- rugged welded case, hermetic
- other standard and custom PLP models available with wide selection of fco

Applications

- test equipment
- lab use
- transmitters/receivers
- military/hi-rel applications

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Outline Drawing



Outline Dimensions (inch / mm)

A	B	C	D	E	F
.770	.800	.385	.400	.370	.400
19.56	20.32	9.78	10.16	9.40	10.16
G	**H**	**J**	**K**		**wt**
.200	.20	.14	.031		grams
5.08	5.08	3.56	0.79		5.2

Low Pass Filter Electrical Specifications

PASSBAND (MHz)	fco (MHz) Nom.	STOPBAND (MHz)		VSWR (:1)	
				Passband	Stopband
(loss < 1 dB)	(loss 3 dB)	(loss > 20 dB)	(loss > 40 dB)	Typ.	Typ.
DC-11	14	19-24	24-200	1.7	18

typical frequency response



Electrical Schematic



Typical Performance Data

Frequency (MHz)	Insertion Loss (dB) x̄	Insertion Loss (dB) σ	Return Loss (dB)	Frequency (MHz)	Group Delay (nsec)
1.00	0.11	0.00	21.77	1.00	68.81
2.60	0.23	0.01	16.16	1.12	67.57
4.30	0.24	0.01	17.81	1.24	68.38
5.90	0.22	0.01	31.76	1.38	67.69
7.50	0.30	0.01	23.25	1.54	67.33
9.10	0.37	0.01	23.48	1.71	68.36
11.00	0.52	0.02	31.19	1.90	68.28
12.40	1.45	0.12	10.50	2.11	66.85
14.00	8.90	0.31	1.41	2.35	66.16
15.60	19.20	0.26	0.40	2.61	67.72
16.30	23.22	0.24	0.31	2.90	68.04
17.00	26.93	0.23	0.26	3.22	68.32
17.60	29.90	0.23	0.23	3.58	69.11
18.30	33.15	0.21	0.20	3.98	68.90
19.00	36.20	0.22	0.18	4.42	70.18
19.70	39.07	0.23	0.17	4.91	71.73
20.60	42.53	0.28	0.15	5.46	73.45
21.40	45.54	0.27	0.14	6.07	74.72
22.30	48.58	0.35	0.13	6.75	76.69
23.10	51.17	0.36	0.12	7.50	78.91
24.00	53.98	0.26	0.12	8.33	82.64
24.90	56.67	0.48	0.11	9.26	88.48
46.80	76.14	1.09	0.05	10.29	99.26
68.70	74.18	1.65	0.04	11.00	111.04
90.60	73.55	1.76	0.04	12.82	151.87
112.50	73.13	1.14	0.04	14.00	113.88
134.30	74.86	0.92	0.04	15.97	48.35
156.20	73.72	1.40	0.05	17.75	28.43
178.10	75.53	2.93	0.05	19.00	21.51
200.00	75.97	4.06	0.05	22.00	11.34

INSERTION LOSS



RETURN LOSS



GROUP DELAY



Notes

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp