

PM-7500 Module Series

Gigabit and Fast Ethernet modules for the PT-7528-24TX Series rackmount Ethernet switches



Features and Benefits

- -40 to 85°C wide operating temperature
- IEC 61850-3 and IEEE 1613 compliant

Certifications



Introduction

The PM-7500 Module Series includes Gigabit and Fast Ethernet modules for the PT-7528-24TX Series rackmount Ethernet switches.

Specifications

Ethernet Interface

100BaseFX Ports (multi-mode SC connector)	PM-7500-2MSC: 2 PM-7500-4MSC: 4
100BaseFX Ports (multi-mode ST connector)	PM-7500-2MST: 2 PM-7500-4MST: 4
100BaseFX Ports (single-mode SC connector)	PM-7500-2SSC: 2 PM-7500-4SSC: 4
Combo Ports (10/100/1000BaseT(X) or 100/1000BaseSFP+)	PM-7500-2GTXSFP: 2 PM-7500-4GTXSFP: 4

Optical Fiber

		100BaseFX		
		Multi-Mode		Single-Mode
Fiber Cable Type		OM1	50/125 μm	G.652
			800 MHz x km	
Typical Distance		4 km	5 km	40 km
Wavelength	Typical (nm)	1300		1310
	TX Range (nm)	1260 to 1360		1280 to 1340
	RX Range (nm)	1100 to 1600		1100 to 1600
Optical Power	TX Range (dBm)	-10 to -20		0 to -5
	RX Range (dBm)	-3 to -32		-3 to -34
	Link Budget (dB)	12		29

	100BaseFX		
	Multi-Mode		Single-Mode
	Fiber Cable Type	OM1	G.652
		50/125 μm 800 MHz x km	
	Dispersion Penalty (dB)	3	1
Note: When connecting a single-mode fiber transceiver, we recommend using an attenuator to prevent damage caused by excessive optical power. Note: Compute the “typical distance” of a specific fiber transceiver as follows: Link budget (dB) > dispersion penalty (dB) + total link loss (dB).			

Warranty

Warranty Period	5 years
Details	See www.moxa.com/warranty

Package Contents

Device	1 x PM-7500 Series module
Documentation	1 x warranty card 1 x product certificates of quality inspection, Simplified Chinese 1 x product notice, Simplified Chinese

Ordering Information

Model Name	100BaseFX Multi-Mode Ports with SC Connectors	100BaseFX Multi-Mode Ports with ST Connectors	Single-Mode Ports with SC Connectors	Combo Ports, 10/100/1000BaseT(X) or 100/1000BaseSFP	Operating Temp.
PM-7500-2MSC	2	–	–	–	-45 to 85°C
PM-7500-2MST	–	2	–	–	-45 to 85°C
PM-7500-2SSC	–	–	2	–	-45 to 85°C
PM-7500-4MSC	4	–	–	–	-45 to 85°C
PM-7500-4MST	–	4	–	–	-45 to 85°C
PM-7500-4SSC	–	–	4	–	-45 to 85°C
PM-7500-2GTXSFP	–	–	–	2	-45 to 85°C
PM-7500-4GTXSFP	–	–	–	4	-45 to 85°C

Accessories (sold separately)

SFP Modules

SFP-1FELLC-T	SFP module with 1 100Base single-mode with LC connector for 80 km transmission, -40 to 85°C operating temperature
SFP-1FEMLC-T	SFP module with 1 100Base multi-mode with LC connector for 4 km transmission, -40 to 85°C operating temperature
SFP-1FESLC-T	SFP module with 1 100Base single-mode with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1G10ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G10ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G10BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature

