

PMWD26UN

Dual N-channel μTrenchMOS ultra low level FET

Rev. 02 — 19 May 2005 Product data sheet

1. Product profile

1.1 General description

Dual N-channel enhancement mode Field-Effect Transistor (FET) in a plastic package using TrenchMOS technology.

1.2 Features

- Surface-mounted package
- Very low threshold voltage
- Low profile
- Fast switching

1.3 Applications

- Portable appliances
- Battery management
- PCMCIA cards
- Load switching

1.4 Quick reference data

- $V_{DS} \leq 20$ V
- $P_{tot} \leq 3.1$ W
- $I_D \leq 7.8$ A
- $R_{DSon} \leq 30$ mΩ

2. Pinning information

Table 1: Pinning

Pin	Description	Simplified outline	Symbol
1	drain1 (D1)		
2, 3	source1 (S1)		
4	gate1 (G1)		
5	gate2 (G2)		
6, 7	source2 (S2)		
8	drain2 (D2)		



SOT530-1 ((TSSOP8))



PHILIPS

3. Ordering information

Table 2: Ordering information

Type number	Package		
	Name	Description	Version
PMWD26UN	TSSOP8	plastic thin shrink small outline package; 8 leads; body width 4.4 mm	SOT530-1

4. Limiting values

Table 3: Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions		Min	Max	Unit
V_{DS}	drain-source voltage (DC)	25 °C ≤ T_j ≤ 150 °C		-	20	V
V_{DGR}	drain-gate voltage (DC)	25 °C ≤ T_j ≤ 150 °C; R_{GS} = 20 kΩ		-	20	V
V_{GS}	gate-source voltage			-	±10	V
I_D	drain current (DC)	T_{sp} = 25 °C; V_{GS} = 4.5 V; Figure 2 and 3	[1]	-	7.8	A
		T_{sp} = 100 °C; V_{GS} = 4.5 V; Figure 2	[1]	-	4.7	A
I_{DM}	peak drain current	T_{sp} = 25 °C; pulsed; t_p ≤ 10 μs; Figure 3	[1]	-	31.3	A
P_{tot}	total power dissipation	T_{sp} = 25 °C; Figure 1	[1]	-	3.1	W
T_{stg}	storage temperature			–55	+150	°C
T_j	junction temperature			–55	+150	°C
Source-drain diode						
I_S	source (diode forward) current (DC)	T_{sp} = 25 °C		-	2.6	A
I_{SM}	peak source (diode forward) current	T_{sp} = 25 °C; pulsed; t_p ≤ 10 μs		-	10.3	A

[1] Single device conducting.

© Koninklijke Philips Electronics N.V. 2005. All rights reserved.



$$P_{der} = \frac{P_{tot}}{P_{tot(25\ ^\circ C)}} \times 100\ \%$$

Fig 1. Normalized total power dissipation as a function of solder point temperature



$V_{GS} \geq 4.5$ V

$$I_{der} = \frac{I_D}{I_{D(25\ ^\circ C)}} \times 100\ \%$$

Fig 2. Normalized continuous drain current as a function of solder point temperature



T_{sp} = 25 °C; I_{DM} is single pulse

Fig 3. Safe operating area; continuous and peak drain currents as a function of drain-source voltage

© Koninklijke Philips Electronics N.V. 2005. All rights reserved.

5. Thermal characteristics

Table 4: Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j-sp)}$	thermal resistance from junction to solder point	Figure 4	-	-	40	K/W
$R_{th(j-a)}$	thermal resistance from junction to ambient	mounted on a printed-circuit board; minimum footprint; vertical in still air	-	100	-	K/W



Fig 4. Transient thermal impedance from junction to solder point as a function of pulse duration

© Koninklijke Philips Electronics N.V. 2005. All rights reserved.

6. Characteristics

Table 5: Characteristics

T_j = 25 °C unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static characteristics						
$V_{(BR)DSS}$	drain-source breakdown voltage	I_D = 250 μA; V_{GS} = 0 V				
		T_j = 25 °C	20	-	-	V
		T_j = –55 °C	18	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	I_D = 1 mA; V_{DS} = V_{GS}; Figure 9 and 10	0.45	0.7	-	V
I_{DSS}	drain-source leakage current	V_{DS} = 20 V; V_{GS} = 0 V				
		T_j = 25 °C	-	-	1	μA
		T_j = 150 °C	-	-	100	μA
I_{GSS}	gate-source leakage current	V_{GS} = ±10 V; V_{DS} = 0 V	-	-	100	nA
R_{DSon}	drain-source on-state resistance	V_{GS} = 4.5 V; I_D = 3.5 A; Figure 7 and 8				
		T_j = 25 °C	-	26	30	mΩ
		T_j = 150 °C	-	44	51	mΩ
		V_{GS} = 1.8 V; I_D = 3.5 A; Figure 7 and 8	-	34	40	mΩ
		V_{GS} = 2.5 V; I_D = 3.5 A; Figure 7 and 8	-	29	35	mΩ
Dynamic characteristics						
$Q_{g(tot)}$	total gate charge	I_D = 4 A; V_{DS} = 16 V; V_{GS} = 4.5 V; Figure 13	-	23.6	-	nC
Q_{gs}	gate-source charge		-	2.1	-	nC
Q_{gd}	gate-drain (Miller) charge		-	6.7	-	nC
C_{iss}	input capacitance	V_{GS} = 0 V; V_{DS} = 16 V; f = 1 MHz; Figure 11	-	1366	-	pF
C_{oss}	output capacitance		-	399	-	pF
C_{rss}	reverse transfer capacitance		-	239	-	pF
$t_{d(on)}$	turn-on delay time	V_{DS} = 10 V; R_L = 1 Ω; V_{GS} = 4.5 V; R_G = 6 Ω	-	14	-	ns
t_r	rise time		-	22	-	ns
$t_{d(off)}$	turn-off delay time		-	56	-	ns
t_f	fall time		-	33	-	ns
Source-drain diode						
V_{SD}	source-drain (diode forward) voltage	I_S = 4 A; V_{GS} = 0 V; Figure 12	-	0.67	1.2	V
t_{rr}	reverse recovery time	I_S = 4 A; dI_S/dt = –100 A/μs; V_{GS} = 0 V; V_R = 20 V	-	45	-	ns
Q_r	recovered charge		-	13	-	nC

© Koninklijke Philips Electronics N.V. 2005. All rights reserved.



T_j = 25 °C

Fig 5. Output characteristics: drain current as a function of drain-source voltage; typical values



T_j = 25 °C and 150 °C; $V_{DS} > I_D \times R_{DSon}$

Fig 6. Transfer characteristics: drain current as a function of gate-source voltage; typical values



T_j = 25 °C

Fig 7. Drain-source on-state resistance as a function of drain current; typical values



$$a = \frac{R_{DSon}}{R_{DSon(25\,^{\circ}C)}}$$

Fig 8. Normalized drain-source on-state resistance factor as a function of junction temperature

© Koninklijke Philips Electronics N.V. 2005. All rights reserved.



I_D = 1 mA; V_{DS} = V_{GS}

Fig 9. Gate-source threshold voltage as a function of junction temperature



T_j = 25 °C; V_{DS} = 5 V

Fig 10. Sub-threshold drain current as a function of gate-source voltage



V_{GS} = 0 V; f = 1 MHz

Fig 11. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values



T_j = 25 °C and 150 °C; V_{GS} = 0 V

Fig 12. Source (diode forward) current as a function of source-drain (diode forward) voltage; typical values

© Koninklijke Philips Electronics N.V. 2005. All rights reserved.



I_D = 4 A; V_{DD} = 16 V

Fig 13. Gate-source voltage as a function of gate charge; typical values

© Koninklijke Philips Electronics N.V. 2005. All rights reserved.

7. Package outline

TSSOP8: plastic thin shrink small outline package; 8 leads; body width 4.4 mm **SOT530-1**



DIMENSIONS (mm are the original dimensions)

UNIT	A max.	A_1	A_2	A_3	b_p	c	$D^{(1)}$	$E^{(2)}$	e	H_E	L	L_p	v	w	y	$Z^{(1)}$	θ
mm	1.1	0.15 0.05	0.95 0.85	0.25	0.30 0.19	0.20 0.13	3.1 2.9	4.5 4.3	0.65	6.5 6.3	0.94	0.7 0.5	0.1	0.1	0.1	0.70 0.35	8° 0°

Notes

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.
2. Plastic or metal protrusions of 0.25 mm maximum per side are not included.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT530-1		MO-153				~~00-02-24~~ 03-02-18

Fig 14. Package outline SOT530-1 (TSSOP8)

© Koninklijke Philips Electronics N.V. 2005. All rights reserved.

8. Revision history

Table 6: Revision history

Document ID	Release date	Data sheet status	Change notice	Doc. number	Supersedes
PMWD26UN_2	20050519	Product data sheet	-	9397 750 14982	PMWD26UN-01
Modifications:	• The format of this data sheet has been redesigned to comply with the new presentation and information standard of Philips Semiconductors. • P_{tot} and I_D data revised in Section 1.4 “Quick reference data” • Section 3 “Ordering information” added • P_{tot}, I_D, I_S, I_{DM} and I_{SM} data revised in Table 3 “Limiting values” • $R_{th(j-sp)}$ data revised in Table 4 “Thermal characteristics” • Figure 3, 4, 5, 6, 7 and 12 revised.				
PMWD26UN-01	20030122	Product data	-	9397 750 10834	-

© Koninklijke Philips Electronics N.V. 2005. All rights reserved.

9. Data sheet status

Level	Data sheet status [1]	Product status [2] [3]	Definition
I	Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
II	Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
III	Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN).

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL http://www.semiconductors.philips.com.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

10. Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

11. Disclaimers

Life support — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

12. Trademarks

Notice — All referenced brands, product names, service names and trademarks are the property of their respective owners.
TrenchMOS — is a trademark of Koninklijke Philips Electronics N.V.

13. Contact information

For additional information, please visit: http://www.semiconductors.philips.com

For sales office addresses, send an email to: sales.addresses@www.semiconductors.philips.com

© Koninklijke Philips Electronics N.V. 2005. All rights reserved.

14. Contents

1	**Product profile**	**1**
1.1	General description	1
1.2	Features	1
1.3	Applications	1
1.4	Quick reference data	1
2	**Pinning information**	**1**
3	**Ordering information**	**2**
4	**Limiting values**	**2**
5	**Thermal characteristics**	**4**
6	**Characteristics**	**5**
7	**Package outline**	**9**
8	**Revision history**	**10**
9	**Data sheet status**	**11**
10	**Definitions**	**11**
11	**Disclaimers**	**11**
12	**Trademarks**	**11**
13	**Contact information**	**11**

© Koninklijke Philips Electronics N.V. 2005

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Date of release: 19 May 2005
Document number: 9397 750 14982

Published in The Netherlands