LINEAR SYSTEMS

PN4392
Single N-Channel JFET switch

micross

Linear Systems replaces discontinued Siliconix PN4392

The PN4392 features many of the superior characteristics of JFETs which make it a good choice for demanding analog switching applications and for specialized amplifier circuits.

PN4392 Benefits:

- Low Error Voltage
- High-Speed Analog Circuit Performance
- Negligible "Off-Error," Excellent Accuracy
- Good Frequency Response, Low Glitches
- Eliminates Additional Buffering

PN4392 Applications:

- Analog Switches
- Choppers, Sample-and-Hold
- Normally "On" Switches, Current Limiters

FEATURES	
DIRECT REPLACEMENT FOR SILICONIX PN4392	
LOW ON RESISTANCE	$r_{DS(on)} \leq 60\Omega$
LOW GATE OPERATING CURRENT	$I_{D(off)} = 5pA$
FAST SWITCHING	$t_{(ON)} \leq 15ns$
ABSOLUTE MAXIMUM RATINGS[1] @ 25°C (unless otherwise noted)	
Maximum Temperatures	
Storage Temperature	-65°C to +200°C
Operating Junction Temperature	-55°C to +200°C
Maximum Power Dissipation	
Continuous Power Dissipation	350mW
MAXIMUM CURRENT	
Gate Current (Note 1)	$I_G = 50mA$
MAXIMUM VOLTAGES	
Gate to Drain Voltage / Gate to Source Voltage	-40V

PN4392 ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTIC	MIN	TYP.	MAX	UNITS	CONDITIONS
BV_{GSS}	Gate to Source Breakdown Voltage	-40	--	--	V	$I_G = -1\mu A$, $V_{DS} = 0V$
$V_{GS(off)}$	Gate to Source Cutoff Voltage	-2	--	-5		$V_{DS} = 20V$, $I_D = 1nA$
$V_{GS(F)}$	Gate to Source Forward Voltage	--	0.7	1		$I_G = 1mA$, $V_{DS} = 0V$
$V_{DS(on)}$	Drain to Source On Voltage	--	0.25	--		$V_{GS} = 0V$, $I_D = 3mA$
$V_{DS(on)}$	Drain to Source On Voltage	--	0.3	0.4		$V_{GS} = 0V$, $I_D = 6mA$
$V_{DS(on)}$	Drain to Source On Voltage	--	0.35	--		$V_{GS} = 0V$, $I_D = 12mA$
I_{DSS}	Drain to Source Saturation Current[2]	25	--	100	mA	$V_{DS} = 20V$, $V_{GS} = 0V$
I_{GSS}	Gate Reverse Current	--	-5	-1000	pA	$V_{GS} = -20V$, $V_{DS} = 0V$
I_G	Gate Operating Current	--	-5	--		$V_{DG} = 15V$, $I_D = 10mA$
$I_{D(off)}$	Drain Cutoff Current	--	5	--		$V_{DS} = 20V$, $V_{GS} = -5V$
		--	5	1000		$V_{DS} = 20V$, $V_{GS} = -7V$
		--	5	1		$V_{DS} = 20V$, $V_{GS} = -12V$
$r_{DS(on)}$	Drain to Source On Resistance	--	--	60	Ω	$V_{GS} = 0V$, $I_D = 1mA$

PN4392 DYNAMIC ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTIC	TYP	MIN	MAX	UNITS	CONDITIONS
g_{fs}	Forward Transconductance	6	--	--	mS	$V_{DS} = 20V$, $I_D = 1mA$, f = 1kHz
g_{os}	Output Conductance	25	--	--	µS	$V_{DS} = 20V$, $I_D = 1mA$, f = 1kHz
$r_{ds(on)}$	Drain to Source On Resistance	--	--	60	Ω	$V_{GS} = 0V$, $I_D = 0A$, f = 1kHz
C_{iss}	Input Capacitance	12	--	16	pF	$V_{DS} = 20V$, $V_{GS} = 0V$, f = 1MHz
C_{rss}	Reverse Transfer Capacitance	3.5	--	--		$V_{DS} = 0V$, $V_{GS} = -5V$, f = 1MHz
C_{rss}		3.4	--	5		$V_{DS} = 0V$, $V_{GS} = -7V$, f = 1MHz
C_{rss}		3.0	--	--		$V_{DS} = 0V$, $V_{GS} = -12V$, f = 1MHz
e_n	Equivalent Input Noise Voltage	3	--	--	nV/√Hz	$V_{DS} = 10V$, $I_D = 10mA$, f = 1kHz

PN4392 SWITCHING ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)


SYMBOL	CHARACTERISTIC	TYP	MIN	MAX	UNITS	CONDITIONS
$t_{d(on)}$	Turn On Time	2	--	15	ns	$V_{DD} = 10V$, $V_{GS(H)} = 0V$
t_r		2	--	5		
$t_{d(off)}$	Turn Off Time	6	--	35		
t_f		13	--	20		

Notes: 1. Absolute ratings are limiting values above which serviceability may be impaired
2. Pulse test: PW ≤ 300µs, Duty Cycle ≤ 3%

PN4392 SWITCHING CIRCUIT PARAMETERS

$V_{GS(L)}$	-7V
R_L	1600Ω
$I_{D(on)}$	6mA

TO-92 (Bottom View)



Available Packages:


PN4392 in TO-92
PN4392 in bare die.
Contact Micross for full package and die dimensions

Micross Components Europe

micross

Tel: +44 1603 788967
Email: chipcomponents@micross.com
Web: http://www.micross.com/distribution

SWITCHING CIRCUIT



Click To Buy

Information furnished by Linear Integrated Systems and Micross Components is believed to be accurate and reliable. However, no responsibility is assumed for its use; nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Linear Integrated Systems.