



45 Watt Universal 2-Wire Input Adapter



Features

- Low Cost
- EISA Energy Efficiency Compliance
- Ecodesign ErP Directive 2009/125/EC level 2 annex 1b Compliant
- Level VI Efficiency Compliant
- Non-Vented/Spill-proof Case
- Low Profile Design
- Class B EMI

Applications

- Portable Equipment
- Notebook Computers
- Networking
- Gaming Machines

Safety Approvals

- CE
- CB
- cUL/UL

Mechanical Characteristics

- Length: 120mm (4.72in)
- Width: 50mm (1.97in)
- Height: 31.5mm (1.24in)
- Weight: 250g (8.82oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple P-P (max.)
		Min.	Max.	
PSAC45W-120	12V	0A	3.750A	150mV
PSAC45W-180	18V	0A	2.500A	180mV
PSAC45W-240	24V	0A	1.875A	240mV
PSAC45W-480	48V	0A	0.938A	480mV
PSAC45W-560	56V	0A	0.804A	560mV

PhiHong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

Input:**AC Input Voltage Rating**

100~240VAC

AC Input Voltage Range

90~264VAC

AC Input Frequency

47~63Hz

Input Current

1.2A (RMS) Max at 120VAC

Leakage Current

250uA maximum

Inrush Current120A max. at 120V AC and max load
(Ambient 25°C cold start)**Input Power Saving**

0.1W maximum at nominal input

Output:**Efficiency**

DOE Level VI

87.7% minimum

Environmental:**Temperature**

Operation 0 to 40°C

Non-operation -20 to 70°C

Operating Humidity 5 to 90%

EMC

FCC Class B

EN55022 Class B

Immunity

IEC61000-4-2

IEC61000-4-3

IEC61000-4-4

IEC61000-4-5

IEC61000-4-6

IEC61000-4-8

IEC61000-4-11

EN61000-3-2

Over-Voltage Protection

Auto-restart

Over-Current Protection

Auto-restart

Short-Circuit Protection

Protected against short circuit –

Output can be shorted permanently
without damage**Dielectric Withstand (Hi-pot) Test**Primary to Secondary: 3000V AC, 10mA
for 1 minute**Insulation Resistance**

Primary to secondary: >7M ohm 500V DC

DC Output ConnectorCenter Positive Barrel (10mm x 5.5mm x
2.1mm)**DC Cord**

1500mm ± 50

Dimension Diagram Unit: mm (inch)

