
PROTEK DEVICES
Only One Name Means ProTek'Tion™

PSD03 thru PSD36C

STANDARD CAPACITANCE TVS ARRAY

APPLICATIONS

- ✔ Laptop Computers
- ✔ Cellular Phones
- ✔ Digital Cameras
- ✔ Personnal Digital Assistant (PDA)



SOD-323

IEC COMPATIBILITY (EN61000-4)

- ✔ 61000-4-2 (ESD): Air - 15kV, Contact - 8kV
- ✔ 61000-4-4 (EFT): 40A - 5/50ns
- ✔ 61000-4-5 (Surge): 24A, 8/20µs - Level 2(Line-Ground) & Level 3(Line-Line)

FEATURES


- ✔ Unidirectional: 500 Watts Peak Pulse Power per Line (tp = 8/20µs)
- ✔ BidirectionalL 400 Watts Peak Pulse Power per Line (tp = 8/20µs)
- ✔ Unidirectional & Bidirectional Configurations
- ✔ Replacement for MLV (0805)
- ✔ Protects One Power or I/O Port
- ✔ ESD Protection > 40 kilovolts
- ✔ Low Clamping Voltage
- ✔ Available in Multiple Voltage Types Ranging from 3V to 36V
- ✔ RoHS Compliant in Lead-Free Versions

MECHANICAL CHARACTERISTICS


- ✔ Molded JEDEC SOD-323
- ✔ Weight 5 milligrams (Approximate)
- ✔ Available in Tin-Lead or Lead-Free Pure-Tin Plating(Annealed)
- ✔ Solder Reflow Temperature:
  - Tin-Lead - Sn/Pb, 85/15: 240-245°C
  - Pure-Tin - Sn, 100: 260-270°C
- ✔ Flammability Rating UL 94V-0
- ✔ 8mm Tape and Reel Per EIA Standard 481
- ✔ Device Marking: Marking Code & Polarity Band *(Unidirectional Only)*

PIN CONFIGURATIONS

UNIDIRECTIONAL



BIDIRECTIONAL



DEVICE CHARACTERISTICS

MAXIMUM RATINGS @ 25°C Unless Otherwise Specified			
PARAMETER	SYMBOL	VALUE	UNITS
Undirectional: Peak Pulse Power (t_p = 8/20µs) - See Fig. 1	P_{PP}	500	Watts
Bidirectional: Peak Pulse Power (t_p = 8/20µs) - See Fig. 1	P_{PP}	400	Watts
Operating Temperature	T_J	-55°C to 150°C	°C
Storage Temperature	T_{STG}	-55°C to 150°C	°C

ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified							
PART NUMBER (See Notes 1-2)	DEVICE MARKING	RATED STAND-OFF VOLTAGE V_{WM} VOLTS	MINIMUM BREAKDOWN VOLTAGE @ 1mA $V_{(BR)}$ VOLTS	MAXIMUM CLAMPING VOLTAGE (See Fig. 2) @ I_P = 1A V_C VOLTS	MAXIMUM CLAMPING VOLTAGE (See Fig. 2) @8/20µs V_C @ I_{PP}	MAXIMUM LEAKAGE CURRENT @V_{WM} I_D µA	TYPICAL CAPACITANCE @0V, 1 MHz C_J pF
PSD03	A	3.3	4.0	6.5	10.9V @ 43.0A	125	500
PSD03C	G	3.3	4.0	7.0	10.9V @ 39.0A	125	200
PSD05	B	5.0	6.0	9.8	13.5V @ 42.0A	10	350
PSD05C	H	5.0	6.0	9.8	14.5V @ 28.0A	10	175
PSD08	C	8.0	8.5	13.4	16.9V @ 34.0A	10	250
PSD08C	J	8.0	8.5	13.4	18.5V @ 17.0A	10	150
PSD12	D	12.0	13.3	19.0	25.9V @ 21.0A	1	150
PSD12C	K	12.0	13.3	19.0	29.5V @ 14.0A	1	50
PSD15	E	15.0	16.7	24.0	30.0V @ 17.0A	1	100
PSD15C	L	15.0	16.7	24.0	33.0V @ 12.0A	1	40
PSD18	G	18.0	20.0	29.0	40.0V @ 9.0A	1	90
PSD18C	N	18.0	20.0	29.0	40.0V @ 9.0A	1	40
PSD24	F	24.0	26.7	43.0	49.0V @ 12.0A	1	88
PSD24C	M	24.0	26.7	43.0	46.2V @ 9.0A	1	40
PSD36	R	36.0	40.0	60.0	75.0V @ 5.0A	1	75
PSD36C	T	36.0	40.0	60.0	75.0V @ 5.0A	1	35

Note 1: Part numbers with an additional “C” suffix are bidirectional devices, i.e., PSD05C.
Note 2: *For Bidirectional Devices Only:* Electrical characteristics apply in both directions.

GRAPHS

FIGURE 1
PEAK PULSE POWER VS PULSE TIME




FIGURE 2
PULSE WAVE FORM




FIGURE 3
POWER DERATING CURVE




FIGURE 4
OVERSHOOT & CLAMPING VOLTAGE FOR PSD03






FIGURE 5
TYPICAL REVERSE VOLTAGE VS CAPACITANCE FOR PSD05



PACKAGE OUTLINE & DIMENSIONS

PACKAGE OUTLINE




SOD-323 PACKAGE



PACKAGE DIMENSIONS

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.60	1.90	0.063	0.075
B	1.15	1.45	0.045	0.057
C	2.39	2.70	0.094	0.106
D	0.92	1.10	0.033	0.043
E	0.25	0.40	0.010	0.016
F	0.10	0.20	0.004	0.008
H	-	0.10	-	0.004

MOUNTING PAD



NOTES

1. Controlling Dimensions in Millimeters.
2. Dimensions are exclusive of mold flash and metal burrs.


TAPE & REEL ORDERING NOMENCLATURE

1. Surface mount product is taped and reeled in accordance with EIA-481.
2. Suffix -T7 = 7 Inch Reel - 3,000 pieces per 8mm tape, i.e., *PSD05C-T7.*
3. Suffix - LF = Lead-Free, Pure-Tin Plating,i.e., *PSD05C-LF-T7.*

Outline & Dimensions: Rev 2 - 9/05, 06010

Tape & Reel Specifications (Dimensions in millimeters)

Reel Dia.	Tape Width	A0	B0	K0	D	E	F	W	P0	P2	P	tmax
178mm (7")	8mm	1.55 ± 0.10	2.90 ± 0.10	1.35 ± 0.10	1.50 ± 0.10	1.75 ± 0.10	3.50 ± 0.05	8.00 ±0.30	4.00 ±0.10	2.00 ±0.05	4.00 ±0.10	0.25



COPYRIGHT © ProTek Devices 2005
SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

ProTek Devices
2929 South Fair Lane, Tempe, AZ 85282
Tel: 602-431-8101 Fax: 602-431-2288
E-Mail: sales@protekdevices.com
Web Site: www.protekdevices.com