



2.75W Compact Fixed Blade USB Power Adapter (China)



Features

- Fixed Blade
- No-Load Power Draw <0.3mW
- No Y Cap
- Low Cost
- Low Profile

Applications

- Smart Phones
- PDA
- Personal Electronics
- Digital Camera

Safety Approvals

- CCC

Mechanical Characteristics

- Length: 42mm (1.65in)
- Width: 43mm (1.65in)
- Height: 21.0mm (0.87in)
- Weight: 80g (3oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple ⁽¹⁾ P-P (Max)	Regulation		Case Color
		Min.	Max.		Line	Load	
PSM03C-050Q-3	5V	0A	0.55A	100mV	±5%		Black

Note: (1) Measured after 10 minutes with by-pass capacitors 0.1uf // 10uf at output connector terminal and oscilloscope set at 20MHz.

(2) Minimum order quantity applies for this model

PhiHong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:**AC Input Voltage Rating**

100 to 240VAC

AC Input Voltage Range

90 to 264VAC

AC Input Current

0.1A(RMS) max.

Leakage Current

0.25mA max. @ 230VAC

OUTPUT:**Power**

2.75W Maximum

Efficiency

63.7% at 115VAC/230VAC

No-Load Power Saving

≤30mW maximum at 115VAC/230VAC

Hold-up Time

8mS min. @ 120VAC and max. load

Over-voltage Protection

120% Typical

Short-Circuit Protection

Latch requires power cycle to restart

ENVIRONMENTAL:**Temperature**

Operation 0 to +40°C

Non-operation -40 to +85°C

Humidity

Operation 10 to 90%

Immunity

ESD: EN61000-4-2. Level 4

Surge: EN61000-4-5. Level 4

Harmonic: EN61000-3-2

Flicker: EN61000-3-3

Emissions

FCC Class B

EN55022 Class B

Dielectric Withstand (Hi-pot) Test

Primary to Secondary: 3000VAC

Insulation Resistance

Primary to Secondary: >7M ohm 500VDC

DC Output Connector

USB A

D+ and D- pins shorted together inside the charger

Dimension Diagram Unit: mm