

## 500W with PFC and Parallel Function

# PSP-500 series



## ■ Features :

- Universal AC input / Full range
- Built-in active PFC function, PF>0.95
- Protections: Short circuit/Over load/Over voltage/Over temperature
- Forced air cooling by built-in DC fan
- Current sharing up to 2000W(3+1)
- With power good and fail signal output
- Built-in remote ON-OFF control
- Built-in remote sense function
- 3 years warranty




## SPECIFICATION

| MODEL                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | PSP-500-5                                                                                                                                                              | PSP-500-12   | PSP-500-13.5 | PSP-500-15 | PSP-500-24   | PSP-500-27 | PSP-500-48   |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--------------|------------|--------------|------------|--------------|
| OUTPUT                                  | DC VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 5V                                                                                                                                                                     | 12V          | 13.5V        | 15V        | 24V          | 27V        | 48V          |
|                                         | RATED CURRENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 80A                                                                                                                                                                    | 41.5A        | 37A          | 33A        | 20.8A        | 18.5A      | 10.5A        |
|                                         | CURRENT RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0 ~ 80A                                                                                                                                                                | 0 ~ 41.5A    | 0 ~ 37A      | 0 ~ 33A    | 0 ~ 20.8A    | 0 ~ 18.5A  | 0 ~ 10.5A    |
|                                         | RATED POWER                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 400W                                                                                                                                                                   | 498W         | 499.5W       | 495W       | 499.2W       | 499.5W     | 504W         |
|                                         | RIPPLE & NOISE (max.) <small>Note.2</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 100mVp-p                                                                                                                                                               | 150mVp-p     | 150mVp-p     | 150mVp-p   | 150mVp-p     | 150mVp-p   | 200mVp-p     |
|                                         | VOLTAGE ADJ. RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 4.75 ~ 5.5V                                                                                                                                                            | 10 ~ 13.2V   | 12 ~ 15V     | 13.5 ~ 18V | 20 ~ 26.4V   | 24 ~ 30V   | 41 ~ 56V     |
|                                         | VOLTAGE TOLERANCE <small>Note.3</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | ±2.0%                                                                                                                                                                  | ±1.0%        | ±1.0%        | ±1.0%      | ±1.0%        | ±1.0%      | ±1.0%        |
|                                         | LINE REGULATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | ±0.5%                                                                                                                                                                  | ±0.3%        | ±0.3%        | ±0.3%      | ±0.2%        | ±0.2%      | ±0.2%        |
|                                         | LOAD REGULATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | ±2.0%                                                                                                                                                                  | ±0.5%        | ±0.5%        | ±0.5%      | ±0.5%        | ±0.5%      | ±0.5%        |
|                                         | SETUP, RISE TIME                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 1500ms, 50ms at full load                                                                                                                                              |              |              |            |              |            |              |
| HOLD TIME (Typ.)                        | 24ms at full load                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                        |              |              |            |              |            |              |
| INPUT                                   | VOLTAGE RANGE <small>Note.6</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 90 ~ 264VAC                                                                                                                                                            | 127 ~ 370VDC |              |            |              |            |              |
|                                         | FREQUENCY RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 47 ~ 63Hz                                                                                                                                                              |              |              |            |              |            |              |
|                                         | POWER FACTOR (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 0.95/230VAC      0.98/100VAC at full load                                                                                                                              |              |              |            |              |            |              |
|                                         | EFFICIENCY (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 76%                                                                                                                                                                    | 82%          | 82%          | 82%        | 84%          | 84%        | 86%          |
|                                         | AC CURRENT (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 7A/115AVC                                                                                                                                                              | 3.5A/230VAC  |              |            |              |            |              |
|                                         | INRUSH CURRENT (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 20A/115VAC                                                                                                                                                             | 40A/230VAC   |              |            |              |            |              |
|                                         | LEAKAGE CURRENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | <1mA / 240VAC                                                                                                                                                          |              |              |            |              |            |              |
| PROTECTION                              | OVER LOAD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 110 ~ 125% rated output power<br>Protection type : Constant current limiting, recovers automatically after fault condition is removed                                  |              |              |            |              |            |              |
|                                         | OVER VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 5.75 ~ 6.75V                                                                                                                                                           | 13.8 ~ 16.2V | 15.5 ~ 18.2V | 18 ~ 21V   | 27.6 ~ 32.4V | 31 ~ 36.5V | 57.6 ~ 67.2V |
|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Protection type : Shut down o/p voltage, re-power on to recover                                                                                                        |              |              |            |              |            |              |
|                                         | OVER TEMPERATURE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | RTH2≥95℃ Detect on heatsink of Q1,Q7 power transistor & L3 output choke<br>Protection type : Shut down o/p voltage, recovers automatically after temperature goes down |              |              |            |              |            |              |
| FUNCTION                                | REMOTE CONTROL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | RC+/RC-: 0 ~ 0.8V=power on ; 4 ~ 10V=power off      sink current <4 ~ 10mA                                                                                             |              |              |            |              |            |              |
| ENVIRONMENT                             | WORKING TEMP.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | -10 ~ +60℃ (Refer to output load derating curve)                                                                                                                       |              |              |            |              |            |              |
|                                         | WORKING HUMIDITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 20 ~ 90% RH with 30CFM forced air non-condensing                                                                                                                       |              |              |            |              |            |              |
|                                         | STORAGE TEMP., HUMIDITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | -20 ~ +85℃, 10 ~ 95% RH                                                                                                                                                |              |              |            |              |            |              |
|                                         | TEMP. COEFFICIENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | ±0.03%/℃ (0 ~ 50℃ )                                                                                                                                                    |              |              |            |              |            |              |
|                                         | VIBRATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes                                                                                                           |              |              |            |              |            |              |
| SAFETY & EMC<br><small>(Note 4)</small> | SAFETY STANDARDS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | UL60950-1, TUV EN60950-1 Approved                                                                                                                                      |              |              |            |              |            |              |
|                                         | WITHSTAND VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | I/P-O/P:3KVAC    I/P-FG:1.5KVAC    O/P-FG:0.5KVAC                                                                                                                      |              |              |            |              |            |              |
|                                         | ISOLATION RESISTANCE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | I/P-O/P, I/P-FG, O/P-FG:100M Ohms/500VDC                                                                                                                               |              |              |            |              |            |              |
|                                         | EMI CONDUCTION & RADIATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Compliance to EN55022 (CISPR22) Class B                                                                                                                                |              |              |            |              |            |              |
|                                         | HARMONIC CURRENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Compliance to EN61000-3-2,-3                                                                                                                                           |              |              |            |              |            |              |
|                                         | EMS IMMUNITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Compliance to EN61000-4-2,3,4,5,6,8,11; ENV50204, EN55024, Light industry level, criteria A                                                                            |              |              |            |              |            |              |
| OTHERS                                  | MTBF                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 130.1K hrs min.      MIL-HDBK-217F (25℃)                                                                                                                               |              |              |            |              |            |              |
|                                         | DIMENSION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 278*129*63.5mm (L*W*H)                                                                                                                                                 |              |              |            |              |            |              |
|                                         | PACKING                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 2.6Kg; 6pcs/15.7Kg/0.89CUFT                                                                                                                                            |              |              |            |              |            |              |
| NOTE                                    | 1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25℃ of ambient temperature.<br>2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.<br>3. Tolerance : includes set up tolerance, line regulation and load regulation.<br>4. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.<br>5. In parallel connection, maybe only one unit operated, if the total output load less than 5% of rated load condition.<br>6. Derating may be needed under low input voltages. Please check the derating curve for more details. |                                                                                                                                                                        |              |              |            |              |            |              |

**Mechanical Specification**

Case No. 919A Unit:mm



AC Input Terminal Pin. No. Assignment



| Pin No. | Assignment  |
|---------|-------------|
| 1       | AC/L        |
| 2       | AC/N        |
| 3       | FG $\equiv$ |


DC Output Terminal Pin. No Assignment

| Pin No. | Assignment   |
|---------|--------------|
| 1~3     | DC OUTPUT +V |
| 4~6     | DC OUTPUT -V |



Control Pin. No Assignment : MOLEX 5559-NP uses 5558 male crimp terminal

| Pin No. | Assignment       | Pin No. | Assignment            | Mating connector | Terminal                                    |
|---------|------------------|---------|-----------------------|------------------|---------------------------------------------|
| 1       | P(Current share) | 5       | NC                    | MOLEX 5557-NR    | MOLEX 5556 Female crimp Terminal receptacle |
| 2       | -S               | 6       | PF(Power fail signal) |                  |                                             |
| 3       | G                | 7       | +S                    |                  |                                             |
| 4       | RC-              | 8       | RC+                   |                  |                                             |



**Derating Curve****Output Derating VS Input Voltage**

**Control terminal instruction manual****Power Fail Signal**


PF Signal is the voltage difference between "G" and "PF" pin output

**Remote Sensing****Remote Control**

Power ON: When VRC+, RC-=0 ~ 0.8V or Open  
Power OFF: When VRC+, RC-=4 ~ 10V

**Parallel Operation****Parallel Operation With Remote Sensing****Parallel Operation With Remote Control**

## 500W with PFC and Parallel Function

**PSP-500-P series**

**■ Features :**

- Universal AC input / Full range
- Built-in active PFC function, PF>0.95
- Protections: Short circuit/Over load/Over voltage/Over temperature
- Forced air cooling by built-in DC fan
- Current sharing up to 2000W(3+1)
- With power good and fail signal output
- Built-in remote ON-OFF control
- Built-in remote sense function
- 3 years warranty


**SPECIFICATION**

| MODEL                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | PSP-500-5P                                                                                                                                                             | PSP-500-12P              | PSP-500-13.5P | PSP-500-15P | PSP-500-24P  | PSP-500-27P | PSP-500-48P  |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|---------------|-------------|--------------|-------------|--------------|
| OUTPUT                   | DC VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 5V                                                                                                                                                                     | 12V                      | 13.5V         | 15V         | 24V          | 27V         | 48V          |
|                          | RATED CURRENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 80A                                                                                                                                                                    | 41.5A                    | 37A           | 33A         | 20.8A        | 18.5A       | 10.5A        |
|                          | CURRENT RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 0 ~ 80A                                                                                                                                                                | 0 ~ 41.5A                | 0 ~ 37A       | 0 ~ 33A     | 0 ~ 20.8A    | 0 ~ 18.5A   | 0 ~ 10.5A    |
|                          | RATED POWER                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 400W                                                                                                                                                                   | 498W                     | 499.5W        | 495W        | 499.2W       | 499.5W      | 504W         |
|                          | RIPPLE & NOISE (max.) <small>Note.2</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 100mVp-p                                                                                                                                                               | 150mVp-p                 | 150mVp-p      | 150mVp-p    | 150mVp-p     | 150mVp-p    | 200mVp-p     |
|                          | VOLTAGE ADJ. RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 4.75 ~ 5.5V                                                                                                                                                            | 10 ~ 13.2V               | 12 ~ 15V      | 13.5 ~ 18V  | 20 ~ 26.4V   | 24 ~ 30V    | 41 ~ 56V     |
|                          | VOLTAGE TOLERANCE <small>Note.3</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | ±2.0%                                                                                                                                                                  | ±1.0%                    | ±1.0%         | ±1.0%       | ±1.0%        | ±1.0%       | ±1.0%        |
|                          | LINE REGULATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | ±0.5%                                                                                                                                                                  | ±0.3%                    | ±0.3%         | ±0.3%       | ±0.2%        | ±0.2%       | ±0.2%        |
|                          | LOAD REGULATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | ±2.0%                                                                                                                                                                  | ±0.5%                    | ±0.5%         | ±0.5%       | ±0.5%        | ±0.5%       | ±0.5%        |
|                          | SETUP, RISE TIME                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 1500ms, 50ms at full load                                                                                                                                              |                          |               |             |              |             |              |
| HOLD TIME (Typ.)         | 24ms at full load                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                        |                          |               |             |              |             |              |
| INPUT                    | VOLTAGE RANGE <small>Note.5</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 90 ~ 264VAC                                                                                                                                                            | 127 ~ 370VDC             |               |             |              |             |              |
|                          | FREQUENCY RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 47 ~ 63Hz                                                                                                                                                              |                          |               |             |              |             |              |
|                          | POWER FACTOR (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0.95/230VAC                                                                                                                                                            | 0.98/100VAC at full load |               |             |              |             |              |
|                          | EFFICIENCY (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 76%                                                                                                                                                                    | 82%                      | 82%           | 82%         | 84%          | 84%         | 86%          |
|                          | AC CURRENT (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 7A/115AVC                                                                                                                                                              | 3.5A/230VAC              |               |             |              |             |              |
|                          | INRUSH CURRENT (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 20A/115VAC                                                                                                                                                             | 40A/230VAC               |               |             |              |             |              |
|                          | LEAKAGE CURRENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | <1mA / 240VAC                                                                                                                                                          |                          |               |             |              |             |              |
| PROTECTION               | OVER LOAD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 110 ~ 125% rated output power<br>Protection type : Constant current limiting, recovers automatically after fault condition is removed                                  |                          |               |             |              |             |              |
|                          | OVER VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 5.75 ~ 6.75V                                                                                                                                                           | 13.8 ~ 16.2V             | 15.5 ~ 18.2V  | 18 ~ 21V    | 27.6 ~ 32.4V | 31 ~ 36.5V  | 57.6 ~ 67.2V |
|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Protection type : Shut down o/p voltage, re-power on to recover                                                                                                        |                          |               |             |              |             |              |
|                          | OVER TEMPERATURE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | RTH2≥95℃ Detect on heatsink of Q1,Q7 power transistor & L3 output choke<br>Protection type : Shut down o/p voltage, recovers automatically after temperature goes down |                          |               |             |              |             |              |
| FUNCTION                 | REMOTE CONTROL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | RC+/RC-: 0 ~ 0.8V=power on ; 4 ~ 10V=power off      sink current <4 ~ 10mA                                                                                             |                          |               |             |              |             |              |
| ENVIRONMENT              | WORKING TEMP.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | -10 ~ +60℃ (Refer to output load derating curve)                                                                                                                       |                          |               |             |              |             |              |
|                          | WORKING HUMIDITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 20 ~ 90% RH with 30CFM forced air non-condensing                                                                                                                       |                          |               |             |              |             |              |
|                          | STORAGE TEMP., HUMIDITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | -20 ~ +85℃, 10 ~ 95% RH                                                                                                                                                |                          |               |             |              |             |              |
|                          | TEMP. COEFFICIENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | ±0.03%/℃ (0 ~ 50℃ )                                                                                                                                                    |                          |               |             |              |             |              |
|                          | VIBRATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes                                                                                                           |                          |               |             |              |             |              |
| SAFETY & EMC<br>(Note 4) | SAFETY STANDARDS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | UL1950, TUV EN60950-1 Approved                                                                                                                                         |                          |               |             |              |             |              |
|                          | WITHSTAND VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | I/P-O/P:3KVAC    I/P-FG:1.5KVAC    O/P-FG:0.5KVAC                                                                                                                      |                          |               |             |              |             |              |
|                          | ISOLATION RESISTANCE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | I/P-O/P, I/P-FG, O/P-FG:100M Ohms/500VDC                                                                                                                               |                          |               |             |              |             |              |
|                          | EMI CONDUCTION & RADIATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Compliance to EN55022 (CISPR22) Class B                                                                                                                                |                          |               |             |              |             |              |
|                          | HARMONIC CURRENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Compliance to EN61000-3-2,-3                                                                                                                                           |                          |               |             |              |             |              |
|                          | EMS IMMUNITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Compliance to EN61000-4-2,3,4,5,6,8,11; ENV50204, EN55024, Light industry level, criteria A                                                                            |                          |               |             |              |             |              |
| OTHERS                   | MTBF                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 130.1K hrs min.      MIL-HDBK-217F (25℃ )                                                                                                                              |                          |               |             |              |             |              |
|                          | DIMENSION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 250*123*50mm (L*W*H)                                                                                                                                                   |                          |               |             |              |             |              |
|                          | PACKING                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 1.3Kg; 6pcs/7.8Kg/0.89CUFT                                                                                                                                             |                          |               |             |              |             |              |
| NOTE                     | 1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25℃ of ambient temperature.<br>2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.<br>3. Tolerance : includes set up tolerance, line regulation and load regulation.<br>4. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.<br>5. Derating may be needed under low input voltages. Please check the derating curve for more details. |                                                                                                                                                                        |                          |               |             |              |             |              |

# PSP-500-P series

Unit:mm

