




## Features

- Input Voltage Range: 36V to 75V
- 1500 VDC Isolation
- On/Off Control
- $V_o$  Adjust
- Differential Remote Sense
- Current Limit
- Short-Circuit Protection
- Over-Temperature Shutdown
- Undervoltage Lockout
- UL1950 Recognized
- Flexible SIP Package
- CSA 22.2 950 Certified
- EN60950 Approved
- VDE Licensed
- 4.9 x10<sup>6</sup> Hrs MTBF
- Meets FCC Class A Radiated Limits

## Description

The PT3320 series is a single-output isolated DC/DC converter, housed in a 19-pin aluminum SIP package. These modules are UL, CSA, and VDE approved for telecom applications, and rated at 30 watts or 8 A. Standard output voltages range from 1.8 V to 15 V, each adjustable by up to  $\pm 10\%$  of nominal.

Operating features include a remote on/off control, an under-voltage-lockout (UVLO), and a differential remote sense. The PT3320 series also incorporates many protection features. These include output current limit, short-circuit protection, and over-temperature shutdown.

A 330 $\mu$ F of output capacitance is required for proper operation.

## Ordering Information

|               |                   |
|---------------|-------------------|
| <b>PT3321</b> | = 3.3V/8A (26.4W) |
| <b>PT3322</b> | = 5.0V/6A         |
| <b>PT3323</b> | = 12.0V/2.5A      |
| <b>PT3324</b> | = 15.0V/2A        |
| <b>PT3325</b> | = 2.0V/8A (16W)   |
| <b>PT3326</b> | = 2.5V/8A (20W)   |
| <b>PT3327</b> | = 1.8V/8A (14.4W) |
| <b>PT3328</b> | = 5.2V/6A         |

## PT Series Suffix (PT1234x)

| Case/Pin Configuration | Order Suffix | Package Code * |
|------------------------|--------------|----------------|
| Vertical               | <b>N</b>     | (EHG)          |
| Horizontal             | <b>A</b>     | (EHH)          |
| SMD                    | <b>C</b>     | (EHJ)          |

\* Previously known as package styles 840 & 850.


(Reference the applicable package code drawing for the dimensions and PC board layout)

## Pin-Out Information

| Pin | Function        |
|-----|-----------------|
| 1   | Do Not Use      |
| 2   | Remote On/Off † |
| 3   | Do Not Use      |
| 4   | - $V_{in}$      |
| 5   | - $V_{in}$      |
| 6   | - $V_{in}$      |
| 7   | + $V_{in}$      |
| 8   | + $V_{in}$      |
| 9   | + $V_{in}$      |
| 10  | - $V_o$         |
| 11  | - $V_o$         |
| 12  | - $V_o$         |
| 13  | -Remote Sense   |
| 14  | + $V_o$         |
| 15  | + $V_o$         |
| 16  | + $V_o$         |
| 17  | + $V_o$         |
| 18  | $V_o$ Adjust †  |
| 19  | +Remote Sense   |

† For more information, see application notes.

## Standard Application



$C_{in}$  = Optional 100 $\mu$ F/100V electrolytic  
 $C_{out}$  = Required 330 $\mu$ F electrolytic (See Notes)  
 $Q_1$  = N-Channel MOSFET  
 $R_i/C_i$  = Optional (see application notes)

# PT3320 Series

## 30-W 48-V Input Isolated DC/DC Converter

### Specifications (Unless otherwise stated, $T_a = 25^\circ\text{C}$ , $V_{in} = 48\text{V}$ , $C_{out} = 330\mu\text{F}$ , and $I_o = I_{o,max}$ )

| Characteristic                 | Symbol                      | Conditions                                                                      |                                                                                                               | PT3320 SERIES                                                                          |                               |                                            | Units                          |
|--------------------------------|-----------------------------|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|-------------------------------|--------------------------------------------|--------------------------------|
|                                |                             |                                                                                 |                                                                                                               | Min                                                                                    | Typ                           | Max                                        |                                |
| Output Current                 | $I_o$                       | Over $V_{in}$ range                                                             | $V_o = 15\text{V}$<br>$V_o = 12\text{V}$<br>$V_o = 5.0\text{V}$<br>$V_o \leq 3.3\text{V}$                     | 0.1 <sup>(1)</sup><br>0.1 <sup>(1)</sup><br>0.25 <sup>(1)</sup><br>0.25 <sup>(1)</sup> | —<br>—<br>—<br>—              | 2.0<br>2.5<br>6.0<br>8.0                   | A                              |
| Input Voltage Range            | $V_{in}$                    | Over $I_o$ Range                                                                |                                                                                                               | 36.0                                                                                   | 48.0                          | 75.0                                       | V                              |
| Set Point Voltage Tolerance    | $V_o \text{ tol}$           |                                                                                 | $V_o \geq 5.0\text{V}$<br>$V_o \leq 3.3\text{V}$                                                              | —<br>—                                                                                 | $\pm 1$<br>$\pm 33$           | $\pm 1.5$<br>$\pm 50$                      | $\%V_o$<br>mV                  |
| Temperature Variation          | $\text{Reg}_{temp}$         | $-40^\circ \leq T_a \leq +85^\circ\text{C}$                                     |                                                                                                               | —                                                                                      | $\pm 0.5$                     | —                                          | $\%V_o$                        |
| Line Regulation                | $\text{Reg}_{line}$         | Over $V_{in}$ range                                                             | $V_o \geq 5.0\text{V}$<br>$V_o \leq 3.3\text{V}$                                                              | —<br>—                                                                                 | $\pm 0.2$<br>$\pm 7$          | $\pm 1.0$<br>$\pm 33$                      | $\%V_o$<br>mV                  |
| Load Regulation                | $\text{Reg}_{load}$         | Over $I_o$ range                                                                | $V_o \geq 5.0\text{V}$<br>$V_o \leq 3.3\text{V}$                                                              | —<br>—                                                                                 | $\pm 0.4$<br>$\pm 13$         | $\pm 1.0$<br>$\pm 33$                      | $\%V_o$<br>mV                  |
| Total Output Voltage Variation | $\Delta V_{otot}$           | Includes set-point, line, load,<br>$-40^\circ \leq T_a \leq +85^\circ\text{C}$  | $V_o \geq 5.0\text{V}$<br>$V_o \leq 3.3\text{V}$                                                              | —<br>—                                                                                 | $\pm 2$<br>$\pm 67$           | —<br>—                                     | $\%V_o$<br>mV                  |
| Efficiency                     | $\eta$                      |                                                                                 | $V_o = 15\text{V}$<br>$V_o = 12\text{V}$<br>$V_o = 5.0\text{V}$<br>$V_o = 3.3\text{V}$<br>$V_o = 1.8\text{V}$ | —<br>—<br>—<br>—<br>—                                                                  | 85<br>87<br>84<br>80<br>69    | —<br>—<br>—<br>—<br>—                      |                                |
| $V_o$ Ripple (pk-pk)           | $V_r$                       | 20MHz bandwidth                                                                 | $V_o \geq 5.0\text{V}$<br>$V_o \leq 3.3\text{V}$                                                              | —<br>—                                                                                 | 1.0<br>50                     | 2.0<br>75                                  | $\%V_o$<br>mV <sub>pp</sub>    |
| Transient Response             | $t_{tr}$<br>$\Delta V_{tr}$ | 0.1A/ $\mu\text{s}$ load step, 50% to 100% $I_{o,max}$<br>$V_o$ over/undershoot | $V_o \geq 5.0\text{V}$<br>$V_o \leq 3.3\text{V}$                                                              | —<br>—                                                                                 | 100<br>$\pm 3.0$<br>$\pm 100$ | 200<br>$\pm 5.0$<br>$\pm 150$              | $\mu\text{s}$<br>$\%V_o$<br>mV |
| Short Circuit Current          | $I_{sc}$                    |                                                                                 |                                                                                                               | —                                                                                      | $2xI_{o,max}$                 | —                                          | A                              |
| Switching Frequency            | $f_s$                       | Over $V_{in}$ range                                                             | $V_o > 10\text{V}$<br>$V_o < 10\text{V}$                                                                      | 400<br>600                                                                             | 500<br>750                    | 600<br>900                                 | kHz                            |
| Under-Voltage Lockout          | UVLO                        | $V_{in}$ increasing<br>$V_{in}$ decreasing                                      |                                                                                                               | —<br>—                                                                                 | 34<br>33                      | —<br>—                                     | V                              |
| Remote On/Off Input (pin 2)    |                             | Referenced to $-V_{in}$ (pins 4-6)                                              |                                                                                                               |                                                                                        |                               |                                            |                                |
| Input High Voltage             | $V_{IH}$                    |                                                                                 |                                                                                                               | 2.5                                                                                    | —                             | 15 <sup>(2)</sup>                          | V                              |
| Input Low Voltage              | $V_{IL}$                    |                                                                                 |                                                                                                               | -0.2                                                                                   | —                             | +0.8                                       |                                |
| Input Low Current              | $I_{IL}$                    |                                                                                 |                                                                                                               | -3                                                                                     | -6                            | -10                                        | $\mu\text{A}$                  |
| Standby Input Current          | $I_{in \text{ standby}}$    | pins 2 & 4 connected                                                            |                                                                                                               | —                                                                                      | 8                             | 16                                         | mA                             |
| Internal Input Capacitance     | $C_{in}$                    |                                                                                 |                                                                                                               | —                                                                                      | 0.66                          | —                                          | $\mu\text{F}$                  |
| External Output Capacitance    | $C_{out}$                   | Between $+V_o$ and $-V_o$                                                       | $V_o \geq 9\text{V}$<br>$V_o \leq 5\text{V}$                                                                  | 260<br>260                                                                             | 330<br>330                    | 600 <sup>(3)</sup><br>1,000 <sup>(3)</sup> | $\mu\text{F}$                  |
| Isolation Voltage              |                             | Input-output/input-case                                                         |                                                                                                               | 1500                                                                                   | —                             | —                                          | V <sub>dc</sub>                |
| Capacitance                    |                             | Input-output                                                                    |                                                                                                               | —                                                                                      | 1200                          | —                                          | pF                             |
| Resistance                     |                             | Input-output                                                                    |                                                                                                               | 10                                                                                     | —                             | —                                          | M $\Omega$                     |
| Operating Temperature Range    | $T_a$                       | Over $V_{in}$ range                                                             |                                                                                                               | -40 <sup>(4)</sup>                                                                     | —                             | +85 <sup>(5)</sup>                         | $^\circ\text{C}$               |
| Maximum Case Temperature       | $T_c$                       |                                                                                 |                                                                                                               | —                                                                                      | —                             | 100                                        | $^\circ\text{C}$               |
| Storage Temperature Range      | $T_s$                       |                                                                                 |                                                                                                               | -40                                                                                    | —                             | +125                                       | $^\circ\text{C}$               |
| Reliability                    | MTBF                        | Per Bellcore TR-332<br>50% stress, $T_a = 40^\circ\text{C}$ , ground benign     |                                                                                                               | 4.9                                                                                    | —                             | —                                          | 10 <sup>6</sup> Hrs            |
| Mechanical Shock               | —                           | Per Mil-Std-883D, method 2002.3,<br>1mS, half-sine, mounted to a fixture        |                                                                                                               | —                                                                                      | 500                           | —                                          | G's                            |
| Mechanical Vibration           | —                           | Per Mil-Std-883D, method 2007.2,<br>20-2000Hz, soldered in board                |                                                                                                               | —                                                                                      | 10                            | —                                          | G's                            |
| Weight                         | —                           | —                                                                               |                                                                                                               | —                                                                                      | 43                            | —                                          | grams                          |
| Flammability                   | —                           | Materials meet UL 94V-0                                                         |                                                                                                               | —                                                                                      | —                             | —                                          |                                |

**Notes:** (1) The DC/DC converter will operate at no load with reduced specifications.

(2) The Remote On/Off input has an internal pull-up. If it is left open circuit the module will operate when input power is applied. A low-leakage (<100nA) MOSFET is recommended to control this input. The open-circuit voltage is less than 10V. See application notes for interface considerations.





(3) Output capacitor values are absolute. Allowances must be made for any additional de-coupling capacitors and the total external capacitor tolerance. The value of external capacitance is limited due to regulator startup current requirements. Consult the factory for further details.

(4) For operation below  $0^\circ\text{C}$ , the required external output capacitor must have temperature stable characteristics. E.g. Tantalum or Oscon® types.





(5) See Safe Operating Area curves or contact the factory for the appropriate thermal derating.

30-W 48-V Input  
Isolated DC/DC Converter





PT3321, 3.3 VDC (See Note A)

Safe Operating Area,  $V_{in} = 48V$  (See Note B)

PT3322, 5.0 VDC (See Note A)

Safe Operating Area,  $V_{in} = 48V$  (See Note B)

PT3323, 12.0 VDC (See Note A)

Safe Operating Area,  $V_{in} = 48V$  (See Note B)

**Note A:** All data listed in the above graphs has been developed from actual products tested at 25°C. This data is considered typical data for the DC-DC Converter.

**Note B:** SOA curves represent operating conditions at which internal components are at or below manufacturer's maximum rated operating temperature.

## Adjusting the Output Voltage of Power Trends' 30W Isolated DC/DC Converter Series

The factory pre-set output voltage of Power Trends' 30W series of isolated DC/DC converters may be adjusted within a nominal  $\pm 10\%$  range. This is accomplished with the addition of a single external resistor. For the input voltage range specified in the data sheet, Table 1 gives the allowable adjustment range for each model as  $V_o$  (min) and  $V_o$  (max).

**Adjust Up:** An increase in the output voltage is obtained by adding a resistor,  $R_2$  between  $V_o$  adjust (pin 18), and -Remote Sense (pin 13). See note 4.

**Adjust Down:** Add a resistor ( $R_1$ ), between  $V_o$  adjust (pin 18), and +Remote Sense (pin 19). See note 4.

Refer to Figure 1 and Tables 2 & 3 for both the placement and value of the required resistor, ( $R_1$ ) or  $R_2$ .

### Notes:

1. Use only a single 1% resistor in either the ( $R_1$ ) or  $R_2$  location. Place the resistor as close to the ISR as possible.
2. Never connect capacitors to  $V_o$  adjust. Any capacitance added to the  $V_o$  adjust control pin will affect the stability of the ISR.

3. If the remote sense pins are not being used, the resistors ( $R_1$ ) and  $R_2$  can be connected to  $+V_{out}$  or  $-V_{out}$  respectively.
4. The adjusted output voltage,  $V_a$  effectively sets the voltage across pins 13 and 19 ( $\pm$ Remote Sense). When using the remote sense pins,  $V_{out}$  (measured directly across pins 10–12, and 14–17) can be significantly higher than  $V_a$ , and may exceed  $V_o$  (max). If  $V_a$  is adjusted upward of  $V_o$  (max), the minimum input voltage is increased by the same percentage as  $V_{out}$  exceeds  $V_o$  (max).

The values of ( $R_1$ ) [adjust down], and  $R_2$  [adjust up], can also be calculated using the following formulas.

$$(R_1) = \frac{K_o (V_a - V_r)}{V_r (V_o - V_a)} - R_s \quad k\Omega$$

$$R_2 = \frac{K_o}{(V_a - V_o)} - R_s \quad k\Omega$$


Where  $V_o$  = Original output voltage  
 $V_a$  = Adjusted output voltage  
 $V_r$  = Reference voltage (Table 1)  
 $K_o$  = Multiplier constant (Table 1)  
 $R_s$  = Series resistance (Table 1)

Table 1

DC/DC CONVERTER ADJUSTMENT RANGE AND FORMULA PARAMETERS

| Series Pt #           |        |        |        |        |        |        |        |        |        |
|-----------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| AL Case:              |        |        |        |        |        |        |        |        |        |
| 24V Bus               |        |        |        |        | PT3341 | PT3342 |        | PT3343 | PT3344 |
| 48V Bus               | PT3327 | PT3325 | PT3326 | PT3321 | PT3322 |        | PT3323 | PT3324 |        |
| CU Case:              |        |        |        |        |        |        |        |        |        |
| 24V Bus               | PT4585 |        |        | PT4581 | PT4582 |        | PT4583 | PT4584 |        |
| 48V Bus               | PT4567 | PT4565 | PT4566 | PT4561 | PT4562 | PT4571 | PT4563 | PT4564 |        |
| $V_o$ (nom)           | 1.8V   | 1.8V   | 2.0V   | 2.5V   | 3.3V   | 5.0V   | 9.0V   | 12.0V  | 15.0V  |
| $V_o$ (min)           | 1.62V  | 1.62V  | 1.8V   | 2.25V  | 2.95V  | 4.5V   | 7.0V   | 10.8V  | 13.5V  |
| $V_o$ (max)           | 2.5V   | 1.98V  | 2.2V   | 2.75V  | 3.65V  | 5.5V   | 10.0V  | 13.2V  | 16.5V  |
| $V_r$                 | 1.225V | 1.225V | 1.225V | 1.225V | 1.225V | 1.225V | 2.5V   | 2.5V   | 2.5V   |
| $K_o$ (V·k $\Omega$ ) | 69.58  | 69.58  | 62.47  | 42.33  | 68.89  | 68.71  | 133.25 | 135.9  | 137.5  |
| $R_s$ (k $\Omega$ )   | 80.6   | 80.6   | 150.0  | 121.0  | 150.0  | 121.0  | 110    | 90.9   | 80.6   |

Figure 1



## PT3320/3340/4560/4580 Series

Table 2

## DC/DC CONVERTER ADJUSTMENT RESISTOR VALUES

Series Pt #

AL Case

|         |        |        |        |  |        |
|---------|--------|--------|--------|--|--------|
| 24V Bus |        |        |        |  | PT3341 |
| 48V Bus | PT3327 | PT3325 | PT3326 |  | PT3321 |

CU Case

|         |        |        |        |        |        |
|---------|--------|--------|--------|--------|--------|
| 24V Bus | PT4585 |        |        |        | PT4581 |
| 48V Bus |        | PT4567 | PT4565 | PT4566 | PT4561 |

|                      |      |      |      |      |      |
|----------------------|------|------|------|------|------|
| Current              | 8Adc | 8Adc | 8Adc | 8Adc | 8Adc |
| V <sub>o</sub> (nom) | 1.8V | 1.8V | 2.0V | 2.5V | 3.3V |

V<sub>a</sub>(req'd)

|      |           |           |           |            |  |
|------|-----------|-----------|-----------|------------|--|
| 1.65 | (80.3)kΩ  | (80.3)kΩ  |           |            |  |
| 1.7  | (189.0)kΩ | (189.0)kΩ |           |            |  |
| 1.75 | (516.0)kΩ | (516.0)kΩ |           |            |  |
| 1.8  |           |           |           |            |  |
| 1.85 | 1.31MΩ    | 1.31MΩ    | (62.5)kΩ  |            |  |
| 1.9  | 615.0kΩ   | 615.0kΩ   | (194.0)kΩ |            |  |
| 1.95 | 383.0kΩ   | 383.0kΩ   | (589.0)kΩ |            |  |
| 2.0  | 267.0kΩ   |           |           |            |  |
| 2.05 | 198.0kΩ   |           | 1.1MΩ     |            |  |
| 2.1  | 151.0kΩ   |           | 475.0kΩ   |            |  |
| 2.15 | 118.0kΩ   |           | 266.0kΩ   |            |  |
| 2.2  | 93.3kΩ    |           | 162.0kΩ   |            |  |
| 2.25 | 74.0kΩ    |           |           | (20.7)kΩ   |  |
| 2.3  | 58.6kΩ    |           |           | (64.7.0)kΩ |  |
| 2.35 | 45.9kΩ    |           |           | (138.0)kΩ  |  |
| 2.4  | 35.4kΩ    |           |           | (285.0)kΩ  |  |
| 2.45 | 26.4kΩ    |           |           | (726.0)kΩ  |  |
| 2.5  | 18.8kΩ    |           |           |            |  |
| 2.55 |           |           | 726.0kΩ   |            |  |
| 2.6  |           |           | 302.0kΩ   |            |  |
| 2.65 |           |           | 161.0kΩ   |            |  |
| 2.7  |           |           | 90.6kΩ    |            |  |
| 2.75 |           |           | 48.3kΩ    |            |  |
| 2.95 |           |           |           | (127.0)kΩ  |  |
| 3.0  |           |           |           | (183.0)kΩ  |  |
| 3.05 |           |           |           | (261.0)kΩ  |  |
| 3.1  |           |           |           | (377.0)kΩ  |  |
| 3.15 |           |           |           | (572.0)kΩ  |  |
| 3.2  |           |           |           | (961.0)kΩ  |  |
| 3.25 |           |           |           | (2.13)MΩ   |  |
| 3.3  |           |           |           |            |  |
| 3.35 |           |           |           | 1.23MΩ     |  |
| 3.4  |           |           |           | 539.0kΩ    |  |
| 3.45 |           |           |           | 309.0kΩ    |  |
| 3.5  |           |           |           | 194.0kΩ    |  |
| 3.55 |           |           |           | 126.0kΩ    |  |
| 3.6  |           |           |           | 79.6kΩ     |  |
| 3.65 |           |           |           | 46.8kΩ     |  |

R1 = (Blue)      R2 = Black

**Table 3**

### DC/DC CONVERTER ADJUSTMENT RESISTOR VALUES

Series Pt #

AL Case

| 24V Bus | PT3342 |  | PT3343 | PT3344 |
|---------|--------|--|--------|--------|
| 48V Bus | PT3322 |  | PT3323 | PT3324 |

CU Case

|                      |        |  |        |        |        |
|----------------------|--------|--|--------|--------|--------|
| 24V Bus              | PT4582 |  | PT4583 | PT4584 |        |
| 48V Bus              | PT4562 |  | PT4571 | PT4563 | PT4564 |
| Current              | 6Adc   |  | 3.3Adc | 2.5Adc | 2.0Adc |
| V <sub>o</sub> (nom) | 5.0V   |  | 9.0V   | 12.0V  | 15.0V  |

| V <sub>a</sub> (req'd) |           | V <sub>a</sub> (req'd) |            |
|------------------------|-----------|------------------------|------------|
| 4.5                    | (246.0)kΩ | 7.0                    | (9.9)kΩ    |
| 4.55                   | (293.0)kΩ | 7.2                    | (29.2)kΩ   |
| 4.6                    | (352.0)kΩ | 7.4                    | (53.2)kΩ   |
| 4.65                   | (428.0)kΩ | 7.6                    | (84.2)kΩ   |
| 4.7                    | (529.0)kΩ | 7.8                    | (125.0)kΩ  |
| 4.75                   | (670.0)kΩ | 8.0                    | (183.0)kΩ  |
| 4.8                    | (882.0)kΩ | 8.2                    | (270.0)kΩ  |
| 4.85                   | (1.23)MΩ  | 8.4                    | (414.0)kΩ  |
| 4.9                    | (1.94)MΩ  | 8.6                    | (703.0)kΩ  |
| 4.95                   |           | 8.8                    | (1.57)MΩ   |
| 5.0                    |           | 9.0                    |            |
| 5.05                   |           | 9.2                    | 556.0kΩ    |
| 5.1                    | 566.0kΩ   | 9.4                    | 223.0kΩ    |
| 5.15                   | 337.0kΩ   | 9.6                    | 112.0kΩ    |
| 5.2                    | 223.0kΩ   | 9.8                    | 56.6kΩ     |
| 5.25                   | 154.0kΩ   | 10.0                   | 23.3kΩ     |
| 5.3                    | 108.0kΩ   | •                      |            |
| 5.35                   | 75.3kΩ    | 10.8                   | (285.0)kΩ  |
| 5.4                    | 50.8kΩ    | 11.0                   | (371.0)kΩ  |
| 5.45                   | 31.7kΩ    | 11.2                   | (500.0)kΩ  |
| 5.5                    | 16.4kΩ    | 11.4                   | (715.0)kΩ  |
|                        |           | 11.6                   | (1.15)MΩ   |
|                        |           | 11.8                   |            |
|                        |           | 12.0                   |            |
|                        |           | 12.2                   | 588.0kΩ    |
|                        |           | 12.4                   | 249.0kΩ    |
|                        |           | 12.6                   | 136.0kΩ    |
|                        |           | 12.8                   | 78.9kΩ     |
|                        |           | 13.0                   | 45.0kΩ     |
|                        |           | 13.2                   | 22.3kΩ     |
|                        |           | •                      |            |
|                        |           | 13.5                   | (323.0)kΩ  |
|                        |           | 13.6                   | (355.0)kΩ  |
|                        |           | 13.8                   | (437.0)kΩ  |
|                        |           | 14.0                   | (522.0)kΩ  |
|                        |           | 14.2                   | (724.0)kΩ  |
|                        |           | 14.4                   | (1010.0)kΩ |
|                        |           | 14.6                   | (1.58)MΩ   |
|                        |           | 14.8                   |            |
|                        |           | 15.0                   |            |
|                        |           | 15.2                   | 607.0kΩ    |
|                        |           | 15.4                   | 263.0kΩ    |
|                        |           | 15.6                   | 149.0kΩ    |
|                        |           | 15.8                   | 91.3kΩ     |
|                        |           | 16.0                   | 56.9kΩ     |
|                        |           | 16.5                   | 11.1kΩ     |

R1 = (Blue)      R2 = Black

## Using Remote On/Off on Power Trends' 30W Isolated DC-DC Converter Series

Power Trends' 30W isolated series of DC/DC converters incorporate a *Remote On/Off* function. This function may be used in applications for battery conservation, power-up/shutdown sequencing, or to co-ordinate the power-up of the regulator for active in-rush current control. (See TI application reports, SLTA021, and SLUA250).

The Remote On/Off function is provided by pin 2. If pin 2 is left open-circuit, the converter provides a regulated output whenever a valid source voltage <sup>1</sup> is applied between +V<sub>in</sub> (pins 7-9), and -V<sub>in</sub> (pins 4-6). Applying a low voltage <sup>2</sup>, with respect to -V<sub>in</sub> (pin 2), disables the regulator output <sup>3</sup>. Table 1 details the control requirements for this input. Figure 1 shows how a discrete MOSFET (Q<sub>1</sub>) may be referenced to the negative input voltage rail to control the Remote On/Off pin.

**Table 1 Remote On/Off Control Requirements <sup>2</sup>**

| Parameter                  | min               | max                                |
|----------------------------|-------------------|------------------------------------|
| Enable (V <sub>IH</sub> )  | 2.5V <sup>5</sup> | 15V (or open circuit) <sup>4</sup> |
| Disable (V <sub>IL</sub> ) | -0.3V             | 0.8V                               |

### Notes:

- These converters incorporate an "Under Voltage Lockout" (UVLO) function. This function automatically holds the converter output in the "Off" state until there is sufficient input voltage for the converter to produce a regulated output. Table 2 gives the applicable UVLO thresholds.


**Table 2 UVLO Thresholds**

| Series      | UVLO Threshold | V <sub>in</sub> Range |
|-------------|----------------|-----------------------|
| PT3320/4560 | 34 ± 2.0V      | 36 – 75V              |
| PT3340/4580 | 16.5 ± 1.5V    | 18 – 60V              |

- The Remote On/Off control pin uses -V<sub>in</sub> (pins 4-6) as its ground reference. All voltages specified are with respect to -V<sub>in</sub>.
- When the converter output is disabled the current drawn from the input supply is typically reduced to 8mA (16mA maximum).
- The internal circuitry comprises of a high impedance (3μA -10μA) current source. The open-circuit voltage is less than 10V.
- The Remote On/Off pin is ideally controlled using devices with an open-collector (or open-drain) output. A small low-leakage MOSFET (<100nA) is recommended. A pull-up resistor is not required, but may be necessary to ensure that the Remote On/Off pin exceeds V<sub>IH</sub>(min) (see Table 1). *Do not* use a pull-up resistor to the +V<sub>in</sub> input, or drive the pin above V<sub>IH</sub>(max).


- Keep the on/off transition to less than 1ms. This prevents erratic operation of the ISR, whereby the output voltage may drift un-regulated between 0V and the rated output voltage during power-up.
- In Figure 1, Q<sub>1</sub> is a low-threshold MOSFET. The components R<sub>1</sub> and C<sub>1</sub> are added to improve noise susceptibility.

**Figure 1**



**Turn-On Time:** When the Remote On/Off input is left open-circuit, the output of the converter is automatically enabled when a valid input voltage <sup>1</sup> is applied to the input power pins. The converter typically rises to full regulation within 30ms of the application of power (or after the release of the Remote On/Off pin with input power applied). The actual turn-on time will vary with the input voltage, output load, and the total amount of capacitance connected to the output. Using the circuit of Figure 1, Figure 2 shows the typical output voltage and input current waveforms for a PT3322/PT4562 after Q<sub>1</sub> is turned off. The turn off of Q<sub>1</sub> correlates with the fall of the Q<sub>1</sub> V<sub>gs</sub> waveform. The waveforms were measured with a 48Vdc input voltage, and 5-A resistive load.

**Figure 2**



## **VDE Approved Installation Instructions (Installationsanleitung)**

|                                            |                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                 |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Nennspannung (Rated Voltage):              | PT3320 36 to 72 Vdc, Transient to 75Vdc<br>PT3340 18 to 60 Vdc                                                                                                                                                                                                                                                                       |                                                                                                                                 |
| Nennaufnahme (Rated Input):                | PT3320 1.5 Adc<br>PT3340 3.0 Adc                                                                                                                                                                                                                                                                                                     |                                                                                                                                 |
| Nennleistung (Rated Power):                | 30 Watts Maximum                                                                                                                                                                                                                                                                                                                     |                                                                                                                                 |
| Ausgangsspannung (Sec. Voltage):           | PT3320 Series<br>PT3321, 3.3 Vdc, 8.0 Adc<br>PT3322, 5.0 Vdc, 6.0 Adc<br>PT3323, 12.0 Vdc, 2.5 Adc<br>PT3324, 15.0 Vdc, 2.0 Adc<br>PT3325, 2.0 Vdc, 8.0 Adc<br>PT3326, 2.5 Vdc, 8.0 Adc<br>PT3327, 1.8 Vdc, 8.0 Adc<br>PT3328, 5.2 Vdc, 6.0 Adc<br>PT3329, 6.0 Vdc, 5.0 Adc<br>PT3330, 8.0 Vdc, 3.75 Adc<br>PT3331, 9.0 Vdc, 3.3 Adc | PT3340 Series<br>PT3341, 3.3 Vdc, 8.0 Adc<br>PT3342, 5.0 Vdc, 6.0 Adc<br>PT3343, 12.0 Vdc, 2.5 Adc<br>PT3344, 15.0 Vdc, 2.0 Adc |
| Ausgangsstrom (Sec. Current):<br>oder (or) |                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                 |
| Ausgangsleistung (Sec. Power):             |                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                 |

### Angabe der Umgebungstemperatur

(Information on ambient temperature): +85°C Ambient or 100°C Case Maximum

### Besondere Hinweise (Special Instructions):

Es ist vorzusehen, daß die Spannungsversorgung in einer Endanwendung über eine isolierte Sekundarschaltung bereit gestellt wird. Die Eingangsspannung der Spannungsversorgungsmodule muss eine verstärkte Isolierung von der Wechselstromquelle aufweisen.

Die Spannungsversorgung muss gemäß den Gehäuse-, Montage-, Kriech- und Luftstrecken-, Markierungs- und Trennanforderungen der Endanwendung installiert werden. Bei Einsatz eines TNV-3-Einganges muss die SELV-Schaltung ordnungsgemäß geerdet werden.

(The power supply is intended to be supplied by isolated secondary circuitry in an end use application. The input power to these power supplies shall have reinforced insulation from the AC mains.)

The power supply shall be installed in compliance with the enclosure, mounting, creepage, clearance, casualty, markings, and segregation requirements of the end-use application. When the input is TNV-3, the SELV circuitry must be reliably grounded.)

Offenbach,

**VDE Prüf- und Zertifizierungsinstitut**  
Abteilung / Department TD

(Jürgen Bärwinkel)

Ort / Place:

Datum / Date:

 12/12/01  
(Stempel und Unterschrift des Herstellers / Stamp  
and signature of the manufacturer)

## **IMPORTANT NOTICE**

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Mailing Address:

Texas Instruments  
Post Office Box 655303  
Dallas, Texas 75265