

Features

- Carbon element
- Red, orange, green, amber and white LED colors
- Center detent option
- Assortment of resistance tapers
- Various travel lengths
- Various lever sizes

BOURNS® PRO AUDIO

PTL Series Slide Potentiometer w/LED

Electrical Characteristics

Standard Resistance Range
..... 1K ohms to 1 megohm
Standard Resistance Tolerance... ±20 %
End Resistance
20 mm Travel..... 10 ohms max.
30 mm Travel..... 20 ohms max.
45 mm Travel..... 20 ohms max.
60 mm Travel..... 30 ohms max.
Insulation Resistance @ 250 VDC
..... 100 megohms min.
Dielectric Withstanding Voltage
..... 300 VAC
Standard Taper..... Linear, Audio
Power Rating - Linear
20 mm Travel..... 0.05 watt
30 mm Travel..... 0.1 watt
45 mm Travel..... 0.125 watt
60 mm Travel..... 0.2 watt
Power Rating - Audio
20 mm Travel..... 0.025 watt
30 mm Travel..... 0.05 watt
45 mm Travel..... 0.06 watt
60 mm Travel..... 0.1 watt
Slider Noise ..... 200 mV max.

Environmental Characteristics


Operational Life ..... 15,000 cycles
TR Shift ..... ±15 %
Operating Temperature Range
..... -10 °C to +55 °C
Resistance to Solder Heat..... ±5 %

Mechanical Characteristics

Mechanical Travel..... Length ±0.5 mm
Operating Force ..... 30 gf to 250 gf
Center Detent Force..... 20 gf to 200 gf
Stop Strength ..... 5 kgf min.
Shaft Axial Force ..... 5 kgf min.
Shaft Wobble.. 2(2 x L/20) mm p-p max.
Soldering Condition
Manual .....300 °C ±5 °C for 3 sec.
Wave .....260 °C ±5 °C for 5 sec.
Wash .....Not recommended


Product Dimensions

20 mm Length of Travel



Lever Length
10.0 (.394)
15.0 (.591)
19.0 (.748)


Mounting Hole Detail



Standard Resistance Table

Resistance (Ohms)	Resistance Code
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
50,000	503
100,000	104
200,000	204
500,000	504
1,000,000	105

Schematic



*RoHS Directive 2002/95/EC Jan 27, 2003 including Annex.
Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

Applications


- Mixing consoles
- Drum machines
- Keyboards and synthesizers
- Equalizers


PTL Series Slide Potentiometer w/LED


BOURNS®

Product Dimensions


30 mm Length of Travel









Mounting Hole Detail




DIMENSIONS: MM / (INCHES)


45 mm Length of Travel







Mounting Hole Detail




Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

PTL Series Slide Potentiometer w/LED


BOURNS®

Product Dimensions

60 mm Length of Travel





Mounting Hole Detail




DIMENSIONS: MM / (INCHES)

Tapers







Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

LED Characteristics

Emitter Color	Item	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Red	Forward Voltage	V_F	I_F = 20 mA		2.1	2.5	V
	Luminous Intensity	I_V		0.3	0.6		mcd
	Peak Emission Wavelength	λ_p			660		nm
	Dominant Wavelength	λ_d			643		nm
	Spectral Line Half Width	$\Delta\lambda$			20		nm
Orange	Forward Voltage	V_F	I_F = 20 mA		2.2	2.5	V
	Luminous Intensity	I_V		1.5	3.0		mcd
	Peak Emission Wavelength	λ_p			610		nm
	Dominant Wavelength	λ_d			605		nm
	Spectral Line Half Width	$\Delta\lambda$			35		nm
Green	Forward Voltage	V_F	I_F = 20 mA		2.1	2.5	V
	Luminous Intensity	I_V		0.6	1.2		mcd
	Peak Emission Wavelength	λ_p			530		nm
	Dominant Wavelength	λ_d			35		nm
	Spectral Line Half Width	$\Delta\lambda$			160		nm
Amber	Forward Voltage	V_F	I_F = 20 mA		2.1	2.6	V
	Luminous Intensity	I_V			5.0		mcd
	Peak Emission Wavelength	λ_p			585		nm
	Dominant Wavelength	λ_d		582	–	595	nm
	Spectral Line Half Width	$\Delta\lambda$			35		nm
White	Forward Voltage	V_F	I_F = 20 mA		3.5	4	V
	Luminous Intensity	I_V			300.0		mcd
	Peak Emission Wavelength	λ_p			520		nm
	Dominant Wavelength	λ_d		460	–	470	nm
	Spectral Line Half Width	$\Delta\lambda$			35		nm

How To Order

PTL 30 - 10 R 0 - 103 B2

Model Number Designator
PTL = Slide Potentiometer w/LED

Length of Travel
20 = 20 mm 45 = 45 mm
30 = 30 mm 60 = 60 mm

Lever Length
10 = 10 mm
15 = 15 mm
19 = 19 mm


LED Color
R = Red A = Amber
O = Orange W = White
G = Green

Detent Option
0 = No Detent
1 = Center Detent

Resistance Code
(See Standard Resistance Table)

Resistance Taper (See Taper Charts)
Taper Series followed by Curve Number

Circuit



REV. 09/11

Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.