PUMX1

DUAL TRANSISTOR

NPN GENERAL PURPOSE DUAL TRANSISTOR



SOT-363

Lead-free: PUMX1L
Halogen-free: PUMX1G

■ DESCRIPTION

Two independently operating NPN transistors.

■ FEATURES

* Low current (max.100mA)
* Low voltage (max.40V)
* Reduces number of components and board space.
* Complement to PUMT1.

■ APPLICATIONS

* General purpose switching and amplification.

■ SYMBOL



■ ORDERING INFORMATION

Ordering Number			Package	Pin Assignment						Packing
Normal	Lead Free	Halogen-Free		1	2	3	4	5	6	
PUMX1-AL6-R	PUMX1L-AL6-R	PUMX1G-AL6-R	SOT-363	E1	B1	C2	E2	B2	C1	Tape Reel

PUMX1L-AL6-R (1)Packing Type (2)Package Type (3)Lead Plating	(1) R: Tape Reel (2) AL6: SOT-363 (3) G: Halogen Free, L: Lead Free Plating, Blank: Pb/Sn

■ MARKING



Copyright © 2008 Unisonic Technologies Co., Ltd

■ ABSOLUTE MAXIMUM RATINGS (T_a=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Base Voltage	V_{CBO}	50	V
Collector-Emitter Voltage	V_{CEO}	40	V
Emitter-Base Voltage	V_{EBO}	5	V
Collector Current (DC)	I_C	100	mA
Peak Collector Current	I_{CM}	200	mA
Peak Base Current	I_{BM}	200	mA
Collector Power Dissipation	P_C	300	mW
Junction Temperature	T_J	150	°C
Storage Temperature	T_{STG}	-65~+150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS (T_a=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Emitter Saturation Voltage (Note)	$V_{CE(SAT)}$	I_C=50mA, I_B=5mA			200	mV
Collector Cutoff Current	I_{CBO}	I_E=0, V_{CB}=30V			100	nA
Emitter Cutoff Current	I_{EBO}	V_{EB}=4V, I_C=0			100	nA
DC Current Transfer Ratio	h_{FE}	I_C=1mA, V_{CE}=6V	120			
Transition Frequency	f_T	I_C=2mA, V_{CE}=12V, f=100MHz	100			MHz
Collector capacitance	C_C	I_E=I_E=0, V_{CB}=12V, f=1MHz			1.5	pF

Note: Pulse test: tp≦300μs, δ≦0.02

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.