


PV3-48-3.3



Sales Region	Worldwide
Series	PV
Status	Production
Option	
Option Lineup	
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics	
Rated Input Voltage[DC]	48V
Input Voltage Range[DC]	36 to 72V
Efficiency	75% Typ.
Rated Output Voltage[DC]	3.3V
Output Voltage Range[DC]	3.3 to 3.67V
Maximum Output Current	
Maximum Ripple Noise	100mV
Maximum Output Power	2W
Withstanding Voltage1	Input - Output: 500VAC: 1min.
Withstanding Voltage2	
Withstanding Voltage3	

Cases Shape & Size	
Case□ shape	On board/Power module
Width(W)	33mm Nom.
Height(H)	18mm Nom.
Depth(D)	8.5mm Nom.
Weight	4g Typ.
Industry Standard Size	
Terminal Style	SIP

Other	
Operating Temp. Range	-20 to 70°C
Isolated / Non-isolated	Isolated
Feature	
Safety Standard(Certified)	
Safety Standard(Conformed)	

Images are for reference only and show exemplary products.
 This PDF document was created based on the data listed on the TDK Corporation website.
 All specifications are subject to change without notice.

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.