

Sales Region	Worldwide (except Japan)
Series	PXE
Model	PXE20
Status	 Production
Option	
Option Lineup	
Recommended EMC Filter	
Accessories	Please refer to here.



Electrical Characteristics	
Nominal Input Voltage[DC]	24Vdc
Input Voltage Range[DC]	9 to 36Vdc
Efficiency	81% Typ.
Rated Output Voltage[DC]	+12Vdc -12Vdc
Output Voltage Range[DC]	10.8 to 13.2Vdc -10.8 to -13.2Vdc
Maximum Output Current	0.833A 0.833A
Maximum Ripple Noise	100mV 100mV
Maximum Output Power	20W
Withstanding Voltage1	Input - Output: 1600DC: 1min.
Withstanding Voltage2	Input - Case: 1600DC: 1min.
Withstanding Voltage3	

Package Type & Size	
Package / Mounting	PCB mount
Width(W)	50.8mm Nom. (2.00in Nom.)
Height(H)	10.2mm Nom. (0.40in Nom.)
Depth(D)	40.6mm Nom. (1.60in Nom.)
Weight	
Industry Standard Size	2x1.6 inch size
Terminal Style	DIP

Other	
Operating Temp. Range	-40 to 100°C
Isolation	Isolated
Feature	

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Safety Standard(Certified)	IEC60950-1
	EN60950-1
	UL60950-1
Safety Standard(Conformed)	
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.